

# Signed Integer Arithmetic on the HPC™

National Semiconductor  
Application Note 603  
Raj Gopalan  
July 1989



This report describes the implementation of signed integer arithmetic operations on the HPC. HPC hardware support for unsigned arithmetic operation. In order to support signed integer arithmetic operations on the HPC, the user can represent negative numbers in two's complement form and perform the signed arithmetic operations explicitly through software.

The following signed integer arithmetic routines are implemented in the package:

#### Multiplication:

16 by 16 yielding 16-bit result  
32 by 32 yielding 32-bit result

#### Division:

16 by 8 yielding 16-bit quotient and 16-bit remainder  
32 by 16 yielding 16-bit quotient and 16-bit remainder  
32 by 32 yielding 16-bit quotient and 16-bit remainder

#### Addition:

16 by 16 yielding 16-bit

#### Subtraction:

16 by 16 yielding 16-bit

#### Comparison:

16 by 16 for greater to, less than or equal to.

#### REPRESENTATION OF NEGATIVE NUMBERS:

For binary numbers, negative numbers are represented in two's complement form. In this system, a number is positive if the MSB is 0, negative if it is 1.

The decimal equivalent of two's complement number is computed the same as for an unsigned number, except that weight of the MSB is  $-2^{**n} - 1$  instead of  $+2^{**n} - 1$ . The range of representable numbers is  $-(2^{**n} - 1)$  through  $(2^{**n} - 1 - 1)$ .

The two's complement of a binary number is obtained by complementing its individual bits and adding one to it.

The advantage of representing a negative number in two's complement form is that addition and subtraction can be done directly using unsigned hardware.

```
.title      SIMUSL
.sect      code,rom8,byte,rel

;Signed multiply (16 by 16)
;      B      Multiplicand
;      A      Multiplier
;      X;A    return
;
      .public signed_mult_16
      .local
signed_mult_16:
      st      a,0.w
      mult   a,b          ;do unsigned multiplication.
      sc
      ifbit  7,(1).b     ;if multiplier is negative
      subc  x,b
      sc
      ifbit  7,(B+1).b   ;if multiplicand is negative
      subc  x,0.w
$exit:
      ret

      .endsect
```

## MULTIPLICATION

### Method 1:

Signed multiplication can be achieved by taking care of the signs and magnitudes of the multiplicand and multiplier separately.

Perform the multiplication on the magnitudes alone.

The sign of the result can be set based on the signs of the multiplier and the multiplicand.

### Method 2:

This method does not require finding the magnitude of the operands. Multiplication can be done using unsigned hardware on the two's complement numbers. The result will be signed based on the signs of the operands.

```
.title      SIMULL
.sect      code,rom8,byte,rel
;Multiply (Signed or Unsigned are the same)
;32 bit
;      K:A      Multiplicand
;      -4:6[SP] Multiplier
;      K:A      return
;
      .public multiply_32
      .local
multiply_32:
      push      x
      st        a,0.w
      ld        a,k
      mult      a,-8[sp].w
      x
      push      a
      mult      a-8[sp].w
      add       0.w,a
      pop       a
      mult      a,-8[sp].w
      add       x,0.w
      ld        k,x
      pop       x
      ret

      .endsect
```

The algorithm is as follows:

Step 1. Result = op1 \* op2

Step 2. If op1 < 0 then subtract op2 from upper half of the result.

Step 3. If op2 < 0 then subtract op1 from upper half of the result.

Now the Result will yield the correct value of the multiplication on two's complement numbers.

### Method 3:

By sign extending the multiplier and multiplicand to the size of the result one can always obtain the correct result of signed multiplication using unsigned multiplication.

## DIVISION

Similar to multiplication method 1, one can perform the division on the magnitudes of the dividend and divisor.

The sign of the quotient can be set based on the signs of the dividend and the divisor.

The sign of the remainder will be same as the dividend.

```
.title      SIDVSS
.sect      code,rom8,byte,rel

;Division & Remainder
;16,8 bit (signed only, unsigned uses inline code)
;      A      Dividend
;      -4[SP]  Divisor
;      A      return
;
      .public signed_divide_8,signed_remainder_8
      .public signed_divide_16,signed_remainder_16
      .local
signed_divide_8:
      jsr      $shared_8          ;Uses shared routine
      ret
;
signed_remainder_8:
      jsr      $shared_8          ;Uses shared routine
      ld      a,k                ;Return remainder
      ret
;
$shared_8:
      ifgt    a,#0x7f
      or     a,#0xff00
      st     a,k                ;Get arguments
      ld     a,-6[sp].w
      ifgt    a,#0x7f
      or     a,#0xff00
      jp     $shared
;
signed_divide_16:
      jsr      $shared_16         ;Uses shared routine
      ret
;
signed_remainder_16:
      jsr      $shared_16         ;Uses shared routine
      ld      a,k                ;Return remainder
      ret
;
$share_16:
      st     a,k                ;Get arguments
      ld     a,-6[sp].w
$shared
      ifeq    a,#0
      ret     ;division by zero
      push   x
      ifgt    a,#0x7fff
      jp     $unknown_negative   ;unknown/negative
      x
      ifgt    a,#0x7fff
      jp     $negative_positive  ;negative/positive
      div    a,k                 ;Positive/positive is plus,plus
      jp     $positive_positive
```

```

$unknown_negative:                                ;Unknown/negative
    comp      a
    inc       a
    x         a,k
    ifgt     a,#0x7fff
    jp       $negative_negative                  ; negative/negative
    div      a,k                                ;Positive/negative is minus,plus
    comp     a
    inc      a
$positive_positive:
    ld       k,x
    jp       $exit
$negative_positive:                                ;Negative/positive is minus,minus
    comp     a
    inc     a
    div     a,k
    comp     a
    inc     a
    jp     $negate_remainder
$negative_negative:                                ;Negative/negative is plus,minus
    comp     a
    inc     a
    div     a,k
$negate_remainder:
    x       a,x
    comp     a
    inc     a
    st      a,k
    ld      a,x
$exit:
    pop     x
    ret
    .endsect

```

```

        .title      SIDVLS
        .sect       code,rom8,byte,rel

;Division & Remainder
;Signed 32 by 16 divide
;   X;A      Dividend
;   K        Divisor
;   X,A      return (remainder and quotient)
;
        .public signed_div_32
        .local
signed_div_32:
        sc
        ifeq      k,#0
        ret
;Divide by zero, set carry and return
$shared_signed:
        ifbit     7,x+1.b
        jp       $negative_dividend
        jsr      $process_divisor
        ret
;Skipping return
;+ / += +, +
$negate_quotient:
        comp     a
        inc     a
        ret
;+ / -= -, +
$negative_dividend:
        comp     a
        add     a,#01
        x       a,x
        comp     a
        adc     a,#0
        x       a,x
        jsr     $process_divisor
        jsr     $negate_quotient
;skipping return
;- / += -, -
$negate_remainder:
        x       a,x
        comp     a
        inc     a
        x       a,x
        ret
$process_divisor:
        ifbit     7,k+1.b
        jp       $negative_divisor
        divd     a,k
        ret
;? / +
$negative_divisor:
        x       a,k
        comp     a
        inc     a
        x       a,k
        divd     a,k
        retsk
;? / -

        .endsect

```

```

        .title      SUDVLL
        .sect       code,rom8,byte,rel

;Division & Remainder
;Signed 32 by 32 Divide
;      K:A          Dividend
;      -4:6[SP]     Divisor
;      K:A          return
;
;Stack frame as built and used consists of
;top:
;      0, initial subtrahend hi /dividend shifts into subtrahend
;      0, initial subtrahend lo /becomes remainder
;      k, dividend hi /dividend shifts into subtrahend, and
;      a, dividend lo /quotient shifts into dividend
;      b preserved
;      x preserved
;      return address
;      sp-4-12, divisor hi
;      sp-6-12, divisor lo
;Sign flag (0 = negative, 1 = positive, for test sense at exit)
;bit 0, divisor sign (1 = negative)
;bit 1, dividend sign (1 = positive)
;Inc of flag causes bit 1 = (bit 1 xor bit 0) by carry/nocarry out of bit 0
;so that two positives (010) or two negatives (001) indicate a positive
;quotient (011 or 010) in bit 1. Bit 1 always indicates sign if remainder.
;Operation is indicated by bit 3 of the flag, 1 = remainder.
;
        .public signed_divide_32, signed_remainder_32
        .public unsigned_divide_32, unsigned_remainder_32
        .local
signed_divide_32:
        ld          1.b,#0x02
        jp          $shared_signed
;
signed_remainder_32:
        ld          1.b,#0x0a
$shared_signed:
        ifbit       7,k+1.b          ;Check dividend
        jsr         $negate          ;Negate dividend and note sign
        ifbit       7,-6+3[sp].b    ;Check divisor
        jp          $negate_divisor
        jmp         $shared
;
$negate_divisor:
        x           a,-6[sp].w      ;Negate divisor and note sign
        comp        a
        add         a,#1
        x           a,-6[sp].w
        x           a,-4[sp].w
        comp        a
        adc         a,#0
        x           a,-4[sp].w
        sbit        0,1.b
        jp          $shared
;
unsigned_divide_32:
        ld          1.b,#0x02
        jp          $shared
;
unsigned_remainder_32:
        ld          1.b,#0x0a

```

```

$shared:
    push        x                ;Preserve registers
    push        b
    ld          b,sp             ;Place dividend, becomes quotient
    push        a
    push        k
    ld          x,sp             ;Set subtrahend, becomes remainder
    clr        a
    push        a
    push        a
    ld          k,#-18           ;Access divisor argument
    add        k,sp
    ld          a,[k].w
    or         a,2[k].w
    ifeq       a,#0
    jmp        $zero            ;division by zero
    ld          0,b,#32         ;Set counter

$loop:
    ld          a,[b].w          ;Shift Dividend:Quotient
    shl        a
    xs         a,[b+].w
    nop
    ld          a,[b].w
    rlc        a
    xs         a,[b-].w
    nop
    ld          a,[x].w
    rlc        a
    x          a,[x+].w
    ld          a,[x].w
    rlc        a
    x          a,[x-].w
    ifc
    jp         $subtract        ;Carry out - dividend divisor
    sc         ;Check for dividend divisor
    ld          a,[x+].w
    subc       a,[k].w
    ld          a,[x-].w
    subc       a,2[k].w
    ifnc
    jp         $count           ;dividend divisor

$subtract:
    ld          a,[x].w          ;Subtract out divisor (c is set)
    subc       a,[k].w
    x          a,[x+].w
    ld          a,[x].w
    subc       a,2[k].w
    x          a,[x-].w
    sbit       0,[b].b         ;Set quotient bit

$count:
    decsz     0,b               ;Count 32 shifts
    jmp        $loop

$zero:
    pop        k                ;Get Remainder and/or Quotient
    pop        a                ;and clear working off stack
    pop        x
    pop        b
    ifbit     3,1,b
    jp        $exit             ;want remainder, have it
    ld        a,b               ;Want Quotient
    ld        k,x
    inc       1,b               ;Divisor's sign Xors Dividend's

```

```

$exit:
    pop        b                ;Restore registers
    pop        x
    ifbit     1,1,b
    ret                    ;positive result
$negate:
    comp      a                ;Negate K:A
    add       a,#1
    x         a,k
    comp      a
    adc       a,#0
    x         a,k
    rbit     1,1,b            ;Note sign (for entrance)
    ret

    .endsect

```

## ADDITION

Two's complement numbers can be added by ordinary binary addition, ignoring any carries beyond the MSB. The result will always be the correct sum as long as the result doesn't exceed the range.

If the result is the same as for the subtrahend, then overflow has occurred.

```
.title      SIADD
.sect      code,rom8,byte,rel
;Signed add (16 by 16)
;      A      Operand1
;      B      Operand2
;      Carry  Return
;      .public sign_add
;      .local

sign_add:
    ld      0.b,#00
    ifbit 7,(A+1).b
    inc     0.b
    ifbit 7,(B+1).b
    inc     0.b

    ;if bit 0 of 0.b = 1 then opl and op2 have different sign
    ;if bit 0 of 0.b = 0 then opl and op2 sign are same
    ;then if bit 1 of 0.b = 0 both operands are positive
    ;else both operands are negative.

    add     a,b          ;Perform unsigned addition
    rc
    ifbit 0,0.b          ;both operands are different sign
    ret
    ifbit 1,0.b          ;both opl and op2 are negative
    jp $negatives
$positives:             ;both opl and op2 are positive
    ifbit 7,(A+1).b     ;if result sign is negative then
                        ;set overflow bit
    sc
    ret                ;overflow
$negatives:
    ifbit 7,(A+1).b     ;if sign bit of result is
                        ;negative, then no overflow

    ret
    sc                  ;overflow
$exit:
    ret

.endsect
```

## SUBTRACTION

Subtraction can be achieved by negating the subtrahend and perform the addition operation.

Overflow can be detected as mentioned before by checking the signs of minuend and the negation of the subtrahend and that of the sum.

```
.title      SISUB
.sect      code,rom8,byte,rel

;Signed subtract (16 by 16)

;      B      Operand1
;      A      Operand2
;      Carry,A  Return
      .public sign_sub
      .local

sign_sub:
      ld      0.b,#00          ;initialize sign flags
      ifbit  7,(B+1).b
      inc 0.b

$negate_A:
      comp A
      inc A
$ngative_comp_A:
      ifbit 7,(A+1).b
      inc 0.b
      ;if bit 0 of 0.b = 1 then op1 and op2 have different sign
      ;if bit 0 of 0.b = 0 then op1 and op2 sign are same
      ;then if bit 1 of 0.b = 0 both operands are positive
      ;else both operands are negative.
      add A,B                  ;Perform unsigned addition
      rc
      ifbit 0,0.b              ;both operands are different sign
      ret
      ifbit 1,0.b              ;both op1 and op2 are negative
      jp $negatives

$positives:                    ;both op1 and op2 are positive
      if bit 7, (A+1).b        ;if result sign is negative then
                                set overflow bit
      sc                       ;bit 0 of byte 0.b is set to
                                indicate overflow
      ret

$negatives:                    ;if sign bit of result is
                                negative, then no overflow
      ifbit 7, (A+1).b
      ret
      sc                       ;sign bit of result is positive,
                                hence overflow.

$exit:ret

      .endsect
```

```

        .title      NSISUB
        .sect       code,rom8,byte,rel

;Signed sub (16 by 16)

;      A      Operand1
;      B      Operand2
;      Carry   Return
        .public sign_sub
        .local

sign_sub:
        ld        0.b,#00
        ifbit 7,(A+1).b
        inc       0.b
        ifbit 7,(B+1).b
        inc       0.b
        ;if bit 0 of 0.b = 1 then opl and op2 have different sign
        ;if bit 0 of 0.b = 0 then opl and op2 sign are same
        ;then if bit 1 of 0.b = 0 both operands are positive
        ;else both operands are negative.
        sc
        subc      a,b                ;Perform unsigned addition
        rc
        ifbit 0,0.b                ;both operands are different sign
        jp        $chkovf
        ret                        ;both operands are same sign,
                                   can't produce overflow

$chkovf:
        ifbit     7,(B+1).b
        jp        $negminu

$posminu:
        ifbit     7,(A+1).b
        sc
        ret

$negminu:
        ifbit     7,(A+1).b
        sc
        ret

        .endsect

```

**COMPARISON**

To do signed comparison on  $n$  bit two's complement numbers first add  $2^{n-1}$  to the numbers. This will basically shift the numbers from  $-(2^{n-1})$  to  $(2^{n-1}-1)$  range to  $0$  to  $2^{n-1}-1$ .

Now comparison operations on the numbers will produce the correct result.

```

        .title      SICMP
        .sect       code,rom8,byte,rel

;Signed compare (16 by 16)

;      A      Operand1
;      B      Operand2
;      0.b    Return=00          if a = b
;              02              if a > b
;              01              if a < b
signed_compare:
    push      a
    push      b
    add       a,#08000
    add       b,#08000
    ifgt     a,b
    jp       $great
    ifeq     a,b
    jp       $equ
$less:
    ld       0.b,#01
    pop      b
    pop      a
    ret
$great:
    ld       0.b,#02
    pop      b
    pop      a
    ret
$equ:
    ld       0.b,#00
    pop      b
    pop      a
    ret

        .endsect

```

**LIFE SUPPORT POLICY**

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.



**National Semiconductor Corporation**  
2900 Semiconductor Drive  
P.O. Box 58090  
Santa Clara, CA 95052-8090  
Tel: (600) 272-9959  
TWX: (910) 339-9240

**National Semiconductor GmbH**  
Livry-Gargan-Str. 10  
D-82256 Fürstenfeldbruck  
Germany  
Tel: (81-41) 35-0  
Telex: 527849  
Fax: (81-41) 35-1

**National Semiconductor Japan Ltd.**  
Sumitomo Chemical  
Engineering Center  
Bldg. 7F  
1-7-1, Nakase, Mihama-Ku  
Chiba-City,  
Ciba Prefecture 261  
Tel: (043) 299-2300  
Fax: (043) 299-2500

**National Semiconductor Hong Kong Ltd.**  
13th Floor, Straight Block,  
Ocean Centre, 5 Canton Rd.  
Tsimshatsui, Kowloon  
Hong Kong  
Tel: (852) 2737-1600  
Fax: (852) 2736-9960

**National Semicondutores Do Brazil Ltda.**  
Rue Deputado Lacorda Franco  
120-3A  
Sao Paulo-SP  
Brazil 05418-000  
Tel: (55-11) 212-5066  
Telex: 391-1131931 NSBR BR  
Fax: (55-11) 212-1181

**National Semiconductor (Australia) Pty. Ltd.**  
Building 16  
Business Park Drive  
Monash Business Park  
Nottingham, Melbourne  
Victoria 3168 Australia  
Tel: (3) 558-9999  
Fax: (3) 558-9998