



Best UNIX® compatibility and video performance in a 14" monochrome terminal



Compatibility

No matter which operating environment you're working in, the ADDS 4000/160 and 4000/260 will be right at home. Both terminals are fully compatible with SCO®, UNIX® V.4, XENIX, PICK®, Multiuser DOS and many other operating environments. The 4000/160 and 4000/260 emulation set includes Wyse WY-60, WY-50/50+, DEC VT-320, VT-220 and VT-100, ADDS Viewpoint and PCTerm. The 4000/260 also has advanced data access, data manipulation and display features, including cut-and-paste, WordPerfect® graphics support and dual-host/session capability.

Video Modes

The 4000/160 and 4000/260 feature selectable refresh rates up to 100Hz for clear, flicker-free viewing and an ISO 9241.3-compliant mode to reduce operator eyestrain. Bezel-to-bezel overscan is also available in up to 82Hz.

4000/260: Superior SCO Console Implementation

As a SCO developer partner, you can count on the ADDS 4000/260 to function properly in the SCO operating environment. The 4000/260 features 10 pages of memory and function-key programming for each MScreen session.

Save Money Today and Tomorrow

The 4000/160 and 4000/260 were designed to deliver the lowest cost of ownership in their class:

- EPA ENERGY STAR™-compliant power management feature conserves power

- High reliability virtually eliminates downtime
- Extended warranties reduce maintenance and support costs
- User-friendly features increase operator efficiency and productivity

Ethernet Connectivity

Users have the optional ability to access a single telnet session with their ADDS text terminal via our Ethernet Interface Adapter. It's a cost-effective alternative to using a PC to access text-based applications. It also helps protect your investment in terminals as your applications change.

Built to Suit

Boundless Technologies' "Just in Time" manufacturing techniques allow on-time delivery of any lot size in any configuration. You can select the 4000/160 and 4000/260 of your choice, with options of phosphor color, keyboards and customized logos or firmware. Whether you choose a standard or customized terminal, your order can be shipped quickly.

Built to Last

The ADDS 4000/160 and 4000/260 video display terminals are designed and manufactured in Boundless Technologies' manufacturing plant in the U.S.A. Boundless backs its ADDS text terminal product line with a three-year warranty.



ERGONOMICS

14" flat-face, reduced-glare, high-resolution screen (11.1" active area +/-0.1")

Bezel-to-bezel overscan display (up to 82Hz)

60, 71, 82, and 100Hz selectable refresh rates for clear, flicker-free viewing

Choice of green, amber or page-white phosphor

Variable-speed smooth scroll

Conveniently located contrast, brightness and power controls

Fully adjustable tilt and swivel

ISO 9241.3-compliant mode

DISPLAY FEATURES

26, 30, 44 or 52 lines with top and/or bottom status lines

80 or 132 columns

Four pages of memory (160 only)

Two pages of display, full or split-screen viewing (260 only)

10 pages of memory (260 only)

Variable-speed smooth scroll

Double-high, double-wide and double-high/wide characters

Selectable screen saver

Programmable tab stops

EMULATIONS

4000/160&260

- Wyse WY-60, WY-50/50+

- DEC VT-320, VT-220, VT-100

- ADDS Viewpoint

- PCTerm (925 PC)

- TeleVideo TVI-925

4000/260 also includes

- SCO console

- AT 386 (UNIX Console)

- WordPerfect® graphics

COMPATIBILITY

SCO, UNIX V.4, XENIX, PICK, DOS and many other operating systems

Most PC extender products

DUAL-HOST SUPPORT

4000/260

- Simultaneous connection and operation with two hosts

- Flexible display formats: 26-line alternating or 44-line split-screen

- "Hot key" to alternate between hosts

- Printer port support for both hosts

ADDITIONAL FEATURES

IBM® PC character set includes standard ASCII, line drawing, national symbols and special graphics symbols

Desk accessories - calculator, calendar, clock and ASCII chart

KEYBOARDS

PC 104

ANSI (VT-220)

Programmable function keys

- 12/24 PFKs for PC 104

- 20/40 PFKs for ANSI (VT-220 style)

Not all keyboards are available in all languages

LANGUAGES/ CHARACTER SETS

4000/160 & 4000/260

International language and keyboard support: Danish, French, Belgian/Flemish, Dutch, Finnish, French Canadian, German, Italian, Latin American, Norwegian, Portuguese, Spanish, Swedish, Swiss/French, Swiss/German, Turkish, U.K. English, U.S. English

4000/260 also supports

Polish, Czech, Hungarian, Romanian, Russian, Slovakian, Serbian/Latin, Slovenian, Croatian, Bosnian, Greek, Hebrew

COMMUNICATIONS

Full/half duplex, local, block and monitor modes of operation

Serial host port (SES1-EIA)

- RS-232C, main host

- DTE, DB-25 female

- Up to 134.4K baud

Serial auxiliary port (SES2-AUX) 4000/160

- RS-232 bi-directional serial port

- DCE, DB-25 female


- Up to 38.4K baud

Serial auxiliary port (SES2-AUX) 4000/260

- RS-232C second host/serial port

- DCE, DB-25 female

- Up to 38.4K baud



Parallel printer port (PAR)

- IBM PC cable and Centronic®-compatible

OPTIONS

RS-422, Current loop

Ethernet (TCP/IP) Interface Adapter-10BaseT

ENVIRONMENTAL

Operating environment

- Temperature: 32° to 104°F (10° to 40°C)

- Altitude: 0 to 10,000 ft (0 to 3,048 m)

- Humidity: 30 to 80% RH, non-condensing

Storage environment

- Temperature: 32° to 122°F (0° to 50°C)

- Humidity: 10 to 95% RH, non-condensing

POWER REQUIREMENTS

Voltage: autosensing, wide input, 90/264 VAC

Frequency: 47/63Hz

Current: 0.5/0.2 amps

EPA ENERGY STAR® "Sleep Mode"

PHYSICAL DIMENSIONS

Display Unit

Length: 13.0" 33.0 cm

Width: 12.5" 31.8 cm

Height: 13.4" 34.0 cm

Shipping wt.: 29.0 lbs 13.2 kg

CERTIFICATIONS

UL 1950

CSA Standard 22.2, No. 950

EN60950/VDE 0805

EN61000-1, -2, -3, -4

TUV-GS Mark

VCCI

EN 55022 Class B (CISPR B)

VFG 243 B (VDE Class B)

DHHS

ZHI/618

CE Mark

EPA ENERGY STAR®

CB Report Available

MPR-II (Electromagnetic Compliance Only)

Full MPR-II Optional

ISO 9241.3

Boundless Technologies

1916 Route 96, Phelps, NY 14532

Phone (toll-free): 1-800-231-5445

Phone: 1-315-548-6189

Fax: 1-315-548-5100

http://www.BoundlessTerminals.com



Boundless Technologies continually improves products as new technologies become available, and therefore reserves the right to change specifications without prior notice. All features, functions and operations described herein may not be marketed by Boundless Technologies in all parts of the world. Consult your Boundless representative or local Boundless office for availability. © 1997 Boundless Technologies, Inc. All rights reserved. The Boundless Technologies logo is a trademark of Boundless Technologies, Inc. ENERGY STAR is a U.S. registered mark. As an ENERGY STAR Partner, Boundless Technologies has determined that this product meets the Energy Star guidelines for energy efficiency. All other trademarks and registered trademarks are the properties of their respective owners. Printed in the U.S.A.