

# DATAPOINT 1170 DISPERSED PROCESSOR



# DATAPOINT 1170 DISPERSED PROCESSOR

The Datapoint 1170 Dispersed Processor provides users with the perfect balance of processing power and flexibility. Incorporating a 5500-type processor with 48K user memory, the 1170 also offers the convenience and economics of the diskette storage medium.

This processor will support virtually all the standard software designed to run on the 5500 Advanced Business Processor, including a version of the DATASHARE Business Timesharing System developed especially for diskettes. This diskette-based DATASHARE package, designated DS41170, can be configured with up to four video display 3600 or 3610 Datastations, and will support the remote file processing (DSNET) and real-time telecommunications (MULTILINK) enhancements of DATASHARE 4.

The Datapoint 1170 also functions as a stand-alone business computing facility. The 48K processor will both compile and execute application programs in DATABUS, RPGII, BASIC and COBOL. The system is available with two, three, or four diskette drives, for a maximum on-line storage capacity of one million characters. The four-drive model is required for the DATASHARE implementation.

The 1170 will accommodate a wide variety of printers, terminals, and synchronous and asynchronous communications interfaces for a truly versatile networking capability.

## Functional Characteristics

- 2 sets of eight 8-bit program accessible registers
- 16 deep pushdown stack
- 4-bit instruction modification register
- Multi-byte (string) instructions
- Address manipulation instructions
- High-speed parallel I/O system
- Block transfer instructions

### Keyboard:

- Standard typewriter, 55 keys
- 11-key numeric pad
- 5 control keys
- Audio tones

### Video Display:

- 7x3.5 inch viewing area
- 80 columns by 12 rows
- 960 character positions
- Upper and lower case, plus special characters
- 5x7 dot matrix for high legibility
- Programmable display memory allows generation of 128 characters under program control
- High-speed character display

### Diskettes:\*

- Up to four drives
- 256,256 characters/drive
- Average access time of 83 milliseconds
- Completely processor controlled

\* See Diskette listing in the catalog for detailed specifications

### Memory:

- 4K system memory restriction
- 48K user memory, maximum
- 0.8 microsecond cycle time
- Parity checking
- Parity bit
- Memory allocation
- Memory protection

## Physical Characteristics

### Equipment Dimensions:

- Width: 53.0 in. (134.6 cm)
- Height: 28.0 in. (71.1 cm)
- Depth: 24.0 in. (60.9 cm)
- Weight: 247 lbs. (112 kg)

### Power Requirements:

- 115 VAC, 50 or 60 Hz
- (240 VAC, 50 or 60 Hz optional)

### Environment:

- 50 to 100 degrees F
- 10 to 38 degrees C
- 40 to 60% relative humidity, non-condensing

## Model Codes

- 1172 Datapoint Diskette 1170  
Two Diskette Drives, 115 VAC, 50 or 60 Hz
- 1173 Datapoint Diskette 1170  
Three Diskette Drives
- 1174 Datapoint Diskette 1170  
Four Diskette Drives
- 5163 240 VAC, 50 or 60 Hz Power Option