

# LP14/11/05

LINEPRINTER TEST  
MD-11-DZLPK-F

EP-DZLPK-F-DL-A  
COPYRIGHT © 1977  
FICHE 1 OF 1

APR 1977  
**digital**  
MADE IN USA

The image displays a grid of 14 columns and 11 rows of small, illegible data tables or charts. Each cell contains a small table with multiple columns and rows of text and numbers. The content is too small to read but appears to be a series of test results or data points for a lineprinter. The tables are arranged in a regular grid pattern across the left side of the page.

14  
11  
05



46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93

CONTENTS

- 1.0 ABSTRACT
- 2.0 REQUIREMENTS
  - 2.1 EQUIPMENT
  - 2.2 STORAGE
  - 2.3 PRELIMINARY PROGRAMS
- 3.0 LOADING PROCEDURE
  - 3.1 METHOD
- 4.0 STARTING PROCEDURE
  - 4.1 CONTROL SWITCH SETTINGS
  - 4.2 STARTING ADDRESS OR ADDRESSES
  - 4.3 PROGRAM AND/OR OPERATOR OPERATION
- 5.0 OPERATING PROCEDURE
  - 5.1 OPERATIONAL SWITCH SETTINGS
  - 5.2 ABSENCE OF HARDWARE SWITCH REGISTER
  - 5.3 IOT CHANGES
- 6.0 ERRORS
  - 6.1 COMPUTER DETECTED ERRORS
  - 6.2 VISUALLY DETECTED ERRORS



95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125

- 7.0 TEST DESCRIPTIONS
- 7.1 TEST 1 CONTROL AND OPERATOR INTERACTION
  - 7.1.1 TEST 1 SECTION 1 PRINTER READY TESTS POWER UP
  - 7.1.2 TEST 1 SECTION 2 MANUAL PRINT SPEED TEST
  - 7.1.3 TEST 1 SECTION 3 TOP OF FORM SWITCH TEST
  - 7.1.4 TEST 1 SECTION 4 DAVFU TESTS
- 7.2 PRINTING TESTS
  - 7.2.1 TEST 2 DATA TRANSFER PATHS TEST
  - 7.2.2 TEST 3 CHARACTER GENERATOR AND COMPARATOR TESTS
  - 7.2.3 TEST 4 OVER PRINT TEST
  - 7.2.4 TEST 5 SHUTTLE POSITIONING TEST
  - 7.2.5 TEST 6 PRINT CONTROL TEST
  - 7.2.6 TEST 7 MULTIPLE LINE ADVANCE TEST
  - 7.2.7 TEST 8 HIGH SPEED PRINT TEST
  - 7.2.8 TEST 9 SINGLE CHARACTER, ALL COLUMNS TEST
  - 7.2.9 TEST 10 DRUM PATTERN TEST
  - 7.2.10 TEST 11 RIGHT & LEFT HAND WEDGES
  - 7.2.11 TEST 12 HAMMER ALIGNMENT TEST
  - 7.2.12 TESTS D1&D2 DAVFU - LINE COUNT SLEWING TEST
  - 7.2.13 TEST D3 DAVFU - CHANNEL SLEWING TEST
- 7.3 SCOPE DRIVE TEST

127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178

## 1.0 ABSTRACT

THE LINE PRINTER DIAGNOSTIC PROGRAM IS DIVIDED INTO THREE SECTIONS. INTERNALLY DETECTED ERROR CONDITIONS ARE DISPLAYED ON THE TELEPRINTER, WHILE BRIEF DESCRIPTIONS OF EACH ERROR ARE PRESENTED IN THE LISTING. PRINT PATTERNS USED IN THESE TESTS HAVE BEEN CHOSEN FOR EASE OF VISUAL VERIFICATION.

THE FIRST SECTION IS DESIGNED TO CHECK-OUT THE PROCESSOR INTERFACE CONTROL ELECTRONICS AND THE INTER-COMMUNICATIONS DATA PATHS. IT WILL ALSO PERFORM ALL TESTS THAT REQUIRE OPERATOR INTERVENTION. THE SECOND SECTION IS A PRINTING TEST DESIGNED TO TEST THE LINE PRINTER MECHANISM ITSELF. THE LAST SECTION IS A SCOPE DRIVER ROUTINE FOR USE IN TROUBLE SHOOTING THE PRINTER INTERFACE.

## 2.0 REQUIREMENTS

## 2.1 EQUIPMENT

THIS DIAGNOSTIC SHOULD RUN ON ALL PDP-11 FAMILY COMPUTERS HAVING LINE PRINTER CONTROLS, LINE PRINTERS, AND TELETYPES COMPATIBLE WITH THE FOLLOWING:

LPC11	LINE PRINTER INTERFACE
LP05	DATAPRODUCTS 132 COLUMN 64 OR 96 CHARACTER LINE PRINTER
LP11	DATAPRODUCTS 132 COLUMN 64 OR 96 CHARACTER LINE PRINTER
LP14	DATAPRODUCTS 132 COLUMN 64 OR 96 CHARACTER LINE PRINTER
TELETYPE MODEL 33 OR EQUIVALENT CONSOLE UNIT	

## 2.2 STORAGE

MEMORY LOCATIONS 0 - TO - 17004 ARE USED BY THIS DIAGNOSTIC.

## 2.3 PRELIMINARY PROGRAMS

ALL APPLICABLE PDP-11 DIAGNOSTICS SHOULD RUN ON THE PROCESSOR AND TELETYPE.

180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228

3.0 LOADING PROCEDURE

3.1 METHOD

POWER DOWN THE LINE PRINTER

POWER UP THE PROCESSOR ONLY

LOAD THE BOOTSTRAP AND ABSOLUTE LOADERS

LOAD THE LP11/LP05 DIAGNOSTIC PROGRAM TAPE

4.0 STARTING PROCEDURE

4.1 CONTROL SWITCH SETTINGS

SET CONTROL SWITCHES AS DESIRED - (SEE SECTION 5.1 FOR DESCRIPTION OF SWITCH FUNCTIONS) MAKE SURE SWITCH 0 IS DOWN BEFORE STARTING THE TEST.

4.2 STARTING ADDRESS OR ADDRESSES

THE INITIAL STARTING ADDRESS TO RUN THE ENTIRE LP14/LP11/LP05 DIAGNOSTIC IS LOCATION 200(8). TO SKIP THE OPERATOR INTERVENTION TESTS AND START WITH THE PRINTING TESTS, START AT LOCATION 600(8). TO RUN THE SPECIAL SCOPE DRIVER ROUTINE USE START ADDRESS 700(8) OR 720(8). TO START AT ANY OTHER TEST USE THE START ADDRESS FROM THE FOLLOWING TABLE:

START ADDRESS	TEST
300	DAVFU ILLEGAL LOAD TEST
304	DAVFU NO STOP BIT TEST
310	DAVFU LINE COUNT SLEW TEST
314	DAVFU CHANNEL SLEW TEST
400	PRINT SPEED TEST USING MANUAL TIMING
404	PRINT SPEED TEST USING KW11-L
410	PRINT SPEED TEST USING KW11-P
414	CHECK TOP OF FORM SWITCH SETTINGS

230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272

600	TEST 2 INTERFACE & DATA PATHS TEST (ALSO GENERAL PRINT TEST STARTING ADDRESS)
610	TEST 3 CHAR COMPARATOR TEST
614	TEST 4 OVER PRINT TEST
620	TEST 5 SHUTTLE POSITIONING TEST
624	TEST 6 PRINT CONTROL TEST
630	TEST 7 MULTIPLE LINE ADVANCE TEST
634	TEST 8 HIGH SPEED PRINT TEST
640	TEST 9 SINGLE CHAR. ALL COLUMNS
644	TEST 10 DRUM PATTERN CHAR TEST
650	TEST 11 SPURIOUS HAMMER FIRING TESTS (LEFT & RIGHT WEDGES)
654	TEST 12 HAMMER ALIGNMENT
700	SCOPE DRIVER ROUTINE
720	SCOPE DRIVER WITHOUT LINE FEEDS

THE PROGRAM WILL START THROUGH THE TEST SEQUENCE BEGINNING WITH THE  
SELECTED TEST UNLESS SWITCH 12 IS SET TO LOOP ON TEST (SEE SECTION  
5.1)

#### 4.3 PROGRAM AND/OR OPERATOR ACTION

DURING INITIAL START-UP OF THE LINE PRINTER DIAGNOSTIC TEST, THE  
HEADER MESSAGE "LPOS/LP11/LP14 LINE PRINTER TEST" WILL BE TYPED OUT ON THE  
TELEPRINTER FOLLOWED BY EXECUTION OF THE PRINTER READY PORTION OF TEST  
1. PRINTING OF THE MESSAGE "POWER-UP" ON THE TELEPRINTER FOLLOWING  
THE TEST HEADER PRINT-OUT INDICATES START OF THIS TEST SEQUENCE. THIS  
TEST IS CARRIED OUT BY AN INTERACTIVE EXCHANGE BETWEEN THE OPERATOR  
AND THE TEST PROGRAM. THE OPERATIONAL DESCRIPTION OF THIS TEST  
APPEARS AS PART OF THE TEST DESCRIPTION FOR TEST 1 (SEE SECTION  
7.1.1). AFTER SUCCESSFUL COMPLETION OF THIS SECTION OF TEST 1, THE  
PRINT SPEED AND TOP OF FORM SWITCH SETTINGS TESTS WILL BE PERFORMED.  
(SEE SECTIONS 7.1.2 AND 7.1.3 RESPECTIVELY.) IF THE DAVFU IS AVAILAABLE  
AND SWITCH 14 IS SET, THE DAVFU TESTS WILL ALSO BE PERFORMED. AFTER  
COMPLETION OF ALL OF TEST 1, PRESS CONTINUE TO ENTER THE PRINTING  
TESTS DIRECTLY. NO OTHER OPERATOR ACTION WILL BE REQUIRED.

274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329

## 5.0 OPERATING PROCEDURE

### 5.1 OPERATIONAL SWITCH SETTINGS

THE USE OF THIS PROGRAM ON PROCESSORS NOT HAVING A HARDWARE SWITCH REGISTER NECESSITATES OPERATOR INTERACTION; THE OPERATOR MUST SET UP LOCATION 174 WITH THE SOFTWARE DISPLAY VALUES AND LOCATION 176 WITH THE SOFTWARE SWITCH VALUES. (SEE SECTION 5.2)

SWITCH	FUNCTION IN "UP" POSITION
15	LOOP ON ERROR (IN TEST : ONLY)
14	OPTIONAL DAVFU AVAILABLE
13	DOWN - 64 CHARACTER SET UP - 96 CHARACTER SET
12	LOOP ON TEST
11	SEND ONLY ONE CHARACTER TO LINE PRINTER IN SCOPE DRIVER - THEN HALT
10	UP - LP14 DOWN - LPOS/LP11
0	USED FOR PRINT SPEED MANUAL TIMING IF NO CLOCK AVAILABLE

#### 1. SWITCH - 0

TO START PRINTING IN THE MANUAL PRINT SPEED TEST, PLACE SWITCH 0 IN THE UP POSITION. AT THE END OF ONE MINUTE PUT SWITCH 0 DOWN. THE APPROXIMATE PRINT SPEED WILL BE PRINTED ON BOTH THE LINE PRINTER AND THE TELEPRINTER. SWITCH 0 IS NOT USED IN ANY OTHER TESTS. MAKE SURE SWITCH 0 IS DOWN AT THE START OF THE TEST IF USING MANUAL TIMING OR UP IF USING AN INTERNAL CLOCK OPTION (KW11-L OR KW11-P).

#### 2. SWITCH - 10

SWITCH 10 SHOULD BE SET IN THE UP FOR TESTING THE LP14 LINE PRINTER. SWITCH 10 SHOULD BE SET DOWN FOR TESTING THE LPOS/LP11 LINE PRINTER.

#### 3. SWITCH - 11

SWITCH 11 IN THE UP POSITION CAUSES THE CONTENTS OF THE SWITCH REGISTER TO BE SENT ONLY ONCE TO THE LINE PRINTER THEN HALT IN THE SCOPE DRIVER ROUTINE. TO SEND ANOTHER CHARACTER, RESET SWITCHES AND DEPRESS CONTINUE. WITH SWITCH 11 DOWN, THE SWITCH REGISTER IS SENT CONTINUOUSLY TO THE LINE PRINTER



101

MAINDEC-11-DZLPK-E-D MACY11 2.(1006) 01-FEB-77 08:51 PAGE 7-1  
DZLPKF.P11 01-FEB-77 08:48

SEQ 0008

330  
331

WITH A LINE FEED SENT AFTER EVERY 132 CHARACTERS. TO STOP  
SENDING CHARACTERS, PUT SWITCH 11 UP.

333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388

4. SWITCH - 12

SWITCH 12 IN THE UP POSITION IS USED TO AUTOMATICALLY LOOP ON THE CURRENT TEST IF IN TESTS 2 TO 12. PLACING SWITCH 12 IN THE UP POSITION WILL FORCE THE PROGRAM TO CONSTANTLY LOOP ON THE CURRENT TEST. REPLACING THE SWITCH TO THE DOWN POSITION WILL MAKE THE PROGRAM RESUME ITS NORMAL TEST SEQUENCE AT THE COMPLETION OF THE CURRENT TEST.

5. SWITCH - 13

SWITCH 13 SHOULD BE SET UP IF THE 96 CHARACTER SET IS AVAILABLE. IF THE 64 CHARACTER SET IS USED SWITCH 13 SHOULD BE DOWN.

6. SWITCH - 14

SWITCH 14 SHOULD BE SET UP IF THE OPTIONAL DAVFU IS AVAILABLE AND IT IS DESIRED TO RUN THE DAVFU DIAGNOSTIC TESTS.

7. SWITCH - 15

WITH SWITCH 15 IN THE DOWN POSITION THE PROGRAM WILL HALT AFTER AN ERROR TYPE OUT IN TEST 1. WITH SWITCH 15 IN THE UP POSITION, THE PROGRAM WILL LOOP ON THE ERROR IN TEST 1.

REFER TO SECTION 6.1 TO CONTINUE AFTER AN ERROR DURING ANY OTHER TESTS.

5.2 ABSENCE OF HARDWARE SWITCH REGISTER

WHEN THE DIAGNOSTIC IS STARTED AT ADDRESS 200(8), IT WILL DETERMINE IF THE PROCESSOR HAS A HARDWARE (H/W) SWITCH REGISTER (SWR). IF THERE IS NO H/W SWR, THE DIAGNOSTIC WILL USE THE SOFTWARE (S/W) SWR LOCATED AT ADDRESS 176(8).

THE DIAGNOSTIC WILL PROMPT THE OPERATOR WITH THE MESSAGE:

SWR = XXXXXX NEW SWR =

THE FIRST TIME THE SWR VALUE IS NEEDED. ANY TIME THEREAFTER, THE OPERATOR MAY CHANGE THE VALUE OF THE SWR BY ENTERING A CONTROL-G (+G) AT THE CONSOLE.

IF THERE IS NO H/W SWITCH REGISTER AND THE DIAGNOSTIC IS TO BE STARTED AT AN ADDRESS OTHER THAN 200(8):

ENTER THE NUMBER 176(8) IN LOCATION 1004(8)

ENTER THE INITIAL VALUE OF THE SWR IN LOCATION 176(8).

389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443

AFTER EXECUTION BEGINS, THE OPERATOR MAY CHANGE, AT ANY TIME,  
THE VALUE OF THE SWR BY ENTERING A CONTROL-G (↑G) AT THE CONSOLE.

THE FOLLOWING COMMANDS ALLOW THE OPERATOR TO MODIFY THE  
S/W SWR:

CONTROL-G (↑G): ALLOWS MODIFICATION OF THE S/W SWR.  
ENTERING A ↑G WILL RESULT IN THE FOLLOWING  
MESSAGE OUTPUT AT THE CONSOLE

SWR = XXXXXX NEW SWR =

THE OPERATOR MAY THEN ENTER UP TO SIX (6) OCTAL DIGITS.  
THE DIGITS MAY BE ANY COMBINATION OF :0,1,2,3,4,5,6,7,OR  
NO ENTRY AT ALL.  
ALL SWR VALUES ENTERED WILL BE TRUNCATED TO THE  
LOWER SIXTEEN (16) BITS.  
ENTERING MORE THAN SIX DIGITS OR A CHARACTER OTHER THAN A DIGIT  
RESULTS IN A "?" OUTPUT ON THE CONSOLE AND A REPEAT OF  
THE PROMPTING MESSAGE.

CARRIAGE RETURN (CR): ENTERS THE NEW SWR VALUE. IF NO  
DIGITS HAVE BEEN ENTERED, THE SWR VALUE REMAINS UNCHANGED.

CONTROL-U (↑U): ERASES THE SWR VALUE BEING ENTERED. A  
CARRIAGE RETURN AND LINE FEED WILL BE OUTPUT AT THE  
CONSOLE. THE CORRECT SWR VALUE MAY THEN BE ENTERED.

ENTERING ANY CHARACTER BEFORE A CONTROL-G (↑G) HAS  
BEEN ENTERED WILL RESULT IN A "?" OUTPUT AT THE CONSOLE.

NOTE: IT IS POSSIBLE FOR THE DIAGNOSTIC TO  
OUTPUT MESSAGES AT THE CONSOLE BEFORE THE NEW SWR  
VALUE HAS BEEN ENTERED. SHOULD THIS HAPPEN, THE  
OPERATOR SHOULD ENTER A CONTROL-U (↑U) AND THEN  
ENTER THE CORRECT SWR VALUE.

### 5.3 IOT CHANGES

THE LINE PRINTER STATUS IS LOCATION 177514 AS USED BY THE PROGRAM.  
THE LINE PRINTER VECTOR ADDRESS IS LOCATION 1030 AS USED BY THE PROGRAM.  
THE LINE PRINTER PSW IS LOCATION 1032 AS USED BY THE PROGRAM  
THE LINE PRINTER BUFFER IS LOCATION 177516 AS USED BY THE PROGRAM.

FOR OTHER THAN THESE, PLACE THE CORRECT STATUS LOCATION IN LOCATION  
1000(8) AND THE CORRECT BUFFER LOCATION IN LOCATION 1002(8), THE  
CORRECT VECTOR ADDRESS IN LOCATION 1030(8) AND THE CORRECT PSW IN  
LOCATION 1032(8) .

445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497

## 6.0 ERRORS

## 6.1 COMPUTER DETECTED ERRORS

THE FOLLOWING DISCUSSION DESCRIBES (IN GENERAL) THE METHOD USED FOR INTERNAL ERROR DETECTION AND ERROR DISPLAY BY THE LINE PRINTER DIAGNOSTIC PROGRAM. MONITORING OF THE CURRENT CONDITION OF THE READY LINE AFTER EACH OPERATION IS CARRIED ON CONTINUOUSLY DURING ALL TESTS WHERE APPROPRIATE AND IS DESCRIBED IN THE FOLLOWING PARAGRAPHS. HOWEVER, ADDITIONAL TESTING IS PERFORMED ESPECIALLY DURING EXECUTION OF THE FIRST TEST. FOR A COMPLETE DESCRIPTION OF THE TESTING PROCEDURES USED IN TEST 1 AND THE CORRESPONDING ERROR CONDITIONS, THE READER IS REFERRED TO THE DESCRIPTION OF THE TEST AND THE TEST LISTING.

ERROR PRINT-OUTS ARE LIMITED TO THE ERROR NUMBER (ERROR COUNT). ADDITIONAL INFORMATION MAY BE OBTAINED FROM THE TEST DESCRIPTION OR FROM THE LISTING. TO FIND THE ERROR IN THE LISTING, SEE THE SYMBOL TABLE AT THE END OF THE LISTING TO FIND THE LOCATION OF THE ERROR.

ERROR TAGS WILL BE LISTED AS "ERRXX" WHERE XX = ERROR NUMBER.

IN GENERAL, THE TEST PROGRAM MONITORS PROPER OPERATION OF THE LINE PRINTER AFTER EACH PRINTER OPERATION HAS BEEN COMPLETED, THROUGH THE PRINTER "READY" LINE AND THE SETTING OF THE CHARACTER FLAG OF THE PRINTER "DEMAND" RETURN LINE. WITH REGARDS TO THE READY LINE, THE FOLLOWING ERROR CONDITIONS, IF DETECTED WITHIN THE LINE PRINTER ITSELF, WILL CAUSE THE READY LINE TO DROP:

1. PAPER OUT OR TORN
2. DRUM GATE OPEN
3. RIBBON STALL CONDITION
4. POWER SUPPLY FAULT
5. HAMMER BANK FAULT
6. DAVFU ERROR (IF AVAILABLE)
7. SWITCHED OFF LINE

IT SHOULD BE NOTED THAT THE "DEMAND" RETURN FROM THE PRINTER IS CONDITIONAL UPON THE PRINTER "READY" AND THEREFORE THESE ITEMS SHOULD BE CHECKED FIRST IN CASE OF DIFFICULTY.

499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551

## 6.2 VISUALLY DETECTED ERRORS

SINCE THE COMPUTER CAN ONLY DETECT THE CURRENT CONDITION OF THE READY AND DEMAND RETURN LINES AND DOES NOT RECEIVE ANY ADDITIONAL DATA BACK FROM THE LINE PRINTER, IT IS NECESSARY TO EXAMINE THE PRINT PATTERNS PRODUCED BY THE VARIOUS TEST ROUTINES OR RESORT TO MANUAL SCOPING PROCEDURES, AS PROVIDED BY THE SCOPE DRIVER ROUTINE, TO DETECT AND DIAGNOSE ADDITIONAL DIFFICULTIES. DETAILED DESCRIPTIONS OF EACH TEST PATTERN APPEARS IN THE DESCRIPTION OF THE CORRESPONDING TEST ROUTINES.

## 7.0 TEST DESCRIPTIONS

## 7.1 TEST 1 - CONTROL TESTS AND OPERATOR INTERACTIVE TESTS

TEST 1 IS MADE UP OF FOUR SECTIONS LINKED TOGETHER AND EXECUTED IN SEQUENCE AS A SINGLE TEST. THE FOLLOWING DESCRIPTIONS TREAT EACH SECTION SEPARATELY.

## 7.1.1 TEST 1 - SECTION 1 - COMMAND DECODE, CONTROL INTERFACE

THIS PORTION OF TEST 1 IS DESIGNED AS A COMMAND DECODE AND CONTROL INTERFACE TEST AND INCLUDES CHECKOUT OF THE PRINTER INTERRUPT FACILITY. UPON INITIAL ENTRY INTO THIS ROUTINE, MANUAL INTERVENTION IS REQUIRED TO TEST THE VARIOUS TESTABLE ERROR (NON-READY) CONDITIONS OF THE PRINTER. THE OPERATING SEQUENCE IS DESCRIBED IN DETAIL BELOW.

THE PRINTER READY LINE CONTINUOUSLY MONITORS THE FOLLOWING CONDITIONS WITHIN THE PRINTER AND ITS TRUE STATE AT THE CONTROL ELECTRONICS INTERFACE IS CONDITIONAL UPON NONE OF THEM EXISTING:

1. PAPER OUT OR TORN
2. DRUM GATE OPEN
3. RIBBON STALL CONDITION
4. POWER SUPPLY FAULT
5. HAMMER BANK FAULT
6. DAVFU ERROR (IF AVAILABLE)
7. SWITCHED OFF LINE

THE MANUAL-INTERACTIVE TEST SEQUENCE WHICH FOLLOWS IS DESIGNED TO TEST THE PROPER OPERATION OF THE READY LINE AS IT APPEARS AT THE INTERFACE ELECTRONICS WITH RESPECT TO THOSE OF THE ABOVE ITEMS WHICH ARE TESTABLE (I.E. - A,B,F&G) INITIAL MANUAL TEST SEQUENCE:

1. AFTER "POWER ON - TURN ON LINE" HAS BEEN TYPED ON THE TELEPRINTER BRING POWER - UP ON THE LINE PRINTER AND TURN ON LINE, MAKING SURE THAT THE PAPER IS IN PLACE IN THE TRACTORS AND THAT THE DRUM GATE IS CLOSED.

553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603

2. DEPRESS CONTINUE, "READY SET OK - TRY TORN PAPER SWITCH" WILL BE TYPED OUT IF PRINTER IS ON LINE AND NO ERRORS EXIST.
3. PAPER - TEAR THE PAPER OFF BELOW THE PRINTER DRUM GATE AND USE THE MANUAL TOP OF FORM SWITCH TO DRIVE ALL THE PAPER OUT OF THE PRINTER AND OBSERVE THAT THE PRINTER READY LIGHT GOES OUT AND THE PAPER ERROR LIGHT GOES ON ON THE PRINTER CONTROL PANEL. ATTEMPT TO PLACE THE PRINTER ON LINE. THE ON-LINE AND READY LIGHTS ON THE PRINTER CONTROL PANEL SHOULD REMAIN OFF.
4. DEPRESS CONTINUE, AN ERROR TYPE-OUT (ERROR COUNT 2) WILL OCCUR IF THE PRINTER READY LINE REMAINS HIGH AT THE INTERFACE ELECTRONICS.
5. READY - AFTER SUCCESSFUL COMPLETION OF STEPS 3 AND 4 THE MESSAGE "ERROR SET OK - TURN ON LINE" WILL BE TYPED. RESTORE PAPER TO THE TRACTORS, CLOSE THE DRUM GATE AND PLACE THE PRINTER IN THE READY-ON LINE STATE. OBSERVE THAT BOTH THE ON-LINE AND READY LIGHTS COME ON ON THE PRINTER CONTROL PANEL.
6. DEPRESS CONTINUE, AN ERROR TYPE-OUT (ERROR COUNT 4) WILL OCCUR IF THE PRINTER READY LINE DOES NOT GO HIGH AT THE INTERFACE ELECTRONICS.
7. DRUM GATE - AFTER SUCCESSFUL COMPLETION OF STEPS 5 & 6 THE MESSAGE "READY SET OK-TRY, DRUM GATE SWITCH" WILL BE TYPED. OPEN THE PRINTER DRUM GATE AND OBSERVE THAT THE ON-LINE AND READY LIGHTS GO OUT AND THE DRUM GATE ERROR LIGHT GOES ON ON THE PRINTER CONTROL PANEL.
8. DEPRESS CONTINUE, AN ERROR TYPE-OUT (ERROR COUNT 5) WILL OCCUR IF THE PRINTER READY LINE APPEARS TO REMAIN HIGH AT THE INTERFACE ELECTRONICS.
9. READY - AFTER SUCCESSFUL COMPLETION OF STEPS 7 & 8 THE MESSAGE "ERROR SET OK - TURN ON LINE" WILL BE TYPED.
10. DEPRESS CONTINUE TO COMPLETE THE COMMAND AND REGISTER TESTING ALONG WITH THE INTERRUPT TESTING. IF ANY ERROR CONDITIONS EXIST, ERROR TYPE-OUTS GIVING THE ERROR COUNT WILL BE PRINTED. CHECK THE LISTING FOR DESCRIPTIONS OF THESE ERRORS.
11. SECTION 2 OF TEST 1 WILL BE ENTERED DIRECTLY UPON COMPLETION OF SECTION 1.



605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655

## 7.1.2 TEST 1 - SECTION 2 - PRINT SPEED TIMING TEST.

THIS SECTION OF TEST 1 IS DESIGNED TO TIME THE PRINTER FOR ONE FULL MINUTE. DURING THIS TIME THE PRINTER WILL PRINT THE DIAGNOL OF THE DRUM PATTERN SO THAT ONLY TWO HAMMERS (MAXIMUM) WILL FIRE AT ANY GIVEN INSTANT AND MAXIMUM PRINT TIME IS USED FOR EACH LINE.

IF A KW11-L OR KW11-P ARE AVAILABLE THEY WILL BE USED TO TIME THE PRINTER. IF BOTH ARE AVAILABLE, THE KW11-L WILL BE USED. IF NEITHER ARE AVAILABLE, MANUAL TIMING WILL BE USED. WHEN MANUAL TIMING IS USED INSTRUCTIONS WILL BE TYPED ON THE TELEPRINTER. TO START THE TIMING PLACE SWITCH 0 IN THE UP POSITION. AT THE END OF ONE FULL MINUTE PLACE SWITCH 0 IN THE DOWN POSITION TO STOP THE TIMING. IF USING AN INTERNAL CLOCK FOR TIMING, PLACE SWITCH 0 IN THE UP POSITION BEFORE STARTING THE TEST. WHICH EVER METHOD OF TIMING IS USED, AT THE END OF ONE FULL MINUTE THE APPROXIMATE PRINT SPEED WILL BE TYPED ON BOTH THE TELEPRINTER AND LINE PRINTER.

IF BOTH A KW11-L OR KW11-P ARE AVAILABLE OR IT IS DESIRED TO MANUALLY TIME THE PRINTER IF EITHER IS AVAILABLE USE THE FOLLOWING START ADDRESSES TO RUN THE DESIRED PRINT SPEED TIMING TEST:

400 FOR MANUAL TIMING  
404 FOR KW11-L  
410 FOR KW11-P

NOTE: IF THE LINE FREQUENCY IS 50 HZ. CHANGE THE CONTENTS OF "MINCNT TO 5670(B) ... REFER TO THE END OF THE PRINTING ROUTINE. (SEARCH FOR "MINCNT" IN THE CROSS REFERENCE LISTING)

SECTION 3 OF TEST 1 WILL BE ENTERED DIRECTLY AFTER COMPLETION OF SECTION 2.

## 7.1.3 TEST 1 - SECTION 3 - TOP OF FORM SWITCH TEST

THIS TEST CHECKS ALL POSITIONS OF THE TOP OF FORM SWITCH. THE PROGRAM WILL GIVE THE CORRECT SETTINGS FOR THE TOP OF FORM SWITCH ON THE TELETYPE AND THEN WAIT FOR THE OPERATOR. AFTER SETTING THE SWITCH, DEPRESS CONTINUE TO TEST THAT SWITCH POSITION. AFTER CHECKING ALL POSITIONS THE PRINTER OUTPUT CAN BE MANUALLY VERIFIED. A LINE OF ALL DASHES IS PRINTED AS A STARTING POINT FOR EACH SETTING AND THEN A LINE IS PRINTED TELLING THE PROPER SPACING (IN INCHES) FROM THE DASHED LINE TO THAT LINE.

UPON COMPLETION OF THIS SECTION OF TEST 1 THE MESSAGE "TURN ON DAVFU IF AVAILABLE AND RESET TOP OF FORM SWITCH TO 11 INCHES" WILL BE TYPED, THEN THE PROGRAM WILL HALT. RESET THE TOP OF FORM SWITCH TO 11 INCHES AND TURN ON THE DAVFU (IF AVAILABLE).

657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709

DEPRESS CONTINUE TO ENTER DIRECTLY INTO THE PRINTING TEST SEQUENCE STARTING WITH TEST 2 IF THE DAVFU IS NOT AVAILABLE (SWITCH 14 DOWN). IF THE DAVFU IS AVAILABLE (SWITCH 14 UP) SECTION 4 OF TEST 1 WILL BE ENTERED DIRECTLY AFTER DEPRESSING CONTINUE.

#### 7.1.4 TEST 1 - SECTION 4 - DAVFU ERROR TESTS

THIS SECTION OF TEST 1 CONTAINS TWO PARTS DESIGNED TO TEST THE DAVFU ERROR CONDITIONS. THE FIRST PART OF THIS TEST ATTEMPTS TO LOAD THE DAVFU WITH INCOMPLETE DATA (AN ODD NUMBER OF DATA WORDS) BETWEEN THE START LOAD AND STOP LOAD COMMANDS. THIS SHOULD CAUSE A FORMAT ERROR TO OCCUR IN THE LINE PRINTER. FAILURE TO CAUSE AN ERROR IN THE LINE PRINTER WILL CAUSE AN ERROR TYPE-OUT "ERROR COUNT 27" TO OCCUR. UPON SUCCESSFUL COMPLETION OF THIS PART OF THE TEST THE MESSAGE "ERROR SET OK - CLEAR AND TURN ON LINE" WILL BE TYPED. CLEAR THE FORMAT ERROR IN THE PRINTER AND PLACE THE PRINTER IN THE READY - ON LINE STATE. PART TWO OF THIS TEST WILL NOW BE EXECUTED TO TEST THAT CHANNEL SLEW COMMANDS REFERENCING CHANNELS WITH NO STOP BITS WILL CAUSE AN ERROR IN THE LINE PRINTER. THE DAVFU WILL BE LOADED WITH ALL ZEROS BETWEEN THE START LOAD AND STOP LOAD COMMANDS. EACH CHANNEL WILL THEN BE TESTED IN SEQUENCE STARTING WITH CHANNEL 0. IF THE ERROR DOES NOT OCCUR MESSAGE "ERROR COUNT 31" WILL BE TYPED. UPON SUCCESSFUL COMPLETION OF THE TEST ON EACH CHANNEL A MESSAGE "ERROR SET OK - CLEAR AND TRY NEXT CHANNEL" WILL BE TYPED. AFTER THIS MESSAGE, CLEAR THE PRINTER ERROR AND PRESS CONTINUE. THE DAVFU WILL THEN BE RELOADED WITH ALL ZEROS AND THE NEXT CHANNEL WILL BE TESTED. UPON SUCCESSFUL COMPLETION OF THIS TEST, THE MESSAGE "ERROR SET OK - CLEAR AND TURN ON LINE" WILL BE TYPED. CLEAR THE PRINTER ERROR AND PLACE THE PRINTER IN THE READY, ON-LINE STATE. DEPRESS CONTINUE TO ENTER THE PRINTING TEST SEQUENCE DIRECTLY STARTING WITH TEST 2.

#### 7.2 LINE PRINTER PRINTING TESTS

TESTS 2 TO 12 PRODUCE VARIOUS PRINT PATTERNS DESIGNED FOR EASE OF VISUAL VERIFICATION. THESE TESTS CHECK ALL OF THE VARIOUS PRINTING ASPECTS OF THE PRINTER. DETAILED DESCRIPTIONS OF EACH INDIVIDUAL TEST FOLLOWS.

##### 7.2.1 TEST 2 - DATA TRANSFER PATHS TEST

THIS TEST IS DESIGNED TO TEST THE DATA TRANSFER PATHS (WITH ALTEPNATING ONES AND ZEROS), FROM THE PROCESSOR INTERFACE, THRU THE LINE PRINTER INPUT REGISTER, AND INTO THE PRINTER'S BUFFER. AN ALTERNATING STRING OF "\*" AND "U" CHARACTERS ARE TRANSMITTED TO THE PRINTER ON A FULL 132 COLUMN BASIS. SINCE THESE CHARACTERS ARE COMPLIMENTARY BITWISE, THEY PROVIDE BOTH A ONES AND ZEROES CHECK OF ALL TRANSMISSION LINES. END OF LINE IS SENSED WITHIN THE PROCESSOR AND A LINE FEED CHARACTER IS TRANSMITTED TO PRINT EACH LINE. PRINTING OF THE TEST LINE IS REPEATED 32 TIMES, ALTERNATING THE COLUMN POSITIONS OF THE "\*" AND "U" CHARACTERS TO PRODUCE A CHECKER-BOARD PATTERN.

711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765

## 7.2.2 TEST 3 - CHARACTER GENERATOR AND COMPARATOR TEST

TEST 3 IS DESIGNED PRIMARILY TO TEST THE LINE PRINTER CHARACTER GENERATOR AND COMPARATOR LOGIC AND ITS ABILITY TO DETECT AND ACT UPON BOTH PRINTABLE AND ILLEGAL (NON-PRINTING) CHARACTERS. A SERIES OF ALL 64 OR 96 PRINTABLE CHARACTERS ARE TRANSMITTED IN SEQUENCE TO THE LINE PRINTER AND PRINTED ON A SINGLE LINE BEGINNING WITH THE SPACE CHARACTER. THIS IS FOLLOWED BY AN ALTERNATE LINE OF ALL 64 OR 32 ILLEGAL CHARACTERS, EACH OF WHICH SHOULD BE CONVERTED TO A SPACE CHARACTER PRODUCING NO VISIBLE PRINTING. THIS SEQUENCE OF ALTERNATING ALL PRINTABLE CHARACTERS FOLLOWED BY ALL ILLEGAL CHARACTERS IS REPEATED 10 TIMES ALONG WITH AN EXTRA LINE OF ILLEGAL CHARACTERS INSERTED AT THE BEGINNING OF THE TEST TO PRODUCE 21 LINES OF PRINT (11 OF WHICH WILL BE BLANK).

## 7.2.3 TEST 4 - OVER PRINT TEST

THIS TEST CHECKS THE CARRIAGE RETURN (015) CONTROL FOR OVERPRINTING A LINE. THE TEST PRODUCES 24 LINES OF ALTERNATING E'S AND SPACES, OVERPRINTED WITH E'S AND SPACES IN THE SAME LOCATIONS. THE STARTING CHARACTER FOR EACH LINE IS ALSO ALTERNATED PRODUCING A CHECKERBOARD PATTERN. OVERPRINTED E'S SHOULD BE ALIGNED WITH THE FIRST E'S PRINTED.

## 7.2.4 TEST 5 - SHUTTLE POSITIONING TEST

THIS TEST CHECKS THE HAMMER SHUTTLE FOR CORRECT OPERATION. FULL LINES OF E'S ARE PRINTED BY PRINTING A PAIR OF E'S AT A TIME THEN OVERPRINTING THOSE E'S PRINTED WITH SPACES AND ADDING ANOTHER PAIR OF E'S TO THE LINE UNTIL THE LINE IS COMPLETED. THEN A FULL LINE OF M'S ARE PRINTED FOR COMPARISON. A TOTAL OF 16 LINES ARE PRINTED DURING THIS TEST. THERE IS NO SHUTTLE IN THE LP14 LINE PRINTER. EACH COLUMN HAS A HAMMER. THE PRINTER LOGIC SELECTS WHICH HAMMER IS TO FIRE.

## 7.2.5 TEST 6 - PRINT CONTROL TEST

THIS TEST CHECKS THE PRINT CONTROL LOGIC BY SENDING MORE THAN 132 CHARACTERS BEFORE SENDING A PRINT COMMAND. THE PRINTER SHOULD SAVE THE FIRST 132 CHARACTERS RECEIVED AND PRINT THEM CORRECTLY WHEN THE PRINT COMMAND IS RECEIVED. ALL CHARACTERS AFTER THE FIRST 132 SHOULD BE LOST. THE PROGRAM SENDS A FULL LINE OF 132 ZEROS THEN THE FULL CHARACTER SET BEFORE SENDING A LINE FEED TO PRINT THE LINE. THE PRINTED LINE SHOULD CONTAIN ONLY ZEROS. THIS IS REPEATED USING ONES, TWOS, THREES, FOURS, AND FIVES. THEN A LINE OF SPACES ARE SENT AND THE FULL CHARACTER SET BEFORE THE LINE FEED. A BLANK LINE SHOULD BE PRINTED. AFTER THE BLANK LINE, THE NUMBERS 6 TO 9 ARE SENT AS BEFORE. A TOTAL OF 11 LINES WILL BE PRINTED WITH THE MIDDLE LINE BLANK.

767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820

7.2.6 TEST 7 - MULTIPLE LINE ADVANCE TEST

THIS TEST CHECKS THE MULTIPLE LINE ADVANCE OF THE LINE PRINTER. A LINE OF NUMBERS IS PRINTED THEN THE PAPER IS ADVANCED THAT NUMBER OF LINES. THUS THE NUMBER PRINTED WILL INDICATE THE NUMBER OF BLANK LINES FOLLOWING THAT LINE. THE NUMBER IS VARIED BETWEEN 2 AND 9, AND A LINE OF ALL ZEROS WILL END THE TEST.

7.2.7 TEST 8 - HIGH SPEED PRINT TEST

THIS TEST PRINTS AT A SPEED GREATER THAN 300 LINES PER MINUTE (APPROXIMATELY 500 LINES PER MINUTE) BY PRINTING A FULL LINE OF THE DRUM PATTERN AND THEN SKIPPING FOUR (4) LINES AND PRINTING THAT DRUM LINE, ETC. THIS WILL TEST THE HAMMER SUPPLY FOR MAXIMUM CURRENT SURGE AND WILL TEST FOR WORST CASE NOISE SINCE ALL HAMMERS WILL FIRE AT ONCE ON EACH LINE.

7.2.8 TEST 9 - SINGLE CHAR, ALL COLUMNS TEST

THIS TEST IS DESIGNED AS AN ENDURANCE TEST OF THE LINE PRINTER AS WELL AS A CHARACTER CHECK OF THE DRUM. 132 COLUMNS OF EACH OF THE 64 OR 96 CHARACTERS ARE TRANSMITTED TO THE LINE PRINTER AND PRINTED IN ROTATION. A SAMPLE OF THE PRINT OUT FOLLOWS:

```
?????-----?????  
jjjjj-----jjjjj  
AAAAA-----AAAAA  
BBBBB-----BBBBB  
-----  
-----  
ZZZZZ-----ZZZZZ
```

7.2.9 TEST 10 - DRUM PATTERN TEST

THIS TEST IS DESIGNED TO PRODUCE AN IMAGE OF THE ENTIRE DRUM PATTERN. THIS IS A WORST CASE NOISE AND ENDURANCE TEST, AND A CHECK OF THE DRUM PATTERN.

7.2.10 TEST 11 - SPURIOUS HAMMER FIRING TEST

THIS TEST IS DESIGNED TO DETECT SPURIOUS HAMMER FIRINGS AND DEFECTIVE HAMMER DRIVERS DURING OPERATION OF THE LINE PRINTER. THE PATTERNS WHICH ARE PRODUCED ARE RIGHT AND LEFT HAND WEDGES, EACH COMPOSED OF 132 LINES OF PRINT AS FOLLOWS:

LEFT HAND WEDGE - WILL END EACH LINE WITH A "?" CHARACTER.

RIGHT HAND WEDGE - WILL START EACH LINE WITH A "?" CHARACTER.

ANY PRINT OUTSIDE OF THE WEDGE WILL BE CAUSED BY A HAMMER MISFIRE OR HAMMER BOUNCE.

822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867

## 7.2.11 TEST 12 - HAMMER ALIGNMENT TEST

THIS ROUTINE IS DESIGNED TO BE USED AS A DRIVER FOR MANUAL HAMMER ALIGNMENT AND INTENSITY ADJUSTMENTS ON THE LINE PRINTER. THIS TEST PRINTS A FULL 132 COLUMN LINE OF "E" CHARACTERS FOR 63 LINES.

## 7.2.12 TESTS D1 &amp; D2 - DAVFU LINE COUNT SLEWING TESTS

THIS TEST IS DESIGNED TO TEST THE LINE COUNT METHOD OF PAPER CONTROL USING THE DAVFU. BEFORE STARTING THIS TEST, A MESSAGE WILL BE TYPED INSTRUCTING THE OPERATOR THAT THE DAVFU TESTS ARE BEING RUN. THE DAVFU MEMORY WILL BE LOADED WITH DUMMY DATA, THEN EACH OF THE LINE COUNT SLEWING COMMANDS WILL BE TESTED IN TURN STARTING WITH A SLEW OF ZERO (0) LINES. IF THE SLEW OF ZERO LINES OPERATES CORRECTLY, THE MESSAGE "THIS LINE SHOULD BE PRINTED ALL ON ONE LINE --- IF SLEWED 0 LINES" WILL BE PRINTED ALL ON ONE LINE. THEN EACH OF THE REMAINING COMMANDS WILL BE TESTED. AFTER EACH SLEW, A LINE WILL BE PRINTED INDICATING THE CORRECT NUMBER OF BLANK LINES BETWEEN THE LAST PRINTED LINE AND THAT LINE. AFTER COMPLETION OF TEST D1, THE SEQUENCE IS REPEATED (TEST D2), CHANGING THE TWO (2) UNUSED BITS IN THE PAPER INSTRUCTION TO INSURE THEY HAVE NO EFFECT ON THE DAVFU. UPON COMPLETION OF TEST D2, TEST D3 IS ENTERED DIRECTLY.

## 7.2.13 TEST D3 - DAVFU CHANNEL SLEW COMMAND TEST

THIS TEST IS DESIGNED TO TEST THE CHANNEL SLEW COMMANDS ON THE DAVFU. THE DAVFU IS FIRST LOADED, THEN EACH OF THE CHANNELS IS TESTED IN TURN STARTING WITH CHANNEL 0. THE DATA PATTERNS (STOP BITS) LOADED INTO THE DAVFU ARE CHOSEN SUCH THAT NO TWO ADJACENT CHANNELS HAVE THE SAME PATTERN. CHANNELS 1 AND 7 WILL CAUSE ONE BLANK LINE BETWEEN EACH PRINTED LINE. CHANNELS 2 AND 8 WILL CAUSE TWO BLANK LINES BETWEEN EACH PRINTED LINE. CHANNELS 3 AND 9 WILL CAUSE THREE BLANK LINES BETWEEN EACH PRINTED LINE. CHANNELS 4 AND 10 WILL CAUSE SIX BLANK LINES BETWEEN EACH LINE. CHANNELS 5 AND 11 WILL CAUSE 24 LINES BETWEEN EACH PRINTED LINE. CHANNELS 6 AND 12 WILL CAUSE 143 BLANK LINES BETWEEN THE HEADER AND THE PRINTED REFERENCeline. BEFORE TESTING EACH CHANNEL, A HEADER MESSAGE IS PRINTED TELLING WHICH CHANNEL IS BEING TESTED. AFTER TESTING EACH SLEW COMMAND, A LINE IS PRINTED GIVING THE CORRECT NUMBER OF BLANK LINES FROM THE LAST PRINTED LINE TO THAT LINE. UPON COMPLETION OF THIS TEST THE DIAGNOSTIC WILL RESTART THE PRINTING TESTS WITH TEST 2.

869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894

## 7.3 SCOPE DRIVE ROUTINE

THE PROPOSE OF THIS TEST SEQUENCE IS TO PROVIDE THE OPERATOR WITH A SHORT BUT COMPREHENSIVE SCOPE DRIVER ROUTINE FOR USE IN TROUBLE SHOOTING THE P'INTER INTERFACE CONTROL MODULE WITH THE SCOPE. DEPENDING ON THE SETTING OF SWITCH 11 THIS TEST WILL EITHER CONTINUALLY SEND WHATEVER CHARACTER IS SET IN THE SWITCH REGISTER TO THE LINE PRINTER, OR ONLY SEND IT ONCE AND HALT. (SEE DESCRIPTION OF SWITCH 11 OPERATION IN SECTION 5.1)

TO INSERT A LINE FEED CHARACTER AFTER EVERY 132 CHARACTERS, WHEN SENDING CHARACTERS CONTINUOUSLY, START AT LOCATION 700(8).

TO LEAVE OUT THE LINE FEED, START AT LOCATION 710(8). THIS ROUTINE SHOULD BE USEFUL WHEN TROUBLE SHOOTING THE DAYFU.

WHEN SWITCH 11 IS UP, TO SEND ONLY ONE CHARACTER THEN HALT, DEPRESS CONTINUE TO SEND THE NEXT CHARACTER AFTER SETTING THE SWITCH REGISTER AS DESIRED. TO RESUME SENDING CONTINUOUS CHARACTERS, PLACE SWITCH 11 DOWN, SET THE SWITCHES, AND DEPRESS CONTINUE. TO STOP SENDING CONTINUOUSLY PLACE SWITCH 11 UP.

:ENDR  
:



896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951

.TITLE MAINDEC-11-DZLPK-E-D  
;COPYRIGHT (C) 1975,1974 DIGITAL EQUIPMENT CORP., MAYNARD, MASS.  
;\*\*\*\*\* LP14/LP11/LP05 LINE PRINTER TEST \*\*\*\*\*

;LIST OF SWITCH SETTINGS USED IN THIS TEST

SWITCH NO.	DESCRIPTION
15	LOOP ON ERROR IN TEST 1 ONLY !!!
14	OPTIONAL DAYFU AVAILABLE
13	"DOWN" 64 CHAR./"UP"-96 CHAR OPTION
12	LOOP ON TEST
11	SEND ONLY ONE CHAR TO LINE PRINTER IN SCOPE TEST - THEN HALT
10	DOWN - LP05/LP11, UP - LP14
0	USED TO TEST PRINT SPEED IN TEST 1 IF NO CLOCK IS AVAILABLE

000000	R0=%0
000001	R1=%1
000002	R2=%2
000003	R3=%3
000004	R4=%4
000005	R5=%5
000006	R6=%6
000007	R7=%7
000006	SP=R6
000007	PC=R7
100000	BIT15 =100000
040000	BIT14 =40000
020000	BIT13 =20000
010000	BIT12 =10000
004000	BIT11 =4000
002000	BIT10 =2000
001000	BIT9 =1000
000400	BIT8 =400
000200	BIT7 =200
000100	BIT6 =100
000040	BIT5 =40
000020	BIT4 =20
000010	BIT3 =10
000004	BIT2 =4
000002	BIT1 =2
000001	BIT0 =1
	.ENABLE ABS
	.ENABLE AMA
000000	.=0
000100	.REPT 100
	.+2
	HALT



```

1008 000410 000137 002546      JMP      KW11P      ;START FOR KW11-P LINE CLOCK
1009 000414 000137 003444      JMP      SLEWCK    ;CHECK TOP OF FORM SWITCH
1010
1011
1012
1013          000600          . =600
1014
1015 000600 012706 001000      MOV      #1000,%6  ;START OF PRINTING TESTS SEQUENCE
1016 000604 000137 004550      JMP      TEST2     ;TEST 2
1017 000610 000137 005012      JMP      TEST3     ;TEST 3
1018 000614 000137 005366      JMP      CHRCHK    ;TEST 4
1019 000620 000137 005650      JMP      OVRPRT    ;TEST 5
1020 000624 000137 006146      JMP      PRTCTL    ;TEST 6
1021 000630 000137 006446      JMP      MLF       ;TEST 7
1022 000634 000137 006662      JMP      HSPRT     ;TEST 8
1023 000640 000137 007464      JMP      SNGCHR    ;TEST 9
1024 000644 000137 007660      JMP      ROTATE    ;TEST 10
1025 000650 000137 010422      JMP      LFTTR     ;TEST 11
1026 000654 000137 011136      JMP      HAMALN    ;TEST 12
1027
1028
1029          000700          . =700
1030
1031 000700 012737 016760 017004      MOV      #LSCA,LOSCOP ;SEND LF AFTER 132 CHARS
1032 000706 000137 016636      JMP      SCOPE
1033
1034          000720          . =720
1035
1036 000720 012737 016636 017004      MOV      #SCOPE,LOSCOP ;NO LF'S SENT IN SCOPE ROUTINE
1037 000726 000137 016636      JMP      SCOPE     ;DO SCOPE ROUTINE
1038
1039
1040          001000          . =1000
1041
1042          ;LINE PRINTER HARDWARE REGISTERS
1043
1044 001000 177514      LPS:    177514      ;STATUS REGISTER
1045          ;BIT 15=ERROR
1046          ;BIT 7=READY
1047          ;BIT 6=INTERRUPT ENABLE
1048
1049 001002 177516      LPB:    177516      ;DATA BUFFER REGISTER
1050          ;BITS 0-6=7 BIT ASCII CHARACTER BUFFER
1051          ;BITS 7-15=NOT USED
1052
1053
1054 001004 177570      SWR:    177570
1055 001006 177570      DISPLAY:177570
1056 001010 177776      PSW:    177776
1057 001012 177566      TPB:    177566
1058 001014 177562      TKB:    177562
1059 001016 177564      TPS:    177564
1060 001020 177560      TKS:    177560
1061 001022 172542      CSBR:   172542
1062 001024 172540      PLKS:   172540
1063 001026 177546      LKS:    177546
    
```

1064 001030 000200  
1065 001032 000202  
1066 000240  
1067 000000  
1068 000002  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119

```

PTRVEC: .WORD 200
PTRPSW: .WORD 202
NOP      =240
N        =0
M        =2

;MACRO FOR SETTING UP ERROR COUNT
.LIST ME
ERR'X': .MACR  $ERROR X
MOV      #X,   ERCOUNT      ;SET UP ERROR COUNT X
N=N+1
.ENDM    $ERROR

;MACRO FOR PRINTING TEST NUMBER AT START OF TEST
.LIST ME
.MACR    $PRINT Y
MOV      TNO'Y',MES15      ;SET TEST NUMBER FOR MESSAGE
JSR      %4,PRNNT         ;PRINT TEST NUMBER
M=M+1
.ENDM    $PRINT

;MACRO FOR WAITING FOR PRINTER TO PRINT OR SLEW
.LIST ME
.MACR    $WAIT
TSTB    %LPS              ;TEST READY
BPL      -4                ;WAIT FOR READY
.ENDM    $WAIT

;MACRO FOR ENABLING KEYBOARD INTERUPT IF THERE IS NO
;H/W SWITCH REGISTER AND THERE IS A S/W SWITCH REGISTER
.LIST ME
.MACR    $ENABLE
CMP      #176,SWR          ;S/W SWR ?
BNE      .+10              ;NO- CONTINUE
BIS      #100,%TKS         ;ENABLE KEYBOARD INTERRUPT
.ENDM    $ENABLE

;MACRO USED TO LOAD THE PSW WITH THE
;CORRECT PROCESSOR PRIORITY LEVEL

```

1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
(1)  
(1)  
(1)

.LIST ME

```
.MACR  $SETPSW
MOV     PC,-(SP)      ;MOVE PRESENT LOCATION TO STACK
ADD     #6,(SP)       ;SET UP FOR NEXT INSTRUCTION
RTI
.ENDM   $SETPSW      ;LOAD PSW
```

;MEMORY LOCATIONS USED AS PROGRAM FLAGS AND COUNTERS

```
SEGCNT: 0
CHRCNT: 0
CHRGEN: 0
LINCNT: 0
CYCCNT: 0
WORK:    0
SAVE:    0
ERCOUNT: 0
STRCHR:  0
STRCNT:  0
LEGCHR:  0
NUMCHR:  0
OFFSET:  0
DIGITS:  0
SIGNAL:  0
SET:      0
CHAR:     0
OCT:      0
```

;ROUTINE TO TEST THE MECH. OPERATION OF THE LPO5

```
SETUP: JSR     %4,TYPINT
        RESET
        MOV     4,-(SP)      ;CLEAR WORLD
        MOV     6,-(SP)      ;SAVE CURRENT VECTORS
        MOV     #1$4
        TST    @SWR          ;SET UP TIMEOUT VECTOR
        BR     2$           ;TRY TO ACCESS HARDWARE SWR
        ;IF THERE, GO TO 2$

1$:     MOV     #SWREG,SWR    ;POINT TO SOFTWARE SWR
        MOV     #DISPREG,DISPLAY ;POINT TO SOFTWARE DISPLAY
        CMP     (SP)+,(SP)+  ;RESTORE STACK
        MOV     (SP)+,6      ;RESTORE TIMEOUT VECTORS
        MOV     (SP)+,4
        ;
        $ENABLE
        CMP     #176,SWR     ;S/W SWR ?
        BNE     .+10         ;NO- CONTINUE
        BIS     #100,@TKS    ;ENABLE KEYBOARD INTERRUPT
```

```

1173
1174 001176 104000 EMT +0
1175 001200 012714 MES1 ;TYPE DIAGNOSTIC TITLE
1176 001202 104000 EMT +0
1177 001204 012757 MES2 ;TYPE RESTART ADDRESS INFO
1178 001206 104000 EMT +0 ;TYPE MESSAGE
1179 001210 013004 MES3 ;POWER UP
1180 001212 000000 HALT ;DEPRESS CONTINUE WHEN READY TO START TEST
1181
1182 001214 005777 177560 STP1: TST QLP5 ;TEST FOR ERROR
1183 001220 100006 BPL STP2 ;NO ERROR TEST FOR READY
1184 001222 SERROR \N
(1) 001222 012737 000000 001052 ERRO: MOV #0, ERCOUNT ;SET UP ERROR COUNT 0
(1) 000001 N=N+1
1185 001230 004537 011706 JSR %5,STAER ;REPORT ERROR BIT SET
1186 001234 000767 BR STP1 ;GO TEST FOR ERROR
1187 001236 105777 177536 STP2: TSTB QLP5 ;TEST FOR READY
1188 001242 100406 BMI STP3 ;READY SET OK
1189 001244 SERROR \N
(1) 001244 012737 000001 001052 ERR1: MOV #1, ERCOUNT ;SET UP ERROR COUNT 1
(1) 000002 N=N+1
1190 001252 004537 011706 JSR %5,STAER ;REPORT READY NOT SET
1191 001256 000767 BR STP2 ;GO TEST FOR READY
1192 001260 104000 STP3: EMT +0 ;TYPE MESSAGE
1193 001262 013035 MES4 ;PRINTER OK "READY SET" TRY TORN PAPER SWITCH
1194 001264 000000 HALT ;DEPRESS CONTINUE WHEN READY
1195 001266 STP4:
1196 001266 012777 000014 177506 MOV #14,QLPB ;SEND A "FF" TO THE PRINTER
1197 001274 012777 000015 177500 MOV #15,QLPB ;ATTEMPT "FF" BY SENDING A "CR"
1198 001302 005777 177472 TST QLP5 ;TEST FOR ERROR
1199 001306 100406 BMI STP5 ;BRANCH IF ERROR SET
1200 001310 SERROR \N
(1) 001310 012737 000002 001052 ERR2: MOV #2, ERCOUNT ;SET UP ERROR COUNT 2
(1) 000003 N=N+1
1201 001316 004537 011706 JSR %5,STAER ;REPORT ERROR NOT SET
1202 001322 000761 BR STP4 ;LOOP ON ERROR
1203 001324 104000 STP5: EMT +0 ;TYPE MESSAGE
1204 001326 013146 MES6 ;ERROR SET OK - TURN ON LINE
1205 001330 000000 HALT ;WAIT FOR OPERATOR
1206
1207 001332 005777 177442 STP5A: TST QLP5 ;TEST FOR ERROR
1208 001336 100006 BPL STP5B ;NO ERROR CONTINUE
1209 001340 SERROR \N
(1) 001340 012737 000003 001052 ERR3: MOV #3, ERCOUNT ;SET UP ERROR COUNT 3
(1) 000004 N=N+1
1210 001346 004537 011706 JSR %5,STAER ;REPORT ERROR SET
1211 001352 000767 BR STP5A ;LOOP ON ERROR
1212 001354 105777 177420 STP5B: TSTB QLP5 ;TEST READY
1213 001360 100406 BMI STP5C ;READY SET OK
1214 001362 SERROR \N
(1) 001362 012737 000004 001052 ERR4: MOV #4, ERCOUNT ;SET UP ERROR COUNT 4
(1) 000005 N=N+1
1215 001370 004537 011706 JSR %5,STAER ;REPORT ERROR NOT SET
1216 001374 000767 BR STP5B ;LOOP ON ERROR
1217 001376 104000 STP5C: EMT +0 ;TYPE MESSAGE
1218 001400 013101 MESS ;READY SET OK - TRY DRUM GATE SWITCH
    
```



```

1219 001402 000000          HALT          ;DEPRESS CONTINUE WHEN READY
1220
1221 001404 005777 177370    STP6:   TST      2LPS          ;TEST FOR ERROR
1222 001410 100006          BMI      STP7          ;BRANCH IF ERROR SET
1223 001412          $ERROR  \N
(1) 001412 012737 000005 001052 ERR5:   MOV      #5,      ERCOUNT          ;SET UP ERROR COUNT 5
(1)          000006          N=N+1
1224 001420 004537 011706    JSR     %5, STAER          ;REPORT ERROR NOT SET
1225 001424 000767          BR      STP6          ;LOOP ON ERROR
1226 001426 104000          STP7:   EMT      +0          ;TYPE MESSAGE
1227 001430 013146          MES6
1228 001432 000000          HALT          ;DEPRESS CONTINUE WHEN READY
1229
1230          ;TEST 1
1231          ;PERFORMS PRELIMINARY COMMAND AND REGISTER TESTING.
1232
1233          ;IS THE PRINTER FREE OF ERRORS
1234
1235 001434 000005          TEST1:  RESET          ;CLEAR THE WORLD
1236 001436 005777 177336    TST     2LPS          ;IS ERROR FLAG CLEAR
1237 001442 100006          BPL     TEST1A        ;ERROR IS CLEAR OK
1238 001444          $ERROR  \N
(1) 001444 012737 000006 001052 ERR6:   MOV      #6,      ERCOUNT          ;SET UP ERROR COUNT 6
(1)          000007          N=N+1
1239 001452 004537 011706    JSR     %5, STAER          ;REPORT ERROR SET
1240 001456 000766          BR      TEST1         ;LOOP ON ERROR
1241
1242          ;IS READY SET (NO ERRORS EXIST)
1243
1244 001460 000005          TEST1A: RESET          ;CLEAR THE WORLD
1245 001462 105777 177312    TSTB   2LPS          ;IS READY SET
1246 001466 100406          BMI     TEST1B        ;READY SET! PRINTER OK
1247 001470          $ERROR  \N
(1) 001470 012737 000007 001052 ERR7:   MOV      #7,      ERCOUNT          ;SET UP ERROR COUNT 7
(1)          000010          N=N+1
1248 001476 004537 011706    JSR     %5, STAER          ;REPORT READY NOT SET
1249 001502 000766          BR      TEST1A        ;LOOP ON ERROR
1250
1251          ;DOES LOADING THE BUFFER RESET READY
1252
1253 001504 005037 001046          TEST1B: CLR      WORK          ;CLEAR COUNTER
1254 001510 012777 000015 177264    MOV     #15, 2LPB        ;LOAD CARRIAGE RETURN INTO BUFFER
1255 001516 105777 177256    TSTB   2LPS          ;IS READY CLEAR
1256 001522 100006          BPL     LP1           ;READY TO CLEAR OK!
1257 001524          $ERROR  \N
(1) 001524 012737 000010 001052 ERR10:  MOV      #10,     ERCOUNT          ;SET UP ERROR COUNT 10
(1)          000011          N=N+1
1258 001532 004537 011706    JSR     %5, STAER          ;REPORT READY STILL SET
1259 001536 000762          BR      TEST1B        ;LOOP ON ERROR
1260 001540 005777 177234    LP1:   TST     2LPS          ;IS THERE AN ERROR
1261 001544 100006          BPL     LP2           ;NO ERROR CONTINUE
1262 001546          $ERROR  \N
(1) 001546 012737 000011 001052 ERR11:  MOV      #11,     ERCOUNT          ;SET UP ERROR COUNT 11
(1)          000012          N=N+1
1263 001554 004537 011706    JSR     %5, STAER          ;REPORT ERROR OCCURRED
1264 001560 000751          BR      TEST1B        ;LOOP ON ERROR
    
```

```

1265 001562 105777 177212 LP2: TSTB 2LPS ;IS THE PRINTER STILL BUSY
1266 001566 100411 BMI TESTIC ;NO! GO TO NEXT TEST
1267 001570 005237 001046 INC WORK ;YES! GO CHECK FLAGS
1268 001574 001361 BNE LP1 ;PRINTER STILL BUSY WAIT
1269 001576 SERROR \N
(1) 001576 012737 000012 001052 ERR12: MOV #12, ERCOUNT ;SET UP ERROR COUNT 12
(1) 000013 N=N+1
1270 001604 004537 011706 JSR %5,STAER ;ERROR REPORT TIME OUT
1271 001610 000735 BR TEST1B ;LOOP ON ERROR
1272
1273 ;CHECK INTERRUPT LEVEL OF PRINTER
1274 ;THE PRINTER SHOULD BE AT LEVEL 4
1275
1276 ;TEST THAT THE PRINTER WILL NOT INTERRUPT AT LEVEL 7
1277
1278 001612 012777 002076 177210 TEST1C: MOV #INTIC,2PTRVEC ;SET UP INT VECTOR
1279 001620 012777 000340 177204 MOV #340,2PTRPSW ;SET PRIORITY
1280 001626 005777 177146 TST 2LPS ;TEST FOR ERROR
1281 001632 100006 BPL LP3 ;NO ERROR CONTINUE
1282 001634 SERROR \N
(1) 001634 012737 000013 001052 ERR13: MOV #13, ERCOUNT ;SET UP ERROR COUNT 13
(1) 000014 N=N+1
1283 001642 004537 011706 JSR %5,STAER ;REPORT ERROR SET
1284 001646 000761 BR TESTIC ;LOOP ON ERROR
1285 001650 105777 177124 LP3: TSTB 2LPS ;TST FOR READY
1286 001654 100406 BMI LP3X ;READY SET OK
1287 001656 SERROR \N
(1) 001656 012737 000014 001052 ERR14: MOV #14, ERCOUNT ;SET UP ERROR COUNT 14
(1) 000015 N=N+1
1288 001664 004537 011706 JSR %5,STAER ;REPORT READY NOT SET
1289 001670 000750 BR TESTIC ;LOOP ON ERROR
1290 001672 SERROR \N
(1) 001672 012737 000015 001052 LP3X: ERR15: MOV #15, ERCOUNT ;SET UP ERROR COUNT 15
(1) 000016 N=N+1
1291 001700 012746 000340 MOV #340,-(SP) ;LOCKUP PROCESSOR, NEW PRIORITY
1292 001704 SSETPSW
(1) 001704 010746 MOV PC,-(SP) ;MOVE PRESENT LOCATION TO STACK
(1) 001706 062716 000006 ADD #6,(SP) ;SET UP FOR NEXT INSTRUCTION
(1) 001712 000002 RTI ;LOAD PSW
1293 001714 052777 000100 177056 BIS #100,2LPS ;SET PRINTER INTO ENABLE
1294 001722 000240 NOP ;WAIT
1295 001724 042777 000100 177046 BIC #100,2LPS ;CLEAR PRINTER INT. ENABLE
1296
1297 ;TEST THAT THE PRINTER WILL NOT INTERRUPT AT LEVEL 6
1298
1299 001732 SERROR \N
(1) 001732 012737 000016 001052 ERR16: MOV #16, ERCOUNT ;SET UP ERROR COUNT 16
(1) 000017 N=N+1
1300 001740 012746 000300 MOV #300,-(SP) ;SET PROCESSOR PRIORITY LEVEL 6
1301 001744 SSETPSW
(1) 001744 010746 MOV PC,-(SP) ;MOVE PRESENT LOCATION TO STACK
(1) 001746 062716 000006 ADD #6,(SP) ;SET UP FOR NEXT INSTRUCTION
(1) 001752 000002 RTI ;LOAD PSW
1302 001754 052777 000100 177016 BIS #100,2LPS ;SET PRINTER INT ENABLE
1303 001762 000240 NOP ;WAIT
1304 001764 042777 000100 177006 BIC #100,2LPS ;CLEAR PRINTER INT. ENABLE

```

```

1305
1306 ;TEST THAT THE PRINTER WILL NOT INT. AT
1307 ;PROCESSOR LEVEL 5
1308
1309 001772 $ERROR \N
(1) 001772 012737 000017 001052 ERR17: MOV #17, ERCOUNT ;SET UP ERROR COUNT 17
(1) 000020 N=N+1
1310 002000 012746 000240 MOV #240,-(SP) ;SET UP PROCESSOR TO LEVEL 5
1311 002004 $SETPSW
(1) 002004 010746 MOV PC,-(SP) ;MOVE PRESENT LOCATION TO STACK
(1) 002006 062716 000006 ADD #6,(SP) ;SET UP FOR NEXT INSTRUCTION
(1) 002012 000002 RTI ;LOAD PSW
1312 002014 052777 000100 176756 BIS #100,2LPS ;SET PRINTER INT ENABLE
1313 002022 000240 NOP ;WAIT
1314 002024 042777 000100 176746 BIC #100,2LPS ;CLEAR INT ENABLE PRINTER OK
1315
1316 ;TEST THAT THE PRINTER WILL NOT INTERRUPT
1317 ;WHEN THE PROCESSOR IS AT LEVEL 4
1318
1319 002032 $ERROR \N
(1) 002032 012737 000020 001052 ERR20: MOV #20, ERCOUNT ;SET UP ERROR COUNT 20
(1) 000021 N=N+1
1320 002040 012746 000200 MOV #200,-(SP) ;SET PROCESSOR TO LEVEL 4
1321 002044 $SETPSW
(1) 002044 010746 MOV PC,-(SP) ;MOVE PRESENT LOCATION TO STACK
(1) 002046 062716 000006 ADD #6,(SP) ;SET UP FOR NEXT INSTRUCTION
(1) 002052 000002 RTI ;LOAD PSW
1322 002054 052777 000100 176716 BIS #100,2LPS ;SET PRINTER INT. ENABLE
1323 002062 000240 NOP ;WAIT
1324 002064 042777 000100 176706 BIC #100,2LPS ;CLEAR PRINTER INT ENABLE
1325 002072 000137 002110 JMP TEST10 ;PRINTER OK CONTINUE
1326
1327 ;INTERRUPT HANDLE FOR TEST1C
1328 ;RESTORE STACK AND REPORT ERROR
1329
1330 002076 022626 INT1C: CMP (6)+(6)+ ;RESTORE STACK
1331 002100 004537 011706 JSR %5,STAER ;REPORT ERROR
1332 002104 000137 001612 JMP TEST1C ;RE-ENTER TEST1C
1333
1334 ;TEST THE ABILITY OF THE PRINTER TO INTERRUPT
1335 ;AT PRIORITY LEVEL 4
1336
1337 002110 012777 002230 176712 TEST1D: MOV #INT1D,2PTRVEC ;SET UP INTERRUPT VECTOR
1338 002116 012777 000340 176706 MOV #340,2PTRPSW ;LOCK UP PRIORITIES
1339 002124 005777 176650 TST 2LPS ;IS THERE A PRINTER ERROR
1340 002130 100006 BPL LP4 ;NO! CONTINUE
1341 002132 $ERROR \N
(1) 002132 012737 000021 001052 ERR21: MOV #21, ERCOUNT ;SET UP ERROR COUNT 21
(1) 000022 N=N+1
1342 002140 004537 011706 JSR %5,STAER ;REPORT PRINTER ERROR
1343 002144 000761 BR TEST1D ;LOOP ON ERROR
1344 002146 105777 176626 LP4: TSTB 2LPS ;IS READY SET
1345 002152 100406 BMI LP5 ;YES - PRINTER READY
1346 002154 $ERROR \N
(1) 002154 012737 000022 001052 ERR22: MOV #22, ERCOUNT ;SET UP ERROR COUNT 22
(1) 000023 N=N+1
    
```

```

1347 002162 004537 011706      JSR      %5,STAER      ;REPORT READY NOT SET
1348 002166 000750              BR        TESTID      ;LOOP ON ERROR
1349 002170 012746 000140      LPS:    MOV      #140,-(SP) ;SET PRIORITY TO LEVEL 3
1350 002174              $SETPSW
      (1) 002174 010746      MOV      PC,-(SP)      ;MOVE PRESENT LOCATION TO STACK
      (1) 002176 062716 000006      ADD      #6,(SP)      ;SET UP FOR NEXT INSTRUCTION
      (1) 002202 000002              RTI              ;LOAD PSW
1351 002204 052777 000100 176566      BIS      #100,%LPS      ;SET PRINTER INTERRUPT ENABLE
1352 002212 000240              NOP              ;WAIT
1353 002214              $ERROR \N
      (1) 002214 012737 000023 001052 ERR23: MOV      #23,   ERCOUNT      ;SET UP ERROR COUNT 23
      (1) 000024              N=N+1
1354 002222 004537 011706      JSR      %5,STAER      ;REPORT ERROR
1355 002226 000730              BR        TESTID      ;LOOP ON ERROR
1356
1357              ; INTERRUPT HANDLER FOR TESTID
1358
1359 002230 022626              INTID:  CMP      (6)+,(6)+      ;RESET STACK
1360 002232 042777 000100 176540      BIC      #100,%LPS      ;CLEAR INT. ENABLE FOR PRINTER
1361 002240 012746 000000              MOV      #0,-(SP)      ;CLEAR PROCESSOR STATUS
1362 002244              $SETPSW
      (1) 002244 010746      MOV      PC,-(SP)      ;MOVE PRESENT LOCATION TO STACK
      (1) 002246 062716 000006      ADD      #6,(SP)      ;SET UP FOR NEXT INSTRUCTION
      (1) 002252 000002              RTI              ;LOAD PSW
1363 002254 012777 012706 176546      MOV      #12706,%PTRVEC ;RESET INSTRUCTION AT 200
1364 002262 012777 001000 176542      MOV      #1000,%PTRPSW ;RESET INSTRUCTION AT 202
1365
1366
1367              ; GET INITIAL SWR VALUE
1368              ; IF THERE IS NO H/W SWR
1369
1370
1371 002270 022737 000176 001004      CMP      #176,SWR      ;S/W SWR ?
1372 002276 001044              BNE      SKIP          ;NO- CONTINUE
1373 002300 005037 001070              CLR      SIGNAL        ;INITIALIZE INTERRUPT ROUTINE
1374 002304 005037 001066              CLR      DIGITS        ;
1375 002310 005037 001072              CLR      SET           ;
1376 002314 005037 001074              CLR      CHAR          ;
1377 002320 013746 000034              MOV      34,-(SP)      ;SAVE VECTOR
1378 002324 013746 000036              MOV      36,-(SP)      ;SAVE VECTOR
1379 002330 012737 011736 000034      MOV      #TKINT,34     ;SET UP NEW VECTOR
1380 002336 012737 000300 000036      MOV      #300,36       ;SET UP NEW VECTOR
1381 002344 005237 001072              INC      SET           ;SET HEADER FLAG
1382 002350 104400              TRAP      +0          ;ENTER INTERRUPT ROUTINE
1383 002352 005037 001072              CLR      SET           ;CLEAR HEADER FLAG
1384 002356 012637 000036              MOV      (SP)+,36      ;RESTORE VECTOR
1385 002362 012637 000034              MOV      (SP)+,34      ;RESTORE VECTOR
1386 002366 012777 000100 176424      MOV      #100,%TKS     ;ENABLE KEYBOARD INTERRUPT
1387 002374 000001              WT:    WAIT
1388 002376 000240              NOP
1389 002400 022737 000001 001070      CMP      #1,SIGNAL     ;SWR VALUE ENTERED ?
1390 002406 001772              BEQ      WT           ;NO- WAIT
1391 002410 000240              SKIP:  NOP
1392
1393
1394

```

```

1395 ;1 MINUTE PRINT SPEED CHECK
1396 ;IF A KW11-L OR KW11-P ARE NOT AVAILABLE, THE SR BIT0 IS USED
1397 ;FOR MANUAL TIMING OF THE PRINTER.
1398
1399 002412 012737 000002 000006 CLCKAV: MOV #RTI, @#6 ;SET TRAP TO RETURN
1400 002420 012737 000006 000004 MOV #6, @#4
1401 002426 000261 SEC
1402 002430 105777 176372 TSTB @PLKS ;KW11-L AVAILABLE?
1403 002434 103404 BCS IS ;NO BRANCH
1404 002436 005037 000004 CLR @#4 ;RESET TRAP VECTOR TO HALT
1405 002442 000137 002626 JMP KW11L ;USE KW11L FOR TIMING
1406 002446 000261 IS: SEC
1407 002450 105777 176350 TSTB @PLKS ;KW11-P AVAILABLE?
1408 002454 103404 BCS SWTIME ;NO USE SWITCH REG FOR TIMING
1409 002456 005037 000004 CLR @#4 ;RESET TRAP VECTOR TO HALT
1410 002462 000137 002546 JMP KW11P ;USE KW11-P FOR TIMING
1411 002466 SWTIME: $ENABLE
(1) 002466 022737 000176 001004 CMP #176, SWR ;S/W SWR ?
(1) 002474 001003 BNE .+10 ;NO- CONTINUE
(1) 002476 052777 000100 176314 BIS #100, @TKS ;ENABLE KEYBOARD INTERRUPT
1412 002504 005037 001042 CLR LINCNT ;CLEAR LINE COUNT
1413 002510 004437 011472 JSR %4, TYPINT
1414 002514 005037 000004 CLR @#4 ;RESET TRAP VECTOR TO HALT
1415 002520 104000 EMT +0 ;TYPE MESSAGE
1416 002522 012475 MESC ;PRINT SPEED CHECK USING MANUAL TIMING
1417 002524 012737 000002 003232 MOV #2, DIA ;SET DUMMY ADDRESS
1418 002532 032777 000001 176244 IS: BIT #BIT0, @SWR ;START?
1419 002540 001774 BEQ IS ;WAIT FOR START
1420 002542 000137 002702 JMP STARO ;START PRINTING
1421
1422
1423 ;START FOR KW11-P.....
1424
1425 002546 KW11P: $ENABLE
(1) 002546 022737 000176 001004 CMP #176, SWR ;S/W SWR ?
(1) 002554 001003 BNE .+10 ;NO- CONTINUE
(1) 002556 052777 000100 176234 BIS #100, @TKS ;ENABLE KEYBOARD INTERRUPT
1426 002564 005037 001042 CLR LINCNT ;CLEAR LINE COUNT
1427 002570 004437 011472 JSR %4, TYPINT
1428 002574 012706 001000 MOV #1000, %6 ;RESET STACK
1429 002600 013777 003226 176214 MOV MINCNT, @CSBR ;SET CLOCK COUNT
1430 002606 013737 001024 003232 MOV PLKS, DIA ;STORE PLKS ADDRESS
1431 002614 012777 000105 176202 MOV #105, @PLKS ;START CLOCK
1432 002622 000137 002702 JMP STARO ;START PRINTING
1433
1434 ;START FOR KW11-L.....
1435
1436 002626 KW11L: $ENABLE
(1) 002626 022737 000176 001004 CMP #176, SWR ;S/W SWR ?
(1) 002634 001003 BNE .+10 ;NO- CONTINUE
(1) 002636 052777 000100 176154 BIS #100, @TKS ;ENABLE KEYBOARD INTERRUPT
1437 002644 005037 001042 CLR LINCNT ;CLEAR LINE COUNT
1438 002650 004437 011472 JSR %4, TYPINT
1439 002654 012706 001000 MOV #1000, %6 ;RESET STACK
1440 002660 013737 003226 003230 MOV MINCNT, CNTR ;SET CLOCK COUNT
1441 002666 013737 001026 003232 MOV LKS, DIA ;STORE LKS ADDRESS

```

```

1442 002674 012777 000100 176124      MOV      #100,ALKS      ;ENABLE CLOCK INTERRUPT
1443
1444      ;PRINTING ROUTINE.....
1445
1446 002702 032777 020000 176074  STARO:  BIT      #BIT13,ASWR      ;CHECK CHAR SET
1447 002710 001007          BNE      STAROA      ;BRANCH IF 96
1448 002712 012737 000140 001060      MOV      #140,LEGCHR   ;LEGAL CHECK
1449 002720 012737 000100 001062      MOV      #100,NUMCHR   ;#CHARS
1450 002726 000406          BR       STAROC      ;CONTINUE
1451 002730 012737 000200 001060  STAROA: MOV      #200,LEGCHR ;LEGAL CHECK
1452 002736 012737 000140 001062      MOV      #140,NUMCHR   ;#CHARS
1453 002744 013737 001060 001054  STAROC: MOV      LEGCHR,STRCHR ;SET FIRST CHAR IF LP14
1454 002752 032777 002000 176024  STAROB: BIT      #BIT10,ASWR ;CHECK FOR NEW DRUM(LP14)/OLD DRUM
1455 002760 001063          BNE      TIMTST
1456 002762 012737 000204 001036      MOV      #132,CHRCNT   ;SET CHAR COUNT
1457 002770 012737 003424 001054      MOV      #PATTB,STRCHR ;INITIALIZE TABLE POINTER
1458 002776 012737 000021 001044  STARA:  MOV      #17,CYCCNT ;SET GROUP COUNT
1459 003004 017737 176044 001040      MOV      2STRCHR,CHRCNT ;GET CHAR FROM TABLE
1460 003012 063737 001042 001040      ADD      LINCNT,CHRCNT ;ADD LINE COUNT
1461 003020 023737 001060 001040  1$:    CMP      LEGCHR,CHRCNT ;LEGAL CHAR?
1462 003026 003004          BGT      STAR1      ;YES, BRANCH
1463 003030 163737 001062 001040      SUB      NUMCHR,CHRCNT ;NO, MAKE LEGAL
1464 003036 000770          BR       1$         ;RECHECK CHAR
1465 003040 013777 001040 175734  STAR1:  MOV      CHRCNT,ALPB   ;LOAD BUFFER
1466 003046 005337 001036          DEC      CHRCNT      ;DECREMENT CHAR COUNT
1467 003052 001410          BEQ      STARED     ;BRANCH IF DONE LINE
1468 003054 005337 001044          DEC      CYCCNT     ;DECREMENT CYCCLE COUNT
1469 003060 001367          BNE      STAR1     ;CONTINUE IF NOT DONE GROUP
1470 003062 062737 000002 001054      ADD      #2,STRCHR   ;ADD 2 TO TABLE POINTER
1471 003070 000137 002776          JMP      STARA      ;CONTINUE
1472 003074 005237 001042          STARED: INC      LINCNT ;INCREMENT LINE COUNT
1473 003100 012777 000012 175674      MOV      #12,ALPB    ;SEND LF
1474 003106          $WAIT
1475 (1) 003106 105777 175666      TSTB    ALPS         ;TEST READY
1476 (1) 003112 100375          BPL     -4          ;WAIT FOR READY
1477 003114 032777 000001 175662      BIT     #BIT0,ASWR  ;STOP PRINT?
1478 003122 001450          BEQ     CONVRT     ;YES, BRANCH
1479 003124 000137 002752          JMP     STAROB     ;CONTINUE
1480
1481      ;LP14 PRINTING ROUTINE
1482 003130 012737 000204 001036  TIMTST: MOV      #132,CHRCNT ;SET CHARACTER COUNT
1483 003136 005337 001054          DEC      STRCHR     ;GET NEXT STARTING CHARACTER
1484 003142 023727 001054 000040      CMP     STRCHR,#40  ;LEGAL CHARACTER ?
1485 003150 100003          BPL     3$         ;YES-CONTINUE
1486 003152 063737 001062 001054      ADD     NUMCHR,STRCHR ;NO-MAKE LEGAL
1487 003160 013737 001054 001040  3$:    MOV     STRCHR,CHRCNT ;GET CHARACTER
1488 003166 023727 001040 000040  TMTST2: CMP     CHRCNT,#40 ;LEGAL CHARACTER ?
1489 003174 100003          BPL     1$         ;YES-CONTINUE
1490 003176 063737 001062 001040      ADD     NUMCHR,CHRCNT ;NO-MAKE LEGAL
1491 003204 013777 001040 175570  1$:    MOV     CHRCNT,ALPB ;SEND CHARACTER
1492 003212 005337 001036          DEC     CHRCNT     ;DECREMENT CHARACTER COUNT
1493 003216 001726          BEQ     STARED     ;LINE FINISHED
1494 003220 005337 001040          DEC     CHRCNT     ;GET NEXT CHARACTER
1495 003224 000760          TMTST1: BR     TMTST2 ;CONTINUE

```



1496  
1497 003226 007020  
1498 003230 000000  
1499 003232 000002  
1500  
1501  
1502  
1503  
1504  
1505  
1506 003234 005337 003230  
1507 003240 001401  
1508 003242 000002  
1509  
1510  
1511  
1512  
1513 003244 042777 000100 177760  
1514 003252 005037 011622  
1515 003256 012703 013527  
1516 003262 022737 000144 001042  
1517 003270 003006  
1518 003272 162737 000144 001042  
1519 003300 005237 011622  
1520 003304 000766  
1521 003306 062737 000060 011622  
1522 003314 113723 011622  
1523 003320 005037 011622  
1524 003324 022737 000012 001042  
1525 003332 003006  
1526 003334 162737 000012 001042  
1527 003342 005237 011622  
1528 003346 000766  
1529 003350 062737 000060 011622  
1530 003356 113723 011622  
1531 003362 013737 001042 011622  
1532 003370 062737 000060 011622  
1533 003376 113723 011622  
1534 003402 104000  
1535 003404 013470  
1536 003406 012737 013466 011470  
1537 003414 004437 011452  
1538 003420 000137 003444  
1539  
1540  
1541  
1542 003424 000040  
1543 003426 000117  
1544 003430 000076  
1545 003432 000055  
1546 003434 000134  
1547 003436 000113  
1548 003440 000072  
1549 003442 000051  
1550  
1551

MINCNT: 7020  
CNTR: 0  
DIA: 2

;NOTE -- PLACE 5670 (8) IN MINCNT FOR 50 HZ. LINE FREQUENCY !!!

;LINE CLOCK SERVICE ROUTINE FOR KW11-L

LKSRV: DEC CNTR ; DECREMENT COUNTER  
BEQ CONVRT ; EXIT IF 1 MINUTE  
RTI ; RETURN

;ROUTINE TO PRINT NUMBER OF LINES PRINTED IN 1 MINUTE

CONVRT: BIC #100,301A ; DISABLE CLOCK INTERRUPT IF CLOCK AVAILABLE  
CLR TYPDAT ; CLEAR DIGIT COUNT  
MOV #MES12,%3 ; SET MESSAGE POINTER  
1\$: CMP #100.,LINCNT ; GREATER THAN 100?  
BGT 2\$ ; NO, PRINT HUNDRED'S DIGIT  
SUB #100.,LINCNT ; YES, SUBTRACT 100  
INC TYPDAT ; INCREMENT HUNDRED'S DIGIT  
BR 1\$ ; CONTINUE CONVERSION  
2\$: ADD #60,TYPDAT ; MAKE ASCII  
MOVB TYPDAT,(%3)+ ; STORE DIGIT  
CLR TYPDAT ; CLEAR DIGIT COUNTER  
3\$: CMP #10.,LINCNT ; GREATER THEN 10?  
BGT 4\$ ; NO, PRINT DIGIT  
SUB #10.,LINCNT ; YES, SUBTRACT 10  
INC TYPDAT ; INCREMENT TEN'S DIGIT  
BR 3\$ ; CONTINUE CONVERSION  
4\$: ADD #60,TYPDAT ; MAKE ASCII  
MOVB TYPDAT,(%3)+ ; STORE DIGIT  
MOV LINCNT,TYPDAT ; GET ONE'S DIGIT  
ADD #60,TYPDAT ; MAKE ASCII  
MOVB TYPDAT,(%3)+ ; STORE DIGIT  
EMT +0 ; TYPE MESSAGE  
MES11 ; TYPE PRINT SPEED  
MOV #MES11A,PRMSG ; SET PRINTER MESSAGE ADDRESS  
JSR %4,RINT ; PRINT PRINTER SPEED ON LINE PRINTER  
JMP SLEWCK ; NEXT TEST

PATTB: 40  
117  
76  
55  
134  
113  
72  
51

;CHECK TOP OF FORM SWITCH

```

1552
1553 003444          SLEWCK: $ENABLE
      (1) 003444 022737 000176 001004  CMP      #176,SWR          ;S/W SWR ?
      (1) 003452 001003          BNE      .+10          ;NO- CONTINUE
      (1) 003454 052777 000100 175336  BIS      #100,ATKS     ;ENABLE KEYBOARD INTERRUPT
1554 003462 004437 011472          JSR      %4,TYPINT
1555 003466 004537 011346          JSR      %5,PRINT     ;INITIALIZE PRINTER
1556 003472 000406          BR       SLW          ;BRANCH IF OK
1557 003474          $ERROR  \N
      (1) 003474 012737 000024 001052  ERR24:  MOV      #24,   ERCOUNT ;SET UP ERROR COUNT 24
      (1)          000025          N=N+1
1558 003502 004537 011706          JSR      %5,STAER     ;REPORT PRINTER NOT READY
1559 003506 000000          HALT          ;HALT ON ERROR
1560 003510 012737 003724 001042  SLW:    MOV      #FFTAB,LINCNT ;LINE COUNT FOR SWITCH SETTING
1561 003516 012704 004002          MOV      #FFSET,%4   ;INIT SWITCH SETTING TABLE POINTER
1562 003522 012703 013242          SLW0:   MOV      #MES8,%3   ;INIT MESSAGE POINTER
1563 003526 012702 013355          MOV      #MES10,%2
1564 003532 111413          SLW1:   MOV      (%4),(%3)   ;PUT SWITCH SETTINGS INTO MESSAGES
1565 003534 111412          MOV      (%4),(%2)
1566 003536 122423          CMP      (%4)+,(%3)+ ;INCREMENT POINTERS
1567 003540 105722          TST      (%2)+
1568 003542 105714          TST      (%4)         ;DONE MOVING SWITCH SETTINGS TO MSG'S?
1569 003544 001372          BNE      SLW1        ;BRANCH IF NOT DONE
1570 003546 005204          INC      %4         ;TABLE POINTER SET FOR NEXT SWITCH SETTING
1571 003550 104000          EMT      +0         ;TYPE MESSAGE
1572 003552 013206          MES7
1573 003554 000000          HALT          ;SET TOP OF FORM SWITCH TO ---
1574 003556 005777 175260          SLW11:  TST      @LINCNT     ;WAIT FOR OPERATOR TO SET SWITCH
1575 003562 001003          BNE      SLW1A       ;CHECK LINE COUNT
1576 003564 012737 013556 011470          MOV      #MES13,PRTMSG ;BRANCH IF NOT ZERO
1577 003572 005777 175202          SLW1A:  TST      @LPS       ;CHANGE PRINTER MESSAGE
1578 003576 100006          BPL      SLW2        ;TEST FOR ERRORS
1579 003600          $ERROR  \N         ;BRANCH IF NO ERROR
      (1) 003600 012737 000025 001052  ERR25:  MOV      #25,   ERCOUNT ;SET UP ERROR COUNT 25
      (1)          000026          N=N+1
1580 003606 004537 011706          JSR      %5,STAER     ;REPORT ERROR SET
1581 003612 000000          HALT          ;HALT ON ERROR
1582 003614 012777 000014 175160  SLW2:   MOV      #14,@LPB    ;SEND FF
1583 003622          $WAIT
      (1) 003622 105777 175152          TST      @LPS       ;TEST READY
      (1) 003626 100375          BPL      .-4         ;WAIT FOR READY
1584 003630 004437 011452          JSR      %4,RINT     ;PRINT MESSAGE ON LINE PRINTER
1585 003634 062737 000002 001042  ADD      #2,LINCNT   ;NEXT LINE COUNT
1586 003642 022737 004000 001042  CMP      #FTABE,LINCNT ;DONE TEST?
1587 003650 001410          BEQ      DAVAV       ;YES, EXIT
1588 003652 005777 175164          TST      @LINCNT   ;DONE CHECK OF THIS SWITCH SETTING?
1589 003656 001721          BEQ      SLW0        ;YES, NEXT SWITCH SETTING
1590 003660 012737 013260 011470          MOV      #MES9,PRTMSG ;NO, CHECK THIS SETTING
1591 003666 000137 003556          JMP      SLW11       ;CONTINUE
1592 003672 013737 014536 013242  DAVAV:  MOV      TN013,MES8  ;SET MESSAGE
1593 003700 104000          EMT      +0         ;TYPE MESSAGE
1594 003702 013204          MES7A
1595 003704 000000          HALT          ;RESET TOP OF FORM SWITCH
1596 003706 032777 040000 175070  BIT      #BIT14,@SWR  ;WAIT FOR OPERATOR
1597 003714 001060          BNE      INDAT       ;DAVFU AVAILABLE?
1598 003716 000000          HALT          ;YES, DO DAVFU TESTS
                    ;DONE OPERATOR TESTS - HALT

```

```

1599 003720 000137 004550          JMP      TEST2          ;DEPRESS CONTINUE TO START PRINTING TESTS
1600
1601 003724 000000          FFTAB:  0              ;LOOP COUNTS FOR SLEW CHECKS
1602 003726 000022          18.
1603 003730 000000          0
1604 003732 000025          21.
1605 003734 000000          0
1606 003736 000030          24.
1607 003740 000000          0
1608 003742 000041          33.
1609 003744 000000          0
1610 003746 000044          36.
1611 003750 000000          0
1612 003752 000052          42.
1613 003754 000000          0
1614 003756 000060          48.
1615 003760 000000          0
1616 003762 000063          51.
1617 003764 000000          0
1618 003766 000102          66.
1619 003770 000000          0
1620 003772 000110          72.
1621 003774 000000          0
1622 003776 000124          84.
1623 004000 000000          FTAB:  0
1624
1625
1626 004002 020063 000040          FFSET:  .ASCIZ  /3 /          ;SWITCH SETTINGS FOR MESSAGES
1627 004006 027063 000065          .ASCIZ  /3.5/
1628 004012 020064 000040          .ASCIZ  /4 /
1629 004016 027065 000065          .ASCIZ  /5.5/
1630 004022 020066 000040          .ASCIZ  /6 /
1631 004026 020067 000040          .ASCIZ  /7 /
1632 004032 020070 000040          .ASCIZ  /8 /
1633 004036 027070 000065          .ASCIZ  /8.5/
1634 004042 030461 000040          .ASCIZ  /11 /
1635 004046 031061 000040          .ASCIZ  /12 /
1636 004052 032061 000040          .ASCIZ  /14 /
1637
1638
1639          .EVEN
1640
1641          ;CHECK THAT VFU WILL NOT ACCEPT INCOMPLETE DATA
1642
1643 004056          INDAT:  $ENABLE
(1) 004056 022737 000176 001004          CMP      #176,SWR          ;S/W SWR ?
(1) 004064 001003          BNE      .+10              ;NO- CONTINUE
(1) 004066 052777 000100 174724          BIS      #100,JKS          ;ENABLE KEYBOARD INTERRUPT
1644 004074 004437 011472          JSR      %4,TYPINT
1645 004100 012737 004230 001040          MOV      #INDATT,CHRGEN ;SET TABLE POINTER
1646 004106 005777 174666          INDO:   TST      @LPS      ;TEST FOR ERROR
1647 004112 100010          BPL      INDATO          ;BRANCH IF NO ERROR
1648 004114          $ERROR  \N
(1) 004114 012737 000026 001052          ERR26:  MOV      #26, ERRCOUNT ;SET UP ERROR COUNT 26
(1) 004114 000027          N=N+1
1649 004:22 004537 011706          JSR      %5,STAER          ;REPORT ERROR SET

```

```

1650 004126 000000          HALT          ;HALT ON ERROR
1651 004130 000137 004056    JMP          INDAT        ;RESTART TEST
1652 004134 017777 174700 174640 INDATA: MOV      @CHRGEN,@LPB ;LOAD BUFFER
1653 004142 062737 000002 001040 ADD      #2,CHRGEN      ;NEXT DATA
1654 004150 005777 174664    TST      @CHRGEN      ;TEST CHAR
1655 004154 001405          BEQ        INDI         ;CONTINUE IF DONE
1656 004156          $WAIT
(1) 004156 105777 174616    TSTB     @LPS         ;TEST READY
(1) 004162 100375          BPL      .-4         ;WAIT FOR READY
1657 004164 000137 004106    JMP          INDI
1658 004170 005777 174604    INDI:  TST      @LPS         ;TEST FOR ERROR SET
1659 004174 100410          BMI      INDATA1      ;BRANCH IF ERROR SET
1660 004176          $ERROR
(1) 004176 012737 000027 001052 ERR27: MOV      #27, ERRCOUNT ;SET UP ERROR COUNT 27
(1)          000030          N=N+1
1661 004204 004537 011706    JSR      %5,STAER     ;REPORT ERROR NOT SET
1662 004210 000000          HALT          ;HALT ON ERROR
1663 004212 000137 004056    JMP          INDAT        ;RESTART TEST
1664 004216 104000          INDATA1: EMT      +0     ;TYPE MESSAGE
1665 004220 012355          MESA
1666 004222 000000          HALT          ;ERROR SET OK - CLEAR & TURN ON LINE
1667          ;WAIT FOR OPERATOR
1668 004224 000137 004244    JMP          NODAT      ;DEPRESS CONTINUE WHEN READY FOR NEXT TEST
1669          ;NEXT TEST
1670 004230 000356          INDATA: 356          ;DATA TABLE FOR ABOVE TEST
1671 004232 000001          1
1672 004234 000002          2
1673 004236 000003          3
1674 004240 000357          357
1675 004242 000000          0
1676
1677          ;CHECK THAT CHANNELS WITH NO STOP BITS CAUSE ERRORS IF CHANNEL SELECTED
1678
1679 004244          NODAT: $ENABLE
(1) 004244 022737 000176 001004    CMP      #176,SWR     ;S/W SWR ?
(1) 004252 001003          BNE      .+10        ;NO- CONTINUE
(1) 004254 052777 000100 174536    BIS      #100,@TKS    ;ENABLE KEYBOARD INTERRUPT
1680 004262 004437 011472    JSR      %4,TYPINT
1681 004266 012737 000200 001054    MOV      #200,STRCHR ;SET PAPER INSTRUCTION
1682 004274 012737 004470 001040 NODDA: MOV      @NODAT3,CHRGEN ;SET TABLE POINTER FOR LOAD
1683 004302 005777 174472    NODD:  TST      @LPS         ;TEST FOR ERROR
1684 004306 100007          BPL      NODATO      ;BRANCH IF NO ERROR
1695 004310          $ERROR
(1) 004310 012737 000030 001052 ERR30: MOV      #30, ERRCOUNT ;SET UP ERROR COUNT 30
(1)          000031          N=N+1
1686 004316 004537 011706    JSR      %5,STAER     ;REPORT ERROR SET
1687 004322 000000          HALT          ;HALT ON ERROR
1688 004324 000747          BR          NODAT      ;RESTART TEST
1689 004326 017777 174506 174446 NODATU: MOV      @CHRGEN,@LPB ;LOAD BUFFER
1690 004334 062737 000002 001040 ADD      #2,CHRGEN      ;NEXT DATA
1691 004342 022737 004550 001040 CMP      #NODAT4+2,CHRGEN ;DONE LOAD?
1692 004350 001405          BEQ        NODATA     ;BRANCH IF DONE
1693 004352          $WAIT
(1) 004352 105777 174422    TSTB     @LPS         ;TEST READY
(1) 004356 100375          BPL      .-4         ;WAIT FOR READY
1694 004360 000137 004302    JMP          NODD
    
```

```

1695 004364 013777 001054 174410 NODATA: MOV STRCHR,ALPB ;SEND DATA
1696 004372 005037 001036 CLR CHRCNT ;DELAY
1697 004376 005237 001036 1$: INC CHRCNT
1698 004402 001375 BNE 1$
1699 004404 005777 174370 TST ALPS ;TEST FOR ERROR SET
1700 004410 100410 BMI NODAT1 ;BRANCH IF ERROR SET
1701 004412 $ERROR \N
(1) 004412 012737 000031 001052 ERR31: MOV #31, ERCOUNT ;SET UP ERROR COUNT 31
(1) 000032 N=N+1
1702 004420 004537 011706 JSR %5,STAER ;REPORT ERROR NOT SET
1703 004424 000000 HALT ;HALT ON ERROR
1704 004426 000137 004274 JMP NODDA ;RETEST
1705 004432 005237 001054 NODAT1: INC STRCHR ;NEXT PAPER INSTRUCTION
1706 004436 022737 000214 001054 CMP #214,STRCHR ;DONE TEST?
1707 004444 001404 BEQ NODAT2 ;CONTINUE IF NOT DONE
1708 004446 104000 EMT +0 ;TYPE MESSAGE
1709 004450 012422 MESB ;ERROR SET OK - CLEAR & TRY NEXT CHANNEL
1710 004452 000000 HALT ;WAIT FOR OPERATOR
1711 004454 000707 BR NODDA ;RELOAD & TEST NEXT CHANNEL
1712 004456 104000 NODAT2: EMT +0 ;TYPE MESSAGE
1713 004460 012355 MESA ;ERROR SET OK - TURN ON LINE
1714 004462 000000 HALT
1715 004464 000137 004550 JMP TEST2 ;JUMP
1716
1717
1718 004470 000356 NODAT3: 356 ;START LOAD
1719 004472 000000 0
1720 004474 000000 0
1721 004476 000000 0
1722 004500 000000 0
1723 004502 000000 0
1724 004504 000000 0
1725 004506 000000 0
1726 004510 000000 0
1727 004512 000000 0
1728 004514 000000 0
1729 004516 000000 0
1730 004520 000000 0
1731 004522 000000 0
1732 004524 000000 0
1733 004526 000000 0
1734 004530 000000 0
1735 004532 000000 0
1736 004534 000000 0
1737 004536 000000 0
1738 004540 000000 0
1739 004542 000000 0
1740 004544 000000 0
1741 004546 000357 NODAT4: 357 ;STOP LOAD
1742
1743 ;TEST 2
1744 ;TESTS INTERFACE AND PRINTER DATA PATHS
1745 ;WITH ALTERNATING ONES AND ZEROS
1746
1747 004550 TEST2: $ENABLE
(1) 004550 022737 000176 001004 CMP #176,SWR ;S/W SWR ?

```

```

(1) 004556 001003 BNE .+10 ;NO- CONTINUE
(1) 004560 052777 000100 174232 BIS #100,ATKS ;ENABLE KEYBOARD INTERRUPT
1748 004566 004437 011472 JSR %4,TYPINT
1749 004572 004537 011346 JSR %5,PRINT ;INITIALIZE PRINTER
1750 004576 000406 BR TST2AX ;BRANCH IF OK
1751 004600 $ERROR \N
(1) 004600 012737 000032 001052 ERR32: MOV #32, ERCOUNT ;SET UP ERROR COUNT 32
(1) 000033 N=N+1
1752 004606 004537 011706 JSR %5,STAER ;REPORT PRINTER NOT READY
1753 004612 000000 HALT ;HALT ON ERROR
1754 004614 TST2AX: $PRINT \M
(1) 004614 013737 014514 014002 MOV TNO2,MES15 ;SET TEST NUMBER FOR MESSAGE
(1) 004622 004437 011422 JSR %4,PRNT ;PRINT TEST NUMBER
(1) 000003 M=M+1
1755 004626 012737 177740 001044 MOV #-32,CYCCNT ;SET UP LINE COUNT FOR 32 LINES
1756 004634 012737 177574 001036 MOV #-132,CHRCNT ;SET CHAR COUNT TO 132
1757 004642 013737 004716 001054 MOV SCHRSW,STRCHR ;SET CHAR. SWITCH TO U
1758 004650 005777 174124 T3A: TST @LPS ;TEST FOR ERROR
1759 004654 100006 BPL LP2B ;NO ERROR CONTINUE
1760 004656 $ERROR \N
(1) 004656 012737 000033 001052 ERR33: MOV #33, ERCOUNT ;SET UP ERROR COUNT 33
(1) 000034 N=N+1
1761 004664 004537 011706 JSR %5,STAER ;REPORT ERROR SET
1762 004670 000000 HALT ;HALT ON ERROR
1763 004672 300177 174156 LP2B: JMP @STRCHR ;LOAD CHAR
1764 004676 013737 004720 001054 T2A: MOV RCHRSW,STRCHR ;RESET CHAR. SWITCH
1765 004704 012737 000125 001050 MOV #125,SAVE ;STORE CHAR
1766 004712 000137 004736 JMP TSA ;LOAD CHAR
1767
1768 004716 004676 SCHRSW: T2A
1769 004720 004722 RCHRSW: T1A
1770
1771 004722 013737 004716 001054 T1A: MOV SCHRSW,STRCHR ;SET CHAR. SWITCH TO U
1772 004730 012737 000052 001050 MOV #52,SAVE ;STORE CHAR
1773 004736 013777 001050 174036 T5A: MOV SAVE,@LPB ;LOAD BUFFER
1774 004744 005237 001036 INC CHRCNT ;INC CHARACTER COUNT
1775 004750 001337 BNE T3A ;CONTINUE
1776 004752 012777 000012 174022 MOV #12,@LPB ;SEND LF
1777 004760 $WAIT
(1) 004760 105777 174014 TSTB @LPS ;TEST READY
(1) 004764 100375 BPL .-4 ;WAIT FOR READY
1778 004766 012737 177574 001036 MOV #-132,CHRCNT ;RESET CHAR COUNT
1779 004774 005237 001044 INC CYCCNT ;INC CYCLE COUNT
1780 005000 001356 BNE TSA ;CONTINUE IF NOT DONE
1781 005002 032777 010000 173774 BIT #BIT12,@SWR ;LOOP ON TEST?
1782 005010 001257 BNE TEST2 ;LOOP
1783
1784 ;TEST 3
1785 ;TEST CHARACTER COMPARATOR WITH ALTERNATE LINES OF
1786 ;ALL CHARACTERS AND ILLEGAL CHARACTERS
1787
1788 005012 TEST3: $ENABLE
(1) 005012 022737 000176 001004 CMP #176,SWR ;S/W SWR ?
(1) 005020 001003 BNE .+10 ;NO- CONTINUE
(1) 005022 052777 000100 173770 BIS #100,ATKS ;ENABLE KEYBOARD INTERRUPT
1789 005030 004437 011472 JSR %4,TYPINT

```

1790	005034					SPRINT	\M		
(1)	005034	013737	014516	014002		MOV	TN03,MES15		;SET TEST NUMBER FOR MESSAGE
(1)	005042	004437	011422			JSR	%4,PRNNT		;PRINT TEST NUMBER
(1)		000004				M=M+1			
1791	005046	012737	177765	001044		MOV	#-13,CYCCNT		;SET 21 LINES
1792	005054	000137	005206			JMP	LP2H		;SEND ILLEGAL CHARS FIRST TO GIVE BLANK LINE
1793	005060	012737	177574	001036	T280:	MOV	#-132,CHRCNT		;SET CHAR COUNT FOR 132
1794	005066	012737	000040	001040	T280A:	MOV	#40,CHRCNT		;SET FIRST CHAR.
1795	005074	005777	173700		T281:	TST	ALPS		;DOES THE PRINTER HAVE AN ERROR
1796	005100	100006				BPL	LP2E		;BRANCH IF NO ERROR
1797	005102					SERROR	\N		
(1)	005102	012737	000034	001052	ERR34:	MOV	#34, ERCOUNT		;SET UP ERROR COUNT 34
(1)		000035				N=N+1			
1798	005110	004537	011706			JSR	%5,STAER		;REPORT ERROR
1799	005114	000000				HALT			;HALT ON ERROR
1800	005116	013777	001040	173656	LP2E:	MOV	CHRCNT,ALPB		;PRINT CHARACTER
1801	005124	005237	001036			INC	CHRCNT		;INC. CHAR. COUNT
1802	005130	001420				BEQ	T282		;BRANCH IF LINE IS FINISHED
1803	005132	005237	001040			INC	CHRCNT		;NEXT CHAR
1804	005136	032777	020000	173640		BIT	#BIT13,ASWR		;CHECK CHAR SET
1805	005144	001405				BEQ	T282B		;BRANCH IF 64 CHARS
1806	005146	022737	000200	001040		CMPL	#200,CHRCNT		;LEGAL CHAR?
1807	005154	001744				BEQ	T280A		;MAKE SPACE IF ILLEGAL
1808	005156	000746				BR	T281		;CONTINUE IF LEGAL CHAR
1809	005160	022737	000140	001040	T282B:	CMP	#140,CHRCNT		;LEGAL CHAR?
1810	005166	001737				BEQ	T280A		;MAKE SPACE IF ILLEGAL
1811	005170	000741				BR	T281		;CONTINUE IF LEGAL CHAR
1812	005172	012777	000012	173602	T282:	MOV	#12,ALPB		;ISSUE LINE FEED
1813	005200					SWAIT			
(1)	005200	105777	173574			TSTB	ALPS		;TEST READY
(1)	005204	100375				BPL	-4		;WAIT FOR READY
1814	005206	005037	001040		LP2H:	CLR	CHRCNT		;FIRST ILLEGAL CHAR
1815	005212	005777	173562		T283:	TST	ALPS		;TEST FOR ERROR
1816	005216	100006				BPL	LDCH		;BRANCH IF NO ERROR
1817	005220					SERROR	\N		
(1)	005220	012737	000035	001052	ERR35:	MOV	#35, ERCOUNT		;SET UP ERROR COUNT 35
(1)		000036				N=N+1			
1818	005226	004537	011706			JSR	%5,STAER		;REPORT ERROR SET
1819	005232	000000				HALT			;HALT ON ERROR
1820	005234	013777	001040	173540	LDCH:	MOV	CHRCNT,ALPB		;TRANSMIT CHARACTER
1821	005242	005237	001040		T284:	INC	CHRCNT		;NEXT CHAR
1822	005246	022737	000012	001040		CMP	#12,CHRCNT		;TEST FOR LINE FEED
1823	005254	001772				BEQ	T284		;SKIP IF LF
1824	005256	022737	000014	001040		CMP	#14,CHRCNT		;TEST FOR FORM FEED
1825	005264	001766				BEQ	T284		;SKIP IF FF
1826	005266	022737	000015	001040		CMP	#15,CHRCNT		;TEST FOR CARRIAGE RETURN
1827	005274	001762				BEQ	T284		;SKIP IF CR
1828	005276	023727	001040	000040		CMP	CHRCNT,#40		;CHECK IF LEGAL CHAR
1829	005304	002753				BLT	LDCH		;CONTINUE IF STILL ILLEGAL CHAR
1830	005306	032777	020000	173470		BIT	#BIT13,ASWR		;CHECK CHAR SET
1831	005314	001007				BNE	T285		;BRANCH IF 96 CHAR SET
1832	005316	052737	000100	001040		BIS	#100,CHRCNT		;SET BIT 7 IF NOT SET
1833	005324	032737	000200	001040		BIT	#200,CHRCNT		;DONE ILLEGAL CHARS?
1834	005332	001740				BEQ	LDCH		;BRANCH IF NOT DONE
1835	005334	012777	000012	173440	T285:	MOV	#12,ALPB		;ISSUE LINE FEED
1836	005342					SWAIT			

```

(1) 005342 105777 173432          TSTB  @LPS          ;TEST READY
(1) 005346 100375          BPL   .-4          ;WAIT FOR READY
1837 005350 005237 001044          INC  CYCCNT        ;INCREMENT LINE COUNT
1838 005354 001241          BNE  T280         ;CONTINUE IF NOT DONE
1839 005356 032777 010000 173420    BIT  #BIT12,@SWR  ;CHECK TO LOOP ON TEST
1840 005364 001212          BNE  TEST3        ;LOOP
1841
1842          ;TEST 4
1843          ;OVER PRINT TEST
1844          ;OVER PRINT FULL LINES OF ALTERNATING E'S AND SPACES
1845
1846 005366          CHRCHK: SENABLE
(1) 005366 022737 000176 001004    CMP  #176,SWR     ;S/W SWR ?
(1) 005374 001003          BNE  .+10         ;NO- CONTINUE
(1) 005376 052777 000100 173414    BIS  #100,@TKS   ;ENABLE KEYBOARD INTERRUPT
1847 005404 004437 011472          JSR  %4,TYPINT
1848 005410          $PRINT \M
(1) 005410 013737 014520 014002    MOV  TN04,MES15  ;SET TEST NUMBER FOR MESSAGE
(1) 005416 004437 011422          JSR  %4,PRNT     ;PRINT TEST NUMBER
(1) 005422 000005          M=M+1
1849 005422 012737 177750 001042    MOV  #-24,LINCNT ;SET UP LINE COUNT FOR 24 LINES
1850 005430 012737 177776 001044    MOV  #-2,CYCCNT  ;SET UP CYCLE COUNT
1851 005436 013737 005600 001054    MOV  CHRE,STRCHR ;SET CHAR TAG TO SPACE
1852 005444 012737 177574 001036    CR:  MOV  #-132,CHRCNT ;SET CHAR COUNT
1853 005452 005777 173322          CR0: TST  @LPS     ;TEST FOR ERROR
1854 005456 100006          BPL  CR1         ;CONTINUE IF NO ERROR
1855 005460          $ERROR \N
(1) 005460 012737 000036 001052    ERR36: MOV  #36, ERCOUNT ;SET UP ERROR COUNT 36
(1) 005466 004537 011706          N=N+1
1856 005466 004537 011706          JSR  %5,STAER   ;REPORT ERROR SET
1857 005472 000000          HALT            ;HALT ON ERROR
1858 005474 000177 173354          CR1: JMP  @STRCHR   ;OPPOSITE CHAR
1859 005500 013737 005600 001054    CR2: MOV  CHRE,STRCHR ;SET CHAR SWITCH TO SPACE
1860 005506 012737 000105 001050          CR3: MOV  #105,SAVE ;SEND E
1861 005514 013777 001050 173260          MOV  SAVE,@LPB  ;LOAD BUFFER
1862 005522 005237 001036          INC  CHRCNT     ;INCREMENT CHAR COUNT
1863 005526 001351          BNE  CR0        ;BRANCH IF NOT DONE
1864 005530 005237 001044          INC  CYCCNT     ;INCREMENT CYCLE COUNT
1865 005534 001422          BEQ  CR5        ;BRANCH IF FINISHED OVERPRINTS
1866 005536 012777 000015 173236    MOV  #15,@LPB  ;SEND CR
1867 005544          $WAIT
(1) 005544 105777 173230          TSTB @LPS        ;TEST READY
(1) 005550 100375          BPL   .-4        ;WAIT FOR READY
    
```



B04

MAINDEC-11-DZLPK-E-D MACY11 27(1006) 01-FEB-77 08:51 PAGE 18  
DZLPKF.P11 01-FEB-77 08:48

SEG 0040

1869	005552	000137	005444			JMP	CR		;OVERPRINT LINE
1870	005556	013737	005576	001054	CR7:	MOV	CHRS,STRCHR		;RESET CHAR SWITCH
1871	005564	012737	000040	001050		MOV	#40,SAVE		;SEND SPACE

⋮

```

1873 005572 000137 005514          JMP      CR3          ;CONTINUE
1874
1875 005576 005500          CHRS:   CR2
1876 005600 005556          CHRE:   CR7
1877 005602 012777 000012 173172  CRS:   MOV      #12,@LPB      ;SEND LF
1878 005610          SWAIT
(1) 005610 105777 173164          TSTB    @LPS          ;TEST READY
(1) 005614 100375          BPL     .-4           ;WAIT FOR READY
1879 005616 012737 177776 001044  MOV     #-2,CYCCNT    ;RESET CYCLE COUNT
1880 005624 012737 177574 001036  MOV     #-132,CHRCNT ;RESET CHAR COUNT
1881 005632 005237 001042          INC     LINCNT        ;INCREMENT LINE COUNT
1882 005636 001326          BNE     CR3           ;BRANCH IF NOT DONE
1883 005640 032777 010000 173136  BIT     @BIT12,@SWR   ;LOOP ON TEST?
1884 005646 001247          BNE     CHRCHK        ;YES, LOOP
1885
1886
1887
1888
1889
1890

```

```

;TEST 5
;SHUTTLE POSITIONING TEST
;SENDS PAIRS OF E'S, THEN OVER PRINTS THEM WITH SPACES AND ADDS ANOTHER

```

1895  
1896  
1897  
1898 005650  
(1) 005650 022737 000176 001004  
(1) 005656 001003  
(1) 005660 052777 000100 173132  
1899 005666 004437 011472  
1900 005672  
(1) 005672 013737 014522 014002  
(1) 005700 004437 011422  
(1) 000006  
1901 005704 012737 177760 001042  
1902 005712 012737 177574 001036  
1903 005720 012737 177776 001044  
1904 005726 013737 001036 001056  
1905 005734 062737 000205 001056  
1906 005742 012737 000040 001040  
1907 005750 000406  
1908 005752 012737 000105 001040

;PAIR OF E'S TO THE LINE --- THIS IS REPEATED UNTIL A FULL LINE OF E'S  
;HAVE BEEN PRINTED, THEN A FULL LINE OF M'S ARE PRINTED.

OVRPRT: \$ENABLE

CMP #176, SWR ;S/W SWR ?  
BNE .+10 ;NO- CONTINUE  
BIS #100, JTKS ;ENABLE KEYBOARD INTERRUPT  
JSR %4, TYPINT  
\$PRINT \M  
MOV TNOS, MES:5 ;SET TEST NUMBER FOR MESSAGE  
JSR %4, PRNNT ;PRINT TEST NUMBER  
M=M+1  
MOV #-16, LINCNT ;SET LINE COUNT FOR 16 LINES  
OVR: MOV #-132, CHRCNT ;SET CHAR COUNT  
OVR0: MOV #-2, CYCNT ;SET CYCLE COUNT FOR A PAIR OF E'S  
MOV CHRCNT, STRCNT ;NO. CHARS LEFT TO PRINT  
ADD #133, STRCNT ;NO. SPACES +1  
MOV #40, CHRCNT ;SEND SPACE  
BR OVR2 ;BRANCH  
OVR4: MOV #105, CHRCNT ;SEND E

E04

MAINDEC-11-DZLPK-E-D MACY11 27(1006) 01-FEB-77 08:51 PAGE 24  
DZLPKF.P11 01-FEB-77 08:48

SEQ 0043

1910	005760	013777	001040	173014	OVR1:	MOV	CHGEN, @LPB	;LOAD BUFFER
1911	005766	005777	173006		OVR2:	TST	@LPS	;TEST FOR ERROR
1912	005772	100006				BPL	OVR3	;BRANCH IF NO ERROR
1913	005774					ERROR	\N	
(1)	005774	012737	000037	001052	ERR37:	MOV	#37, ERCOUNT	;SET UP ERROR COUNT 37
(1)		000040				N=N+1		
1914	006002	004537	011706			JSR	%5, STAER	;REPORT ERROR SET
1915	006006	000000				HALT		
1916	006010	005337	001056		OVR3:	DEC	STRCNT	;DECREMENT SPACE COUNTER

F04

MAINDEC-11-DZLPK-E-D MACY11 27(1006) 01-FEB-77 08:51 PAGE 26  
DZLPKF.P11 01-FEB-77 08:48

SEQ 0044

1919 006014 003361

BGT OVR1

;BRANCH IF NOT DONE SPACES

-----

G04

MAINDEC-11-DZLPK-E-D MACY11 27(1006) 01-FEB-77 08:51 PAGE 27  
DZLPKF.P11 01-FEB-77 08:48

SEG 0045

1921	006016	001755		BEQ	OVR4	; BRANCH IF NOT FIRST E
1922	006020	005237	001036	INC	CHRCNT	; INCREMENT CHAR COUNT
1923	006024	001437		BEQ	OVR8	; BRANCH IF DONE LINE
1924	006026	005237	001044	OVR5: INC	CYCCNT	; INCREMENT CYCLE COUNT

H04

1926	006032	001352			BNE	OVR1		; CONTINUE SENDING E'S IF NOT DONE
1927	006034	012777	000015	172740	MOV	#15, @LPB		; SEND CR
1928	006042				SWAIT		OVR6:	
(1)	006042	105777	172732		TSTB	@LPS		; TEST READY
(1)	006046	100375			BPL	-4		; WAIT FOR READY
1929	006050	005737	001036		TST	CHRCNT		; LINE DONE?
1930	006054	001321			BNE	OVR0		; NO, CONTINUE OVER PRINT
1931	006056	005237	001042		INC	LINCNT		; YES, INCREMENT LINE COUNT
1932	006062	001425			BEQ	OVRXT		; EXIT IF DONE TEST
1933	006064	032737	000001	001042	BIT	#1, LINCNT		; WHICH LINE NEXT?
1934	006072	001707			BEQ	OVR		; BRANCH TO SEND E'S
1935	006074	012737	000115	001040	MOV	#115, CHRCNT		; SET UP TO SEND M'S
1936	006102	012737	177573	001036	MOV	#-133, CHRCNT		; SET CHAR COUNT
1937	006110	005037	001056		CLR	STRCNT		; CLEAR SPACE COUNT
1938	006114	005037	001044		CLR	CYCCNT		; CLEAR CYCLE COUNT

104

MAINDEC-11-DZLPK-E-D MACY11 27(1006) 01-FEB-77 08:51 PAGE 29  
DZLPKF.P11 01-FEB-77 08:48

SEG 0047

1940	006120	000137	005766			JMP	OVR2		;PRINT LINE OF M'S
1941	006124	012777	000012	172650	OVR8:	MOV	#12,0LPB		;SEND LF



J04

MAINDEC-11-DZLPK-E-D MACY11 27(1006) 01-FEB-77 08:51 PAGE 31  
DZLPKF.P11 01-FEB-77 08:48

SEQ 0048

1944 006132 000137 006042

JMP OVR6

;CONTINUE

K04

MAINDEC-11-DZLPK-E-D MACY11 27(1006) 01-FEB-77 08:51 PAGE 32  
DZLPKF.P11 01-FEB-77 08:48

SEQ 0049

```

1946 006136 032777 010000 172640 OVREXT: BIT #BIT12,JSWR ;LOOP ON TEST?
1947 006144 001241 BNE OVRPRT ;LOOP
1948
1949 ;TEST 6
1950 ;PRINT CONTROL TEST
1951 ;SENDS FULL LINE OF SAME CHARACTER THEN FULL CHAR SET
1952 ;SHOULD ONLY PRINT THE FIRST 132 CHARACTERS RECEIVED
1953
1954 006146 PRTCTL: $ENABLE
(1) 006146 022737 000176 001004 CMP #176,SWR ;S/W SWR ?
(1) 006154 001003 BNE .+10 ;NO- CONTINUE
(1) 006156 052777 000100 172634 BIS #100,JKS ;ENABLE KEYBOARD INTERRUPT
1955 006164 004437 011472 JSR %4,TYPINT

```

L04

1957	006170					SPRINT	\M		
(1)	006170	013737	014524	014002		MOV	TN06,MES15		;SET TEST NUMBER FOR MESSAGE
(1)	006176	004437	011422			JSR	%4,PANNT		;PRINT TEST NUMBER
(1)		000007				M=M+1			
1958	006202	012737	000060	001054		MOV	#60,STRCHR		;FIRST START CHAR
1959	006210	032777	020000	172566	PRT0:	BIT	#BIT13,JSWR		;TEST FOR CHAR SET
1960	006216	001404				BEQ	PRT1		;BRANCH IF 64 CHARS
1961	006220	012737	177641	001034		MOV	#-95.,SEGCNT		;SET OVERFLOW COUNT
1962	006226	000403				BR	PRT2		;BRANCH
1963	006230	012737	177701	001034	PRT1:	MOV	#-63.,SEGCNT		;SET OVERFLOW COUNT
1964	006236	012737	177574	001036	PRT2:	MOV	#-132.,CHRCNT		;SET CHAR COUNT
1965	006244	013737	001054	001040		MOV	STRCHR,CHRCNT		;GET START CHAR
1966	006252	005777	172522		PRT3:	TST	ALPS		;TEST FOR ERROR
1967	006256	100006				BPL	PRT4		;BRANCH IF NO ERROR
1968	006260					\$ERROR	\N		
(1)	006260	012737	000040	001052	ERR40:	MOV	#40, ERCOUNT		;SET UP ERROR COUNT 40
(1)		000041				N=N+1			
1969	006266	004537	011706			JSR	%5,STAER		;REPORT ERROR SET
1970	006272	000000				HALT			;HALT ON ERROR
1971	006274	013777	001040	172500	PRT4:	MOV	CHRCNT,ALPB		;LOAD BUFFER
1972	006302	005237	001036			INC	CHRCNT		;INCREMENT CHAR COUNT
1973	006306	002761				BLT	PRT3		;BRANCH IF NOT 132 CHARS
1974	006310	001433				BEQ	PRTA		;START OVERFLOW
1975	006312	005237	001040			INC	CHRCNT		;NEXT CHAR

```

1977 006316 005237 001034      INC      SEGCNT      ; INCREMENT OVERFLOW COUNT
1978 006322 001353      BNE      PRT3      ; CONTINUE IF NOT DONE
1979 006324 012777 000012 172450      MOV      #12, @LPB ; SEND LF
1980 006332      $WAIT
(1) 006332 105777 172442      TSTB     @LPS      ; TEST READY
(1) 006336 100375      BPL      .-4       ; WAIT FOR READY
1981 006340 022737 000040 001054      CMP      #40, STRCHR ; LAST START CHAR SPACE?
1982 006346 001421      BEQ      PRT6      ; YES BRANCH
1983 006350 022737 000065 001054      CMP      #65, STRCHR ; LAST START CHAR 5?
1984 006356 001422      BEQ      PRT7      ; YES BRANCH
1985 006360 022737 000071 001054      CMP      #71, STRCHR ; DONE?
1986 006366 001423      BEQ      PRT8      ; YES
1987 006370 005237 001054      INC      STRCHR    ; NO GET NEXT START CHAR
1988 006374 000137 006210      JMP      PRT0      ; CONTINUE
1989 006400 012737 000041 001040 PRTA:  MOV      #41, CHRCNT ; GET FIRST CHAR IN SET
1990 006406 000137 006252      JMP      PRT3      ; START OVERFLOW
1991 006412 012737 000066 001054 PRT6:  MOV      #66, STRCHR ; SET START CHAR TO 6
1992 006420 000137 006210      JMP      PRT0      ; CONTINUE
1993 006424 012737 000040 001054 PRT7:  MOV      #40, STRCHR ; SET START CHAR TO SPACE
1994 006432 000137 006210      JMP      PRT0      ; CONTINUE
1995 006436 032777 010000 172340 PRT8:  BIT      #BIT12, @SWR ; CHECK LOOP ON TEST
1996 006444 001240      BNE      PRTCTL    ; LOOP
1997
1998      ; TEST 7
1999      ; MULTIPLE LINE ADVANCE TEST
2000      ; TESTS MULTIPLE LINE ADVANCES AND TIMINGS
2001      ; PRINTS THE NUMBER OF LINES SKIPPED ON THE LINE PRINTER
2002
2003      MLF:  $ENABLE
(1) 006446 022737 000176 001004      CMP      #176, SWR ; S/W SWR ?
(1) 006454 001003      BNE      .+10     ; NO- CONTINUE
(1) 006456 052777 000100 172334      BIS      #100, @TKS ; ENABLE KEYBOARD INTERRUPT
2004 006464 004437 011472      JSR      %4, TYPINT
2005 006470      $PRINT \M
(1) 006470 013737 014526 014002      MOV      TN07, MES15 ; SET TEST NUMBER FOR MESSAGE
(1) 006476 004437 011422      JSR      %4, PRNNT ; PRINT TEST NUMBER
(1) 000010
2006 006502 012737 006634 001054      MOV      #TABSTR, STRCHR ; FIRST CHAR
2007 006510 012737 177574 001036 MLFA:  MOV      #-132, CHRCNT ; SET CHAR COUNT
2008 006516 117737 172332 001040      MOVB    @STRCHR, CHRCNT ; GET CHAR
2009 006524 001452      BEQ      MLF4      ; BRANCH IF DONE
2010 006526 005777 172246      TST     @LPS      ; TEST FOR ERROR
2011 006532 100006      BPL     MLF1      ; CONTINUE IF NO ERROR
2012 006534      $ERROR \N
(1) 006534 012737 000041 001052 ERR41: MOV      #41, ERCOUNT ; SET UP ERROR COUNT 41
(1) 000042
2013 006542 004537 011706      JSR     %5, STAER ; REPORT ERROR
2014 006546 000000      HALT     ; HALT ON ERROR
2015 006550 013777 001040 172224 MLF1:  MOV      CHRCNT, @LPB ; LOAD BUFFER
2016 006556 005237 001036      INC     CHRCNT    ; INCREMENT CHAR COUNT
2017 006562 001361      BNE     MLF0      ; CONTINUE
2018 006564 117737 172264 001042      MOVB    @STRCHR, LINCNT ; GET ASCII LINE COUNT
2019 006572 042737 177770 001042      BIC     #177770, LINCNT ; MAKE OCTAL
2020 006600 005237 001042      INC     LINCNT    ; ADD 1
2021 006604 012777 000012 172170 MLF2:  MOV      #12, @LPB ; SEND LF
2022 006612      $WAIT

```

N04

MAINDEC-11-DZLPK-E-D MACY11 27(1006) 01-FEB-77 08:51 PAGE 34-1  
DZLPKF.P11 01-FEB-77 08:48

SEQ 0052

(1)	006612	105777	172162
(1)	006616	100375	
2023	006620	005337	001042
2024	006624	001367	
2025	006626	005237	001054

TSTB	2LPS
BPL	.-4
DEC	LINCNT
BNE	MLF2
INC	STRCHR

; TEST READY
; WAIT FOR READY
; DECREMENT LINE COUNT
; CONTINUE
; NEXT CHAR

```

2029 006632 000726 BR MLFA ;CONTINUE
2030
2031 006634 033462 033062 033463 TABSTR: .ASCIZ /272637463540/
006642 033064 032463 030064
006650 000
2032
2033 006652 .EVEN
2034
2035 006652 032777 010000 172124 MLF4: BIT #BIT12,2SWR ;CHECK LOOP ON TEST
2036 006660 001272 BNE MLF ;LOOP
2037 .EVEN
2038
2039 ;TEST 8
2040 ;HIGH SPEED PRINT TEST
2041
2042 006662 HSPRT: SENABLE
(1) 006662 022737 000176 001004 CMP #176,SWR ;S/W SWR ?
(1) 006670 001003 BNE .+10 ;NO- CONTINUE
(1) 006672 052777 000100 172120 BIS #100,2TKS ;ENABLE KEYBOARD INTERRUPT
2043 006700 004437 011472 JSR %4,TYPINT
2044 006704 SPRINT \M
(1) 006704 013737 014530 014002 MOV TNO10,MES15 ;SET TEST NUMBER FOR MESSAGE
(1) 006712 004437 011422 JSR %4,PRINT ;PRINT TEST NUMBER
(1) 000011 M=M+1
2045 006716 032777 002000 172060 BIT #BIT10,2SWR ;CHECK FOR NEW DRUM / OLD DRUM
2046 006724 001135 BNE NHSPRT ;BRANCH IF NEW DRUM
2047 006726 032777 020000 172050 BIT #BIT13,2SWR ;CHECK CHAR SET
2048 006734 001007 BNE HS00A ;BRANCH IF 96 CHAR SET
2049 006736 012737 000140 001060 MOV #140,LEGCHR ;LEGAL CHK
2050 006744 012737 000100 001062 MOV #100,NUMCHR ;#CHARS
2051 006752 000406 BR HS00 ;CONTINUE
2052 006754 012737 000200 001060 HS00A: MOV #200,LEGCHR ;LEGAL CHECK
2053 006762 012737 000140 001062 MOV #140,NUMCHR ;#CHARS
2054 006770 012737 000040 001054 HS00: MOV #40,STRCHR ;SET UP FIRST LINE
2055 006776 012737 000177 001042 MOV #127,LINCNT ;SET LINE COUNT FOR 2 PAGES
2056 007004 012737 177574 001036 HS0: MOV #-132,CHRCNT ;SET CHAR COUNT
2057 007012 012737 177757 001044 MOV #-17,CYC CNT ;SET GROUP COUNT
2058 007020 013737 001054 001040 MOV STRCHR,CHRGEN ;STORE START CHAR
2059 007026 005777 171746 HS1: TST 2LPS ;TEST FOR ERROR
2060 007032 100006 BPL HS2 ;BRANCH IF NO ERROR
2061 007034 SERROR \N
(1) 007034 012737 000042 001052 ERR42: MOV #42, ERCOUNT ;SET UP ERROR COUNT 42
(1) 000043 N=N+1
2062 007042 004537 011706 JSR %5,STAER ;REPORT ERROR SET
2063 007046 000000 HALT ;HALT ON ERROR
2064 007050 013777 001040 171724 HS2: MOV CHRGEN,2LPB ;LOAD BUFFER
2065 007056 005237 001036 INC CHRCNT ;INCREMENT CHAR COUNT
2066 007062 001424 BEQ HS4 ;BRANCH IF DONE LINE
2067 007064 005237 001040 INC CHRGEN ;NEXT CHAR
2068 007070 005237 001044 INC CYC CNT ;INCREMENT GROUP COUNT
2069 007074 001410 BEQ HS3 ;BRANCH IF DONE GROUP
2070 007076 023737 001060 001040 CMP LEGCHR,CHRGEN ;LEGAL CHAR?
2071 007104 001350 BNE HS1 ;BRANCH AND CONTINUE IF LEGAL CHAR
2072 007106 163737 001062 001040 SUB NUMCHR,CHRGEN ;MAKE LEGAL
2073 007114 000744 BR HS1 ;CONTINUE
2074 007116 013737 001054 001040 HS3: MOV STRCHR,CHRGEN ;GET FIRST CHAR IN GROUP

```

2075	007124	012737	177757	001044		MOV	#-17.,CYCCNT	;RESET CYCLE COUNT
2076	007132	000735				BR	H51	;CONTINUE
2077	007134	012777	000012	171640	H54:	MOV	#12,@LPB	;SEND LF
2078	007142					SWAIT		
(1)	007142	105777	171632			TSTB	@LPS	;TEST READY
(1)	007146	100375				BPL	.-4	;WAIT FOR READY
2079	007150	005337	001042			DEC	LINCNT	;DECREMENT LINE COUNT
2080	007154	002413				BLT	H56	;EXIT TEST IF DONE
2081	007156	162737	000004	001054		SUB	#4,STRCHR	;SKIP 4 LINES ON DRUM, FIND START CHAR
2082	007164	022737	000040	001054		CMP	#40,STRCHR	;START CHAR A LEGAL CHAR?
2083	007172	003704				BLE	H50	;CONTINUE IF LEGAL START CHAR
2084	007174	063737	001062	001054		ADD	NUMCHR,STRCHR	;MAKE LEGAL AND CONTINUE
2085	007202	000700				BR	H50	;CONTINUE
2086	007204	032777	010000	171572	H56:	BIT	#BIT12,@SWR	;LOOP ON TEST?
2087	007212	001223				BNE	HSPRT	;LOOP
2088								
2089								
2090	007214	000137	007464			JMP	SNGCHR	;JUMP TO TEST 9 AFTER COMPLETION
2091								
2092								
2093								
2094								
2095	007220	032777	020000	171556	NHSPRT:	BIT	#BIT13,@SWR	;CHECK CHARACTER SET
2096	007226	001007				BNE	NH500A	;BRANCH IF 96 CHARACTER SET
2097								
2098	007230	012737	000140	001060		MOV	#140,LEGCHR	;LEGAL CHARACTER CHECK
2099	007236	012737	000100	001062		MOV	#100,NUMCHR	;# CHARACTERS = 64
2100	007244	000406				BR	NH500	;CONTINUE
2101	007246	012737	000200	001060	NH500A:	MOV	#200,LEGCHR	;LEGAL CHARACTER CHECK
2102	007254	012737	000140	001062		MOV	#140,NUMCHR	;# CHARACTERS = 96
2103	007262	012737	000003	001064	NH500:	MOV	#3,OFFSET	;COLUMN/CHARACTER OFFSET
2104	007270	012737	000040	001054		MOV	#40,STRCHR	;SET UP FIRST CHARACTER OF FIRSTLINE
2105	007276	012737	000177	001042		MOV	#127.,LINCNT	;SET LINE COUNT FOR 2 PAGES
2106	007304	012737	177574	001036	NH50:	MOV	#-132.,CHRCNT	;SET CHARACTER COUNT = # COLUMNS
2107	007312	013737	001054	001040		MOV	STRCHR,CHRCNT	;STORE STARTING CHARACTER
2108	007320	005777	171454		NH51:	TST	@LPS	;TEST FOR ERROR
2109	007324	100006				BPL	NH52	;BRANCH IF NO ERROR
2110	007326					\$ERROR	\N	
(1)	007326	012737	000043	001052	ERR43:	MOV	#43, ERCOUNT	;SET UP ERROR COUNT 43
(1)		000044				N=N+1		
2111	007334	004537	011706			JSR	%5,STAER	;REPORT ERROR SET
2112	007340	000000				HALT		;HALT ON ERROR
2113	007342	013777	001040	171432	NH52:	MOV	CHRCNT,@LPB	;LOAD PRINTER BUFFER
2114	007350	005237	001036			INC	CHRCNT	;INCREMENT CHARACTER COUNT
2115	007354	001413				BEQ	NH54	;BRANCH IF LINE DONE
2116	007356	063737	001064	001040		ADD	OFFSET,CHRCNT	;NEXT CHARACTER
2117	007364	023737	001060	001040		CMP	LEGCHR,CHRCNT	;LEGAL CHARACTER
2118	007372	003352				BGT	NH51	;BRANCH + CONTINUE IF LEGAL CHARACTER
2119	007374	163737	001062	001040		SUB	NUMCHR,CHRCNT	;MAKE LEGAL
2120	007402	000746				BR	NH51	;CONTINUE
2121	007404	012777	000012	171370	NH54:	MOV	#12,@LPB	;SEND LINE FEED.
2122	007412					SWAIT		
(1)	007412	105777	171362			TSTB	@LPS	;TEST READY
(1)	007416	100375				BPL	.-4	;WAIT FOR READY
2123	007420	005337	001042			DEC	LINCNT	;DECREMENT LINE COUNT
2124	007424	002413				BLT	NH56	;EXIT IF TEST IS DONE

;NEW DRUM (LP14) HIGH SPEED PRINT TEST

```

2125 007426 162737 000004 001054 SUB #4,STRCHR ;SKIP 4 LINES DOWN DRUM,FIND STARTING CHARACTER
2126 007434 022737 000040 001054 CMP #40,STRCHR ;START CHARACTER A LEGAL CHARACTER
2127 007442 003720 BLE NHS0 ;CONTINUE IF LEGAL START CHARACTER
2128 007444 063737 001062 001054 ADD NUMCHR,STRCHR ;MAKE LEGAL + CONTINUE
2129 007452 000714 BR NHS0 ;CONTINUE
2130 007454 032777 010000 171322 NHS6: BIT #BIT12,@SWR ;LOOP ON TEST
2131 007462 001256 BNE NHSVRT ;LOOP
2132
2133 ;TEST 9
2134 ;WORST CASE NOISE TEST
2135 ;SINGLE CHAR. ACROSS ALL COLS.
2136
2137 007464 SNGCHR: $ENABLE
(1) 007464 022737 000176 001004 CMP #176,SWR ;S/W SWR ?
(1) 007472 001003 BNE .+10 ;NO- CONTINUE
(1) 007474 052777 000100 171316 BIS #100,@TKS ;ENABLE KEYBOARD INTERRUPT
2138 007502 004437 011472 JSR %4,TYPINT
2139 007506 $PRINT \M
(1) 007506 013737 014532 014002 MOV TNO11,MESIS ;SET TEST NUMBER FOR MESSAGE
(1) 007514 004437 011422 JSR %4,PRINT ;PRINT TEST NUMBER
(1) 000012 M=M+1
2140 007520 032777 020000 171256 BIT #BIT13,@SWR ;TEST CHAR SET
2141 007526 001404 BEQ S2 ;BRANCH IF 64
2142 007530 012737 177640 001042 MOV #-96.,LINCNT ;96 CHAR.
2143 007536 000403 BR .+10 ;BRANCH
2144 007540 012737 177700 001042 S2: MOV #-64.,LINCNT ;64 CHAR.
2145 007546 012737 000040 001040 MOV #40,CHRCNT ;SET UP SPACE
2146 007554 012737 177574 001036 S2A: MOV #-132.,CHRCNT ;SET CHAR COUNT FOR 132
2147 007562 005777 171212 S1: TST @LPS ;TEST FOR ERRORS
2148 007566 100006 BPL $ERROR XSIX ;BRANCH IF NO ERRORS
2149 007570 $ERROR \N
(1) 007570 012737 000044 001052 ERR44: MOV #44, ERCOUNT ;SET UP ERROR COUNT 44
(1) 000045 N=N+1
2150 007576 004537 011706 JSR %5,STAER ;REPORT ERROR
2151 007602 000000 HALT ;HALT ON ERROR
2152 007604 013777 001040 171170 XSIX: MOV CHRCNT,@LPB ;LOAD PRINTER BUFFER
2153 007612 005237 001036 INC CHRCNT ;INCREMENT CHAR COUNT
2154 007616 001361 BNE S1 ;CONTINUE IF NOT DONE LINE
2155 007620 012777 000012 171154 S4X2: MOV #12,@LPB ;ISSUE LINE FEED
2156 007626 $WAIT
(1) 007626 105777 171146 TSTB @LPS ;TEST READY
(1) 007632 100375 BPL .-4 ;WAIT FOR READY
2157 007634 005237 001040 INC CHRCNT ;+1 CHAR.
2158 007640 005237 001042 INC LINCNT ;+1 LINE COUNT
2159 007644 002743 BLT S2A ;CONTINUE IF NOT DONE
2160 007646 001764 BEQ S4X2 ;SEND BLANK LINE AT END OF TEST
2161 007650 032777 010000 171126 LPS7: BIT #BIT12,@SWR ;CHECK TO LOOP ON TEST
2162 007656 001302 BNE SNGCHR ;LOOP ON TEST
2163
2164
2165
2166 ;TEST 10
2167 ;DRUM PATTERN CHARACTER TEST
2168
2169 007660 ROTATE: $ENABLE
(1) 007660 022737 000176 001004 CMP #176,SWR ;S/W SWR ?

```



```

(1) 007666 001003          BNE      .+10          ;NO- CONTINUE
(1) 007670 052777 000100 171122  BIS      #100,@TKS    ;ENABLE KEYBOARD INTERRUPT
2170 007676 004437 01.472    JSR      %4,TYPINT
2171 007702          SPRINT  \M
(1) 007702 013737 014534 014002  MOV      TN012,MSG15  ;SET TEST NUMBER FOR MESSAGE
(1) 007710 004437 011422    JSR      %4,PRINT    ;PRINT TEST NUMBER
(1) 000013
2172
2173 007714 032777 002000 171062  BIT      #BIT10,@SWR  ;CHECK FOR NEW DRUM/OLD DRUM
2174 007722 001122          BNE      NROTAT      ;BRANCH IF NEW DRUM
2175 007724 032777 020000 171052  BIT      #BIT13,@SWR  ;TEST CHAR SET
2176 007732 001012          BNE      ROT0        ;SKIP IF 96 CHAR
2177 007734 012737 000137 001042  MOV      #137,LINCNT  ;LAST CHAR
2178 007742 012737 000140 001060  MOV      #140,LEGCHR  ;LEGAL CHK
2179 007750 012737 000100 001062  MOV      #100,NUMCHR  ;#CHARS
2180 007756 000411          BR       ROT1
2181 007760 012737 000177 001042  ROT0:  MOV      #177,LINCNT ;LAST CHAR
2182 007766 012737 000200 001060  MOV      #200,LEGCHR  ;LEGAL CHK
2183 007774 012737 000140 001062  MOV      #140,NUMCHR  ;#CHARS
2184 010002 005037 001044          ROT1:  CLR      CYCCNT   ;CLEAR CYCLE COUNT
2185 010006 005237 001044          ROT2:  INC      CYCCNT   ;INC CYCLE COUNT
2186 010012 005037 001040          CLR      CHRCN      ;CLEAR POINTER
2187 010016 005237 001040          ROT3:  INC      CHRCN   ;INC POINTER
2188 010022 013737 001040 001054  MOV      CHRCN,STRCHR ;STORE POINTER
2189 010030 063737 001042 001054  ADD      LINCNT,STRCHR ;FIND CHAR
2190 010036 023737 001054 001060  CMP      STRCHR,LEGCHR ;LEGAL?
2191 010044 002403          BLT     ROT4
2192 010046 163737 001062 001054  SUB      NUMCHR,STRCHR ;MAKE LEGAL
2193 010054 005777 170720          ROT4:  TST     @LPS
2194 010060 100006          BPL     ROT5
2195 010062          $ERROR  \N
(1) 010062 012737 000045 001052  ERR45: MOV      #45, ERCCOUNT ;SET UP ERROR COUNT 45
(1) 000046
2196 010070 004537 011706          JSR     %5,STAER    ;REPORT ERROR
2197 010074 000000          HALT    ;HALT ON ERROR
2198 010076 013777 001054 170676  ROT5:  MOV      STRCHR,@LPB ;LOAD BUFFER
2199 010104 023727 001040 000021  CMP      CHRCN,#17.  ;DONE GROUP?
2200 010112 001341          BNE     ROT3        ;NO GET NEXT CHAR
2201 010114 023727 001044 000010  CMP      CYCCNT,#8.  ;DONE LINE?
2202 010122 001331          BNE     ROT2        ;NO, NEXT GROUP
2203 010124 012777 000012 170650  MOV      #12,@LPB   ;YES, SEND LF
2204 010132          $WAIT
(1) 010132 105777 170642          TSTB   @LPS        ;TEST READY
(1) 010136 100375          BPL     .-4         ;WAIT FOR READY
2205 010140 005337 001042          DEC     LINCNT      ;DECREMENT LINE COUNT
2206 010144 023727 001042 000037  CMP      LINCNT,#37 ;DONE?
2207 010152 003313          BGT     ROT1        ;NO, NEXT LINE
2208 010154 032777 010000 170622  BIT      #BIT12,@SWR ;LOOP ON TEST?
2209 010162 001236          BNE     ROTATE     ;LOOP
2210
2211 010164 000137 010422          JMP     LFTTR      ;JUMP TO TEST 11 AFTER COMPLETION
2212
2213
2214          ;NEW DRUM (LP14) PATTERN CHARACTER TEST
2215
2216 010170 032777 020000 170606  NROTAT: BIT     #BIT13,@SWR ;TEST CHARACTER SET

```

```

2217 010176 001012      BNE      NROTO      ;SKIP IF 96 CHARACTERS
2218 010200 012737 000137 001042      MOV      #137,LINCNT ;LAST CHARACTER
2219 010206 012737 000140 001060      MOV      #140,LEGCHR ;LEGAL CHECK
2220 010214 012737 000100 001062      MOV      #100,NUMCHR ;# OF CHARACTERS
2221 010222 000411          BR       NROT1      ;CONTINUE
2222 010224 012737 000177 001042 NROTO:  MOV      #177,LINCNT ;LAST CHARACTER
2223 010232 012737 000200 001060      MOV      #200,LEGCHR ;LEGAL CHECK
2224 010240 012737 000140 001062      MOV      #140,NUMCHR ;# OF CHARACTERS
2225 010246 012737 000040 001040 NROT1:  MOV      #40,CHGEN  ;GET POINTER
2226 010254 005237 001040      NROT6:  INC      CHGEN    ;SET POINTER
2227 010260 013737 001040 001054      MOV      CHGEN,STRCHR ;STORE POINTER
2228 010266 005037 001036          CLR      CHRCNT    ;# CHARACTERS PRINTED
2229 010272 005237 001036      NROT2:  INC      CHRCNT  ;INCREMENT CHARACTERS PRINTED
2230 010276 063737 001064 001054      ADD      OFFSET,STRCHR ;INCREMENT POINTER
2231 010304 023737 001054 001060      CMP      STRCHR,LEGCHR ;LEGAL CHARACTER?
2232 010312 002403          BLT     NROT4      ;BRANCH IF LEGAL
2233 010314 163737 001062 001054      SUB      NUMCHR,STRCHR ;MAKE LEGAL
2234 010322 005777 170452      NROT4:  TST      @LPS   ;TEST FOR ERRORS
2235 010326 100006          BPL     NROT5      ;BRANCH IF NO ERRORS
2236 010330          SERROR  \N
(1) 010330 012737 000046 001052 ERR46:  MOV      #46,   ERCOUNT ;SET UP ERROR COUNT 46
(1)          000047          N=N+1
2237 010336 004537 011706          JSR     %5,STAER   ;REPORT ERROR
2238 010342 000000          HALT
2239 010344 013777 001054 170430 NROT5:  MOV      STRCHR,@LPB  ;LOAD BUFFER
2240 010352 023727 001036 000204      CMP      CHRCNT,#132. ;LINE FINISHED?
2241 010360 001344          BNE     NROT2      ;NO GET NEXT CHARACTER
2242 010362 012777 000012 170412      MOV      #12,@LPB   ;YES,SEND LINE FEED
2243 010370          SWAIT
(1) 010370 105777 170404      TSTB   @LPS       ;TEST READY
(1) 010374 100375          BPL     .-4        ;WAIT FOR READY
2244 010376 005337 001042          DEC     LINCNT    ;DECREMENT LINE COUNT
2245 010402 023727 001042 000037      CMP      LINCNT,#37 ;PATTERN FINISHED
2246 010410 003321          BGT     NROT6      ;NO, DO NEXT LINE
2247 010412 032777 010000 170364      BIT     #BIT12,@SWR ;LOOP ON TEST
2248 010420 001263          BNE     NROTAT    ;LOOP
2249
2250          ;TEST 11 ---- SPURIOUS HAMMER FIRING TEST
2251          ;LEFT AND RIGHT TRIANGLES
2252
2253          ; STARTING WITH A LEFT TRIANGLE
2254
2255 010422          LFTTR:  SENABLE
(1) 010422 022737 000176 001004      CMP      #176,SWR   ;S/W SWR ?
(1) 010430 001003          BNE     .+10       ;NO- CONTINUE
(1) 010432 052777 000100 170360      BIS     #100,@TKS   ;ENABLE KEYBOARD INTERRUPT
2256 010440 004437 011472          JSR     %4,TYPINT
2257 010444          $PRINT  \M
(1) 010444 013737 014536 014002      MOV      TNO13,MES15 ;SET TEST NUMBER FOR MESSAGE
(1) 010452 004437 011422          JSR     %4,PRNT    ;PRINT TEST NUMBER
(1)          000014          M=M+1
2258 010456 012737 000204 001042 LFT:    MOV      #132,LINCNT ;SET LINE COUNT
2259 010464 013737 001042 001036 LFT0:  MOV      LINCNT,CHRCNT ;STORE CHAR COUNT
2260 010472 012737 177757 001044      MOV      #-17,CYCCNT ;SET GROUP COUNT
2261 010500 013737 001036 001040      MOV      CHRCNT,CHGEN ;FIND FIRST CHAR ON LINE...
2262 010506 022737 000022 001040 LFT1:  CMP      #18.,CHGEN ;MORE THAN 17 CHARS?

```

2263	010514	003004			BGT	LFT2	; BRANCH IF LESS THAN 17
2264	010516	162737	000021	001040	SUB	#17.,CHRGEN	; SUBTRACT 17, IF > 17
2265	010524	000770			BR	LFT1	; CONTINUE
2266	010526	005437	001040		LFT2:	NEG	; NEGATE CHRGEN
2267	010532	062737	000100	001040	ADD	#100,CHRGEN	; START CHAR IN CHRGEN
2268	010540	013737	001040	001054	MOV	CHRGEN,STRCHR	; STORE STARTING CHAR
2269	010546	005777	170226		LFT3:	TST	; TEST FOR ERROR
2270	010552	100006			BPL	LFT4	; CONTINUE IF NO ERROR
2271	010554				\$ERROR	\N	
(1)	010554	012737	000047	001052	ERR47:	MOV	#47, ERCOUNT ;SET UP ERROR COUNT 47
(1)		000050				N=N+1	
2272	010562	004537	011706		JSR	%5,STAER	; REPORT ERROR SET
2273	010566	000000			HALT		; HALT ON ERROR
2274	010570	013777	001040	170204	LFT4:	MOV	CHRGEN,ALPB ;LOAD BUFFER
2275	010576	005337	001036		DEC	CHRCNT	; DECREMENT CHAR COUNT
2276	010602	001415			BEQ	LFT6	; BRANCH IF DONE LINE
2277	010604	005237	001044		INC	CYCCNT	; INCREMENT GROUP COUNT
2278	010610	001403			BEQ	LFT5	; BRANCH IF DONE GROUP
2279	010612	005237	001040		INC	CHRGEN	; NEXT CHAR IN GROUP
2280	010616	000753			BR	LFT3	; CONTINUE
2281	010620	013737	001054	001040	LFT5:	MOV	STRCHR,CHRGEN ;GET START CHAR AGAIN
2282	010626	012737	177757	001044	MOV	#-17.,CYCCNT	; RESET GROUP COUNT
2283	010634	000744			BR	LFT3	; CONTINUE
2284	010636	012777	000012	170136	LFT6:	MOV	#12,ALPB ;SEND LF
2285	010644				\$WAIT		
(1)	010644	105777	170130		TSTB	ALPS	; TEST READY
(1)	010650	100375			BPL	.-4	; WAIT FOR READY
2286	010652	005337	001042		DEC	LINCNT	; DECREMENT LINE COUNT
2287	010656	003302			BGT	LFT0	; BRANCH IF NOT DONE
2288	010660	001766			BEQ	LFT6	; SEND BLANK LINE AT END OF TEST
2289	010662	032777	010000	170114	BIT	#BIT12,ASWR	; LOOP ON TEST?
2290	010670	001254			BNE	LFTTR	; LOOP
2291							
2292							
2293							
2294							
2295	010672	012737	000001	001042	RTTR:	MOV	#1,LINCNT ;INITIALIZE LINE
2296	010700	012737	000077	001040	RT1:	MOV	#77,CHRGEN ;FIRST CHAR IS A ?
2297	010706	013737	001042	001044		MOV	LINCNT,CYCCNT ;SAVE NO. CHARS ON LINE
2298	010714	012737	177757	001056		MOV	#-17.,STRCNT ;SET GROUP COUNT
2299	010722	012737	000204	001036		MOV	#132.,CHRCNT ;NO. CHARS PER LINE
2300	010730	163737	001042	001036		SUB	LINCNT,CHRCNT ;SUBTRACT NO. OF CHARS ON LINE
2301	010736	001425			BEQ	RT3	; BRANCH IF NO SPACES ON THIS LINE
2302	010740	005777	170034		RT2:	TST	ALPS ;TEST FOR ERROR
2303	010744	100006			BPL	RT2A	; CONTINUE IF NO ERROR
2304	010746				\$ERROR	\N	
(1)	010746	012737	000050	001052	ERR50:	MOV	#50, ERCOUNT ;SET UP ERROR COUNT 50
(1)		000051				N=N+1	
2305	010754	004537	011706		JSR	%5,STAER	; REPORT ERROR SET
2306	010760	000000			HALT		; HALT ON ERROR
2307	010762	012777	000040	170012	RT2A:	MOV	#40,ALPB ;LOAD BUFFER
2308	010770	005237	001056		INC	STRCNT	; INCREMENT GROUP COUNT
2309	010774	001003			BNE	RT2AA	; BRANCH IF NOT DONE GROUP
2310	010776	012737	177757	001056	MOV	#-17.,STRCNT	; RESET GROUP COUNT
2311	011004	005337	001036		RT2AA:	DEC	CHRCNT ;DECREMENT SPACE COUNT
2312	011010	001353			BNE	RT2	; BRANCH IF NOT DONE SPACES

;TEST 11 ----- CONTINUED  
 ;RIGHT TRIANGLE

```

2313 011012 005777 167762          RT3:  TST      @LPS          ;TEST FOR ERROR
2314 011016 100006                    BPL      RT3A          ;CONTINUE IF NO ERROR
2315 011020                    $ERROR  \N
(1) 011020 012737 000051 001052 ERR51: MOV      #51,   ERCOUNT      ;SET UP ERROR COUNT 51
(1) 011020 000052                    N=N+1
2316 011026 004537 011706                    JSR      %5,STAER      ;REPORT ERROR SET
2317 011032 000000                    HALT                                ;HALT ON ERROR
2318 011034 013777 001040 167740 RT3A:  MOV      CHRGEN,@LPB      ;LOAD BUFFER
2319 011042 005237 001040          INC      CHRGEN        ;NEXT CHAR
2320 011046 005237 001056          INC      STRCNT        ;INCREMENT GROUP COUNT
2321 011052 001006                    BNE      RT3B          ;BRANCH IF NOT DONE GROUP
2322 011054 012737 177757 001056          MOV      #-17,STRCNT   ;RESET GROUP COUNT
2323 011062 162737 000021 001040          SUB      #17,CHRGEN    ;GET FIRST GROUP CHAR
2324 011070 005337 001044          RT3B:  DEC      CYCCNT   ;DECREMENT CHAR COUNT
2325 011074 001346                    BNE      RT3          ;CONTINUE
2326 011076 012777 000012 167676          MOV      #12,@LPB     ;SEND LF
2327 011104                    $WAIT
(1) 011104 105777 167670          TSTB    @LPS          ;TEST READY
(1) 011110 100375                    BPL      .-4           ;WAIT FOR READY
2328 011112 005237 001042          INC      LINCNT        ;INCREMENT LINE COUNT
2329 011116 022737 000205 001042          CMP      #133.,LINCNT ;DONE?
2330 011124 003265                    BGT      RT1          ;BRANCH IF NOT DONE
2331 011126 032777 010000 167650          BIT      #BIT12,@SWR  ;LOOP ON TEST?
2332 011134 001256                    BNE      RTTR         ;LOOP
2333
2334 ;TEST 12
2335 ;HAMMER ALIGNMENT
2336
2337 011136                    HAMALN: $ENABLE
(1) 011136 022737 000176 001004          CMP      #176,SWR     ;S/W SWR ?
(1) 011144 001003                    BNE      .+10         ;NO- CONTINUE
(1) 011146 052777 000100 167644          BIS      #100,@TKS    ;ENABLE KEYBOARD INTERRUPT
2338 011154 004437 011472          JSR      %4,TYPINT
2339 011160                    $PRINT \M
(1) 011160 013737 014540 014002          MOV      TNO14,MES15  ;SET TEST NUMBER FOR MESSAGE
(1) 011166 004437 011422          JSR      %4,PRINT     ;PRINT TEST NUMBER
(1) 011166 000015                    M=M+1
2340 011172 012737 177701 001042          MOV      #-63.,LINCNT ;SET UP FOR 63 LINES
2341 011200 012737 177574 001036 HAM1X: MOV      #-132.,CHRCNT ;SET CHAR COUNT
2342 011206 005777 167566          HAM2:  TST      @LPS    ;CHECK FOR ERROR
2343 011212 100006                    JPL      XHAM1        ;BRANCH IF NO ERROR
2344 011214                    $ERROR  \N
(1) 011214 012737 000052 001052 ERR52: MOV      #52,   ERCOUNT      ;SET UP ERROR COUNT 52
(1) 011214 000053                    N=N+1
2345 011222 004537 011706                    JSR      %5,STAER      ;REPORT ERROR OCCURRED
2346 011226 000000                    HALT                                ;HALT ON ERROR
2347 011230                    XHAM1: $WAIT
(1) 011230 105777 167544          TSTB    @LPS          ;TEST READY
(1) 011234 100375                    BPL      .-4           ;WAIT FOR READY
2348 011236 100375                    BPL      .-4           ;WAIT FOR READY
2349 011240 012777 000105 167534 XHAM1X: MOV      #105,@LPB  ;TRANSMIT E TO PRINTER
2350 011246 005237 001036          INC      CHRCNT        ;+1 CHAR COUNT
2351 011252 001355                    BNE      HAM2         ;TRANSMIT ANOTHER CHAR.
2352 011254 012777 000012 167520          MOV      #12,@LPB     ;TRANSMIT LINE FEED
2353 011262                    $WAIT
(1) 011262 105777 167512          TSTB    @LPS          ;TEST READY

```

```

(1) 011266 100375          BPL      .-4          ;WAIT FOR READY
2354 011270 005237 001042    INC      LINCNT      ;+1 TO COUNT
2355 011274 001341          BNE      HAMIX      ;GO DO NEXT LINE
2356 011276 032777 010000 167500 BIT      #BIT12, @SWR ;CHECK TO LOOP ON TEST
2357 011304 001314          BNE      HAMALN     ;LOOP ON TEST
2358
2359 011306 032777 040000 167470 BIT      #BIT14, @SWR ;DAVFU AVAILABLE?
2360 011314 001402          BEQ      HAMX      ;NO, RECYCLE PRINTING TESTS
2361 011316 000137 014550          JMP      DAVFU     ;YES, DO DAVFU PRINTING TESTS
2362 011322
2363 011322 013700 000042    HAMX:    MOV      @#42, R0
2364 011326 001405          BEQ      DOAGN     ;
2365 011330 000005          RESET
2366 011332
2367 011332 004710          LOGICAL: JSR      PC, (R0)
2368 011334 000240          NOP
2369 011336 000240          NOP
2370 011340 000240          NOP
2371 011342
2372 011342 000137 004550    DOAGN:   JMP      TEST2    ;RESTART
2373
2374          ;MISC. ROUTINES
2375
2376
2377
2378
2379
2380          ;ROUTINE TO INITIALIZE PRINTER
2381          ;ENTER FROM JSR %5, PRTINT
2382
2383 011346 005777 167426    PRTINT: TST      @LPS          ;TEST FOR ERROR
2384 011352 100403          BMI      PRTIND     ;BRANCH IF ERROR
2385 011354 105777 167420    TSTB    @LPS          ;TEST FOR READY
2386 011360 100403          BMI      RDYOK      ;READY SET OK
2387 011362 062705 000002    PRTIND: ADD      #2, %5    ;SET UP FOR ERROR REPORT
2388 011366 000205          RTS              ;REPORT READY NOT SET
2389 011370 012777 000014 167404 RDYOK:   MOV      #14, @LPB    ;ISSUE FORM FEED
2390 011376 105777 167376    TSTB    @LPS          ;TEST FOR READY NOT SET
2391 011402 100003          BPL      NTRDY     ;READY NOT SET OK
2392 011404 062705 000002    ADD      #2, %5    ;SET UP FOR REPORT
2393 011410 000205          RTS              ;EXIT AND REPORT
2394 011412
2395 (1) 011412 105777 167362    NTRDY:  $WAIT
2396 (1) 011416 100375          TSTB    @LPS          ;TEST READY
2397 011420 000205          BPL      .-4          ;WAIT FOR READY
2398          RTS      %5    ;READY SET EXIT
2399
2400          ;ROUTINE TO OUTPUT ASCII MESSAGES ON THE LINE PRINTER
2401 011422 012737 013764 011470 PRNNT:  MOV      #MES14, PRMSG ;PRINT TEST NUMBER
2402 011430 005777 167344    TST      @LPS          ;TEST FOR ERROR
2403 011434 100006          BPL      RINT      ;BRANCH IF OK
2404 011436
2405 (1) 011436 012737 000053 001052 ERR53:  MOV      #53,   ERCOUNT ;SET UP ERROR COUNT 53
2406 (1)          000054          N=N+1
    
```

```

2405 011444 004537 011706      JSR      %5,STAER      ;REPORT ERROR SET
2406 011450 000000              HALT                  ;HALT ON ERROR
2407 011452 013737 001000 001016 RINT:  MOV      LPS,TPS ;SET VECTORS -
2408 011460 013737 001002 001012      MOV      LPB,TPB ;TO PRINT ON LINE PRINTER
2409 011466 104000              EMT                  ;PRINT
2410 011470 013764              PRTMSG: MES14        ;MESSAGE
2411 011472 012737 177564 001016 TYPINT: MOV      #177564,TPS ;RESET VECTORS
2412 011500 012737 177566 001012      MOV      #177566,TPB ;FOR TTY
2413 011506 000204              RTS                  ;RETURN

;SUBROUTINE TO OUTPUT ASCII MESSAGES ON TELETYPE PRINTER
2415
2416
2417 011510 011600              TYP:   MOV      @%6,%0 ;GET ADDR. THAT CONTAINS MESS.
2418 011512 062716 000002              ADD      #2,%6 ;SET UP EXIT
2419 011516 011000              MOV      @%0,%0 ;ADDRESS OF MESSAGE IN RO
2420 011520 112037 011622              TYPA:  MOV      (0)+,TYPDAT ;GET CHARACTER
2421 011524 001001              BNE     TYPC ;BRANCH IF NOT DONE
2422 011526 000002              RTI ;EXIT
2423 011530 122737 000045 011622 TYPC:  CMP      #45,TYPDAT ;CHECK FOR "%"
2424 011536 001416              BEQ     TYPF ;BRANCH IF "%"
2425 011540 122737 000043 011622              CMP      #43,TYPDAT ;CHECK FOR "#"
2426 011546 001417              BEQ     TYPG ;BRANCH IF "#"
2427 011550 004737 011556              JSR     %7,TYPD ;TYPE CHARACTER IN TYPDAT
2428 011554 000761              BR     TYPA ;NEXT CHAR IN MESSAGE
2429 011556 113777 011622 167226 TYPD:  MOV      TYPDAT,@TPB ;OUTPUT CHARACTER TO PRINTER
2430 011564 105777 167226 TYPD0: TST      @TPS
2431 011570 100375              BPL     .-4
2432 011572 000207              RTS ;CHAR. TYPED EXIT
2433 011574 112737 000012 011622 TYPF:  MOV      #12,TYPDAT ;OUTPUT LF
2434 011602 004737 011556              JSR     %7,TYPD ;GO TYPE CHAR.
2435 011606 112737 000015 011622 TYPG:  MOV      #15,TYPDAT ;OUTPUT CR
2436 011614 004737 011556              JSR     %7,TYPD ;GO TYPE CHAR.
2437 011620 000737
2438 011622 000000              TYPDAT: 0

;ROUTINE TO CONVERT OCTAL TO ASCII
2439
2440
2441
2442
2443
2444
2445
2446
2447
2448
2449
2450
2451
2452
2453
2454
2455
2456
2457
2458
2459
2460
;ENTER ROUTINE AS FOLLOWS
;JSR %5,CONV
;XXXXXX=ADDRESS OF NUMBER TO BE CONVERTED
;XXXXXX=ADDRESS OF ASCII MESSAGE
;XXXXXX=NUMBER OF OCTAL NO.'S TO BE CONVERTED
CONV:  MOV      @(%5)+,ACNVX ;ADDRESS OF NO. TO BE CONVERTED
      MOV      (5)+,%1 ;ADDRESS OF MESSAGE
      MOV      (%5)+,%2 ;NUMBER OF ASCII CHARACTERS
      ADD      %2,%1 ;FIRST CHAR ADDRESS
ACVN:  MOV      ACNVX,%3 ;STORE NUMBER
      BIC      #177770,%3 ;ISOLATE LEAST SIGNIFICANT BIT
      ADD      #60,%3 ;SET UP ASCII CHARACTER
      MOV      %3,-(1) ;STORE CHARACTER
      CLC ;GET NEXT SIGNIFICANT BIT ...
      ROR      ACNVX
      CLC
      ROR      ACNVX

```

```

2461 011670 000241          CLC
2462 011672 006037 011704    ROR      ACNVX
2463 011676 005302          DEC      %2      ; -1 FROM ASCII CHAR. CNT
2464 011700 001356          BNE     ACVN     ; CONVERT NEXT CHARACTER
2465 011702 000205          RTS      %5     ; EXIT! CONVERSION DONE
2466
2467 011704 000000          ACNVX: 0      ; WORK REGISTER
2468
2469          ;ROUTINE TO REPORT ERROR COUNT
2470
2471 011706 004537 011624    STAER: JSR     %5, CONV ; CONVERT OCTAL TO ASCII
2472 011712 001052          ERCOUNT
2473 011714 012334          HED1
2474 011716 000003          3
2475 011720 104000          EMT      +0     ; TYPE ERROR MESSAGE
2476 011722 012334          HED1
2477 011724 005777 167054    TST     %SWR    ; TEST FOR HALT ON ERROR
2478 011730 100401          BMI     .+4     ; BRANCH IF NO HALT WANTED
2479 011732 000000          HALT
2480 011734 000205          RTS      %5     ; RETURN
2481
2482          ;KEYBOARD INTERRUPT ROUTINE
2483          ;FOR ACCESS TO THE S/W SWITCH REGISTER
2484
2485
2486
2487 011736 010046          TKINT: MOV     %0, -(SP) ; SAVE REGISTERS
2488 011740 010146          MOV     %1, -(SP)
2489 011742 010246          MOV     %2, -(SP)
2490 011744 010346          MOV     %3, -(SP)
2491 011746 010446          MOV     %4, -(SP)
2492 011750 010546          MOV     %5, -(SP)
2493 011752 005737 001072    TST     SET     ; INITIAL SWR ENTRY ?
2494 011756 001130          BNE     TYP SWR ; YES-PRINT HEADER
2495 011760 005737 001070    TST     SIGNAL  ; PREVIOUS CONTROL-G INPUT ?
2496 011764 001477          BEQ     CNTRLG  ; YES-CONTINUE
2497 011766 017737 167022 001074 MOV     @TKB, CHAR ; GET INPUT CHARACTER
2498 011774 042737 177600 001074 BIC     #177600, CHAR ; STRIP OFF PARITY BIT
2499 012002 022737 000015 001074 CMP     #15, CHAR ; CARRIAGE RETURN ?
2500 012010 001456          BEQ     DGT5    ; YES-CONTINUE
2501 012012 022737 000025 001074 CMP     #25, CHAR ; CONTROL-U INPUT ?
2502 012020 001530          BEQ     TK4     ; YES-CONTINUE
2503 012022 023727 001074 000060 CMP     CHAR, #60 ; LEGAL CHECK: LESS THAN 60 ?
2504 012030 100001          BPL     TK1    ; NO-CONTINUE
2505 012032 000466          BR     WT3     ; YES-PRINT ""
2506 012034 022737 000067 001074 TK1:  CMP     #67, CHAR ; LEGAL CHECK: GREATER THAN 67 ?
2507 012042 100001          BPL     TK1    ; NO-CONTINUE
2508 012044 000461          BR     WT3     ; YES-PRINT ""
2509 012046 005237 001066 001066 TK2:  INC     DIGITS ; NEXT DIGIT OF SWR INPUT
2510 012052 022737 000006 001066 CMP     #6, DIGITS ; MORE THAN SIX DIGITS ?
2511 012060 100453          BMI     WT3    ; YES-PRINT ""
2512 012062 105777 166730          WT2:  TSTB   @TPS   ; TTY PRINTER READY ?
2513 012066 100375          BPL     WT2    ; NO-WAIT
2514 012070 013777 001074 166714 MOV     CHAR, @TPB ; PRINT CHARACTER
2515 012076 162737 000060 001074 SUB     #60, CHAR ; CONVERT TO OCTAL
2516 012104 022737 000001 001066 CMP     #1, DIGITS ; FIRST DIGIT ?

```

2517	012112	001411				BEQ	TK5		: YES-CONTINUE
2518	012114	000241				CLC			: ROTATE LEFT THREE
2519	012116	006137	001076			ROL	OCT		: TIMES
2520	012122	000241				CLC			: THIS WILL SHIFT
2521	012124	006137	001076			ROL	OCT		: SWR VALUE ONE
2522	012130	000241				CLC			: PLACE LEFT
2523	012132	006137	001076			ROL	OCT		: OCTAL
2524	012136	063737	001074	001076	TK5:	ADD	CHAR,OCT		: NEW VALUE OF SWR
2525	012144	000464				BR	TK6		: RETURN FROM INTERRUPT
2526	012146	005737	001066		DGTS:	TST	DIGITS		: SWR VALUE CHANGED ?
2527	012152	001451				BEQ	TK3		: NO-RETURN, NO CHANGE TO SWR
2528	012154	013777	001076	166622		MOV	OCT,2SWR		: YES-ENTER NEW SWR VALUE
2529	012162	000445				BR	TK3		: RETURN FROM INTERRUPT
2530	012164	017737	166624	001074	CNTRLG:	MOV	@TKB,CHAR		: GET CHARACTER
2531	012172	042737	177600	001074		BIC	#177600,CHAR		: STRIP OFF PARITY BIT
2532	012200	022737	000007	001074		CMP	#7,CHAR		: CONTROL-G INPUT ?
2533	012206	001414				BEQ	TYP5WR		: YES-PRINT HEADER
2534	012210	105777	166602		WT3:	TSTB	@TPS		: TTY PRINTER READY ?
2535	012214	100375				BPL	WT3		: NO-WAIT
2536	012216	013777	001074	166566		MOV	CHAR,@TPB		: PRINT CHARACTER
2537	012224	104000				EMT	+0		: PRINT "?"
2538	012226	014440				MES22			
2539	012230	005737	001070			TST	SIGNAL		: BAD VALUE ?
2540	012234	001001				BNE	TYP5WR		: YES-PRINT HEADER
2541	012236	000427				BR	TK6		: RETURN FROM INTERRUPT
2542	012240	012737	000001	001070	TYP5WR:	MOV	#1,SIGNAL		: SET FLAG: CONTROL-G ENTERED
2543	012246	104000				EMT	+0		: PRINT HEADER
2544	012250	014444				MES23			
2545	012252	004537	011624			JSR	%5,CONV		: CONVERT SWR VALUE TO ASCII
2546	012256	000176				176			
2547	012260	014474				MES25			
2548	012262	000006				6			
2549	012264	104000				EMT	+0		: PRINT SWR VALUE
2550	012266	014474				MES25			
2551	012270	104000				EMT	+0		: PRINT HEADER
2552	012272	014455				MES24			
2553	012274	000404				BR	TK7		: RETURN FROM INTERRUPT
2554	012276	005037	001070		TK3:	CLR	SIGNAL		: CLEAR CONTROL-G FLAG
2555	012302	104000			TK4:	EMT	+0		: PRINT LINE FEED AND CARRIAGE RETURN
2556	012304	014436				MES21			
2557	012306	005037	001066		TK7:	CLR	DIGITS		: CLEAR DIGIT COUNT
2558	012312	005037	001076			CLR	OCT		: CLEAR SWR INPUT
2559	012316	012605			TK6:	MOV	(SP)+,%5		: RESTORE REGISTERS
2560	012320	012604				MOV	(SP)+,%4		
2561	012322	012603				MOV	(SP)+,%3		
2562	012324	012602				MOV	(SP)+,%2		
2563	012326	012601				MOV	(SP)+,%1		
2564	012330	012600				MOV	(SP)+,%0		
2565	012332	000002				RTI			: RETURN FROM INTERRUPT
2566									
2567									
2571									
2572	012334	020040	020040	051105	HED1:	.ASCIZ	/ ERROR COUNT%/		
2573	012355	105	051122	051117	MESA:	.ASCIZ	/ERROR SET OK - CLEAR & TURN ON LINE%/		
2574	012422	051105	047522	020122	MESB:	.ASCIZ	/ERROR SET OK - CLEAR AND TRY NEXT CHANNEL%/		
2575	012475	045	051120	047111	MESC:	.ASCII	/%PRINT SPEED CHECK USING MANUAL TIMING%/		



```

2576 012544 050045 052125 051440 .ASCII  /%PUT SWITCH 0 UP TO START TIMING%/
2577 012605 045 052520 020124 .ASCIZ  /%PUT SWITCH 0 DOWN AT END OF 1 MINUTE%/
2578 012654 051445 040524 052122 MES00: .ASCIZ  /%STARTING DAVFU PRINTING TESTS%/
2579 012714 046045 030120 026465 MES1:  .ASCIZ  /%LPOS-LP11-LP14 LINE PRINTER TEST%/
2580 012757 122 051505 040524 MES2:  .ASCIZ  /RESTART ADDRESS 600%/
2581 013004 047520 042527 020122 MES3:  .ASCIZ  /POWER ON - TURN ON LINE%/
2582 013035 117 020116 044514 MES4:  .ASCIZ  /ON LINE OK - TRY TORN PAPER SWITCH%/
2583 013101 122 040505 054504 MES5:  .ASCIZ  /READY SET OK - TRY DRUM GATE SWITCH%/
2584 013146 051105 047522 020122 MES6:  .ASCIZ  /ERROR SET OK - TURN ON LINE%/
2585 013204 042522 .EVEN
2586 013206 020040 020040 044440 MES7A: .ASCII  /RE/
2587 013242 026455 026455 026455 MES7:  .ASCII  /SET TOP OF FORM SWITCH TO /
2588 013355 040 020040 020040 MES8:  .ASCIZ  / INCHES%/
2589 013466 005012 .EVEN
2590 013470 050045 044522 052116 MES9:  .ASCII  /----- THIS LINE SHOULD BE /
2591 013527 040 020040 020040 MES10: .ASCIZ  / INCHES FROM THE LAST LINE -----
2592 013556 026455 026455 026455 MES11A: .ASCII  (<12><12>)
2593 013640 026455 026455 026455 MES11: .ASCII  /%PRINT SPEED IS APPROXIMATELY /
2594 013722 026455 026455 026455 MES12: .ASCIZ  / LINES PER MINUTE%/
2595 013764 005012 042524 052123 MES13: .ASCII  /-----/
2596 014002 020040 005012 000012 MES14: .ASCII  (<12><12>)/TEST NUMBER /
2597 014010 044124 051511 046040 MES15: .ASCIZ  / /(<12><12><12>)
2598 014045 040 020040 020040 .EVEN
2599 014150 026455 026455 026455 MES16: .ASCIZ  /THIS LINE SHOULD BE PRINTED#/
2600 014242 020040 020040 020040 MES17: .ASCIZ  / ALL ON ONE LINE --- IF SLEWED 0 LINES%/
2601 014356 052040 051505 044524 .EVEN
2602 014432 020040 000 04436 .EVEN
2603 014436 000045 MES18: .ASCII  /----- THERE SHOULD BE /
2604 014440 037440 000045 MES19: .ASCIZ  / BLANK LINES BEFORE THIS LINE -----
2605 014444 051445 051127 036440 .EVEN
2606 014455 040 020040 042516 MES20: .ASCII  / TESTING CHANNEL SLEWING USING CHANNEL NO. /
2607 014474 020040 020040 020040 MES20A: .ASCIZ  / /
2608 014504 030504 .EVEN
2609 014506 031104 MES21: .ASCIZ  /%/
2610 014510 031504 MES22: .ASCIZ  / ?%/
2611 014512 020061 MES23: .ASCIZ  /%SWR = /
2612 014514 020062 MES24: .ASCIZ  / NEW SWR = /
2613 014516 020063 MES25: .ASCIZ  / /
2614 014520 020064 .EVEN
2615 014522 020065 ;TEST NUMBERS FOR DAVFU TESTS
2616 014524 020066
2617 014526 020067
2618 014530 020070
2619 014532 020071
2620 014534 030061
2621 014536 030461
2622 014540 031061
2623 014544 030061
2624 014548 031061
2625 014552 030061
2626 014556 031061
2627 014600 030061
2628 014604 031061
2629 014608 030061
2630 014612 031061
2631 014616 030061

```

2632	014542	031461			TN015:	.ASCII	/13/	
2633	014544	032061			TN016:	.ASCII	/14/	
2634	014546	032461			TN017:	.ASCII	/15/	
2635						.EVEN		
2636								
2640								
2641								
2642								
2643								
2644								
2645								
2646								
2647	014550				DAVFU:	SENABLE		
(1)	014550	022737	000176	001004		CMP	#176,SWR	;S/W SWR ?
(1)	014556	001003				BNE	.+10	;NO- CONTINUE
(1)	014560	052777	000100	164232		BIS	#100,ATKS	;ENABLE KEYBOARD INTERRUPT
2648	014566	004437	011472			JSR	%4,TYPINT	;INITIALIZE
2649	014572	013737	016634	014244		MOV	SPSP,MES19+2	
2650	014600	104000				EMT	+0	;TYPE MESSAGE
2651	014602	012654				MES00		;STARTING DAVFU TESTS
2652	014604	012737	000220	015300		MOV	#220,DAVI1	;SET DAVFU INSTRUCTIONS
2653	014612	012737	000221	015302		MOV	#221,DAVI2	
2654	014620	013737	014504	014012		MOV	TNDAV1,MES15	;SET TEST NUMBER FOR MESSAGE
2655	014626	004437	011422			JSR	%4,PRINT	;PRINT TEST NUMBER
2656	014632	012737	015232	001040	DAVO:	MOV	#DAVTAB,CHRGEN	;SET TABLE POINTER
2657	014640	005777	164134		DAV00:	TST	ALPS	;TEST FOR ERROR
2658	014644	100010				BPL	DAVI	;BRANCH IF NO ERROR
2659	014646					SERROR	\N	
(1)	014646	012737	000054	001052	ERR54:	MOV	#54, ERCOUNT	;SET UP ERROR COUNT 54
(1)		003055				N=N+1		
2660	014654	004537	011706			JSR	%5,STAER	;REPORT ERROR SET
2661	014660	000000				HALT		;HALT ON ERROR
2662	014662	000137	014632			JMP	DAVO	;RESTART TEST
2663	014666	017777	164146	164106	DAVI:	MOV	ALCHRGEN,ALPB	;LOAD DAVFU
2664	014674	062737	000002	001040		ADD	#2,CHRGEN	;INCREMENT TABLE POINTER
2665	014702	005777	164132			TST	ALCHRGEN	;TEST IF DONE LOAD
2666	014706	001405				BEQ	D5	;CONTINUE IF DONE
2667	014710					SWAIT		;WAIT
(1)	014710	105777	164064			TSTB	ALPS	;TEST READY
(1)	014714	100375				BPL	.-4	;WAIT FOR PREADY
2668	014716	000137	014640			JMP	DAV00	
2669	014722	012737	000002	001044	D5:	MOV	#2,CYCCNT	;SET CYCLE COUNT
2670	014730	012737	014010	011470	D0:	MOV	#MES16,PRMSG	;SET MESSAGE ADDRESS
2671	014736	004437	011452			JSR	%4,PRINT	;PRINT MESSAGE
2672	014742	005777	164032			TST	ALPS	;TEST FOR ERROR
2673	014746	100006				BPL	D1	;CONTINUE IF NO ERROR
2674	014750					SERROR	\N	
(1)	014750	012737	000055	001052	ERR55:	MOV	#55, ERCOUNT	;SET UP ERROR COUNT 55
(1)		000056				N=N+1		
2675	014756	004537	011706			JSR	%5,STAER	;REPORT ERROR SET
2676	014762	000000				HALT		;HALT ON ERROR
2677	014764	013777	015300	164010	D1:	MOV	DAVI1,ALPB	;SEND DAVFU INSTRUCTION, SKIP 0 LINES
2678	014772					SWAIT		
(1)	014772	105777	164002			TSTB	ALPS	;TEST READY
(1)	014776	100375				BPL	.-4	;WAIT FOR READY
2679	015000	012737	014045	011470		MOV	#MES17,PRMSG	;SET PRINTER MESSAGE ADDRESS

;DAVFU PRINTING TESTS IF DAVFU IS AVAILABLE -- SET SWITCH 14

;TESTS D1 AND D2  
 ;CHECK DAVFU LINE COUNT SLEWING

;INITIALIZE

;TYPE MESSAGE  
 ;STARTING DAVFU TESTS  
 ;SET DAVFU INSTRUCTIONS

;SET TEST NUMBER FOR MESSAGE  
 ;PRINT TEST NUMBER  
 ;SET TABLE POINTER  
 ;TEST FOR ERROR  
 ;BRANCH IF NO ERROR

;SET UP ERROR COUNT 54

;REPORT ERROR SET  
 ;HALT ON ERROR  
 ;RESTART TEST  
 ;LOAD DAVFU  
 ;INCREMENT TABLE POINTER  
 ;TEST IF DONE LOAD  
 ;CONTINUE IF DONE  
 ;WAIT  
 ;TEST READY  
 ;WAIT FOR PREADY

;SET CYCLE COUNT  
 ;SET MESSAGE ADDRESS  
 ;PRINT MESSAGE  
 ;TEST FOR ERROR  
 ;CONTINUE IF NO ERROR

;SET UP ERROR COUNT 55

;REPORT ERROR SET  
 ;HALT ON ERROR  
 ;SEND DAVFU INSTRUCTION, SKIP 0 LINES

;TEST READY  
 ;WAIT FOR READY  
 ;SET PRINTER MESSAGE ADDRESS

2680	015006	004437	011452			JSR	%4,RINT	;PRINT MESSAGE
2681	015012	012737	014150	011470		MOV	#MES18,PRMSG	;SET MESSAGE ADDRESS
2682	015020	013737	015302	001040		MOV	DAVI2,CHRGEN	;FIRST DAVFU INSTRUCTION
2683	015026	012737	014512	001054		MOV	#TNO1,STRCHR	;SET TABLE POINTER
2684	015034	012737	000017	001036		MOV	#15.,CHRCNT	;SET TABLE COUNT
2685	015042	005777	163732		D2:	TST	ALPS	;TEST FOR ERROR
2686	015046	100006				BPL	D3	;CONTINUE IF NO ERRORS
2687	015050					SERROR	\N	
(1)	015050	012737	000056	001052	ERR56:	MOV	#56, ERRCOUNT	;SET UP ERROR COUNT 56
(1)		000057				N=N+1		
2688	015056	004437	011706			JSR	%4,STAER	;REPORT ERROR SET
2689	015062	000000				HALT		;HALT ON ERROR
2690	015064	013777	001040	163710	D3:	MOV	CHRGEN,ALPB	;SEND DAVFU INSTR.
2691	015072					SWAIT		;WAIT
(1)	015072	105777	163702			TSTB	ALPS	;TEST READY
(1)	015076	100375				BPL	-4	;WAIT FOR READY
2692	015100	017737	147750	014242		MOV	STRCHR,MES19	;SET PRINTER MESSAGE
2693	015106	004437	011452			JSR	%4,RINT	;PRINT MESSAGE
2694	015112	005337	001036			DEC	CHRCNT	;DEC TABLE COUNT
2695	015116	001407				BEQ	D4	;EXIT TEST IF DONE
2696	015120	005237	001040			INC	CHRGEN	;NEXT DAVFU INSTR.
2697	015124	062737	000002	001054		ADD	#2,STRCHR	;INC TABLE POINTER
2698	015132	000137	015042			JMP	D2	;CONTINUE
2699	015136	005337	001044		D4:	DEC	CYCCNT	;DEC CYCLE COUNT
2700	015142	001415				BEQ	DEXO	;EXIT IF DONE
2701	015144	062737	000140	015300		ADD	#140,DAVI1	;CHANGE DAVFU INSTR.
2702	015152	062737	000140	015302		ADD	#140,DAVI2	;CHANGE DAVFU INSTR.
2703	015160	013737	014506	014002		MOV	TNDV2,MES15	;SET TEST NUMBER FOR MESSAGE
2704	015166	004437	011422			JSR	%4,PRNT	;PRINT TEST NUMBER
2705	015172	000137	014730			JMP	D0	;RETEST LINE COUNT SLEWING
2706	015176	012737	000220	015300	DEXO:	MOV	#220,DAVI1	;RESET DAVFU INSTR.
2707	015204	012737	000221	015302		MOV	#221,DAVI2	;RESET DAVFU INSTR.
2708	015212	032777	010000	163564		BIT	#BIT12,ASWR	;LOOP ON TEST?
2709	015220	001002				BNE	1\$	;LOOP
2710	015222	000137	015304			JMP	DAV2	;NEXT TEST
2711	015226	000137	014550		1\$:	JMP	DAV2	;LOOP
2712								
2713								
2714	015232	000356			DAVTAB:	356		;DAVFU LOAD TABLE
2715	015234	000001				1		
2716	015236	000002				2		
2717	015240	000003				3		
2718	015242	000004				4		
2719	015244	000005				5		
2720	015246	000006				6		
2721	015250	000007				7		
2722	015252	000010				10		
2723	015254	000011				11		
2724	015256	000012				12		
2725	015260	000013				13		
2726	015262	000014				14		
2727	015264	000015				15		
2728	015266	000016				16		
2729	015270	000017				17		
2730	015272	000020				20		
2731	015274	000357				357		

```

2732 015276 000000 0
2733
2734
2735 015300 000220 DAV11: 220
2736 015302 000221 DAV12: 221
2737
2738 ;TEST D3
2739 ;CHECK DAVFU CHANNEL SLEW COMMANDS
2740
2741 015304 DAV2: SENABLE
(1) 015304 022737 000176 001004 CMP #176,SWR ;S/W SWR ?
(1) 015312 001003 BNE .+10 ;NO- CONTINUE
(1) 015314 052777 000100 163476 BIS #100,DTKS ;ENABLE KEYBOARD INTERRUPT
2742 015322 004437 011472 JSR %4,TYPINT ;INITIALIZE
2743 015326 013737 016634 014244 MOV SPSP,MES19+2
2744 015334 013737 014510 014002 MOV TNDV3,MES15 ;SAT TEST NUMBER FOR MESSAGE
2745 015342 004437 011422 JSR %4,PRINT ;PRINT TEST NUMBER D3
2746 015346 012737 016616 016100 MOV #MTAB,MTABP ;SET MESSAGE TABLE POINTER
2747 015354 012737 016564 016074 MOV #ITAB,ITABP ;SET INSTRUCTION TABLE POINTER
2748 015362 017737 000506 001054 MOV #ITABP,STRCHR ;SAT FIRST INSTRUCTION
2749 015370 012737 014512 016102 MOV #TNO1,HTABP ;SET HEADER MESSAGE TABLE POINTER
2750 015376 012737 016546 016076 MOV #ICTAB,ICTABP ;SET INSTR COUNT TABLE POINTER
2751 015404 017737 000466 001056 MOV #ICTABP,STRCNT ;SET FIRST INSTR COUNT
2752 015412 012737 016104 016072 LOAD: MOV #DTAB,DTABP ;SET DATA TABLE POINTER
2753 015420 017737 000446 001040 MOV #DTABP,CHRGEN ;SET FIRST DATA PAIR
2754 015426 005777 163346 TST %LPS ;TEST FOR ERROR
2755 015432 100007 BPL DL1 ;BRANCH IF NO ERROR
2756 015434
(1) 015434 012737 000057 001052 ERR57: MOV #57, ERCOUNT ;SET UP ERROR COUNT 57
(1) 000060 N=N+1
2757 015442 004537 011706 JSR %5,STAER ;REPORT ERROR SET
2758 015446 000000 HALT ;HALT ON ERROR
2759 015450 000760 BR LOAD ;RESTART LOAD
2760 015452 012737 000002 001036 DL1: MOV #2,CHRCNT ;SET PAIR COUNT
2761 015460 013777 001040 163314 DL2: MOV CHRGEN,%LPB ;LOAD DAVFU
2762 015466
(1) 015466 105777 163306 SWAIT ;WAIT
(1) 015472 100375 TST %LPS ;TEST READY
2763 015474 005777 163300 BPL .-4 ;WAIT FOR READY
2764 015500 100010 TST %LPS ;TEST FOR ERROR
2765 015502 BPL DL6 ;BRANCH IF NO ERROR
(1) 015502 012737 000060 001052 ERR60: MOV #60, ERCOUNT ;SET UP ERROR COUNT 60
(1) 000061 N=N+1
2766 015510 004537 011706 JSR %5,STAER ;REPORT ERROR SET
2767 015514 000000 HALT ;HALT ON ERROR
2768 015516 000137 015412 JMP LOAD ;RESTART LOAD
2769 015522 022737 000356 001040 DL6: CMP #356,CHRGEN ;LOAD COMMAND?
2770 015530 001407 BEQ DL6A ;YES, SEND ONLY ONCE
2771 015532 022737 000357 001040 CMP #357,CHRGEN ;LOAD COMMAND?
2772 015540 001403 BEQ DL6A ;YES, SEND ONLY ONCE
2773 015542 005337 001036 DEC CHRCNT ;DEC PAIR COUNT
2774 015546 001344 BNE DL2 ;FINISH PAIR IF NOT DONE
2775 015550 062737 000002 016072 DL6A: ADD #2,DTABP ;INC DATA TABLE POINTER
2776 015556 017737 000310 001040 MOV #DTABP,CHRGEN ;SET NEXT DATA PAIR
2777 015564 022737 077777 001040 CMP #77777,CHRGEN ;DONE LOAD?
2778 015572 001327 BNE DL1

```

```

2779
2780 ;START OF CHANNEL SLEW TESTS
2781
2782 DL8: 015574
2783 015574 013777 001054 163200 MOV STRCHR,ALPB ;SEND DAVFU INSTRUCTION
2784 015602 SWAIT
(1) 015602 105777 163172 TSTB ALPS ;TEST READY
(1) 015606 100375 BPL -4 ;WAIT FOR READY
2785 015610 105777 163164 TSTB ALPS ;TEST READY
2786 015614 100375 BPL -4 ;WAIT FOR READY
2787 015616
2788 DL8A: 015616 017737 000260 014432 MOV @HTABP,MES20A ;SET HEADER MSSG ADDRESS
2789 015624 012737 014356 011470 MOV @MES20,PRMSG ;SET HEADER MSG ADDRESS
2790 015632 004437 011452 JSR %4,RINT ;PRINT HEADER MESSAGE
2791 015636 013777 001054 163136 DL9: MOV STRCHR,ALPB ;SEND DAVFU INSTRUCTION
2792 015644 SWAIT ;WAIT
(1) 015644 105777 163130 TSTB ALPS ;TEST READY
(1) 015650 100375 BPL -4 ;WAIT FOR READY
2793 015652 005777 163122 TST ALPS ;TEST FOR ERROR
2794 015656 100010 BPL DL10 ;BRANCH IF OK
2795 015660
(1) 015660 012737 000061 001052 ERR61: MOV #61, ERRCOUNT ;SET UP ERROR COUNT 61
(1) 000062 N=N+1
2796 015666 004537 011706 JSR %5,STAER ;REPORT ERROR SET
2797 015672 000000 HALT ;HALT ON ERROR
2798 015674 000137 015412 JMP LOAD ;RELOAD DAVFU
2799 015700 017737 000174 014242 DL10: MOV @MTABP,MES19 ;SET MESSAGE
2800 015706 027727 000164 000001 CMP @ICTABP,#1 ;CHECK IF MAX LINE SLEW
2801 015714 001004 BNE DL10A ;NOT, CONTINUE
2802 015716 013737 016632 014244 MOV FS,MES19+2 ;SET MESSAGE
2803 015724 000403 BR DL10B ;CONTINUE
2804 015726 013737 016634 014244 DL10A: MOV SPSP,MES19+2 ;SET MESSAGE
2805 015734 012737 014150 011470 DL10B: MOV @MES18,PRMSG ;SET MSG ADDRESS
2806 015742 004437 011452 JSR %4,RINT ;PRINT MESSAGE
2807 015746 005337 001056 DEC STRCNT ;DEC INSTR COUNT
2808 015752 001331 BNE DL9 ;FINISH TESTING THIS CHANNEL
2809 015754 062737 000002 016100 ADD #2,MTABP ;INC MSG TABLE POINTER
2810 015762 062737 000002 016102 ADD #2,HTABP ;INC HEADER MSG TABLE POINTER
2811 015770 062737 000002 016076 ADD #2,ICTABP ;INC INSTR COUNT TABLE POINTER
2812 015776 005777 000074 TST @ICTABP ;CHECK INSTR COUNT
2813 016002 001636 BNE DL12
2814 016004 012737 016546 016076 MOV @ICTAB,ICTABP ;RESET TABLE POINTER
2815 016012 012737 016616 016100 MOV @MTAB,MTABP ;RESET MSG TABLE POINTER
2816 016020 017737 000052 001056 DL12: MOV @ICTABP,STRCNT ;GET INSTR COUNT
2817 016026 062737 000002 016074 ADD #2,ITABP ;INC INSTR TABLE POINTER
2818 016034 017737 000034 001054 MOV @ITABP,STRCHR ;GET INSTRUCTION
2819 016042 001254 BNE DL8 ;CONTINUE IF NOT DONE TEST
2820 016044 013737 016634 014244 MOV SPSP,MES19+2 ;RESET MESSAGE
2821 016052 032777 010000 162724 BIT #BIT12,ASWR ;LOOP ON TEST?
2822 016060 001402 BEQ DLEX
2823 016062 000137 015304 JMP DAV2 ;LOOP ON TEST
2824 016066 000137 004550 DLEX: JMP TEST2 ;RECYCLE PRINTING TESTS
2825
2826 016072 000000 DTABP: 0 ;DATA TABLE POINTER
2827 016074 000000 ITABP: 0 ;INSTRUCTION TABLE POINTER
2828 016076 000000 ICTABP: 0 ;INSTR COUNT TABLE POINTER

```

2829	016100	000000
2830	016102	000000
2831		
2832		
2833		
2834	016104	000356
2835	016106	000077
2836	016110	000000
2837	016112	000001
2838	016114	000002
2839	016116	000005
2840	016120	000000
2841	016122	000003
2842	016124	000010
2843	016126	000005
2844	016130	000002
2845	016132	000001
2846	016134	000000
2847	016136	000007
2848	016140	000000
2849	016142	000011
2850	016144	000002
2851	016146	000005
2852	016150	000000
2853	016152	000003
2854	016154	000000
2855	016156	000005
2856	016160	000012
2857	016162	000001
2858	016164	000000
2859	016166	000007
2860	016170	000020
2861	016172	000001
2862	016174	000002
2863	016176	000015
2864	016200	000000
2865	016202	000003
2866	016204	000000
2867	016206	000005
2868	016210	000002
2869	016212	000001
2870	016214	000010
2871	016216	000007
2872	016220	000000
2873	016222	000001
2874	016224	000002
2875	016226	000005
2876	016230	000000
2877	016232	000013
2878	016234	000000
2879	016236	000005
2880	016240	000002
2881	016242	000001
2882	016244	000000
2883	016246	000007
2884	016250	000010

MTABP:	0	; MESSAGE TABLE POINTER
HTABP:	0	; HEADER MESSAGE TABLE POINTER
		; DATA TABLE FOR DAVFU LOAD
DTAB:	356	; START LOAD
	77	; HEADER MESSAGES
	0	
	1	
	2	
	3	
	4	
	5	
	6	
	7	
	8	
	9	
	10	
	11	
	12	
	13	
	14	
	15	
	16	
	17	
	18	
	19	
	20	
	21	
	22	
	23	
	24	
	25	
	26	
	27	
	28	
	29	
	30	
	31	
	32	
	33	
	34	
	35	
	36	
	37	
	38	
	39	
	40	
	41	
	42	
	43	
	44	
	45	
	46	
	47	
	48	
	49	
	50	
	51	
	52	
	53	
	54	
	55	
	56	
	57	
	58	
	59	
	60	
	61	
	62	
	63	
	64	
	65	
	66	
	67	
	68	
	69	
	70	
	71	
	72	
	73	
	74	
	75	
	76	
	77	
	78	
	79	
	80	
	81	
	82	
	83	
	84	
	85	
	86	
	87	
	88	
	89	
	90	
	91	
	92	
	93	
	94	
	95	
	96	
	97	
	98	
	99	
	100	

F06

2885	016252	000021
2886	016254	000002
2887	016256	000005
2888	016260	000000
2889	016262	000003
2890	016264	000000
2891	016266	000015
2892	016270	000002
2893	016272	000001
2894	016274	000000
2895	016276	000007
2896	016300	000000
2897	016302	000001
2898	016304	000012
2899	016306	000005
2900	016310	000000
2901	016312	000003
2902	016314	000000
2903	016316	000005
2904	016320	000002
2905	016322	000011
2906	016324	000000
2907	016326	000007
2908	016330	000000
2909	016332	000001
2910	016334	000022
2911	016336	000005
2912	016340	000010
2913	016342	000003
2914	016344	000000
2915	016346	000005
2916	016350	000002
2917	016352	000001
2918	016354	000000
2919	016356	000017
2920	016360	000000
2921	016362	000001
2922	016364	000002
2923	016366	000005
2924	016370	000000
2925	016372	000003
2926	016374	000010
2927	016376	000005
2928	016400	000002
2929	016402	000001
2930	016404	000000
2931	016406	000007
2932	016410	000000
2933	016412	000011
2934	016414	000002
2935	016416	000025
2936	016420	000000
2937	016422	000003
2938	016424	000000
2939	016426	000005
2940	016430	000012

21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883

2941	016432	000001
2942	016434	000000
2943	016436	000007
2944	016440	000000
2945	016442	000001
2946	016444	000002
2947	016446	000015
2948	016450	000000
2949	016452	000003
2950	016454	000000
2951	016456	000005
2952	016460	000002
2953	016462	000001
2954	016464	000010
2955	016466	000007
2956	016470	000000
2957	016472	000001
2958	016474	000002
2959	016476	000005
2960	016500	000020
2961	016502	000013
2962	016504	000000
2963	016506	000005
2964	016510	000002
2965	016512	000001
2966	016514	000000
2967	016516	000007
2968	016520	000010
2969	016522	000001
2970	016524	000002
2971	016526	000005
2972	016530	000000
2973	016532	000003
2974	016534	000000
2975	016536	000001
2976	016540	000000
2977	016542	000357
2978	016544	077777

1  
0  
7  
0  
1  
2  
15  
0  
3  
0  
2  
1  
10  
7  
0  
1  
2  
20  
13  
0  
5  
2  
1  
10  
1  
5  
0  
3  
0  
1  
0  
357  
77777

;STOP LOAD  
;STOP !!!!!

;INSTRUCTION COUNT TABLE - FOR DAVFU CHANNEL SLEW INSTRUCTIONS

ICTAB: 105  
56  
42  
23  
5  
1  
0

;END OF TABLE

;INSTRUCTION TABLE - DAVFU CHANNEL SLEW INSTRUCTIONS

ITAB:	200	;CHANNEL 1
	201	;CHANNEL 2
	202	;CHANNEL 3
	203	;CHANNEL 4
	204	;CHANNEL 5

2992	016564	000200
2993	016566	000201
2994	016570	000202
2995	016572	000203
2996	016574	000204



2997	016576	000205	205	: CHANNEL 6
2998	016600	000206	206	: CHANNEL 7
2999	016602	000207	207	: CHANNEL 8
3000	016604	000210	210	: CHANNEL 9
3001	016606	000211	211	: CHANNEL 10
3002	016610	000212	212	: CHANNEL 11
3003	016612	000213	213	: CHANNEL 12
3004	016614	000000	0	: END OF TABLE

;MESSAGE TABLE FOR BLANK LINE COUNTS IN MESSAGE

3008	016616	030440	MTAB:	.ASCII	/ 1/
3009	016620	031040		.ASCII	/ 2/
3010	016622	031440		.ASCII	/ 3/
3011	016624	033040		.ASCII	/ 6/
3012	016626	032062		.ASCII	/24/
3013	016630	032061		.ASCII	/14/
3014	016632	020063	FS:	.ASCII	/3 /
3015	016634	020040	SPSP:	.ASCII	/ /

;SCOPE LOOP ROUTINE

;SET CHARACTER IN SWITCH REGISTER -0.

3021	016636		SCOPE:	SENABLE	
(1)	016636	022737		CMP	#176,SWR ;S/W SWR ?
(1)	016644	001003		BNE	.+10 ;NO- CONTINUE
(1)	016646	052777	000100	BIS	#100,@TKS ;ENABLE KEYBOARD INTERRUPT
3022	016654	004437	011472	JSR	%4,TYPINT
3023	016660	017737	162120	MOV	@SWR,SAVE ;FETCH SWITCHES
3024	016666	012737	177574	MOV	#-132,CHRCNT ;SET CHAR COUNT
3025	016674	042737	177400	BIC	#177400,SAVE ;MASK CHARACTER
3026	016702		LDLPX:	\$WAIT	
(1)	016702	105777		TSTB	@LPS ;TEST READY
(1)	016706	100375		BPL	.-4 ;WAIT FOR READY
3027	016710	005777		TST	@LPS ;TEST FOR ERROR

MAINDEC-11-DZLPK-E-D MACY11 27(1006) 01-FEB-77 08:51 PAGE 49  
DZLPKF.P11 01-FEB-77 08:48

SEQ 0073

3040	016714	100006				BPL	LPSCOPE		;BRANCH IF NO ERROR
3041	016716					SERROR	\N		
(1)	016716	012737	000062	001052	ERR62:	MOV	#62,	ERCOUNT	;SET UP ERROR COUNT 62
(1)		000063				N=N+1			

J06

MAINDEC-11-DZLPK-E-D MACY11 27(1006) 01-FEB-77 08:51 PAGE 52  
DZLPKF.P11 01-FEB-77 08:48

SEQ 0074

3045	016724	004537	011706	JSR	%5, STAER	;REPORT ERROR SET
3046	016730	000000		HALT		;HALT ON ERROR
3047	016732	013777	001050 162042	LPSCOPE:MOV	SAVE, 2LPB	;LOAD PRINTER BUFFER

K06

3053	016740	032777	004000	162036	BIT	#BIT11, @SWR	: SEND ONLY ONE CHAR?
3054	016746	001402			BEQ	LSCO	: NO BRANCH
3055	016750	000000			HALT		: HALT - WAIT FOR OPERATOR
3056	016752	000731			BR	SCOPE	: NEXT CHAR
3057	016754	000177	000024		LSCO: JMP	@LSCOP	: SEND LF?
3058	016760	005237	001036		LSCA: INC	CHRCNT	: INCREMENT CHAR COUNT
3059	016764	001346			BNE	LDLPX	: CONTINUE IF NOT DONE LINE
3060	016766	012777	000012	162006	MOV	#12, @LPB	: SEND LF
3061	016774				\$WAIT		
(1)	016774	105777	162000		TSTB	@LPS	: TEST READY
(1)	017000	100375			BPL	-4	: WAIT FOR READY
3062	017002	000715			BR	SCOPE	: CONTINUE
3063							
3064							
3065	017004	016760			LSCOP: LSCA		
3066							
3067							
3068							
3069		000001			.END		





ERR31	004412	1701#								
ERR32	004600	1751#								
ERR33	004656	1760#								
ERR34	005102	1797#								
ERR35	005220	1817#								
ERR36	005460	1855#								
ERR37	005774	1913#								
ERR4	001362	1214#								
ERR40	006260	1968#								
ERR41	006534	2012#								
ERR42	007034	2061#								
ERR43	007326	2110#								
ERR44	007570	2149#								
ERR45	010062	2195#								
ERR46	010330	2236#								
ERR47	010554	2271#								
ERR5	001412	1223#								
ERR50	010746	2304#								
ERR51	011020	2315#								
ERR52	011214	2344#								
ERR53	011436	2404#								
ERR54	014646	2659#								
ERR55	014750	2674#								
ERR56	015050	2687#								
ERR57	015434	2756#								
ERR6	001444	1238#								
ERR60	015502	2765#								
ERR61	015660	2795#								
ERR62	016716	3041#								
ERR7	001470	1247#								
FFSET	004002	1561	1626#							
FFTAB	003724	1560	1601#							
FS	016632	2802	3014#							
FTABE	004000	1586	1623#							
HAMALN	011136	1026	2337#	2357						
HAMX	011322	2360	2362#							
HAM1X	011200	2341#	235							
HAM2	011206	2342#	2351							
HED1	012334	2473	2476	2572#						
HSPRT	006662	1022	2042#	2087						
H50	007004	2056#	2083	2085						
H500	006770	2051	2054#							
H500A	006754	2048	2052#							
H51	007026	2059#	2071	2073	2076					
H52	007050	2060	2064#							
H53	007116	2069	2074#							
H54	007134	2066	2077#							
H56	007204	2080	2086#							
HTABP	016102	2749#	2788	2810#	2830#					
ICTAB	016546	2750	2814	2982#						
ICTABP	016076	2750#	2751	2800	2811#	2812	2814#	2816	2828#	
INDAT	004056	997	1597	1643#	1651	1663				
INDATT	004230	1645	1670#							
INC+TO	004134	1647	1652#							
INCATI	004216	1659	1664#							
INDO	004106	1646#	1657							









ROT2	010006	2185#	2202																	
ROT3	010016	2187#	2200																	
ROT4	010054	2191	2193#																	
ROT5	010076	2194	2198#																	
RTTR	010672	2295#	2332																	
RT1	010700	2296#	2330																	
RT2	010740	2302#	2312																	
RT2A	010762	2303	2307#																	
RT2AA	011004	2309	2311#																	
RT3	011012	2301	2313#	2325																
RT3A	011034	2314	2318#																	
RT3B	011070	2321	2324#																	
SAVE	001050	1143#	1765#	1772*	1773	1860*	1861	1871*	3023*	3025*	3047									
SCHRSW	004716	1757	1768#	1771																
SCOPE	016636	1032	1036	1037	3021#	3056	3062													
SEGCNT	001034	1137#	1961*	1963*	1977*															
SET	001072	1152#	1375*	1381*	1383*	2493														
SETUP	001100	991	1159#																	
SIGNAL	001070	1151#	1373*	1389	2495	2539	2542*	2554*												
SKIP	002410	1372	1391#																	
SLEWCK	003444	1009	1538	1553#																
SLW	003510	1556	1560#																	
SLWD	003522	1562#	1589																	
SLW1	003532	1564#	1569																	
SLW1A	003572	1575	1577#																	
SLW11	003556	1574#	1591																	
SLW2	003614	1578	1582#																	
SNGCHR	007464	1023	2090	2137#	2162															
SPSP	016634	2649	2743	2804	2820	3015#														
STAE	011706	1185	1190	1201	1210	1215	1224	1239	1248	1258	1263	1270	1283	1288						
		1331	1342	1347	1354	1558	1580	1649	1661	1686	1702	1752	1761	1798						
		1818	1856	1914	1969	2013	2062	2111	2150	2196	2237	2272	2305	2316						
		2345	2405	2471#	2660	2675	2688	2757	2766	2796	3045									
STARA	002776	1458#	1471																	
STARAD	003074	1467	1472#	1492																
STARO	002702	1420	1432	1446#																
STAROA	002730	1447	1451#																	
STAROB	002752	1454#	1477																	
STAROC	002744	1450	1453#																	
STAR1	003040	1462	1465#	1469																
STP1	001214	1182#	1186																	
STP2	001236	1183	1187#	1191																
STP3	001260	1188	1192#																	
STP4	001266	1195#	1202																	
STP5	001324	1199	1203#																	
STPSA	001332	1207#	1211																	
STPSB	001354	1208	1212#	1216																
STPSC	001376	1213	1217#																	
STP6	001404	1221#	1225																	
STP7	001426	1222	1226#																	
STRCHR	001054	1145#	1453#	1457*	1459	1470*	1482*	1483	1485*	1486	1681*	1695	1705*	1706						
		1757#	1763	1764*	1771*	1851*	1858	1859*	1870*	1958*	1965	1981	1983	1985						
		1987#	1991*	1993*	2006*	2008	2018	2025*	2054*	2058	2074	2081*	2082	2084*						
		2104*	2107	2125*	2126	2128*	2188*	2189*	2190	2192*	2198	2227*	2230*	2231						
		2233*	2239	2268*	2281	2683*	2692	2697*	2748*	2783	2791	2818*	2830*	2831						
STRCNT	001056	1146#	1904*	1905*	1916*	1937*	2298*	2308*	2310*	2320*	2322*	2751*	2807*	2816*						



MAINDEC-11-DZLPK-E-D MACY11 27(1006)  
DZLPKF.P11 01-FEB-77 08:48

01-FEB-77 08:51 PAGE 58-8  
CROSS REFERENCE TABLE -- USER SYMBOLS

SEQ 0084

TYP	011530	2421	2423#											
TYPD	011556	2427	2429#	2434	2436									
TYPDAT	011622	1514#	1519#	1521#	1522	1523#	1527#	1529#	1530	1531#	1532#	1533	2420#	2423
		2425	2429	2433#	2435#	2438#								
TYPDO	011564	2430#												
TYPF	011574	2424	2433#											
TYPG	011606	2426	2435#											
TYPINT	011472	1159	1413	1427	1438	1554	1644	1680	1748	1789	1847	1899	1955	2004
		2043	2138	2170	2256	2338	2411#	2648	2742	3022				
TYPSTR	012240	2494	2533	2540	2542#									
T1A	004722	1769	1771#											
T2A	004676	1764#	1768											
T280	005060	1793#	1838											
T280A	005066	1794#	1807	1810										
T281	005074	1795#	1808	1811										
T282	005172	1802	1812#											
T282B	005160	1805	1809#											
T283	005212	1815#												
T284	005242	1821#	1823	1825	1827									
T285	005334	1831	1835#											
T3A	004650	1758#	1775											
T5A	004736	1766	1773#	1780										
WORK	001046	1142#	1253#	1267#										
WT	002374	1387#	1390											
WT2	012062	2512#	2513											
WT3	012210	2505	2508	2511	2534#	2535								
XHAM1	011230	2343	2347#											
XHAM1X	011240	2349#												
XS1X	007604	2148	2152#											
.	= 017006	947#	952	955#	961#	965#	967#	971#	976#	984#	988#	994#	1003#	1013#
		1029#	1034#	1040#	1172	1411	1425	1436	1474	1553	1583	1643	1656	1679
		1693	1747	1777	1788	1813	1836	1846	1867	1878	1898	1928	1954	1980
		2003	2022	2033#	2042	2078	2122	2137	2143	2156	2169	2204	2243	2255
		2285	2327	2337	2347	2348	2353	2394	2431	2478	2585#	2589#	2610#	2616#
		2647	2667	2678	2691	2741	2762	2784	2786	2792	3021	3026	3061	

H07

MAINDEC-11-DZLPK-E-D MACY11 27(1006) 01-FEB-77 08:51 PAGE 59  
DZLPKF.P11 01-FEB-77 08:48 CROSS REFERENCE TABLE -- MACRO NAMES

SEQ 0085

SENABL	1109#	1172	1411	1425	1436	1553	1643	1679	1747	1788	1846	1898	1954	2003	2042
	2137	2169	2255	2337	2647	2741	3021								
SERROR	1074#	1184	1189	1200	1209	1214	1223	1238	1247	1257	1262	1269	1282	1287	1290
	1299	1309	1319	1341	1346	1353	1557	1579	1648	1660	1685	1701	1751	1760	1797
	1917	1855	1913	1968	2012	2061	2110	2149	2195	2236	2271	2304	2315	2344	2404
	2659	2674	2687	2756	2765	2795	3041								
SPRINT	1084#	1754	1790	1848	1900	1957	2005	2044	2139	2171	2257	2339			
SSETPS	1124#	1292	1301	1311	1321	1350	1362								
SWAIT	1095#	1474	1583	1656	1693	1777	1813	1836	1867	1878	1928	1980	2022	2078	2122
	2156	2204	2243	2285	2327	2347	2353	2394	2667	2678	2691	2762	2784	2792	3026
	3061														

. ABS. 017006 000

ERRORS DETECTED: 0  
DEFAULT GLOBALS GENERATED: 0

DZLPKF.BIN,DZLPKF.LST/CRF=DZLPKF.P11  
RUN-TIME: 3 6 .9 SECONDS  
RUN-TIME RATIO: 49/10=4.7  
CORE USED: 9K (17 PAGES)

