



```

BBBBBBBBB      AAAAAA      SSSSSSSS      FFFFFFFF      RRRRRRRR      AAAAAA      MM      MM      EEEEEEEEE
BBBBBBBBB      AAAAAA      SSSSSSSS      FFFFFFFF      RRRRRRRR      AAAAAA      MM      MM      EEEEEEEEE
BB      BB      AA      AA      SS      FF      RR      RR      AA      AA      MMMM      MMMM      EE
BB      BB      AA      AA      SS      FF      RR      RR      AA      AA      MMMM      MMMM      EE
BB      BB      AA      AA      SS      FF      RR      RR      AA      AA      MM      MM      EE
BB      BB      AA      AA      SS      FF      RR      RR      AA      AA      MM      MM      EE
BBBBBBBBB      AA      AA      SSSSSS      FFFFFFFF      RRRRRRRR      AA      AA      MM      MM      EEEEEEE
BBBBBBBBB      AA      AA      SSSSSS      FFFFFFFF      RRRRRRRR      AA      AA      MM      MM      EEEEEEE
BB      BB      AAAAAAAAAA      SS      FF      RR      RR      AAAAAAAAAA      MM      MM      EE
BB      BB      AAAAAAAAAA      SS      FF      RR      RR      AAAAAAAAAA      MM      MM      EE
BB      BB      AA      AA      SS      FF      RR      RR      AA      AA      MM      MM      EE
BB      BB      AA      AA      SS      FF      RR      RR      AA      AA      MM      MM      EE
BBBBBBBBB      AA      AA      SSSSSSSS      FF      RR      RR      AA      AA      MM      MM      EEEEEEEEE
BBBBBBBBB      AA      AA      SSSSSSSS      FF      RR      RR      AA      AA      MM      MM      EEEEEEEEE

```

```

RRRRRRRR      EEEEEEEEE      QQQQQQ
RRRRRRRR      EEEEEEEEE      QQQQQQ
RR      RR      EE      QQ      QQ
RR      RR      EE      QQ      QQ
RR      RR      EE      QQ      QQ
RR      RR      EE      QQ      QQ
RRRRRRRR      EEEEEEEE      QQ      QQ
RRRRRRRR      EEEEEEEE      QQ      QQ
RR      RR      EE      QQ      QQ
RR      RR      EE      QQ      QQ
RR      RR      EE      QQ      QQ
RR      RR      EE      QQ      QQ
RR      RR      EEEEEEEEE      QQQQ      QQ
RR      RR      EEEEEEEEE      QQQQ      QQ

```

This file, BASFRAME.REQ, defines the frame control data for a BASIC procedure. Edit: PLL1010

\*\*\*\*\*
\* COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
\* DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
\* ALL RIGHTS RESERVED.
\* THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
\* ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
\* INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
\* COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
\* OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
\* TRANSFERRED.
\* THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
\* AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
\* CORPORATION.
\* DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
\* SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.
\*\*\*\*\*

Edit History:

- 0-001 Initial coding from BP2VAXDGC. JBS 19-NOV-78
1-001 - Make version 1 to conform to version numbering standard.
(The conversion from BAS\$ prefixes to BSF\$ prefixes will
be in a future revision.) JBS 27-NOV-78
1-002 - Convert from BAS to BSF prefixes, and add BSF\$A\_BASE\_R9.
JBS 08-FEB-1979
1-003 - Add BSF\$K\_LENFCDMAJ, BSF\$K\_LENFCDDEF and BSF\$K\_LENFCDDFS.
JBS 09-FEB-1979
1-004 - Add BSF\$V\_FCD IV. JBS 11-SEP-1979
1-005 - Remove the PRINT statement, for the new BLISS compiler.
JBS 02-OCT-1979
1-006 - Add macro to pick up scale. 29-Oct-79
1-007 - Add copyright notice. SBL 11-Mar-1980
1-008 - Add BSF\$A\_RT\_A\_DESC and BSF\$M\_FCD DV. PLL 12-May-1982
1-009 - Add BSF\$M\_FCD\_RND. PLL 10-Jun-1982
1-010 - Change def of BSF\$A\_RT\_A\_DESC (was overlapping BSF\$A\_USER\_HAND).
PLL 10-Aug-1982

FIELD
BSF\$FCD =
SET

The following appear only in major frames.

```

!+
! BSFSA_RTA_DESC = [-72, 0, %BPVAL, 0], ! ptr to run-time array dscs
! BSFSA_USER_HAND = [-68, 0, %BPVAL, 0], ! (never accessed from FP)
! BSFSA_BASE_PC = [-64, 0, %BPVAL, 0], ! first byte of code
! BSFSA_CUR_DATA = [-60, 0, %BPVAL, 0], ! current byte of data text
! BSFSA_END_DATA = [-56, 0, %BPVAL, 0], ! last byte + 1 of data text
! BSFSB_SCA_V_PAC = [-52, 0, 8, 1], ! scale for packed, 0 to -6.
! BSFSB_SCA_V_DOU = [-51, 0, 8, 1], ! scale for double, 0 to -6.
! BSFSD_SCALE_DOU = [-48, 0, 0, 0], ! scale for double, 1 to 10**6

```

```

!+
! The following are also in DEF and DEF* frames
!-

```

```

! BSFSA_INIT_ARG = [-40, 0, %BPVAL, 0], ! pointer to INIT arg list
! BSFSL_INIT_REL = [-36, 0, %BPVAL, 1], ! relocation for INIT arg list
! BSFSA_STR_DESC = [-32, 0, %BPVAL, 0], ! dynamic string descriptors

```

```

!+
! The following are also in GOSUB, CONDITION HANDLING and IOL frames
!+

```

```

! BSFSB_LEN_FCD = [-28, 0, 8, 0], ! length of FCD
! BSFSB_PROC_CODE = [-27, 0, 8, 1], ! frame type, see below
! BSFSW_FCD_FLAGS = [-26, 0, 16, 0], ! frame flags, see below
! BSFSA_PROC_ID = [-24, 0, %BPVAL, 0], ! info for frame
! BSFSA_BASE_R9 = [-20, 0, %BPVAL, 0], ! R9 for this procedure
! BSFSA_BASE_R10 = [-16, 0, %BPVAL, 0], ! R10 for this procedure
! BSFSA_BASE_R11 = [-12, 0, %BPVAL, 0], ! R11 for this procedure
! BSFSA_BASE_SP = [-8, 0, %BPVAL, 0], ! SP for this procedure
! BSFSA_MARK = [-4, 0, %BPVAL, 0], ! last mark PC

```

```

!+
! The following are also in non-BASIC frames.
!-

```

```

! BSFSA_HANDLER = [0, 0, %BPVAL, 0], ! exception handler
! BSFSA_SAVED_AP = [8, 0, %BPVAL, 0], ! previous value of AP
! BSFSA_SAVED_FP = [12, 0, %BPVAL, 0], ! previous value of FP
! BSFSA_SAVED_PC = [16, 0, %BPVAL, 0], ! return address in previous frame
! TES;

```

```

!+
! Define the frame type codes.
!-

```

```

LITERAL
! BSFSK_PROC_MAIN = 1, ! main program
! BSFSK_PROC_SUB = 2, ! subprogram
! BSFSK_PROC_EXTF = 3, ! external function
! BSFSK_PROC_DEF = 4, ! DEF function
! BSFSK_PROC_DEFS = 5, ! DEF* function
! BSFSK_PROC_GOSB = 6, ! GOSUB (subroutine)
! BSFSK_PROC_ONER = 7, ! condition handler
! BSFSK_PROC_IOL = 8; ! Immediate, On-Line

```

```

!+
! Define the bits in the flags word.
!-

```

```

LITERAL
! BSFSM_FCD_LONG = 1*15, ! compiled with 32-bit integers

```

```

BSFSM_FCD_DOU = 1^14,
BSFSM_FCD_RSTR = 1^13,
BSFSM_FCD_OEGO = 1^12,
BSFSM_FCD_IV = 1^11,
BSFSM_FCD_DV = 1^10,
BSFSM_FCD_RND = 1^9;

```

! compiled with double floating  
! procedure returns a string result  
! special ON ERROR initial processing  
! this procedure has IV set  
! decimal overflow enabled if set  
! decimal rounding if set

!+ The frame control data for the currently active major procedure is pointed to by R11, but R11 is offset by 195 bytes from the base of the frame so that the compiled code can more frequently use byte offsets from R11 to address its local variables. Therefore, to address the frame of the major procedure we need some new names. To avoid a proliferation of names, we name below only the fields we reference directly off of R11; the other fields are referenced by removing the offset first.

```

FIELD
BSF$MAJOR_FRAME =
  SET
  BSF$A_USER_HAND = [127, 0, %BPVAL, 0], ! user's error handling flag
  BSF$A_CODE_BEG = [131, 0, %BPVAL, 0], ! first byte of code
  BSF$A_CUR_DTA = [135, 0, %BPVAL, 0], ! current byte of DATA text
  BSF$A_END_DTA = [139, 0, %BPVAL, 0], ! last byte + 1 of DATA text
  BSF$B_SCA_V_PAC = [143, 0, 8, 1], ! scale for packed, 0 to -6.
  BSF$B_SCA_V_DOU = [144, 0, 8, 1], ! scale for double, 0 to -6.
  BSF$D_SCAE_DOU = [147, 0, 0, 0], ! scale for double, 1 to 10**6
  BSF$A_INIT_ARG = [155, 0, %BPVAL, 0], ! pointer to INIT arg list
  BSF$L_INIT_REL = [159, 0, %BPVAL, 1], ! relocation for INIT arg list
  BSF$A_STR_DESC = [163, 0, %BPVAL, 0], ! dynamic string descriptors
  BSF$B_LEN_FCD = [167, 0, 8, 0], ! length of FCD
  BSF$B_PROC_CODE = [168, 0, 8, 1], ! frame type, see above
  BSF$W_FCD_FLAGS = [169, 0, 16, 0], ! frame flags, see below
  BSF$A_PROC_INFO = [171, 0, %BPVAL, 0], ! info for frame, see BSF$A_PROC_ID
  BSF$A_BASE_R9 = [175, 0, %BPVAL, 0], ! R9 for this procedure
  BSF$A_BASE_R10 = [179, 0, %BPVAL, 0], ! R10 for this procedure
  BSF$A_BASE_R11 = [183, 0, %BPVAL, 0], ! R11 for this procedure
  BSF$A_BASE_SP = [187, 0, %BPVAL, 0], ! SP for this procedure
  BSF$A_MARK = [191, 0, %BPVAL, 0], ! last mark PC
  BSF$FRAME_BASE = [195, 0, 0, 0] ! base of major frame
TES;

```

!+ The minor frame is arranged differently because the offset to R10 is different. However, the only offset we use in the minor frame is BSF\$A\_USER\_HAND, so we can simply define BSF\$MINOR\_FRAME as being the same as BSF\$MAJOR\_FRAME.

```

MACRO
  BSF$MINOR_FRAME =
  BSF$MAJOR_FRAME %;

```

!+ The following are the lengths of the FCD part of the BASIC frame for each of the program units. There are really only three lengths, but

```
! we use separate names for many of them to improve the internal
! documentation.
```

## LITERAL

```
BSFSK_LENFCMAJ = 68,      ! Length of a major frame FCD
BSFSK_LENFCMAJ2 = 72,    ! Length of V2 major frame FCD
BSFSK_LENFCDEF = 44,     ! Length of a DEF function FCD
BSFSK_LENFCDFS = 44,     ! Length of a DEF* function FCD
BSFSK_LENFCGGSB = 32,    ! length of a GOSUB frame FCD
BSFSK_LENFCDONE = 32,   ! length of an ON ERROR frame FCD
BSFSK_LENFCDIOL = 32;    ! length of an IOL frame FCD
```

```
!+
! This macro gets the scale factor from the frame of the caller if the caller
! was a BASIC frame. This macro is used in the BASIC string routines which
! do string to numeric conversions and therefore need to know the scale factor
```

## MACRO

```
$BAS$SCALE =
  BEGIN
  EXTERNAL ROUTINE
    BAS$SCALE_L_R1 : BAS$SCALE_JSB;
  BUILTIN FP;
  LOCAL FMP : REF BLOCK [0, BYTE] FIELD (BSF$FCD);      ! our frame

  FMP = .FP;
  BAS$SCALE_L_R1 (.FMP [BSF$A_SAVED_FP])
  END %;
```

```
!+
! End of file BASFRAME.REQ
```

