

000000000000		AAAAAAAAA	SSSSSSSSSSSS	RRRRRRRRRRRR	TTTTTTTTTTTTTT	LLL
000000000000		AAAAAAAAA	SSSSSSSSSSSS	RRRRRRRRRRRR	TTTTTTTTTTTTTT	LLL
000000000000		AAAAAAAAA	SSSSSSSSSSSS	RRRRRRRRRRRR	TTTTTTTTTTTTTT	LLL
000	000	AAA	SSS	RRR	TTT	LLL
000	000	AAA	SSS	RRR	TTT	LLL
000	000	AAA	SSS	RRR	TTT	LLL
000	000	AAA	SSS	RRR	TTT	LLL
000	000	AAA	SSS	RRR	TTT	LLL
000	000	AAA	SSS	RRR	TTT	LLL
000000000000		AAA	SSSSSSSSSS	RRRRRRRRRRRR	TTT	LLL
000000000000		AAA	SSSSSSSSSS	RRRRRRRRRRRR	TTT	LLL
000000000000		AAA	SSSSSSSSSS	RRRRRRRRRRRR	TTT	LLL
000	000	AAAAAAAAAAAAA	SSS	RRR	TTT	LLL
000	000	AAAAAAAAAAAAA	SSS	RRR	TTT	LLL
000	000	AAAAAAAAAAAAA	SSS	RRR	TTT	LLL
000	000	AAA	SSS	RRR	TTT	LLL
000	000	AAA	SSS	RRR	TTT	LLL
000	000	AAA	SSS	RRR	TTT	LLL
000	000	AAA	SSS	RRR	TTT	LLL
000000000000		AAA	SSSSSSSSSSSS	RRR	TTT	LLLLLLLLLLLLLLLL
000000000000		AAA	SSSSSSSSSSSS	RRR	TTT	LLLLLLLLLLLLLLLL
000000000000		AAA	SSSSSSSSSSSS	RRR	TTT	LLLLLLLLLLLLLLLL

BBBBBBBB	AAAAAA	SSSSSSSS	RRRRRRRR	EEEEEEEEEE	CCCCCCCC	PPPPPPPP	RRRRRRRR	000000
BBBBBBBB	AAAAAA	SSSSSSSS	RRRRRRRR	EEEEEEEEEE	CCCCCCCC	PPPPPPPP	RRRRRRRR	000000
BB	BB	AA	AA	SS	CC	PP	RR	00
BB	BB	AA	AA	SS	CC	PP	RR	00
BB	BB	AA	AA	SS	CC	PP	RR	00
BB	BB	AA	AA	SS	CC	PP	RR	00
BBBBBBBB	AAAAAA	SSSSSSSS	RRRRRRRR	EEEEEEEEEE	CCCCCCCC	PPPPPPPP	RRRRRRRR	000000
BBBBBBBB	AAAAAA	SSSSSSSS	RRRRRRRR	EEEEEEEEEE	CCCCCCCC	PPPPPPPP	RRRRRRRR	000000
BB	BB	AAAAAAAAAA	RR	RR	CC	PP	RR	00
BB	BB	AAAAAAAAAA	RR	RR	CC	PP	RR	00
BB	BB	AA	RR	RR	CC	PP	RR	00
BB	BB	AA	RR	RR	CC	PP	RR	00
BB	BB	AA	RR	RR	CC	PP	RR	00
BBBBBBBB	AAAAAA	SSSSSSSS	RRRRRRRR	EEEEEEEEEE	CCCCCCCC	PPPPPPPP	RRRRRRRR	000000
BBBBBBBB	AAAAAA	SSSSSSSS	RRRRRRRR	EEEEEEEEEE	CCCCCCCC	PPPPPPPP	RRRRRRRR	000000

LL	IIIIII	SSSSSSSS
LL	IIIIII	SSSSSSSS
LL	II	SS
LL	II	SS
LL	II	SS
LL	II	SS
LL	II	SSSSSS
LL	II	SSSSSS
LL	II	SS
LL	II	SS
LL	II	SS
LL	II	SS
LLLLLLLLLL	IIIIII	SSSSSSSS
LLLLLLLLLL	IIIIII	SSSSSSSS

```

1 0001 0 MODULE BAS$$REC_PROC (
2 0002 0   IDENT = '1-095'
3 0003 0   ) =
4 0004 1 BEGIN
5 0005 1
6 0006 1 *****
7 0007 1 *
8 0008 1 *   COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
9 0009 1 *   DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
10 0010 1 *   ALL RIGHTS RESERVED.
11 0011 1 *
12 0012 1 *   THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
13 0013 1 *   ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
14 0014 1 *   INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
15 0015 1 *   COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
16 0016 1 *   OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
17 0017 1 *   TRANSFERRED.
18 0018 1 *
19 0019 1 *   THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
20 0020 1 *   AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
21 0021 1 *   CORPORATION.
22 0022 1 *
23 0023 1 *   DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
24 0024 1 *   SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.
25 0025 1 *
26 0026 1 *****
27 0027 1
28 0028 1
29 0029 1 **
30 0030 1 FACILITY: BASIC Support Library - not user callable
31 0031 1
32 0032 1 ABSTRACT:
33 0033 1
34 0034 1   This module implements the record processing level of
35 0035 1   abstraction which is the 3rd level and is called only from
36 0036 1   the user data formatter level (2nd level) when the user
37 0037 1   portion of a record buffer is full (WRITE) or empty
38 0038 1   (READ). This module adds any per record formatting (as
39 0039 1   distinguished from per I/O statement or per I/O list element
40 0040 1   formatting) and then calls RMS ($PUT or $GET). RMS errors
41 0041 1   are converted to BASIC errors and are signaled.
42 0042 1
43 0043 1 ENVIRONMENT: User access mode; AST level or not.
44 0044 1
45 0045 1 AUTHOR: Donald G. Petersen; CREATION DATE: 16-Mar-78
46 0046 1
47 0047 1 MODIFIED BY:
48 0048 1
49 0049 1 0-61 - Add ATTEMPT TO READ NON-EXISTANT RECORD error to seq. reads.
50 0050 1   JMT 02-Jan-78
51 0051 1   Donald G. Petersen, 16-Mar-78 : VERSION 1-01
52 0052 1 1-01 - original DGP
53 0053 1 1-02 - Change to JSB linkages. DGP 14-Nov-78
54 0054 1 1-004 - Update copyright notice and add device names to REQUIRE
55 0055 1   files. JBS 29-NOV-78
56 0056 1 1-005 - Add BAS$RECOUNT to support the Basic RECOUNT function. DGP
57 0057 1   03-Dec-78

```

. Record processing level of abstraction
 . File: BASRECPRO.B32 Edit:MDL1095

58	0058	1	1-006	- Dot problem in BAS\$RECOUNT. DGP 04-Dec-78
59	0059	1	1-007	- Add fudge factor to RECOUNT for the line terminator if input is from a terminal. DGP 04-Dec-78
60	0060	1		
61	0061	1	1-008	- Change REQUIRE file names from FOR... to OTS... JBS 07-DEC-78
62	0062	1	1-009	- Call BAS\$\$SIGNAL_IO for RMS errors. JBS 18-DEC-78
63	0063	1	1-010	- Add new routines for READ. DGP 19-Dec-78
64	0064	1	1-011	- Change references to ISB\$A_BUF_PTR, BUF_BEG, BUF_END to LUB. DGP 05-Jan-79
65	0065	1		
66	0066	1	1-012	- Change to CR format for terminal data files. DGP 11-Jan-79
67	0067	1	1-013	- Make a few changes for recursive I/O. DGP 15-Jan-79
68	0068	1	1-014	- Remove signalling for ^Z. Moved to UDF level for INPUT LINE handling. DGP 15-Jan-79
69	0069	1		
70	0070	1	1-015	- Change stack frame prefix to BSF\$. JBS 08-FEB-1979
71	0071	1	1-016	- Add BAS\$\$REC_GSE (Basic GET sequential). DGP 19-Feb-79
72	0072	1	1-017	- Add BAS\$\$REC_PSE (Basic PUT sequential). DGP 20-Feb-79
73	0073	1	1-018	- set RAB\$L_RBF in BAS\$\$REC_PSE. DGP 20-Feb-79
74	0074	1	1-019	- Set RAB\$L_RBF in BAS\$GSE. DGP 21-Feb-79
75	0075	1	1-020	- Null fill buffer for GET. DGP 27-Feb-79
76	0076	1	1-021	- Add REC routines for FIND, DELETE, UPDATE, RESTORE, SCRATCH. DGP 27-Feb-79
77	0077	1		
78	0078	1	1-022	- Add BASIOERR.REQ for error handling. DGP 28-Feb-79
79	0079	1	1-023	- Add BASUNLOCK and BASFREE. DGP 28-Feb-79
80	0080	1	1-024	- Set RAB\$L_RBF in BAS\$\$REC_UPD. DGP 01-Mar-79
81	0081	1	1-025	- Add REC_PRE, REC_GRE, REC_FRE. DGP 02-Mar-79
82	0082	1	1-026	- More work on relative I/O. DGP 05-Mar-79
83	0083	1	1-027	- Update pointer for RE D in Basic Major Frame in RMF9. DGP 06-Mar-79
84	0084	1	1-028	- Add support for Basic 'foreign buffers'. DGP 27-Mar-79
85	0085	1	1-029	- Point all GETs and PUTs off to GET_ERROR or PUT_ERROR. DGP 02-Apr-79
86	0086	1	1-030	- Add more routines to support ISAM. DGP 03-Apr-79
87	0087	1	1-031	- Fix PUT sequential to support ISAM. DGP 04-Apr-79
88	0088	1	1-032	- Put in indexed I/O stuff. 06-Apr-79
89	0089	1	1-033	- Bug fixes in indexed. 10-Apr-79 DGP
90	0090	1	1-034	- Implement the WAIT statement, using LUB\$L_WAIT_TIME. JBS 10-APR-1979
91	0091	1		
92	0092	1	1-035	- Implement the ECHO and NOECHO functions, using LUB\$V_NOECHO. JBS 17-APR-1979
93	0093	1		
94	0094	1	1-036	- Add code to handle single-character input from GET SEQUENTIAL. JBS 17-APR-1979
95	0095	1		
96	0096	1	1-037	- Implement the CTRL0 and RCTRL0 functions, using LUB\$V_CCO. JBS 19-APR-1979
97	0097	1		
98	0098	1	1-038	- Implement the Cancel Typeahead function, using LUB\$V_PTA. JBS 01-MAY-1979
99	0099	1		
100	0100	1	1-039	- Add Basic PRINT USING support. DGP 15-May-79
101	0101	1	1-040	- Change BIND to GLOBAL BIND ROUTINE in PRINT USING support. JBS 16-MAY-1979
102	0102	1		
103	0103	1	1-041	- Add BAS\$RECOU_INIT. JBS 04-JUN-1979
104	0104	1	1-042	- Add REC level for MAT INPUT. DGP 05-Jun-79
105	0105	1	1-043	- Clean up a lot and put real code into Matrix Input routines. DGP 14-Jun-79
106	0106	1		
107	0107	1	1-044	- Make REC_MIN1 look for continuation character. DGP 20-Jun-79
108	0108	1	1-045	- Terminal devices use PRN format for output. DGP 10-Jul-79
109	0109	1	1-046	- Add BAS\$NUM_INIT, BAS\$NUM2_INIT, BAS\$MAT_INPUT, BAS\$MAT_READ, BAS\$NUM, BAS\$NUM. DGP 13-Jul-79
110	0110	1		
111	0111	1	1-047	- Change ISB\$L_MAJ_F_PTR to ISB\$A_MAJ_F_PTR. JBS 24-JUL-1979
112	0112	1	1-048	- Signal if READ with no DATA. DGP 07-Aug-79
113	0113	1	1-049	- Debug MAT I/O. DGP 07-Aug-79
114	0114	1	1-050	- STOP a few errors that are being SIGNALLed. DGP 05-Sep-79

115	0115	1	1-051 - FREE and UNLOCK are noops if no record locked. DGP 06-Sep-79
116	0116	1	1-052 - Move NUM_INIT and NUM2_INIT to BAS\$MAT_IO, and move BAS\$BLNK_LINE
117	0117	1	from BAS\$MAT_IO to here. DGP 06-Sep-79
118	0118	1	1-053 - Load LUB\$A_RBUF_ADR for GET and PUT for Locate mode (RMS). DGP
119	0119	1	13-Sep-79
120	0120	1	1-054 - Clear the prompt buffer in GET_ERROR. DGP 17-Sep-79
121	0121	1	1-055 - Fix BAS\$BLNK_LINE. DGP 04-Oct-79
122	0122	1	1-056 - Add MAT_READ. DGP 11-Oct-79
123	0123	1	1-057 - Add a REC9 routine for MAT_PRINT. DGP 12-Oct-79
124	0124	1	1-058 - Add BAS\$REC_MLI1. DGP 12-Oct-79
125	0125	1	1-059 - Fix BAS\$REC_WSL1 to leave the cursor alone. DGP 02-Nov-79
126	0126	1	1-060 - Allow BAS\$REC_WSL1 to accept an argument. DGP 06-Nov-79
127	0127	1	1-061 - GET will only null fill the buffer, if necessary, after a GET. DGP
128	0128	1	12-Nov-79
129	0129	1	1-062 - BAS\$REC_MPR1 needs an LF if no format char. DGP 13-Nov-79
130	0130	1	1-063 - Use LUB\$A_UBF to simplify foreign buffer code. JBS 13-NOV-1979
131	0131	1	1-064 - BAS\$REC_MIN1 should not differentiate between terminal & non-
132	0132	1	terminal devices. DGP 14-Nov-79
133	0133	1	1-065 - GET relative not null filling the buffer properly. DGP 29-Nov-79
134	0134	1	1-066 - Null fill the buffer before restoring foreign buffer pointers for
135	0135	1	GET. DGP 18-Dec-79
136	0136	1	1-067 - RMS does not return a terminator in the STV field for files. DGP
137	0137	1	03-Jan-80
138	0138	1	1-068 - REC_WSL9 should only write a record if the output buffer has some-
139	0139	1	thing in it to write. DGP 03-Jan-80
140	0140	1	1-069 - Addition to 1-068. Should also write a record if there was no element
141	0141	1	transmitter. DGP 04-Jan-80
142	0142	1	1-070 - Unconditionally write a CR in WSL1. DGP 14-Jan-80
143	0143	1	1-071 - Restore 'foreign buffers' properly and set RECOUNT in GET Indexed
144	0144	1	and Relative. DGP 12-Feb-80
145	0145	1	1-072 - Adjust the Global RECOUNT to include the length of an escape sequence.
146	0146	1	DGP 22-Feb-80
147	0147	1	1-073 - A previous edit to fix a problem with foreign buffers reintroduced
148	0148	1	a problem with only null padding the buffer after a successful GET.
149	0149	1	DGP 26-Feb-80
150	0150	1	1-074 - REC_WSL9 should set VFC2 to BAS\$K_NULL (no carriage control) if there
151	0151	1	is a format character. DGP 26-Feb-80
152	0152	1	1-075 - Update the cursor position for INPUT if terminated by an escape.
153	0153	1	DGP 27-Feb-80
154	0154	1	1-076 - When calculating CCPOS (current cursor position) following an INPUT
155	0155	1	statement, take the prompt string into account.
156	0156	1	1-077 - REC_RSL1 is not updating the cursor position correctly. DGP 04-Mar-80
157	0157	1	1-078 - REC_WSL9 should set the 'pre' carriage control for the next record
158	0158	1	to [F if there is no format character 'cuz of recursive I/O. DGP
159	0159	1	07-Mar-80
160	0160	1	1-079 - Rationalize the CCO and PTA bits. CCO is now copied from LUB to RAB
161	0161	1	when initializing for output, and PTA when initializing for input.
162	0162	1	JBS 31-MAR-1980
163	0163	1	1-080 - Clear the dirty bit CCB [LUB\$V_OUTBUF_DR] in PUT_ERROR so BAS\$CLOSE
164	0164	1	when invoked by the unwind won't get confused and do a PUT.
165	0165	1	FM 11-SEP-80
166	0166	1	1-081 - Tack on the terminator(s) to the buffer when a GET is done on a
167	0167	1	terminal device file in BAS\$REC_GSE.
168	0168	1	1-082 - Add/transfer BAS\$WAIT to this module, now wait routines are part of
169	0169	1	the sharable image. The routines added are BAS\$WAIT,
170	0170	1	BAS\$READ_WAIT. We had to make WAIT routines part of the sharable
171	0171	1	image because WAIT was requested to become a GLOBAL, and routines in

```

: 172 0172 1 : this module had to read it.
: 173 0173 1 : 1-083- Only if LUB$B_RAT indicates CR format tack on the CRLF. FM 9-feb-81
: 174 0174 1 : 1-084- Cursor position not updated correctly if INPUT was
: 175 0175 1 : terminated by an escape - code should check if previous
: 176 0176 1 : PRINT was terminated by a semicolon or comma. PLL 5-7-81
: 177 0177 1 : 1-085- The purge typeahead function is no longer setting the PTA bit in
: 178 0178 1 : the LUB, so BAS$$REC_RSLO, BAS$$REC_MINO, and BAS$$REC_GSE don't need
: 179 0179 1 : to check it anymore. PLL 6-Aug-81
: 180 0180 1 : 1-086 - Add support for RFA access and manual record locking. PLL 1-Jun-82
: 181 0181 1 : 1-087 - BAS$$REC_GIN and BAS$$REC_FIN should check for a decimal key
: 182 0182 1 : when setting the key size in the RAB. PLL 6-Jul-1982
: 183 0183 1 : 1-088 - Add support for ANSI INPUT. If not enough data is supplied, the
: 184 0184 1 : entire INPUT must be restarted. PLL 29-Jul-1982
: 185 0185 1 : 1-089 - Fix CTRL/O rationalization. Unconditionally copy whatever its
: 186 0186 1 : state is in the LUB into the RAB, and clear it in the LUB.
: 187 0187 1 : MDL and JBS 10-Aug-1982
: 188 0188 1 : 1-090 - Set buffer pointer (in WSL9) from buffer beginning pointer rather
: 189 0189 1 : than from RBUF_ADR. This fixes the problem of pointing to the
: 190 0190 1 : wrong buffer when the user enters a CTRL/C while a line is being
: 191 0191 1 : written, and his control-c routine writes a line also.
: 192 0192 1 : MDL and PLL 19-Aug-1982
: 193 0193 1 : 1-091 - In BAS$$REC_RSL1, BAS$$SIGNAL_IO the too little data error instead
: 194 0194 1 : of calling BAS$$STOP_IO. PLL 27-Sep-1982
: 195 0195 1 : 1-092 - In BAS$$REC_RSLO, the contents of the print buffer should be $PUT
: 196 0196 1 : before the $GET is done, if this is a non-terminal device. This
: 197 0197 1 : is a requested behavior change that will cause input prompts to
: 198 0198 1 : appear in batch log files. RMS is making a change concurrently
: 199 0199 1 : that will cause the actual input provided to appear in the batch
: 200 0200 1 : log as well, thus making a batch log an exact duplicate of how
: 201 0201 1 : it would appear if run interactively. MDL 26-Jul-1983
: 202 0202 1 : 1-093 - check for RMS$_CONTROL completion status; call new CTRL/C signaller
: 203 0203 1 : if this status is returned. this change is coordinated with rev.
: 204 0204 1 : 2-003 of BAS$CTRLC. MDL 12-Mar-1984
: 205 0205 1 : 1-094 - for the special case of channel 0, edit 1-092 should reach thru the
: 206 0206 1 : buddy ptr and use the output side of channel 0 to write out the
: 207 0207 1 : prompt string. MDL 22-Mar-1984
: 208 0208 1 : 1-095 - routines that set and reset record options should reset them BEFORE
: 209 0209 1 : calling error routines, so that subsequent I/O on the channel will
: 210 0210 1 : work properly (if the user handles the error). MDL 23-Mar-1984
: 211 0211 1 : --
: 212 0212 1 :
: 213 0213 1 : <BLF/PAGE>

```



```
215 0214 1 |
216 0215 1 | SWITCHES:
217 0216 1 |
218 0217 1 |
219 0218 1 | SWITCHES ADDRESSING_MODE (EXTERNAL = GENERAL, NONEXTERNAL = WORD_RELATIVE);
220 0219 1 |
221 0220 1 |
222 0221 1 | LINKAGES
223 0222 1 |
224 0223 1 |
225 0224 1 | REQUIRE 'RTLIN:OTSLNK'; | define all linkages
226 0653 1 |
227 0654 1 |
228 0655 1 | TABLE OF CONTENTS:
229 0656 1 |
230 0657 1 |
231 0658 1 | FORWARD ROUTINE
232 0659 1 | BAS$WAIT : NOVALUE, | Writes into module level OWN WAIT
233 0660 1 | BAS$$READ_WAIT, | Reads the module level OWN WAIT
234 0661 1 | BAS$RECOUNT, | Support Basic RECOUNT function
235 0662 1 | BAS$$RECOU_INIT : NOVALUE, | Initialize RECOUNT
236 0663 1 | BAS$$BLNK_LINE : CALL_CCB NOVALUE, | print a blank line
237 0664 1 | ! write sequential list-directed
238 0665 1 | BAS$$REC_WSL0 : JSB_REC0 NOVALUE, | initialize output buffer
239 0666 1 | BAS$$REC_WSL1 : JSB_REC WSL1 NOVALUE, | write all but last record
240 0667 1 | BAS$$REC_WSL9 : JSB_REC9 NOVALUE, | write last record
241 0668 1 | ! Mat Linput
242 0669 1 | BAS$$REC_MLI1 : JSB_REC1, | always read another record
243 0670 1 | ! Mat Read
244 0671 1 | BAS$$REC_MRE1 : JSB_REC1, | return a failure
245 0672 1 | ! Mat Print
246 0673 1 | BAS$$REC_MPR1 : JSB_REC1 NOVALUE, | write one buffer
247 0674 1 | BAS$$REC_MPR9 : JSB_REC9 NOVALUE, | terminate Mat Print
248 0675 1 | ! read sequential list-directed
249 0676 1 | BAS$$REC_RSL0 : JSB_REC0 NOVALUE, | read first
250 0677 1 | BAS$$REC_RSL1 : JSB_REC1, | read next
251 0678 1 | BAS$$REC_RSL9 : JSB_REC9 NOVALUE, | no-op
252 0679 1 | ! MAT INPUT
253 0680 1 | BAS$$REC_MIN0 : JSB_REC0 NOVALUE, | initialize MAT INPUT
254 0681 1 | BAS$$REC_MIN1 : JSB_REC1, | record handler
255 0682 1 | BAS$$REC_MIN9 : JSB_REC9 NOVALUE, | terminate MAT INPUT
256 0683 1 | ! read memory list-directed
257 0684 1 | BAS$$REC_RMF0 : JSB_REC0 NOVALUE, | initialize read memory
258 0685 1 | BAS$$REC_RMF1 : JSB_REC1 NOVALUE, | signal insufficient data
259 0686 1 | BAS$$REC_RMF9 : JSB_REC9 NOVALUE; | no-op
260 0687 1 |
261 0688 1 | GLOBAL BIND
262 0689 1 | ROUTINE
263 0690 1 | ! write formatted
264 0691 1 | BAS$$REC_WF0 = BAS$$REC_WSL0,
265 0692 1 | BAS$$REC_WF1 = BAS$$REC_WSL1,
266 0693 1 | BAS$$REC_WF9 = BAS$$REC_WSL9;
267 0694 1 |
268 0695 1 | FORWARD ROUTINE
269 0696 1 | ! record operations
270 0697 1 | BAS$$REC_GSE : JSB_DO_READ NOVALUE, | GET sequential
271 0698 1 | BAS$$REC_PSE : JSB_PUT NOVALUE, | PUT sequential
```

```
272 0699 1 BASS$REC_FSE : JSB_REC2 NOVALUE,      ! FIND sequential
273 0700 1 BASS$REC_FRFA: JSB_REC2 NOVALUE,      ! FIND by RFA
274 0701 1 BASS$REC_DSE : JSB_REC0 NOVALUE,      ! DELETE sequential
275 0702 1 BASS$REC_UPD : JSB_DO_WRITE NOVALUE,   ! UPDATE
276 0703 1 BASS$REC_RSE : JSB_REC0 NOVALUE,      ! RESTORE sequential
277 0704 1 BASS$REC_SSE : JSB_REC0 NOVALUE,      ! SCRATCH
278 0705 1 BASS$REC_PRE : JSB_PUT NOVALUE,        ! PUT relative with count
279 0706 1 BASS$REC_GRE : JSB_DO_READ NOVALUE,    ! GET relative
280 0707 1 BASS$REC_GRFA: JSB_DO_READ NOVALUE,    ! GET by RFA
281 0708 1 BASS$REC_FRE : JSB_REC0 NOVALUE,      ! FREE relative
282 0709 1 BASS$REC_UNL : JSB_REC0 NOVALUE,      ! UNLOCK
283 0710 1 BASS$REC_FEE : JSB_REC0 NOVALUE,      ! FREE
284 0711 1 BASS$REC_GIN : JSB_REC_IND1 NOVALUE,   ! GET indexed
285 0712 1 BASS$REC_FIN : JSB_REC_IND1 NOVALUE,   ! FIND indexed
286 0713 1 BASS$REC_RIN : JSB_REC_IND NOVALUE,    ! RESTORE indexed
287 0714 1 PUT_ERROR : CALL_CCB NOVALUE,         ! error in $PUT
288 0715 1 GET_ERROR  : CALL_CCB NOVALUE;        ! error in $GET
289 0716 1
290 0717 1
291 0718 1 ! INCLUDE FILES:
292 0719 1 !
293 0720 1
294 0721 1 REQUIRE 'RTLIN:BASIOERR';              ! I/O error codes
295 0774 1
296 0775 1 REQUIRE 'RTLIN:BASFRAME';              ! Basic frame offsets
297 0978 1
298 0979 1 REQUIRE 'RTLML:OTSISB';                ! I/O statement block (ISB) offsets
299 1147 1
300 1148 1 REQUIRE 'RTLML:OTSLUB';                ! Logical unit block (LUB) offsets
301 1288 1
302 1289 1 REQUIRE 'RTLIN:OTSMAC';                ! Macros
303 1483 1
304 1484 1 REQUIRE 'RTLIN:RTLPSECT';              ! Define DECLARE_PSECTS macro
305 1579 1
306 1580 1 REQUIRE 'RTLML:BASPAR';                ! BASIC inter-module parameters
307 1602 1
308 1603 1 LIBRARY 'RTLSTARLE';                  ! STARLET library for macros and symbols
309 1604 1
310 1605 1
311 1606 1 ! MACROS:
312 1607 1 !
313 1608 1 !
314 1609 1 ! NONE
315 1610 1 !
316 1611 1 ! EQUATED SYMBOLS:
317 1612 1 !
318 1613 1 ! LITERAL
319 1614 1 K_MAT_CONT_CHAR = 'X'26',             ! '8' - Mat Input continuation
320 1615 1 ! character
321 1616 1 K_STOP = 0,                            ! stop after signalling this error
322 1617 1 K_SIGNAL = 1;                          ! signal and allow restart
323 1618 1
324 1619 1 !
325 1620 1 ! PSECT DECLARATIONS:
326 1621 1 !
327 1622 1 DECLARE_PSECTS (BAS);                  ! declare PSECTS for BASS$ facility
328 1623 1 !
```



```

: 329      1624 1 ! OWN STORAGE:
: 330      1625 1
: 331      1626 1 OWN
: 332      1627 1   RECOUNT : INITIAL (0),
: 333      1628 1   WAIT      : WORD INITIAL (0);
: 334      1629 1
: 335      1630 1 !
: 336      1631 1 ! EXTERNAL REFERENCES:
: 337      1632 1 !
: 338      1633 1
: 339      1634 1 EXTERNAL ROUTINE
: 340      1635 1   BAS$$SIGNAL : NOVALUE,
: 341      1636 1   BAS$$STOP_IO : NOVALUE,
: 342      1637 1   BAS$$SIGNAL_IO : NOVALUE,
: 343      1638 1   BAS$$SIGNAL_CTRL : NOVALUE;
: 344      1639 1
: 345      1640 1 !
: 346      1641 1
: 347      1642 1 EXTERNAL LITERAL
: 348      1643 1   BAS$K_OUTOF_DAT : UNSIGNED (8),
: 349      1644 1   BAS$K_ENDFILEDEV : UNSIGNED (8),
: 350      1645 1   BAS$K_NOTENODAT : UNSIGNED (8),
: 351      1646 1   BAS$K_TOOLITDAT : UNSIGNED (8),
: 352      1647 1   BAS$K_RECFILETOO : UNSIGNED (8);
: 353      1648 1
: 354      1649 1 !
: 355      1650 1

```

```

! Signal a BASIC error
! Signal fatal Basic error
! Signal a BASIC I/O error
! Signal CTRL/C

```

```

! out of data (READ)
! end of file on device
! not enough data
! ANSI for above
! record in file too long

```

```

: 357 1651 1 GLOBAL ROUTINE BAS$WAIT (
: 358 1652 1     TIME
: 359 1653 1     ) : NOVALUE =
: 360 1654 1
: 361 1655 1 ++
: 362 1656 1 FUNCTIONAL DESCRIPTION:
: 363 1657 1
: 364 1658 1     Limits the time any input I/O statement ( INPUT, INPUT LINE, LINPUT,
: 365 1659 1     MAT 'all above', GET ) to any terminal will wait. If the user does not
: 366 1660 1     reply before the indicated number of seconds an error trap ( which the
: 367 1661 1     user can intercept ) will be taken. WAIT is a module level OWN in this
: 368 1662 1     module.
: 369 1663 1
: 370 1664 1
: 371 1665 1 FORMAL PARAMETERS:
: 372 1666 1
: 373 1667 1     TIME.rl.v      Number of seconds to wait, max.
: 374 1668 1
: 375 1669 1 IMPLICIT INPUTS:
: 376 1670 1
: 377 1671 1     The module level OWN WAIT
: 378 1672 1
: 379 1673 1 IMPLICIT OUTPUTS:
: 380 1674 1
: 381 1675 1     Writes to the module level OWN WAIT the number of seconds given
: 382 1676 1
: 383 1677 1 ROUTINE VALUE:
: 384 1678 1
: 385 1679 1     None
: 386 1680 1
: 387 1681 1 SIDE EFFECTS:
: 388 1682 1
: 389 1683 1     None
: 390 1684 1
: 391 1685 1 --
: 392 1686 1
: 393 1687 2 BEGIN
: 394 1688 2 ++
: 395 1689 2 If the WAIT time is unreasonable then force it to the acceptable range.
: 396 1690 2 This is until the correct error message is cooked up for this error.
: 397 1691 2 WAIT is a module level OWN.
: 398 1692 2 --
: 399 1693 2 WAIT = MIN ( ABS(.TIME) , 255 );
: 400 1694 2 RETURN;
: 401 1695 1 END;

```

!End of BAS\$WAIT

```

.TITLE BAS$REC_PROC
.IDENT \1-095\

.PSECT _BAS$DATA,NOEXE, PIC,2

00000000 00000 RECOUNT: .LONG 0
0000 00004 WAIT. .WORD 0

.EXTRN BAS$$SIGNAL, BAS$$STOP_IO
.EXTRN BAS$$SIGNAL_IO, BAS$$SIGNAL_CTRL

```



```

: 404      1697 1 ROUTINE BAS$$READ_WAIT      .Read the module level OWN WAIT
: 405      1698 1      : =
: 406      1699 1
: 407      1700 1 ++
: 408      1701 1 FUNCTIONAL DESCRIPTION:
: 409      1702 1
: 410      1703 1      Read the module level OWN WAIT and return it. The value of this
: 411      1704 1      function is the current contents of wait. All routines that need
: 412      1705 1      this value must call this routine.
: 413      1706 1
: 414      1707 1
: 415      1708 1 FORMAL PARAMETERS:
: 416      1709 1
: 417      1710 1      NONE
: 418      1711 1
: 419      1712 1 IMPLICIT INPUTS:
: 420      1713 1
: 421      1714 1      Reads the module level OWN WAIT
: 422      1715 1
: 423      1716 1 IMPLICIT OUTPUTS:
: 424      1717 1
: 425      1718 1      None
: 426      1719 1
: 427      1720 1 ROUTINE VALUE:
: 428      1721 1
: 429      1722 1      The contents of module level OWN WAIT
: 430      1723 1
: 431      1724 1 SIDE EFFECTS:
: 432      1725 1
: 433      1726 1      None
: 434      1727 1 --
: 435      1728 1
: 436      1729 2 BEGIN
: 437      1730 2 +
: 438      1731 2 Just return the value of the module level OWN WAIT
: 439      1732 2 -
: 440      1733 2 RETURN .WAIT;
: 441      1734 1 END;                                !End of BAS$$READ_WAIT

```

0000 00000 BAS\$\$READ_WAIT:

```

50 00000000' EF 3C 00002      .WORD Save nothing
                   04 00C09      MOVZWL WAIT, R0
                   RET

```

: 1697
: 1733
: 1734

: Routine Size: 10 bytes, Routine Base: _BAS\$CODE + 0020

: 442 1735 1

```

: 444      1736 1 GLOBAL ROUTINE BASS$RECOUNT          ! RECOUNT
: 445      1737 1 : =
: 446      1738 1
: 447      1739 1 !++
: 448      1740 1 FUNCTIONAL DESCRIPTION:
: 449      1741 1
: 450      1742 1     This routine supports the Basic RECOUNT function. It returns the number
: 451      1743 1     of bytes read on the last Get. It utilizes a piece of OWN storage which
: 452      1744 1     is written to by the record processing levels which do Gets. In order
: 453      1745 1     to keep the OWN storage from having to be global, this routine is included
: 454      1746 1     in this module
: 455      1747 1
: 456      1748 1 FORMAL PARAMETERS:
: 457      1749 1
: 458      1750 1     NONE
: 459      1751 1
: 460      1752 1 IMPLICIT INPUTS:
: 461      1753 1
: 462      1754 1     RECOUNT.rl          The number of bytes read on the last GET
: 463      1755 1
: 464      1756 1 IMPLICIT OUTPUTS:
: 465      1757 1
: 466      1758 1     NONE
: 467      1759 1
: 468      1760 1 ROUTINE VALUE:
: 469      1761 1
: 470      1762 1     NUM_OF_BYTES.wl.v    number of bytes read on last Get
: 471      1763 1
: 472      1764 1 SIDE EFFECTS:
: 473      1765 1
: 474      1766 1 !--
: 475      1767 1
: 476      1768 2 BEGIN
: 477      1769 2 RETURN .RECOUNT
: 478      1770 1 END;                                ! End of BASS$RECOUNT
```

```

                    0000 00000
50 00000000' EF  D0 00002
                   04 00009
```

```

.ENTRY BASS$RECOUNT, Save nothing
MOVL  RECOUNT, R0
RET
```

```

: 1736
: 1769
: 1770
```

; Routine Size: 10 bytes, Routine Base: _BASS\$CODE + 002A

; 479 1771 1

```
: 481      1772 1 GLOBAL ROUTINE BAS$$RECOU_INIT : NOVALUE =      ! Initialize RECOUNT
: 482      1773 1
: 483      1774 1
: 484      1775 1 ++
: 485      1776 1 FUNCTIONAL DESCRIPTION:
: 486      1777 1
: 487      1778 1      This routine initializes the RECOUNT variable. It is used before a RUN
: 488      1779 1      compiler command in case the previous run of the user's program left
: 489      1780 1      something in RECOUNT.
: 490      1781 1
: 491      1782 1 FORMAL PARAMETERS:
: 492      1783 1
: 493      1784 1      NONE
: 494      1785 1
: 495      1786 1 IMPLICIT INPUTS:
: 496      1787 1
: 497      1788 1      NONE
: 498      1789 1
: 499      1790 1 IMPLICIT OUTPUTS:
: 500      1791 1
: 501      1792 1      RECOUNT.wl      Always set to zero.
: 502      1793 1
: 503      1794 1 ROUTINE VALUE:
: 504      1795 1
: 505      1796 1      NONE
: 506      1797 1
: 507      1798 1 SIDE EFFECTS:
: 508      1799 1
: 509      1800 1 --
: 510      1801 1
: 511      1802 2 BEGIN
: 512      1803 2 RECOUNT = 0;
: 513      1804 1 END;

! End of BAS$$RECOU_INIT
```

```
00000000' EF 0000 00000
                D4 00002
                04 00008
```

```
.ENTRY BAS$$RECOU_INIT, Save nothing
CLRL RECOUNT
RET
```

```
: 1772
: 1803
: 1804
```

; Routine Size: 9 bytes, Routine Base: _BAS\$CODE + 0034

; 514 1805 1


```
516 1806 1 GLOBAL ROUTINE BAS$$BLNK LINE ( ! write a blank line
517 1807 1     FORMAT_CHAR) : CALL_CCB NOVALUE =
518 1808 1
519 1809 1 !++
520 1810 1 FUNCTIONAL DESCRIPTION:
521 1811 1
522 1812 1     Print out a blank line. This is needed between arrays.
523 1813 1
524 1814 1 FORMAL PARAMETERS:
525 1815 1
526 1816 1     FORMAT_CHAR.rlu.v the format character last used
527 1817 1
528 1818 1 IMPLICIT INPUTS:
529 1819 1
530 1820 1     NONE
531 1821 1
532 1822 1 IMPLICIT OUTPUTS:
533 1823 1
534 1824 1     NONE
535 1825 1
536 1826 1 COMPLETION CODES:
537 1827 1
538 1828 1     NONE
539 1829 1
540 1830 1 SIDE EFFECTS:
541 1831 1
542 1832 1     NONE
543 1833 1
544 1834 1 !--
545 1835 1
546 1836 2 BEGIN
547 1837 2
548 1838 2 EXTERNAL REGISTER
549 1839 2     CCB : REF BLOCK [, BYTE];
550 1840 2
551 1841 2 LOCAL
552 1842 2     RMS_STATUS;
553 1843 2
554 1844 2 !+
555 1845 2 ! Actually put out the blank line here.
556 1846 2 !-
557 1847 2     CCB [RAB$W_RSZ] = 0;
558 1848 2     CCB [LUB$A_BUF_PTR] = .CCB [LUB$A_BUF_BEG];
559 1849 2     CCB [LUB 3_BAS_VFC1] = BAS$K_LF;
560 1850 2     CCB [LUB$B_BAS_VFC2] = BAS$K_CR;
561 1851 2
562 1852 2     RMS_STATUS = $PUT (RAB = .CCB);
563 1853 2
564 1854 2 IF .RMS_STATUS EQL RMS$_CTRLC
565 1855 2 THEN
566 1856 2     BAS$$SIGNAL_CTRLC ();
567 1857 2
568 1858 2 IF NOT .RMS_STATUS
569 1859 2 THEN
570 1860 2     PUT_ERROR (K_STOP);
571 1861 2
572 1862 2 RETURN;
```

; 573 1863 1 END;

!End of BAS\$\$BLNK_LINE

				0004 00000	.EXTRN SYSSPUT	
		22	AB	B4 00002	.ENTRY BAS\$\$BLNK_LINE, Save R2	: 1806
	BO	BC	AB	D0 00005	CLRW 34(CCB)	: 1847
	DA	8D01	8F	B0 0000A	MOVL -68(CCB), -80(CCB)	: 1848
			5B	DD 00010	MOVW #36097, -38(CCB)	: 1849
00000000G	00		01	FB 00012	PUSHL CCB	: 1852
	52		50	D0 00019	CALLS #1, SYSSPUT	
00010651	8F		52	D1 0001C	MOVL R0, RMS_STATUS	
			07	12 00023	CMPL RMS_STATUS, #67153	: 1854
00000000G	00		00	FB 00025	BNEQ 1\$	
	07		52	L8 0002C 1\$:	CALLS #0, BAS\$\$SIGNAL_CTRL	: 1856
			7E	D4 0002F	BLBS RMS_STATUS, 2\$	: 1858
0000V	CF		01	FB 00031	CLRL -(SP)	: 1860
			04	00036 2\$:	CALLS #1, PUT_ERROR	: 1863
					RET	

; Routine Size: 55 bytes, Routine Base: _BAS\$CODE + 003D

; 574 1864 1


```

576 1865 1 GLOBAL ROUTINE BASS$REC_MPR1          ! Write Mat Print record
577 1866 1   : JSB_REC1 NOVALUE =
578 1867 1
579 1868 1 !++
580 1869 1 FUNCTIONAL DESCRIPTION:
581 1870 1
582 1871 1   Write one sequential formatted record and initialize for the next
583 1872 1   BASS$REC_MPR1 writes one record for 10 MAT PRINT A() and then
584 1873 1   initializes the output buffer and returns start and end+1 of user
585 1874 1   part of record buffer to be filled by caller.
586 1875 1   FLR records are space padded.
587 1876 1
588 1877 1 FORMAL PARAMETERS:
589 1878 1
590 1879 1   NONE
591 1880 1
592 1881 1 IMPLICIT INPUTS:
593 1882 1
594 1883 1   LUB$V_FORM_CHAR      =1, comma or semicolon format character
595 1884 1   LUB$W_RBUF_SIZE     Size (bytes) allocated for record buffer at OPEN.
596 1885 1   LUB$A_RBUF_ADR      Address of record buffer from OPEN
597 1886 1   LUB$A_BUF_END       points to last char inserted into buffer
598 1887 1                       by UDF level I/O.
599 1888 1   LUB$V_FORCIBLE       Indicates a forcible device
600 1889 1   LUB$V_OUTBUF_DR    Indicates that there is valid data in the output
601 1890 1                       buffer
602 1891 1   RAB$W_RSZ         Record size
603 1892 1
604 1893 1 IMPLICIT OUTPUTS:
605 1894 1
606 1895 1   LUB$B_BAS_VFC2       'Post' carriage control for terminal devices
607 1896 1   LUB$A_BUF_PTR      Address of next char in user part
608 1897 1                       of record buffer
609 1898 1   LUB$A_BUF_END       Address of last+1 char in user part
610 1899 1                       of record buffer
611 1900 1   LUB$V_OUTBUF_DR    indicates valid data in the output buffer
612 1901 1   LUB$A_BUF_BEG      Beginning of the user buffer
613 1902 1   RAB$L_RBF         Pointer to the user record buffer.
614 1903 1
615 1904 1 ROUTINE VALUE:
616 1905 1
617 1906 1   NONE
618 1907 1
619 1908 1 SIDE EFFECTS:
620 1909 1
621 1910 1   NONE
622 1911 1 !--
623 1912 1
624 1913 2 BEGIN
625 1914 2
626 1915 2 EXTERNAL REGISTER
627 1916 2   (CB : REF BLOCK [, BYTE]);
628 1917 2
629 1918 2 LOCAL
630 1919 2   RMS_STATUS;
631 1920 2
632 1921 2 !+
```

```

: 633      1922 2      | If there is no format character, then set the 'pre' and 'post'
: 634      1923 2      | carriage control to delimit a record.
: 635      1924 2      |
: 636      1925 2      |
: 637      1926 2      |
: 638      1927 2      | IF NOT .CCB [LUB$V_FORM_CHAR]
: 639      1928 2      | THEN
: 640      1929 2      | BEGIN
: 641      1930 2      |   CCB [LUB$B_BAS_VF(1)] = BAS$K_LF;
: 642      1931 2      |   CCB [LUB$B_BAS_VF(2)] = BAS$K_CR;
: 643      1932 2      | END;
: 644      1933 2      |
: 645      1934 2      | + Set recordsize to actual length of record
: 646      1935 2      | -
: 647      1936 2      |
: 648      1937 2      | CCB [RAB$W_RSZ] = .CCB [LUB$A_BUF_PTR] - .CCB [LUB$A_BUF_BEG];
: 649      1938 2      |
: 650      1939 2      | +
: 651      1940 2      | Output buffer to RMS and check for errors
: 652      1941 2      | If errors, SIGNAL BAS$_FATSYSIO (12='FATAL SYSTEM I/O FAILURE')
: 653      1942 2      | -
: 654      1943 2      |
: 655      1944 2      | CCB [RAB$L_RBF] = .CCB [LUB$A_RBUF_ADR];
: 656      1945 2      | CCB [LUB$V_OUTBUF_DR] = 0;
: 657      1946 2      |
: 658      1947 2      | RMS_STATUS = $PUT (RAB = .CCB);
: 659      1948 2      |
: 660      1949 2      | IF .RMS_STATUS EQL RMS$_CTRLC
: 661      1950 2      | THEN
: 662      1951 2      |   BAS$$SIGNAL_CTRLC ();
: 663      1952 2      |
: 664      1953 2      | IF NOT .RMS_STATUS
: 665      1954 2      | THEN
: 666      1955 2      |
: 667      1956 2      | +
: 668      1957 2      | Not OPEN or CONNECT - RMS record operation
: 669      1958 2      | -
: 670      1959 2      |
: 671      1960 2      |   PUT_ERROR (K_STOP);
: 672      1961 2      |
: 673      1962 2      | +
: 674      1963 2      | Return next output buffer start and end addresses
: 675      1964 2      | -
: 676      1965 2      |
: 677      1966 2      | CCB [LUB$A_BUF_PTR] = .CCB [LUB$A_RBUF_ADR];
: 678      1967 2      | CCB [LUB$A_BUF_END] = .CCB [LUB$A_RBUF_ADR] + .CCB [LUB$W_RBUF_SIZE];
: 679      1968 2      | RETURN;
: 680      1969 1      | END;
                                | End of routine - BAS$$REC_MPR1
```

```

                                52 DD 00000 BAS$$REC_MPR1::
                                PUSH  R2
06 FE AB 8D01 02 E0 00002 BBS #2, -2(CCB), 1$
                                DA AB 8F B0 00007 MOVW #36097, -38(CCB)
```

```

: 1865
: 1926
: 1929
```

22	AB	B0	AB	BC	AB	A3	0000D	1\$:	SUBW3	-68(CCB), -80(CCB), 34(CCB)	:	1937
		28	AB	EC	AB	D0	00014		MOVL	-20(CCB), 40(CCB)	:	1944
		FE	AB		08	8A	00019		BICB2	#8, -2(CCB)	:	1945
					5B	DD	0001D		PUSHL	CCB	:	1947
		00000000G	00		01	FB	0001F		CALLS	#1, SYSSPUT	:	
			52		50	D0	00026		MOVL	R0, RMS_STATUS	:	
		00010651	8F		52	D1	00029		CMPL	RMS_STATUS, #67153	:	1949
					07	12	00030		BNEQ	2\$	:	
		00000000G	00		00	FB	00032		CALLS	#0, BAS\$\$SIGNAL_CTRL	:	1951
			07		52	E8	00039	2\$:	BLBS	RMS_STATUS, 3\$	:	1953
					7E	D4	0003C		CLRL	-(SP)	:	1960
		0000V	CF		01	FB	0003E		CALLS	#1, PUT_ERROR	:	
		B0	AB	EC	AB	D0	00043	3\$:	MOVL	-20(CCB), -80(CCB)	:	1966
			50	D2	AB	3C	00048		MOVZWL	-46(CCB), R0	:	1967
		B4	AB	EC	BB40	9E	0004C		MOVAB	@-20(CCB)[R0], -76(CCB)	:	
					04	BA	00052		POPR	#*M<R2>	:	1969
					05	00054			RSB		:	

; Routine Size: 85 bytes, Routine Base: _BAS\$CODE + 0074

; 681 1970 1

```

: 683      1971 1 GLOBAL ROUTINE BAS$$REC_MPR9          ! Mat Write sequential
: 684      1972 1   : JSB_REC9 NOVALUE =
: 685      1973 1
: 686      1974 1 ++
: 687      1975 1 FUNCTIONAL DESCRIPTION:
: 688      1976 1
: 689      1977 1   This routine does not write a record. Presumably the MAT PRINT element
: 690      1978 1   transmitter took care of all of that. Since we do not want a blank line
: 691      1979 1   after the array, there is no need to write anything here.
: 692      1980 1
: 693      1981 1 FORMAL PARAMETERS:
: 694      1982 1
: 695      1983 1   NONE
: 696      1984 1
: 697      1985 1 IMPLICIT INPUTS:
: 698      1986 1
: 699      1987 1   LUB$W_RBUF_SIZE      Size (bytes) allocated for record buffer at OPEN.
: 700      1988 1   LUB$A_RBUF_ADR      Address of record buffer from OPEN
: 701      1989 1
: 702      1990 1 IMPLICIT OUTPUTS:
: 703      1991 1
: 704      1992 1   LUB$A_BUF_PTR      Address of next char in user part
: 705      1993 1   of record buffer
: 706      1994 1   LUB$A_BUF_END      Address of last+1 char in user part
: 707      1995 1   of record buffer
: 708      1996 1
: 709      1997 1 ROUTINE VALUE:
: 710      1998 1
: 711      1999 1   NONE
: 712      2000 1
: 713      2001 1 SIDE EFFECTS:
: 714      2002 1
: 715      2003 1   NONE
: 716      2004 1 --
: 717      2005 1
: 718      2006 2 BEGIN
: 719      2007 2
: 720      2008 2 EXTERNAL REGISTER
: 721      2009 2   CCB : REF BLOCK [, BYTE];
: 722      2010 2
: 723      2011 2 ++
: 724      2012 2   Return next output buffer start and end addresses
: 725      2013 2   --
: 726      2014 2
: 727      2015 2 CCB [LUB$A_BUF_PTR] = .CCB [LUB$A_RBUF_ADR];
: 728      2016 2 CCB [LUB$A_BUF_END] = .CCB [LUB$A_RBUF_ADR] + .CCB [LUB$W_RBUF_SIZE];
: 729      2017 2 RETURN;
: 730      2018 1 END;                                ! END BAS$$REC_MPR19
```

```

      B0  AB      EC  AB  D0 00000 BAS$$REC_MPR9::
                                MOVL  -20(CCB), -80(CCB)
      B4  AB      D2  AB  3C 00005      MOVZWL -46(CCB), R0
                                EC BB40 9E 00009      MOVAB  @-20(CCB)[R0], -76(CCB)
```

```

: 2015
: 2016
:
```

BASS\$REC_PROC
1-095

L 5
16-Sep-1984 01:01:12
14-Sep-1984 11:56:35

VAX-11 Bliss-32 V4.0-742
[BASRTL.SRC]BASRECPRO.B32;1

Page 19
(9)

05 0000F

RSB

; 2018

; Routine Size: 16 bytes, Routine Base: _BASS\$CODE + 00C9

; 731 2019 1

```
733 2020 1 GLOBAL ROUTINE BAS$$REC_WSL9          ! Write sequential formatted
734 2021 1   : JSB_REC9 NOVALUE =
735 2022 1
736 2023 1
737 2024 1 ++
738 2025 1 FUNCTIONAL DESCRIPTION:
739 2026 1   Write one sequential formatted record and initialize for the next
740 2027 1   BAS$$REC_WSF1 (and BAS$$REC_WSL9) writes one output buffer and then
741 2028 1   initializes the output buffer and returns start and end+1 of user
742 2029 1   part of record buffer to be filled by caller.
743 2030 1   FLR records are space padded.
744 2031 1   /logical record number is incremented/.
745 2032 1
746 2033 1 FORMAL PARAMETERS:
747 2034 1
748 2035 1   NONE
749 2036 1
750 2037 1 IMPLICIT INPUTS:
751 2038 1
752 2039 1   ISBSV_PRINT_INI      flag to indicate whether there was an element
753 2040 1                     transmitter
754 2041 1   LUB$W_RBUF_SIZE     Size (bytes) allocated for record buffer at OPEN.
755 2042 1   LUB$A_RBUF_ADR     Address of record buffer from OPEN
756 2043 1   LUB$A_BUF_END     points to last char inserted into buffer
757 2044 1                     by UDF level I/O.
758 2045 1   LUB$V_FORM_CHAR   The last element transmitter ended in a comma
759 2046 1                     or semicolon format char.
760 2047 1   LUB$V_FORCIBLE     Indicates a forcible device
761 2048 1   LUB$V_OUTBUF_DR    Indicates that there is valid data in the output
762 2049 1                     buffer
763 2050 1   RAB$W_RSZ         Record size
764 2051 1
765 2052 1 IMPLICIT OUTPUTS:
766 2053 1
767 2054 1   ISBSV_PRINT_INI      reset flag
768 2055 1   LUB$B_BAS_VFC2     'Post' carriage control for terminal devices
769 2056 1   LUB$A_BUF_PTR     Address of next char in user part
770 2057 1                     of record buffer
771 2058 1   LUB$A_BUF_END     Address of last+1 char in user part
772 2059 1                     of record buffer
773 2060 1   LUB$V_OUTBUF_DR    indicates valid data in the output buffer
774 2061 1   LUB$A_BUF_BEG     Beginning of the user buffer
775 2062 1   RAB$L_RBF        Pointer to the user record buffer.
776 2063 1
777 2064 1 ROUTINE VALUE:
778 2065 1
779 2066 1   NONE
780 2067 1
781 2068 1 SIDE EFFECTS:
782 2069 1
783 2070 1   NONE
784 2071 1 --
785 2072 1
786 2073 2 BEGIN
787 2074 2
788 2075 2 EXTERNAL REGISTER
789 2076 2   (CCB : RFF BLOCK [, BYTE];
```



```

790      2077 2
791      2078 2
792      2079 2
793      2080 2
794      2081 2
795      2082 2
796      2083 2
797      2084 2
798      2085 2
799      2086 2
800      2087 2
801      2088 2
802      2089 2
803      2090 2
804      2091 2
805      2092 2
806      2093 2
807      2094 2
808      2095 2
809      2096 2
810      2097 2
811      2098 2
812      2099 2
813      2100 2
814      2101 2
815      2102 2
816      2103 2
817      2104 2
818      2105 2
819      2106 2
820      2107 2
821      2108 2
822      2109 2
823      2110 2
824      2111 2
825      2112 2
826      2113 2
827      2114 2
828      2115 2
829      2116 2
830      2117 2
831      2118 2
832      2119 2
833      2120 2
834      2121 2
835      2122 2
836      2123 2
837      2124 2
838      2125 2
839      2126 2
840      2127 2
841      2128 2
842      2129 2
843      2130 2
844      2131 2
845      2132 2
846      2133 2

LOCAL
  RMS_STATUS;

  !+
  ! If last element ended with a format character and not a terminal device
  ! then return to caller without writing anything. With CR format, we must
  ! PUT a whole record.
  !-

  IF .CCB [LUB$V_FORM_CHAR] AND NOT .CCB [LUB$V_FORCIBLE] THEN RETURN;

  !+
  ! Set the 'post' carriage control to carriage return
  ! if the last element transmitter had no format character following.
  !-

  IF NOT .CCB [LUB$V_FORM_CHAR] THEN CCB [LUB$B_BAS_VFC2] = BAS$K_CR;

  !+
  ! Set recordsize to actual length of record
  !-

  CCB [RAB$W_RSZ] = .CCB [LUB$A_BUF_PTR] - .CCB [LUB$A_BUF_BEG];

  !+
  ! Output buffer to RMS and check for errors
  ! If errors, SIGNAL BAS$FATSYSIO (12='FATAL SYSTEM I/O FAILURE')
  !-

  CCB [RAB$L_RBF] = .CCB [LUB$A_BUF_BEG];

  !+
  ! Write something if there is something in the buffer or if there was no
  ! element transmitter.
  !-

  IF .CCB [LUB$V_OUTBUF_DR] OR .CCB [ISB$V_PRINT_INI]
  THEN
    RMS_STATUS = $PUT (RAB = .CCB);

    IF .RMS_STATUS EQL RMS$_CTRLC
    THEN
      BAS$$SIGNAL_CTRLC ();

    IF NOT .RMS_STATUS
    THEN
      PUT_ERROR (K_STOP);

    CCB [LUB$V_OUTBUF_DR] = 0;
    CCB [ISB$V_PRINT_INI] = 0;

    !+
    ! If there is no format character then set the 'pre' carriage control to LF
    ! for the next record. This is recursive I/O and the rest of the list when
    ! we return should be written on the next line.
    !-

```

```
: 847      2134 2    IF NOT .CCB [LUB$V_FORM_CHAR] THEN CCB [LUB$B_BAS_VFC1] = BAS$K_LF;
: 848      2135 2
: 849      2136 2    !+
: 850      2137 2    !- Return next output buffer start and end addresses
: 851      2138 2
: 852      2139 2
: 853      2140 2    CCB [LUB$A_BUF_PTR] = .CCB [LUB$A_RBUF_ADR];
: 854      2141 2    CCB [LUB$A_BUF_END] = .CCB [LUB$A_RBUF_ADR] + .CCB [LUB$W_RBUF_SIZE];
: 855      2142 2    RETURN;
: 856      2143 1    END;
                                ! END OF ROUTINE
```

			52	DD	00000	BAS\$\$REC	WSL9::			
	0A	FE	AB	02	E1	00002	PUSHL	R2		2020
	66	FE	AB	06	E1	00007	BBC	#2, -2(CCB), 1\$		2087
	05	FE	AB	02	E0	0000C	BBC	#6, -2(CCB), 8\$		
		DB	AB	02	E0	0000C	BBS	#2, -2(CCB), 2\$		2094
22	AB	B0	AB	8D	8F	90 00011	1\$:	MOVB	#-115, -37(CCB)	
		28	AB	BC	AB	A3 00016	2\$:	SUBW3	-68(CCB), -80(CCB), 34(CCB)	2100
	05	FE	AB	BC	AB	D0 0001D		MOVL	-68(CCB), 40(CCB)	2107
	0C	97	AB		03	E0 00022		BBS	#3, -2(CCB), 3\$	2113
					03	E1 00027		BBC	#3, -105(CCB), 4\$	
	00000000G	00			5B	DD 0002C	3\$:	PUSHL	CCB	2116
		52			01	FB 0002E		CALLS	#1, SYSS\$PUT	
	00010651	8F			50	D0 00035		MOVL	R0, RMS_STATUS	
					52	D1 00038	4\$:	CMPL	RMS_STATUS, #67153	2118
	00000000G	00			07	12 0003F		BNEQ	5\$	
		07			00	FB 00041		CALLS	#0, BAS\$\$SIGNAL_CTRL	2120
					52	E8 00048	5\$:	BLBS	RMS_STATUS, 6\$	2122
					7E	D4 0004B		CLRL	-(SP)	2124
	0000V	CF			01	FB 0004D		CALLS	#1, PUT_ERROR	
	FE	AB			08	8A 00052	6\$:	BICB2	#8, -2(CCB)	2126
	97	AB			08	8A 00056		BICB2	#8, -105(CCB)	2127
04	FE	AB			02	E0 0005A		BBS	#2, -2(CCB), 7\$	2134
	DA	AB			01	90 0005F		MOVB	#1, -38(CCB)	
	B0	AB	EC	AB	D0	00063	7\$:	MOVL	-20(CCB), -80(CCB)	2140
		50	D2	AB	3C	00068		MOVZWL	-46(CCB), R0	2141
	B4	AB	EC	BB40	9E	0006C		MOVAB	@-20(CCB)[R0], -76(CCB)	
				04	BA	00072	8\$:	POPR	#*M<R2>	2143
					05	00074		RSB		

: Routine Size: 117 bytes, Routine Base: _BAS\$CODE + 00D9

: 857 2144 1


```
859 2145 1 GLOBAL ROUTINE BASS$REC_RSLO          ' Read initialization
860 2146 1 : JSB_RECO NOVALUE =
861 2147 1
862 2148 1 ++
863 2149 1 FUNCTIONAL DESCRIPTION:
864 2150 1
865 2151 1     BASS$REC_RSr0 (and BASS$REC_RSf1) reads one record if this is not a terminal.
866 2152 1     Then return start and end+1 of user
867 2153 1     part of record to be processed as input.
868 2154 1
869 2155 1 FORMAL PARAMETERS:
870 2156 1
871 2157 1     NONE
872 2158 1
873 2159 1 IMPLICIT INPUTS:
874 2160 1
875 2161 1     LUB$W_RBUF_SIZE      Size of record buffer allocated in OPEN.
876 2162 1     LUB$A_RBUF_ADR      Address of record buffer from OPEN.
877 2163 1     LUB$V_TERM_DEV      flag in LUB which indicates a terminal device.
878 2164 1     RAB$W_RSZ          word in the RAB which contains the buffer size.
879 2165 1     RAB$L_RBF          longword in RAB which points to the buffer.
880 2166 1     LUB$L_WAIT_TIME     Max time to wait for input, in seconds.
881 2167 1     WAIT              The module level OWN WAIT
882 2168 1
883 2169 1 IMPLICIT OUTPUTS:
884 2170 1
885 2171 1     RECOUNT            Global storage to hold number of bytes read from
886 2172 1                     last input.
887 2173 1     LUB$L_LOG_RECNO      Increment logical record number
888 2174 1                     of next record to be read.
889 2175 1     LUB$A_BUF_PTR        points to first char of user part of
890 2176 1                     record buffer.
891 2177 1     LUB$A_BUF_END        points to end+1 of user part of
892 2178 1                     record buffer.
893 2179 1
894 2180 1 ROUTINE VALUE:
895 2181 1
896 2182 1     NONE
897 2183 1
898 2184 1 SIDE EFFECTS:
899 2185 1
900 2186 1     Reads next record from file on this logical unit.
901 2187 1     Throws away things that are pending in the Print buffer for non-terminal
902 2188 1     devices.
903 2189 1     SIGNALs RMS errors directly.
904 2190 1     SIGNALs BASSK_TIMLIMEXC if a wait time was specified and we
905 2191 1     exceed it.
906 2192 1 --
907 2193 1
908 2194 2 BEGIN
909 2195 2
910 2196 2 EXTERNAL REGISTER
911 2197 2     (CB : REF BLOCK [, BYTE]);
912 2198 2
913 2199 2 LITERAL
914 2200 2     K_ESCAPE = %X'1B',
915 2201 2     K_CR = %X'0D';
```

```

916 2202 2
917 2203 2
918 2204 2 LOCAL
919 2205 2 RMS STATUS,
920 2206 2 WAIT_TIME;
921 2207 2 ! Current wait time
922 2208 2
923 2209 2 +
924 2210 2 | If a timeout has been specified, store information in the RAB to tell
925 2211 2 | RMS about it. If no timeout has been specified, clear the TMO bit
926 2212 2 | in case there was an earlier timeout specified.
927 2213 2 -
928 2214 2 +
929 2215 2 | If WAIT is zero then use the LUB's wait. This is to provide upward compatibility
930 2216 2 | , i.e. existing EXE's can run with the LUB wait value in V2.2.
931 2217 2 -
932 2218 2 WAIT_TIME = ( IF ( .WAIT EQL 0 ) THEN .CCB [ LUB$WAIT_TIME ] ELSE .WAIT );
933 2219 2
934 2220 2 IF ( .WAIT_TIME EQL 0 )
935 2221 2 THEN
936 2222 2 CCB [ RAB$V_TMO ] = 0
937 2223 2 ELSE
938 2224 2 BEGIN
939 2225 2 CCB [ RAB$B_TMO ] = .WAIT_TIME;
940 2226 2 CCB [ RAB$V_TMO ] = 1;
941 2227 2 END;
942 2228 2
943 2229 2 +
944 2230 2 | Set the Read-no-echo RMS bit based on the user's last call to
945 2231 2 | ECHO or NOECHO.
946 2232 2 -
947 2233 2 CCB [ RAB$V_RNE ] = .CCB [ LUB$V_NOECHO ];
948 2234 2
949 2235 2 +
950 2236 2 | Check to see if this is a terminal device. If this is NOT
951 2237 2 | a terminal then do a GET. GETs for terminals are done each time more
952 2238 2 | data are needed.
953 2239 2 | Read record into buffer using RMS and check for errors
954 2240 2 -
955 2241 2 IF ( NOT .CCB [ LUB$V_TERM_DEV ] OR .CCB [ LUB$V_ANSI ] )
956 2242 2 THEN
957 2243 2 BEGIN
958 2244 2 LOCAL
959 2245 2 TEMP_CCB : REF BLOCK [, BYTE]; ! Temporary CCB
960 2246 2 TEMP_CCB = .CCB [ LUB$A_BUDDY_PTR ];
961 2247 2
962 2248 2 +
963 2249 2 | If there is something pending in the Print buffer, then $PUT it.
964 2250 2 | It cannot become a prompt, because RMS will throw away prompts
965 2251 2 | to disk files; therefore we must $PUT it.
966 2252 2 -
967 2253 2 IF ( NOT .CCB [ LUB$V_TERM_DEV ] ) AND .TEMP_CCB [ LUB$V_OUTBUF_DR ]
968 2254 2 THEN
969 2255 2 BEGIN
970 2256 2 TEMP_CCB [ RAB$W_RSZ ] = .TEMP_CCB [ LUB$A_BUF_PTR ] - .TEMP_CCB [ LUB$A_BUF_BEG ];
971 2257 2 TEMP_CCB [ RAB$L_RBF ] = .TEMP_CCB [ LUB$A_BUF_BEG ];
972 2258 2
```

```

973      2259 4
974      2260 4      RMS_STATUS = $PUT (RAB = .TEMP_CCB);
975      2261 4
976      2262 4      IF .RMS_STATUS EQL RMS$_CONTROL_C
977      2263 4      THEN
978      2264 4          BAS$$SIGNAL_CTRL_C (';
979      2265 4
980      2266 4      IF NOT .RMS_STATUS
981      2267 4      THEN
982      2268 4          PUT_ERROR (K_STOP);
983      2269 4      END;
984      2270 4
985      2271 4      TEMP_CCB [LUB$_BUF_PTR] = .TEMP_CCB [LUB$_BUF_BEG];
986      2272 4
987      2273 4      RMS_STATUS = $GET (RAB = .CCB);
988      2274 4
989      2275 4      IF .RMS_STATUS EQL RMS$_CONTROL_C
990      2276 4      THEN
991      2277 4          BAS$$SIGNAL_CTRL_C ();
992      2278 4
993      2279 4      IF NOT .RMS_STATUS
994      2280 4      THEN
995      2281 4          GET_ERROR (K_STOP);
996      2282 4
997      2283 4      +
998      2284 4      | Set RECOUNT to the number of bytes read
999      2285 4      | If the file is a terminal format file, then RECOUNT has to be
1000     2286 4      | adjusted for the carriage control terminator. Because RMS does not return
1001     2287 4      | a terminator for a file, we unconditionally put a CRLF on the end and
1002     2288 4      | bump RECOUNT by 2.
1003     2289 4      -
1004     2290 4
1005     2291 4      RECOUNT = .CCB [RAB$_RSZ] + (IF (.CCB [LUB$_TERM_FOR]) AND ((.CCB [LUB$_RAT] AND FAB$_CR) NEQU 0
1006     2292 4      THF 2 ELSE 0);
1007     2293 4
1008     2294 4      +
1009     2295 4      | Put the CR into the STV field since RMS doesn't
1010     2296 4      | We should only do this if the record attributes indicate a CR format.
1011     2297 4      -
1012     2298 4
1013     2299 4      IF (.CCB [LUB$_RAT] AND FAB$_CR) NEQU 0 THEN CCB [RAB$_STV] = 13;
1014     2300 4
1015     2301 4      +
1016     2302 4      | Return start-1 and end+1 address of record just read
1017     2303 4      -
1018     2304 4
1019     2305 4      CCB [LUB$_BUF_PTR] = .CCB [RAB$_RBF] - 1;
1020     2306 4      CCB [LUB$_BUF_END] = .CCB [RAB$_RBF] + .CCB [RAB$_RSZ];
1021     2307 4      END
1022     2308 4      ELSE
1023     2309 4
1024     2310 4      +
1025     2311 4      | This is a terminal. Force a no data in the buffer condition
1026     2312 4      | so the first GET is done on the element transmitter after the
1027     2313 4      | Prompt (if any) is known.
1028     2314 4      -
1029     2315 4      BEGIN
```

```
: 1030      2316 3      CCB [LUBSA_BUF_PTR] = .CCB [RABSL_RBF];  
: 1031      2317 3      CCB [LUBSA_BUF_END] = .CCB [LUBSA_BUF_PTR];  
: 1032      2318 2      END;  
: 1033      2319 2  
: 1034      2320 2      RETURN;  
: 1035      2321 1      END;
```

. End of BAS\$\$REC_RSLO

.EXTRN SYSSGET

```
0C BB 00000 BAS$$REC_RSLO::  
50 00000000' EF 3C 00002 PUSHR #^M<R2,R3> : 2145  
0C 12 00009 MOVZWL WAIT, R0 : 2216  
50 CC AB D0 0000B BNEQ 1$  
06 12 0000F MOVL -52(CCB), WAIT_TIME : 2218  
07 AB 02 8A 00011 BNEQ 1$ : 2220  
08 11 00015 BICB2 #2, 7(CCB)  
50 90 00017 1$: BRB 2$ : 2223  
07 AB 02 88 0001B MOVB WAIT_TIME, 31(CCB)  
00 A0 AB F0 0001F 2$: BISB2 #2, 7(CCB) : 2224  
08 FE AB 05 E1 00026 INSV -96(CCB), #0, #1, 7(CCB) : 2232  
03 A1 AB 04 E0 0002B BBC #5, -2(CCB), 3$ : 2241  
00A3 31 00030 BBS #4, -95(CCB), 3$  
52 BB AB D0 00033 3$: BRW 11$ : 2247  
37 FE AB 05 E0 00037 MOVL -72(CCB), TEMP_CCB : 2254  
32 FE A2 03 E1 0003C BBS #5, -2(CCB), 5$  
22 A2 B0 A2 BC A2 A3 00041 BBC #3, -2(TEMP_CCB), 5$ : 2257  
28 A2 BC A2 D0 00048 SUBW3 -68(TEMP_CCB), -80(TEMP_CCB), 34(TEMP_CCB)  
52 DD 0004D MOVL -68(TEMP_CCB), 40(TEMP_CCB) : 2258  
00000000G 00 01 FB 0004F PUSHL TEMP_CCB : 2260  
53 50 D0 00056 CALLS #1, SYSSPUT  
00010651 8F 53 D1 00059 MOVL R0, RMS_STATUS  
07 12 00060 CMPL RMS_STATUS, #67153 : 2262  
00000000G 00 00 FB 00062 BNEQ 4$ : 2264  
07 53 E8 00069 4$: BLBS RMS_STATUS, 5$ : 2266  
7E D4 0006C CLRL -(SP) : 2268  
0000V CF 01 FB 0006E CALLS #1, PUT_ERROR  
B0 A2 BC A2 D0 00073 5$: MOVL -68(TEMP_CCB), -80(TEMP_CCB) : 2271  
5B DD 00078 PUSHL CCB : 2273  
00000000G 00 01 FB 0007A CALLS #1, SYSSGET  
53 50 D0 00081 MOVL R0, RMS_STATUS  
00010651 8F 53 D1 00084 CMPL RMS_STATUS, #67153 : 2275  
07 07 12 0008B BNEQ 6$ : 2277  
00000000G 00 00 FB 0008D CALLS #0, BAS$$SIGNAL_CTRL C  
07 53 E8 00094 6$: BLBS RMS_STATUS, 7$ : 2279  
7E D4 00097 CLRL -(SP) : 2281  
0000V CF 01 FB 00099 CALLS #1, GET_ERROR  
0A FE AB 04 E1 0009E 7$: BBC #4, -2(CCB), 8$ : 2291  
05 F6 AB 01 E1 000A3 BBC #1, -10(CCB), 8$  
50 02 D0 000A8 MOVL #2, R0  
02 11 000AB BRB 9$  
50 D4 000AD 8$: CLRL R0  
00000000' EF 51 22 AB 3C 000AF 9$: MOVZWL 34(CCB), R1  
04 F6 AB 51 C1 000B3 ADDL3 R1, R0, RECOUNT : 2298  
01 E1 000BB BBC #1, -10(CCB), 10$
```

BASS\$REC_PROC
1-095

6 6
16-Sep-1984 01:01:12 VAX-11 Bliss-32 V4.0-742
14-Sep-1984 11:56:35 [BASRTL.SRC]BASREC(PRO.B32;1

Page 27
(11)

B0	AB	0C	AB	0D	D0	000C0	MOVL	#13, 12(CCB)	:
		28	AB	01	C3	000C4	SUBL3	#1, 40(CCB), -80(CCB)	: 2304
			50	22	AB	3C 000CA	MOVZWL	34(CCB), R0	: 2305
		B4	AB	28	BB40	9F 000CE	MOVAB	@40(CCB)[R0], -76(CCB)	:
					0A	11 000D4	BRB	12\$	: 2241
		B0	AB	28	AB	D0 000D6	MOVL	40(CCB), -80(CCB)	: 2316
		B4	AB	B0	AB	D0 000DB	MOVL	-80(CCB), -76(CCB)	: 2317
					0C	BA 000E0	POPR	#^M<R2,R3>	: 2321
					05	000E2	RSB		:

; Routine Size: 227 bytes, Routine Base: _BASS\$CODE + 014E

; 1036 2322 1

```
1038 2323 1 GLOBAL ROUTINE BASS$REC_MINO ! MAT Input initialization
1039 2324 1 : JSB_RECO NOVALUE =
1040 2325 1
1041 2326 1 ++
1042 2327 1 FUNCTIONAL DESCRIPTION:
1043 2328 1
1044 2329 1 BASS$REC_RSFO (and BASS$REC_RSFI) reads one record if this is not a terminal.
1045 2330 1 Then return start and end+1 of user
1046 2331 1 part of record to be processed as input.
1047 2332 1
1048 2333 1 FORMAL PARAMETERS:
1049 2334 1
1050 2335 1 NONE
1051 2336 1
1052 2337 1 IMPLICIT INPUTS:
1053 2338 1
1054 2339 1 LUB$W_RBUF_SIZE Size of record buffer allocated in OPEN.
1055 2340 1 LUB$A_RBUF_ADR Address of record buffer from OPEN.
1056 2341 1 LUB$V_TERM_DEV flag in LUB which indicates a terminal device.
1057 2342 1 RAB$W_RSZ word in the RAB which contains the buffer size.
1058 2343 1 RAB$L_RBF longword in RAB which points to the buffer.
1059 2344 1 LUB$L_WAIT_TIME Max time to wait for input, in seconds.
1060 2345 1 WAIT Module level OWN WAIT
1061 2346 1
1062 2347 1 IMPLICIT OUTPUTS:
1063 2348 1
1064 2349 1 RECOUNT Global storage to hold number of bytes read from
1065 2350 1 last input.
1066 2351 1 LUB$L_LOG_RECNO Increment logical record number
1067 2352 1 of next record to be read.
1068 2353 1 LUB$A_BUF_PTR points to first char of user part of
1069 2354 1 record buffer.
1070 2355 1 LUB$A_BUF_END points to end+1 of user part of
1071 2356 1 record buffer.
1072 2357 1
1073 2358 1 ROUTINE VALUE:
1074 2359 1
1075 2360 1 NONE
1076 2361 1
1077 2362 1 SIDE EFFECTS:
1078 2363 1
1079 2364 1 Reads next record from file on this logical unit.
1080 2365 1 Throws away things that are pending in the Print buffer for non-terminal
1081 2366 1 devices.
1082 2367 1 SIGNALS BASS$_FATSYSIO (12='FATAL SYSTEM I/O FAILURE')
1083 2368 1 SIGNALS BASS$_ENDFILDEV (11='END-OF-FILE ON DEVICE')
1084 2369 1 SIGNALS BASS$_RECFILTOO if record too big
1085 2370 1 SIGNALS BASS$_TIMLIMEXC if a wait time was specified and we
1086 2371 1 exceed it.
1087 2372 1 --
1088 2373 1
1089 2374 2 BEGIN
1090 2375 2
1091 2376 2 EXTERNAL REGISTER
1092 2377 2 CCB : REF BLOCK [, BYTE];
1093 2378 2
1094 2379 2 LITERAL
```



```
1095 2380      K_ESCAPE = 'X'1B',
1096 2381      K_CH = 'X'0D';
1097 2382
1098 2383      LOCAL
1099 2384          RMS_STATUS,
1100 2385          WAIT_TIME;                                !Current wait time
1101 2386
1102 2387      !+ If a timeout has been specified, store information in the RAB to tell
1103 2388      RMS about it. If no timeout has been specified, clear the TMO bit
1104 2389      in case there was an earlier timeout specified.
1105 2390      -
1106 2391
1107 2392
1108 2393      !+ If WAIT is zero then use the LUB's wait. This is to provide upward compatibility
1109 2394      , i.e. existing EXE's can run with the LUB wait value in V2.2.
1110 2395      -
1111 2396      WAIT_TIME = ( IF ( .WAIT EQL 0 ) THEN .CCB [ LUB$L_WAIT_TIME ] ELSE .WAIT );
1112 2397
1113 2398      IF ( .WAIT_TIME EQL 0 )
1114 2399      THEN
1115 2400          CCB [ RAB$V_TMO ] = 0
1116 2401      ELSE
1117 2402          BEGIN
1118 2403              CCB [ RAB$B_TMO ] = .WAIT_TIME;
1119 2404              CCB [ RAB$V_TMO ] = 1;
1120 2405          END;
1121 2406
1122 2407
1123 2408
1124 2409      !+ Set the Read-no-echo RMS bit based on the user's last call to
1125 2410      ECHO or NOECHO.
1126 2411      -
1127 2412      CCB [ RAB$V_RNE ] = .CCB [ LUB$V_NOECHO ];
1128 2413
1129 2414
1130 2415      !+
1131 2416      Check to see if this is a terminal device. If this is NOT
1132 2417      a terminal then do a GET. GETs for terminals are done each time more
1133 2418      data are needed.
1134 2419      Read record into buffer using RMS and check for errors
1135 2420      If end-of-file, SIGNAL BAS$K_ENDFILDEV (11='END-OF-FILE ON DEVICE')
1136 2421      If record too big for record buffer, SIGNAL BAS$K_RECFTLTOO.
1137 2422      If errors, SIGNAL BAS$K_FATSYSIO (12='FATAL SYSTEM I/O ERROR')
1138 2423      -
1139 2424
1140 2425      IF ( NOT .CCB [ LUB$V_TERM_DEV ] )
1141 2426      THEN
1142 2427          BEGIN
1143 2428              LOCAL
1144 2429                  TEMP_CCB : REF BLOCK [, BYTE];          ! Temporary CCB
1145 2430                  TEMP_CCB = .CCB [ LUB$A_BUDDY_PTR ];
1146 2431
1147 2432
1148 2433      !+
1149 2434      If there is something pending in the Print buffer, then $PUT it.
1150 2435      It cannot become a prompt, because RMS will throw away prompts
1151 2436      to disk files; therefore we must $PUT it.
```

```
1152 2437 3
1153 2438 3
1154 2439 3
1155 2440 4
1156 2441 4
1157 2442 4
1158 2443 4
1159 2444 4
1160 2445 4
1161 2446 4
1162 2447 4
1163 2448 4
1164 2449 4
1165 2450 4
1166 2451 4
1167 2452 4
1168 2453 3
1169 2454 3
1170 2455 3
1171 2456 3
1172 2457 3
1173 2458 3
1174 2459 3
1175 2460 3
1176 2461 3
1177 2462 3
1178 2463 3
1179 2464 3
1180 2465 3
1181 2466 3
1182 2467 3
1183 2468 3
1184 2469 3
1185 2470 3
1186 2471 3
1187 2472 3
1188 2473 4
1189 2474 4
1190 2475 4
1191 2476 4
1192 2477 4
1193 2478 3
1194 2479 3
1195 2480 3
1196 2481 3
1197 2482 3
1198 2483 3
1199 2484 3
1200 2485 3
1201 2486 3
1202 2487 3
1203 2488 3
1204 2489 3
1205 2490 3
1206 2491 3
1207 2492 3
1208 2493 3

!-
IF (NOT .CCB [LUB$V_TERM_DEV]) AND .TEMP_CCB [LUB$V_OUTBUF_DR]
THEN
  BEGIN
    TEMP_CCB [RAB$W_RSZ] = .TEMP_CCB [LUB$A_BUF_PTR] - .TEMP_CCB [LUB$A_BUF_BEG];
    TEMP_CCB [RAB$L_RBF] = .TEMP_CCB [LUB$A_BUF_BEG];

    RMS_STATUS = $PUT (RAB = .CCB);

    IF .RMS_STATUS EQL RMS$_CONTROL_C
    THEN
      BAS$$SIGNAL_CTRL_C ();

    IF NOT .RMS_STATUS
    THEN
      PUT_ERROR (K_STOP);
    END;

    TEMP_CCB [LUB$A_BUF_PTR] = .TEMP_CCB [LUB$A_BUF_BEG];
    RMS_STATUS = $GET (RAB = .CCB);

    IF .RMS_STATUS EQL RMS$_CONTROL_C
    THEN
      BAS$$SIGNAL_CTRL_C ();

    IF NOT .RMS_STATUS
    THEN
      GET_ERROR (K_STOP);

    !+
    ! Set RECOUNT to the number of bytes read
    ! If the file is a terminal format file, then RECOUNT has to be
    ! adjusted for the carriage control terminator.
    !-
    RECOUNT = .CCB [RAB$W_RSZ] + (IF .CCB [LUB$V_TERM_FOR] THEN SELECT ONEU .CCB [RAB$W_STV0] OF
      SET
      [K_ESCAPE] : .CCB [RAB$W_STV2];
      [K_CR] : 2;
      [OTHERWISE] : 0;
      TES ELSE 0);

    !+
    ! Return start-1 and end+1 address of record just read
    !-
    CCB [LUB$A_BUF_PTR] = .CCB [RAB$L_RBF] - 1;
    CCB [LUB$A_BUF_END] = .CCB [RAB$L_RBF] + .CCB [RAB$W_RSZ];

    !+
    ! Check for an '&' as the last character of the record. If it is there,
    ! it is a continuation character and signifies that there is more data to
    ! come in the next record.
    !-
    IF .(.CCB [LUB$A_BUF_END] - 1) < 0, 8> EQLU K_MAT_CONT_CHAR
```


! End of BASS\$REC_MINO

PC	BB	00000	BAS\$\$REC	MINO::		
50	00000000	EF	3C	00002	PUSHR	#*M<R2,R3>
		0C	12	00009	MOVZWL	WAIT, R0
50	CC	AB	D0	0000B	BNEQ	1\$
		06	12	0000F	MOVL	-52(CCB), WAIT_TIME
07	AB	02	8A	00011	BNEQ	1\$
		08	11	00015	BICB2	#2, 7(CCB)
1F	AB	50	90	00017	BRB	2\$
07	AB	02	88	0001B	MOVB	WAIT_TIME, 31(CCB)
		00	AB	F0	BISB2	#2, 7(CCB)
01	03	FE	AB	0001F	INSV	-96(CCB), #0, #1, 7(CCB)
				05	BBC	#5, -2(CCB), 3\$
				31	BRW	12\$
		52	B8	0002B	MOVL	-72(CCB), TEMP_CCB
				05	BBS	#5, -2(CCB), 5\$
37	FE	AB	03	00032	BBC	#3, -2(TEMP_CCB), 5\$
32	FE	A2		00037	SUBW3	-68(TEMP_CCB), -80(TEMP_CCB), 34(TEMP_CCB)
22	A2	B0	BC	0003C	MOVL	-68(TEMP_CCB), 40(TEMP_CCB)
		28	BC	00043	PUSHL	CCB
				5B	CALLS	#1, SYSSPUT
	00000000G	00	01	0004A	MOVL	R0, RMS_STATUS
		53	50	00051	CMPL	RMS_STATUS, #67153
	00010651	8F	53	00054	BNEQ	4\$
			07	0005B	CALLS	#0, BAS\$\$SIGNAL_CTRL
	00000000G	00	00	00050	BLBS	RMS_STATUS, 5\$
		07	53	00064	CLRL	-(SP)
			7E	00067		

	0000V	CF		01	FB	00069		CALLS	#1, PUT_ERROR		
	B0	A2	BC	A2	D0	0006E	5\$:	MOVL	-68(TEMP_CCB), -80(TEMP_CCB)		2455
				5B	DD	00073		PUSHL	CCB		2457
	00000000G	00		01	FB	00075		CALLS	#1, SYS\$GET		
		53		50	D0	0007C		MOVL	R0, RMS_STATUS		
	00010651	8F		53	D1	0007F		CMPL	RMS_STATUS, #67153		2459
				07	12	00086		BNEQ	6\$		
	00000000G	00		00	FB	00088		CALLS	#0, BAS\$\$SIGNAL_CTRL		2461
		07		53	E8	0008F	6\$:	BLBS	RMS_STATUS, 7\$		2463
				7E	D4	00092		CLRL	-(SP)		2465
	0000V	CF		01	FB	00094		CALLS	#1, GET_ERROR		
19	FE	AB		04	E1	00099	7\$:	BBC	#4, -2(CCB), 9\$		2473
		50	0C	AB	3C	0009E		MOVZWL	12(CCB), R0		
		1B		50	B1	000A2		CMPL	R0, #27		2475
				06	12	000A5		BNEQ	8\$		
		50	0E	AB	3C	000A7		MOVZWL	14(CCB), R0		
				0C	11	000AB		BRB	10\$		
		0D		50	B1	000AD	8\$:	CMPL	R0, #13		2476
				05	12	000B0		BNEQ	9\$		
		50		02	D0	000B2		MOVL	#2, R0		
				02	11	000B5		BRB	10\$		
				50	D4	000B7	9\$:	CLRL	R0		2473
		51	22	AB	3C	000B9	10\$:	MOVZWL	34(CCB), R1		
00000000'	EF	50		51	C1	000BD		ADDL3	R1, R0, RECOUNT		
B0	AB	28		01	C3	000C5		SUBL3	#1, 40(CCB), -80(CCB)		2484
		50	22	AB	3C	000CB		MOVZWL	34(CCB), R0		2485
		B4	28	BB40	9E	000CF		MOVAB	@40(CCB)[R0], -76(CCB)		
		50	B4	AB	D0	000D5		MOVL	-76(CCB), R0		2493
		26	FF	A0	91	000D9		CMPL	-1(R0), #38		
				05	12	000DD		BNEQ	11\$		
			B4	AB	D7	000DF		DECL	-76(CCB)		2496
				10	11	000E2		BRB	13\$		2497
	97	AB		02	8A	000E4	11\$:	BICB2	#2, -105(CCB)		2500
				0E	11	000E8		BRB	14\$		2425
	B0	AB	28	AB	D0	000EA	12\$:	MOVL	40(CCB), -80(CCB)		2513
	B4	AB	B0	AB	D0	000EF		MOVL	-80(CCB), -76(CCB)		2514
	97	AB		02	88	000F4	13\$:	BISB2	#2, -105(CCB)		2515
				0C	BA	000F8	14\$:	POPR	#^M<R2,R3>		2519
				05	000FA			RSB			

; Routine Size: 251 bytes, Routine Base: _BAS\$CODE + 0231

; 1235 2520 1

```
1237 2521 1 GLOBAL ROUTINE BAS$$REC_RSL1          ! Read element transmitter
1238 2522 1 : JSB_REC1 =
1239 2523 1
1240 2524 1 ++
1241 2525 1 FUNCTIONAL DESCRIPTION:
1242 2526 1
1243 2527 1     BAS$$REC_RSL1 reads one record if this is a terminal device.
1244 2528 1     Otherwise an error is signalled.
1245 2529 1     Then return start and end+1 of user
1246 2530 1     part of record to be processed as input.
1247 2531 1
1248 2532 1 FORMAL PARAMETERS:
1249 2533 1
1250 2534 1     NONE
1251 2535 1
1252 2536 1 IMPLICIT INPUTS:
1253 2537 1
1254 2538 1     LUB$W_RBUF_SIZE      Size of record buffer allocated in OPEN.
1255 2539 1     LUB$A_RBUF_ADR       Address of record buffer from OPEN.
1256 2540 1     LUB$V_TERM_DEV      flag indicating a terminal device.
1257 2541 1     RAB$L_RBF           Pointer to buffer
1258 2542 1     RAB$W_RSZ          buffer size
1259 2543 1
1260 2544 1 IMPLICIT OUTPUTS:
1261 2545 1
1262 2546 1     RECOUNT             Own storage for RECOUNT function.
1263 2547 1     LUB$A_BUF_PTR        points to first char of user part of
1264 2548 1                       record buffer.
1265 2549 1     LUB$A_BUF_END        points to end+1 of user part of
1266 2550 1                       record buffer.
1267 2551 1
1268 2552 1 ROUTINE VALUE:
1269 2553 1
1270 2554 1     NONE
1271 2555 1
1272 2556 1 SIDE EFFECTS:
1273 2557 1
1274 2558 1     Reads next record from file on this logical unit.
1275 2559 1     SIGNALs Insufficient data or any resultant RMS errors.
1276 2560 1 --
1277 2561 1
1278 2562 2 BEGIN
1279 2563 2
1280 2564 2 EXTERNAL REGISTER
1281 2565 2     (CB : REF BLOCK [, BYTE]);
1282 2566 2
1283 2567 2 LOCAL
1284 2568 2     RMS STATUS,
1285 2569 2     T_(CB : REF BLOCK [, BYTE]);
1286 2570 2
1287 2571 2 LITERAL
1288 2572 2     K_ESCAPE = %X'1B',
1289 2573 2     K_CR = %X'0D';
1290 2574 2
1291 2575 2 ++
1292 2576 2 ! Check to see if this is a terminal device. If this is
1293 2577 2 ! a terminal then do a GET. GETs for terminals are done each time more
```

```
1294 2578 2 | data are needed. If this is not a terminal device then error.
1295 2579 2 | Read record into buffer using RMS and check for errors
1296 2580 2 |
1297 2581 2 |
1298 2582 2 | IF (NOT .CCB [LUB$V_ANSI]) AND .CCB [LUB$V_TERM_DEV]
1299 2583 2 | THEN
1300 2584 2 | BEGIN
1301 2585 2 | RMS_STATUS = $GET (RAB = .CCB);
1302 2586 2 | IF .RMS_STATUS EQL RMSS_CONTROLC
1303 2587 2 | THEN
1304 2588 2 | BAS$$SIGNAL_CTRLC ();
1305 2589 2 |
1306 2590 2 | IF NOT .RMS_STATUS
1307 2591 2 | THEN
1308 2592 2 | GET_ERROR (K_STOP);
1309 2593 2 |
1310 2594 2 |
1311 2595 2 |
1312 2596 2 |
1313 2597 2 | +
1314 2598 2 | Return start-1 and end+1 address of record just read
1315 2599 2 | LUB$A_BUF_PTR is set to the beginning-1 of the buffer only for BASIC
1316 2600 2 | Input. This is seen as a solution to the problem of the user entering
1317 2601 2 | <return> as the response to a prompt (null input record) and an empty
1318 2602 2 | or depleted buffer which requires another Get.
1319 2603 2 | The algorithm:
1320 2604 2 | 1) Does LUB$A_BUF_PTR = LUB$A_BUF_END?
1321 2605 2 | T: The buffer is depleted - another Get is required.
1322 2606 2 | 2) Add one to LUB$A_BUF_PTR
1323 2607 2 | 3) Does LUB$A_BUF_PTR = LUB$A_BUF_END?
1324 2608 2 | T: Return the default value.
1325 2609 2 | 4) Scan for the next field.
1326 2610 2 |
1327 2611 2 |
1328 2612 2 | CCB [LUB$A_BUF_PTR] = .CCB [RAB$L_RBF] - 1;
1329 2613 2 | CCB [LUB$A_BUF_END] = .CCB [RAB$L_RBF] + .CCB [RAB$W_RSZ];
1330 2614 2 | END
1331 2615 2 | ELSE
1332 2616 2 |
1333 2617 2 | +
1334 2618 2 | This is not a terminal device
1335 2619 2 | Signal insufficient data unless this is an ANSI INPUT.
1336 2620 2 | ANSI INPUT errors should cause the statement to be restarted.
1337 2621 2 | (This happens in BAS$$HANDLER).
1338 2622 2 |
1339 2623 2 |
1340 2624 2 | IF NOT .CCB [LUB$V_ANSI]
1341 2625 2 | THEN
1342 2626 2 | BAS$$SIGNAL (BAS$K_NOTENODAT)
1343 2627 2 | ELSE
1344 2628 2 | BAS$$SIGNAL_IO (BAS$K_TOOLITDAT);
1345 2629 2 |
1346 2630 2 |
1347 2631 2 | +
1348 2632 2 | Update the cursor position if this input was terminated by an escape.
1349 2633 2 | Save cursor position if last PRINT terminator was a semi or comma.
1350 2634 2 | Use BUDDY_PTR 'cuz we want to use the PRINT data base for channel 0
```

```
: 1351      2635 2      T_CCB = .CCB [LUB$A BUDDY PTR];
: 1352      2636 3      T_CCB [LUB$L_PRINT_POS] = TIF .CCB [RAB$W_STV0] EQL K_ESCAPE AND .T_CCB [LUB$V_FORM_CHAR] EQLU 1
: 1353      2637 3          THEN .CCB [RAB$W_RSZ] + .T_CCB [LUB$L_PRINT_POS] + 1
: 1354      2638 2          ELSE 0);
: 1355      2639 2
: 1356      2640 2      !+
: 1357      2641 2      ! Set RECOUNT to the number of bytes read
: 1358      2642 2      ! If the file is a terminal format file, then RECOUNT has to be
: 1359      2643 2      ! adjusted for the carriage control terminator.
: 1360      2644 2      !-
: 1361      2645 2
: 1362      2646 3      RECOUNT = .CCB [RAB$W_RSZ] + (IF .CCB [LUB$V_TERM_FOR] THEN SELECTONFU .CCB [RAB$W_STV0] OF
: 1363      2647 3          SET
: 1364      2648 3          [K_ESCAPE] : .CCB [RAB$W_STV2];
: 1365      2649 3          [K_CR] : 2;
: 1366      2650 3          [OTHERWISE] : 0;
: 1367      2651 2          TES ELSE 0);
: 1368      2652 2      RETURN 1;
: 1369      2653 1      END;
```

! End of BAS\$\$REC_RSL1

			52	DD	00000	BAS\$\$REC_RSL1::			
						PUSHL	R2		2521
4F	A1	AB	04	E0	00002	BBS	#4, -95(CCB), 4\$		2582
38	FE	AB	05	E1	00007	BBC	#5, -2(CCB), 3\$		
			5B	DD	0000C	PUSHL	CCB		2586
	00000000G	00	01	FB	0000E	CALLS	#1, SYSSGET		
		52	50	D0	00015	MOVL	R0, RMS_STATUS		
	00010651	8F	52	D1	00018	CMPL	RMS_STATUS, #67153		2588
			07	12	0001F	BNEQ	1\$		
	00000000G	00	00	FB	00021	CALLS	#0, BAS\$\$SIGNAL_CTRL		2590
		07	52	E8	00028	BLBS	RMS_STATUS, 2\$		2592
			7E	D4	0002B	CLRL	-(SP)		2594
	0000V	CF	01	FB	0002D	CALLS	#1, GET_ERROR		
B0	AB	28	01	C3	00032	SUBL3	#1, 40(CCB), -80(CCB)		2612
		50	22	AB	3C	MOVZWL	34(CCB), R0		2613
	B4	AB	28	BB40	9E	MOVAB	@40(CCB)[R0], -76(CCB)		
			1D	11	00042	BRB	5\$		2582
0D	A1	AB	04	E0	00044	BBS	#4, -95(CCB), 4\$		2624
		7E	00G	8F	9A	MOVZBL	#BAS\$K_NOTENODAT, -(SP)		2626
	00000000G	00	01	FB	0004D	CALLS	#1, BAS\$\$SIGNAL		
			0B	11	00054	BRB	5\$		
		7E	00G	8F	9A	MOVZBL	#BAS\$K_TOOLITDAT, -(SP)		2628
	00000000G	00	01	FB	0005A	CALLS	#1, BAS\$\$SIGNAL_10		
		51	B8	AB	D0	MOVL	-72(CCB), T_CCB		2635
		52	0C	AB	3C	MOVZWL	12(CCB), R2		2636
		1B	52	B1	00069	CMPL	R2, #27		
			11	12	0006C	BNEQ	6\$		
0C	FE	A1	02	E1	0006E	BBC	#2, -2(T_CCB), 6\$		
		50	22	AB	3C	MOVZWL	34(CCB), R0		2637
		50	C8	A1	C0	ADDL2	-56(T_CCB), R0		
			50	D6	0007B	INCL	R0		
			02	11	0007D	BRB	7\$		
			50	D4	0007F	CLRL	R0		2636

; 1370 2654 1


```
1372 2655 1 GLOBAL ROUTINE BASS$REC_MIN1          ! MAT Input element transmitter
1373 2656 1 : JSB_REC1 =
1374 2657 1
1375 2658 1
1376 2659 1 ++
1377 2660 1 FUNCTIONAL DESCRIPTION:
1378 2661 1     BASS$REC_MIN1 reads one record and checks for a continuation character.
1379 2662 1     Then return start and end+1 of user
1380 2663 1     part of record to be processed as input.
1381 2664 1
1382 2665 1 FORMAL PARAMETERS:
1383 2666 1
1384 2667 1     NONE
1385 2668 1
1386 2669 1 IMPLICIT INPUTS:
1387 2670 1
1388 2671 1     LUB$W_RBUF_SIZE      Size of record buffer allocated in OPEN.
1389 2672 1     LUB$A_RBUF_ADR      Address of record buffer from OPEN.
1390 2673 1     LUB$V_TERM_DEV     flag indicating a terminal device.
1391 2674 1     RAB$L_RBF        Pointer to buffer
1392 2675 1     RAB$W_RSZ        buffer size
1393 2676 1
1394 2677 1 IMPLICIT OUTPUTS:
1395 2678 1
1396 2679 1     RECOUNT            Own storage for RECOUNT function.
1397 2680 1     LUB$A_BUF_PTR      points to first char of user part of
1398 2681 1                     record buffer.
1399 2682 1     LUB$A_BUF_END      points to end+1 of user part of
1400 2683 1                     record buffer.
1401 2684 1
1402 2685 1 ROUTINE VALUE:
1403 2686 1
1404 2687 1     NONE
1405 2688 1
1406 2689 1 SIDE EFFECTS:
1407 2690 1
1408 2691 1     Reads next record from file on this logical unit.
1409 2692 1     SIGNALs any resultant RMS errors.
1410 2693 1 --
1411 2694 1
1412 2695 2 BEGIN
1413 2696 2
1414 2697 2 EXTERNAL REGISTER
1415 2698 2     (CB : REF BLOCK [, BYTE]);
1416 2699 2
1417 2700 2 LITERAL
1418 2701 2     K_ESCAPE = %X'1B',
1419 2702 2     K_CR = %X'0D';
1420 2703 2
1421 2704 2 LOCAL
1422 2705 2     RMS_STATUS,
1423 2706 2     T (CB : REF BLOCK [, BYTE],
1424 2707 2     STATUS;
1425 2708 2
1426 2709 2
1427 2710 2
1428 2711 2 !+
                                     ! Return status to UDF of whether
                                     ! to keep reading
```

```
1429 2712 2 ! Read record into buffer using RMS and check for errors and a continuation character
1430 2713 2 ! Signal any RMS errors directly.
1431 2714 2
1432 2715 2
1433 2716 2 IF .CCB [ISBSV_MAT_CONT]
1434 2717 2 THEN
1435 2718 2 BEGIN
1436 2719 2
1437 2720 2 RMS_STATUS = $GET (RAB = .CCB);
1438 2721 2
1439 2722 2 IF .RMS_STATUS EQL RMSS_CONTROLC
1440 2723 2 THEN
1441 2724 2 BAS$$SIGNAL_CTRLC ();
1442 2725 2
1443 2726 2 IF NOT .RMS_STATUS
1444 2727 2 THEN
1445 2728 2 GET_ERROR (K_STOP);
1446 2729 2
1447 2730 2
1448 2731 2 +
1449 2732 2 ! Return start-1 and end+1 address of record just read
1450 2733 2 ! LUBSA_BUF_PTR is set to the beginning-1 of the buffer only for BASIC
1451 2734 2 ! Input. This is seen as a solution to the problem of the user entering
1452 2735 2 ! <return> as the response to a prompt (null input record) and an empty
1453 2736 2 ! or depleted buffer which requires another Get.
1454 2737 2 ! The algorithm:
1455 2738 2 ! 1) Does LUBSA_BUF_PTR = LUBSA_BUF_END?
1456 2739 2 ! T: The buffer is depleted - another Get is required.
1457 2740 2 ! 2) Add one to LUBSA_BUF_PTR
1458 2741 2 ! 3) Does LUBSA_BUF_PTR = LUBSA_BUF_END?
1459 2742 2 ! T: Return the default value.
1460 2743 2 ! 4) Scan for the next field.
1461 2744 2
1462 2745 2
1463 2746 2 CCB [LUBSA_BUF_PTR] = .CCB [RABSL_RBF] - 1;
1464 2747 2 CCB [LUBSA_BUF_END] = .CCB [RABSL_RBF] + .CCB [RABSW_RSZ];
1465 2748 2
1466 2749 2
1467 2750 2 +
1468 2751 2 ! Check for an '8' as the last character of the record. If it is there,
1469 2752 2 ! it is a continuation character and signifies that there is more data to
1470 2753 2 ! come in the next record.
1471 2754 2
1472 2755 2 IF .(!.CCB [LUBSA_BUF_END] - 1) < 0, 8> EQLU K_MAT_CONT_CHAR
1473 2756 2 THEN
1474 2757 2 BEGIN
1475 2758 2 CCB [LUBSA_BUF_END] = .CCB [LUBSA_BUF_END] - 1;
1476 2759 2 CCB [ISBSV_MAT_CONT] = 1;
1477 2760 2 END
1478 2761 2 ELSE
1479 2762 2 CCB [ISBSV_MAT_CONT] = 0;
1480 2763 2
1481 2764 2
1482 2765 2 +
1483 2766 2 ! Update the cursor position if this input was terminated by an escape.
1484 2767 2 ! Save the cursor position if last PRINT terminator was a semi or comma.
1485 2768 2 ! Use BUDDY_PTR 'cuz we want to use the PRINT data base for channel 0
```



```

1486      2769 3      T_CCB = .CCB [LUB$A BUDDY_PTR];
1487      2770 4      T_CCB [LUB$L_PRINT_POS] = -(IF .CCB [RAB$W_STV0] EQL K_ESCAPE AND .T_CCB [LUB$V_FORM_CHAR] EQLU 1
1488      2771 4      THEN .CCB [RAB$W_RSZ] + .T_CCB [LUB$L_PRINT_POS] + 1
1489      2772 3      ELSE 0);
1490      2773 3
1491      2774 3
1492      2775 3      ! Set RECOUNT to the number of bytes read
1493      2776 3      ! If the file is a terminal format file, then RECOUNT has to be
1494      2777 3      ! adjusted for the carriage control terminator.
1495      2778 3
1496      2779 3
1497      2780 4      RECOUNT = .CCB [RAB$W_RSZ] + (IF .CCB [LUB$V_ERM_FOR] THEN SELECTONEU .CCB [RAB$W_STV0] OF
1498      2781 4      SET
1499      2782 4      [K_ESCAPE] : .CCB [RAB$W_STV2];
1500      2783 4      [K_CR] : 2;
1501      2784 4      [OTHERWISE] : 0;
1502      2785 3      TES ELSE 0);
1503      2786 3      STATUS = 1;
1504      2787 3      END
1505      2788 2      ELSE
1506      2789 2      STATUS = 0;
1507      2790 2
1508      2791 2      RETURN .STATUS;
1509      2792 1      END;

```

! End of BASS\$REC_MIN1

```

52 DD 00000 BASS$REC_MIN1::
03      97 AB      01 E0 00002      PUSHL R2      2655
009E 31 00007      BBS #1, -105(CCB), 1$      2716
5B DD 0000A 1$:      BRW 11$
01 FB 0000C      PUSHL CCB      2720
50 D0 00013      CALLS #1, SYSSGET
52 D1 00016      MOVL R0, RMS STATUS
07 12 0001D      CMPL RMS STATUS, #67153      2722
00 FB 0001F      BNEQ 2$
52 E8 00026 2$:      CALLS #0, BASS$SIGNAL_CTRL
7E D4 00029      BLBS RMS STATUS, 3$      2726
01 FB 0002B      CLRL -(SP)      2728
01 C3 00030 3$:      CALLS #1, GET ERROR
22 AB 3C 00036      SUBL3 #1, 40(CCB), -80(CCB)      2746
28 BB40 9E 0003A      MOVZWL 34(CCB), R0      2747
B4 AB D0 00040      MOVAB @40(CCB)[R0], -76(CCB)
FF A0 91 00044      MOVL -76(CCB), R0      2755
09 12 00048      CMPB -1(R0), #38
B4 AB D7 0004A      BNEQ 4$
02 88 0004D      DECL -76(CCB)      2758
04 11 00051      BISB2 #2, -105(CCB)      2759
97 AB      02 8A 00053 4$:      BRB 5$      2755
50 BB AB D0 00057 5$:      BICB2 #2, -105(CCB)      2762
52 OC AB 3C 0005B      MOVL -72(CCB), T_CCB      2769
1B 52 B1 0005F      MOVZWL 12(CCB), R2      2770
OC FE A0      11 12 00062      CMPW R2, #27
02 E1 00064      BNEQ 6$
      BBS #2, -2(T_CCB), 6$

```

		51	22	AB	3C	00069	MOVZWL	34(CCB), R1	2771
		51	C8	A0	C0	0006D	ADDL2	-56(T_CCB), R1	
				51	D6	00071	INCL	R1	
				02	11	00073	BRB	7\$	
				51	D4	00075	6\$: CLRL	R1	2770
				51	D0	00077	7\$: MOVL	R1, -56(T_CCB)	
15	C8	A0		04	E1	0007B	BBC	#4, -2(CCB), 9\$	2780
	FE	AB		52	B1	0C080	CMPW	R2, #27	2782
		1B		06	12	00083	BNEQ	8\$	
		50	0E	AB	3C	00085	MOVZWL	14(CCB), R0	
				0C	11	00089	BRB	10\$	
		0D		52	B1	0008B	8\$: CMPW	R2, #13	2783
				05	12	0008E	BNEQ	9\$	
		50		02	D0	00090	MOVL	#2, R0	
				02	11	00093	BRB	10\$	
				50	D4	00095	9\$: CLRL	R0	2780
00000000'	EF	51	22	AB	3C	00097	10\$: MOVZWL	34(CCB), R1	
		50		51	C1	0009B	ADDL3	R1, R0, RECOUNT	
		50		01	D0	000A3	MOVL	#1, STATUS	2786
				02	11	000A6	BRB	12\$	2716
				50	D4	000A8	11\$: CLRL	STATUS	2789
				04	BA	000AA	12\$: POPR	#M<R2>	2792
				05	000AC		RSB		

; Routine Size: 173 bytes, Routine Base: _BAS\$CODE + 03DF

; 1510 2793 1

```

: 1512      2794 1 GLOBAL ROUTINE BAS$$REC_RSL9          ! Read IO_END
: 1513      2795 1   : JSB_REC9 NOVALUE =
: 1514      2796 1
: 1515      2797 1   ++
: 1516      2798 1   FUNCTIONAL DESCRIPTION:
: 1517      2799 1
: 1518      2800 1       BAS$$REC_RSL9 is a no-op!
: 1519      2801 1
: 1520      2802 1   FORMAL PARAMETERS:
: 1521      2803 1
: 1522      2804 1       NONE
: 1523      2805 1
: 1524      2806 1   IMPLICIT INPUTS:
: 1525      2807 1
: 1526      2808 1       NONE
: 1527      2809 1
: 1528      2810 1   IMPLICIT OUTPUTS:
: 1529      2811 1
: 1530      2812 1   ROUTINE VALUE:
: 1531      2813 1
: 1532      2814 1       NONE
: 1533      2815 1
: 1534      2816 1   SIDE EFFECTS:
: 1535      2817 1
: 1536      2818 1   --
: 1537      2819 1
: 1538      2820 2   BEGIN
: 1539      2821 2   RETURN;
: 1540      2822 1   END;                                ! End of BAS$$_REC_RSL9

```

05 00000 BAS\$\$REC_RSL9::
RSB

; 2822

; Routine Size: 1 bytes, Routine Base: _BAS\$CODE + 048C

; 1541 2823 1

```

: 1543      2824 1 GLOBAL ROUTINE BAS$$REC_MIN9      ! MAT Input IO_END
: 1544      2825 1   : JSB_REC9 NOVALUE =
: 1545      2826 1
: 1546      2827 1
: 1547      2828 1 ++
: 1548      2829 1 FUNCTIONAL DESCRIPTION:
: 1549      2830 1     BAS$$REC_RSL9 is a no-op!
: 1550      2831 1
: 1551      2832 1 FORMAL PARAMETERS:
: 1552      2833 1
: 1553      2834 1     NONE
: 1554      2835 1
: 1555      2836 1 IMPLICIT INPUTS:
: 1556      2837 1
: 1557      2838 1     NONE
: 1558      2839 1
: 1559      2840 1 IMPLICIT OUTPUTS:
: 1560      2841 1
: 1561      2842 1 ROUTINE VALUE:
: 1562      2843 1
: 1563      2844 1     NONE
: 1564      2845 1
: 1565      2846 1 SIDE EFFECTS:
: 1566      2847 1
: 1567      2848 1 --
: 1568      2849 1
: 1569      2850 2 BEGIN
: 1570      2851 2 RETURN;
: 1571      2852 1 END;

```

! End of BAS\$\$REC_MIN9

05 00000 BAS\$\$REC_MIN9:.
RSB

; 2852

; Routine Size: 1 bytes, Routine Base: _BAS\$CODE + 0480

; 1572 2853 1

```
1574 2854 1 GLOBAL ROUTINE BASS$REC_MLI1          ! MAT Linput element transmitter
1575 2855 1 : JSB_REC1 =
1576 2856 1
1577 2857 1 ++
1578 2858 1 FUNCTIONAL DESCRIPTION:
1579 2859 1
1580 2860 1     BASS$REC_MLI1 unconditionally reads one record. There s no
1581 2861 1     continuation character for MAT LINPUT.
1582 2862 1     Otherwise an error is signalled.
1583 2863 1     Then return start and end+1 of user
1584 2864 1     part of record to be processed as input.
1585 2865 1
1586 2866 1 FORMAL PARAMETERS:
1587 2867 1
1588 2868 1     NONE
1589 2869 1
1590 2870 1 IMPLICIT INPUTS:
1591 2871 1
1592 2872 1     LUB$W_RBUF_SIZE      Size of record buffer allocated in OPEN.
1593 2873 1     LUB$A_RBUF_ADR      Address of record buffer from OPEN.
1594 2874 1     RAB$L_RBF           Pointer to buffer
1595 2875 1     RAB$W_RSZ          buffer size
1596 2876 1
1597 2877 1 IMPLICIT OUTPUTS:
1598 2878 1
1599 2879 1     RECOUNT            Own storage for RECOUNT function.
1600 2880 1     LUB$A_BUF_PTR       points to first char of user part of
1601 2881 1                        record buffer.
1602 2882 1     LUB$A_BUF_END       points to end+1 of user part of
1603 2883 1                        record buffer.
1604 2884 1
1605 2885 1 ROUTINE VALUE:
1606 2886 1
1607 2887 1     NONE
1608 2888 1
1609 2889 1 SIDE EFFECTS:
1610 2890 1
1611 2891 1     Reads next record from file on this logical unit.
1612 2892 1     SIGNALs any resultant RMS errors.
1613 2893 1 --
1614 2894 1
1615 2895 2 BEGIN
1616 2896 2
1617 2897 2 EXTERNAL REGISTER
1618 2898 2     CCB : REF BLOCK [, BYTE];
1619 2899 2
1620 2900 2 LOCAL
1621 2901 2     RMS STATUS,
1622 2902 2     T_CCB : REF BLOCK [, BYTE];
1623 2903 2
1624 2904 2 LITERAL
1625 2905 2     K_ESCAPE = %X'1B',
1626 2906 2     K_CR = %X'0D';
1627 2907 2
1628 2908 2 ++
1629 2909 2 ! Read record into buffer using RMS and check for errors
1630 2910 2 ! Signal any RMS errors directly.
```

```
1631 2911 2 !-
1632 2912 2
1633 2913 2 RMS_STATUS = $GET (RAB = .CCB);
1634 2914 2
1635 2915 2 IF .RMS_STATUS EQL RMSS$CONTROL.C
1636 2916 2 THEN
1637 2917 2     BAS$$SIGNAL_CTRL_C ();
1638 2918 2
1639 2919 2 IF NOT .RMS_STATUS
1640 2920 2 THEN
1641 2921 2     GET_ERROR (K_STOP);
1642 2922 2
1643 2923 2 +
1644 2924 2 Return start-1 and end+1 address of record just read
1645 2925 2 LUB$A_BUF_PTR is set to the beginning-1 of the buffer only for BASIC
1646 2926 2 Input. This is seen as a solution to the problem of the user entering
1647 2927 2 <return> as the response to a prompt (null input record) and an empty
1648 2928 2 or depleted buffer which requires another Get.
1649 2929 2 The algorithm:
1650 2930 2 1) Does LUB$A_BUF_PTR = LUB$A_BUF_END?
1651 2931 2     T: The buffer is depleted - another Get is required.
1652 2932 2 2) Add one to LUB$A_BUF_PTR
1653 2933 2 3) Does LUB$A_BUF_PTR = LUB$A_BUF_END?
1654 2934 2     T: Return the default value.
1655 2935 2 4) Scan for the next field.
1656 2936 2
1657 2937 2 -
1658 2938 2     .CCB [LUB$A_BUF_PTR] = .CCB [RAB$L_RBF] - 1;
1659 2939 2     .CCB [LUB$A_BUF_END] = .CCB [RAB$L_RBF] + .CCB [RAB$W_RSZ];
1660 2940 2 +
1661 2941 2 Update the cursor position if this input was terminated by an escape.
1662 2942 2 Save the cursor position if last PRINT terminator was a semi or comma.
1663 2943 2 Use BUDDY_PTR 'cuz we want to use the PRINT data base for channel 0
1664 2944 2 -
1665 2945 2     T_CCB = .CCB [LUB$A_BUDDY_PTR];
1666 2946 2     T_CCB [LUB$L_PRINT_POS] = (IF .CCB [RAB$W_STV0] EQL K_ESCAPE AND .T_CCB [LUB$V_FORM_CHAR] EQL 1
1667 2947 2         THEN .CCB [RAB$W_RSZ] + .T_CCB [LUB$L_PRINT_POS] + 1
1668 2948 2         ELSE 0);
1669 2949 2 +
1670 2950 2 Set RECOUNT to the number of bytes read
1671 2951 2 If the file is a terminal format file, then RECOUNT has to be
1672 2952 2 adjusted for the carriage control terminator.
1673 2953 2 -
1674 2954 2     RECOUNT = .CCB [RAB$W_RSZ] + (IF .CCB [LUB$V_TERM_FOR] THEN SELECTONEU .CCB [RAB$W_STV0] OF
1675 2955 2         SET
1676 2956 2         [K_ESCAPE] : .CCB [RAB$W_STV2];
1677 2957 2         [K_CR] : 2;
1678 2958 2         [OTHERWISE] : 0;
1679 2959 2         TES ELSE 0);
1680 2960 2 RETURN 1
1681 2961 1 END;
```

! End of BAS\$\$REC_ML11

; 1682 2962 1

```
1684 2963 1 GLOBAL ROUTINE BASS$REC_WSLO ! Write list-directed
1685 2964 1 : JSB_RECO NOVALUE =
1686 2965 1
1687 2966 1 ++
1688 2967 1 FUNCTIONAL DESCRIPTION:
1689 2968 1
1690 2969 1 BASS$REC_WSLO prepares a record for list-directed output.
1691 2970 1 Then return start and end+1 of user
1692 2971 1 part of record to be processed.
1693 2972 1
1694 2973 1 FORMAL PARAMETERS:
1695 2974 1
1696 2975 1 NONE
1697 2976 1
1698 2977 1 IMPLICIT INPUTS:
1699 2978 1
1700 2979 1 LUB$W_RBUF_SIZE Size (bytes) allocated for record buffer at OPEN.
1701 2980 1 LUB$A_RBUF_ADR Address of record buffer allocated at OPEN
1702 2981 1 LUB$V_FIXED 1 if fixed-length records
1703 2982 1 LUB$V_FORM_CHAR Indicates that the last element transmitter ended
1704 2983 1 in a comma or semicolon format char.
1705 2984 1 LUB$V_FORCIBLE Indicates a forcible device
1706 2985 1 LUB$V_CCO Cancel control 0
1707 2986 1
1708 2987 1 IMPLICIT OUTPUTS:
1709 2988 1
1710 2989 1 LUB$B_BAS_VFC1 'Pre' carriage control
1711 2990 1 LUB$B_BAS_VFC2 'Post' carriage control
1712 2991 1 LUB$A_BUF_PTR pointer to next byte of buffer
1713 2992 1 LUB$A_BUF_END pointer to byte following the buffer
1714 2993 1 RAB$V_CCO Cancel control 0
1715 2994 1
1716 2995 1 ROUTINE VALUE:
1717 2996 1
1718 2997 1 NONE
1719 2998 1
1720 2999 1 SIDE EFFECTS:
1721 3000 1
1722 3001 1 --
1723 3002 1
1724 3003 2 BEGIN
1725 3004 2
1726 3005 2 EXTERNAL REGISTER
1727 3006 2 CCB : REF BLOCK [, BYTE];
1728 3007 2
1729 3008 2 ++
1730 3009 2 Copy the current status of the cancel-control-o bit in the LUB
1731 3010 2 (possibly set by RCTRL0) into the RAB, and clear it from the
1732 3011 2 LUB. The net effect of this is that if the bit is set in the
1733 3012 2 LUB, then the CANCTRL0 modifier will be applied to this write
1734 3013 2 operation only.
1735 3014 2
1736 3015 2
1737 3016 2 CCB [RAB$V_CCO] = CCB [LUB$V_CCO];
1738 3017 2 CCB [LUB$V_CCO] = 0;
1739 3018 2
1740 3019 2 !+
```



```
: 1741      3020  2  ! If there is a format character pending and this is not a forcible
: 1742      3021  2  ! device, then don't change the buffer pointers. The PUT will be done when
: 1743      3022  2  ! there is no format character pending.
: 1744      3023  2  !-
: 1745      3024  2
: 1746      3025  2  IF .CCB [LUB$V_FORM_CHAR] AND NOT .CCB [LUB$V_FORCIBLE] THEN RETURN;
: 1747      3026  2
: 1748      3027  2  !+
: 1749      3028  2  ! If the last statement did not end with a format character,
: 1750      3029  2  ! then put a line feed into the 'pre' carriage control
: 1751      3030  2  ! Unconditionally set the 'post' carriage control to null
: 1752      3031  2  !-
: 1753      3032  2
: 1754      3033  2  CCB [LUB$B_BAS_VFC1] = (IF .CCB [LUB$V_FORM_CHAR] THEN BASSK_NULL ELSE BASSK_LF);
: 1755      3034  2  CCB [LUB$B_BAS_VFC2] = BASSK_NULL;
: 1756      3035  2
: 1757      3036  2  !+
: 1758      3037  2  ! If the buffer is dirty, then this is recursive I/O and we want to
: 1759      3038  2  ! concatenate this record. So leave the buffer pointers alone. Otherwise
: 1760      3039  2  ! return the buffer pointers initialized for another statement
: 1761      3040  2  !-
: 1762      3041  2
: 1763      3042  2  IF NOT .CCB [LUB$V_OUTBUF_DR]
: 1764      3043  2  THEN
: 1765      3044  3      BEGIN
: 1766      3045  3          CCB [LUB$A_BUF_PTR] = .CCB [LUB$A_RBUF_ADR];
: 1767      3046  3          CCB [LUB$A_BUF_END] = .CCB [LUB$A_RBUF_ADR] + .CCB [LUB$W_RBUF_SIZE];
: 1768      3047  2      END;
: 1769      3048  2
: 1770      3049  2  RETURN;
: 1771      3050  1  END;

! END OF BAS$$REC_WSL0
```

50	A0	AB	01	02	EF 00000	BAS\$\$REC_WSL0::			
						EXTZV	#2, #1, -96(CCB), R0	: 3016	
07	AB	01	07	50	F0 00006	INSV	R0, #7, #1, 7(CCB)		
	A0	AB		04	8A 0000C	BICB2	#4, -96(CCB)	: 3017	
	0E	FE	AB	02	E1 00010	BBC	#2, -2(CCB), 1\$	: 3025	
	24	FE	AB	06	E1 00015	BBC	#6, -2(CCB), 3\$		
	04	FE	AB	02	E1 0001A	BBC	#2, -2(CCB), 1\$	: 3033	
				50	D4 0001F	CLRL	R0		
				03	11 00021	BRB	2\$		
		50		01	D0 00023	1\$:	MOVL	#1, R0	
	DA	AB		50	9B 00026	2\$:	MOVZBW	R0, -38(CCB)	
	0F	FE	AB	03	E0 0002A	BBS	#3, -2(CCB), 3\$	: 3042	
	B0	AB	EC	AB	D0 0002F	MOVL	-20(CCB), -80(CCB)	: 3045	
		50	D2	AB	3C 00034	MOVZWL	-46(CCB), R0	: 3046	
	B4	AB	EC	BB40	9E 00038	MOVAB	a-20(CCB)[R0], -76(CCB)		
				05	0003E	3\$:	RSB	: 3050	

; Routine Size: 63 bytes, Routine Base: _BAS\$CODE + 0518

; 1772 3051 1

```

: 1774 3052 1 GLOBAL ROUTINE BAS$$REC_WSL1 (      ! Write list-directed
: 1775 3053 1   CARRIAGE_CTRL) : JSB_REC_WSL1 NOVALUE =      ! Called from BAS$$DO_WRITE
: 1776 3054 1
: 1777 3055 1 ++
: 1778 3056 1 FUNCTIONAL DESCRIPTION:
: 1779 3057 1
: 1780 3058 1   Write one list-directed record and initialize for the next
: 1781 3059 1   BAS$$REC_WSL1 writes one output buffer and then
: 1782 3060 1   initializes the output buffer and returns start and end+1 of user
: 1783 3061 1   part of record buffer to be filled by caller.
: 1784 3062 1   If this routine is called because the buffer overflowed then the 'post'
: 1785 3063 1   carriage control should be null. If this routine is called because the
: 1786 3064 1   margin overflowed, then the 'post' carriage control should be 'CR'.
: 1787 3065 1
: 1788 3066 1 FORMAL PARAMETERS:
: 1789 3067 1
: 1790 3068 1   CARRIAGE_CTRL.rlu.v      carriage control for the record
: 1791 3069 1
: 1792 3070 1 IMPLICIT INPUTS:
: 1793 3071 1
: 1794 3072 1   LUB$W_RBUF_SIZE      Size (bytes) allocated for record buffer at OPEN.
: 1795 3073 1   LUB$A_RBUF_ADR      Address of record buffer allocated at OPEN
: 1796 3074 1   LUB$A_BUF_PTR      Pointer to next byte in user buffer.
: 1797 3075 1   RAB$L_RBF      Pointer to user buffer
: 1798 3076 1
: 1799 3077 1 IMPLICIT OUTPUTS:
: 1800 3078 1
: 1801 3079 1   LUB$B_BAS_VFC1      'Pre' carriage control
: 1802 3080 1   LUB$B_BAS_VFC2      'Post' carriage control
: 1803 3081 1   LUB$A_BUF_PTR      Pointer to start of user part of record buffer
: 1804 3082 1   LUB$A_BUF_END      Pointer to end+1 of user part of record buffer
: 1805 3083 1   LUB$V_OUTBUF_DR      Indicates valid data in the output buffer
: 1806 3084 1   RAB$W_RSZ      Size of user buffer
: 1807 3085 1
: 1808 3086 1 ROUTINE VALUE:
: 1809 3087 1
: 1810 3088 1   NONE
: 1811 3089 1
: 1812 3090 1 SIDE EFFECTS:
: 1813 3091 1
: 1814 3092 1   Writes one RMS sequential record.
: 1815 3093 1   SIGNALs BAS$K_FATSYSIO on PUT error.
: 1816 3094 1 --
: 1817 3095 1
: 1818 3096 2 BEGIN
: 1819 3097 2
: 1820 3098 2 EXTERNAL REGISTER
: 1821 3099 2   CCB = 11 : REF BLOCK [, BYTE];
: 1822 3100 2
: 1823 3101 2 LITERAL
: 1824 3102 2   K_NO_CR = 2;
: 1825 3103 2
: 1826 3104 2 LOCAL
: 1827 3105 2   RMS_STATUS;
: 1828 3106 2
: 1829 3107 2 !+
: 1830 3108 2 ! Set 'post' carriage control to CR or NULL depending on whether the margin
```

```
1831 3109 2 | overflowed or the buffer overflowed.
1832 3110 2 | If this is a file, the carriage control is ignored and a record is PUT.
1833 3111 2 |
1834 3112 2 | CCB [LUB$B_BAS_VFC2] = (IF .CARRIAGE_CTRL EQL BAS$K_BUF_EXC THEN BAS$K_NULL ELSE BAS$K_CR);
1835 3113 2 |
1836 3114 2 | +
1837 3115 2 | | perform the record write.
1838 3116 2 | | Set recordsize to actual length of record
1839 3117 2 | |
1840 3118 2 | -
1841 3119 2 | CCB [RAB$W_RSZ] = .CCB [LUB$A_BUF_PTR] - .CCB [LUB$A_BUF_BEG];
1842 3120 2 |
1843 3121 2 | +
1844 3122 2 | | Output buffer to RMS and check for errors
1845 3123 2 | | If errors, SIGNAL_STO
1846 3124 2 | |
1847 3125 2 | -
1848 3126 2 | CCB [RAB$L_RBF] = .CCB [LUB$A_BUF_BEG];
1849 3127 2 | CCB [LUB$V_OUTBUF_DR] = 0;
1850 3128 2 |
1851 3129 2 | RMS_STATUS = $PUT (RAB = .CCB);
1852 3130 2 |
1853 3131 2 | IF .RMS_STATUS EQL RM$S_CONTROLC
1854 3132 2 | THEN
1855 3133 2 | | BAS$$SIGNAL_CTRLC ();
1856 3134 2 |
1857 3135 2 | IF NOT .RMS_STATUS
1858 3136 2 | THEN
1859 3137 2 | | PUT_ERROR (K_STOP);
1860 3138 2 |
1861 3139 2 | +
1862 3140 2 | | Set the 'pre' carriage control to LF if CARRIAGE_CTRL warrants it.
1863 3141 2 | | Set the 'post' carriage control to null.
1864 3142 2 | |
1865 3143 2 | -
1866 3144 2 | CCB [LUB$B_BAS_VFC1] = (IF .CARRIAGE_CTRL EQL BAS$K_BUF_EXC THEN BAS$K_NULL ELSE BAS$K_LF);
1867 3145 2 | CCB [LUB$B_BAS_VFC2] = BAS$K_NULL;
1868 3146 2 |
1869 3147 2 | +
1870 3148 2 | | Initialize record buffer for another list-directed write
1871 3149 2 | | return record buffer pointers to caller
1872 3150 2 | |
1873 3151 2 | -
1874 3152 2 | CCB [LUB$A_BUF_PTR] = .CCB [LUB$A_RBUF_ADR];
1875 3153 2 | CCB [LUB$A_BUF_END] = .CCB [LUB$A_RBUF_ADR] + .CCB [LUB$W_RBUF_SIZE];
1876 3154 2 | RETURN;
1877 3155 1 | END;
! End of routine - BAS$$UDF_WSL1
```

```
0C BB 00000 BAS$$REC WSL1::
08 53 D4 00002 PUSHM #M<R2,R3>
50 D1 00004 CLRL R3
06 12 00007 CMPL CARRIAGE_CTRL, #8
BNEQ 15
```

```
: 3052
: 3112
:
```

			53	D6	00009	INCL	R3		
			50	D4	0000B	CLRL	R0		
			04	11	0000D	BRB	2\$		
		50	8D	8F	9A 0000F	1\$:	MOVZBL	#141, R0	
22	AB	DB	AB	50	90 00013	2\$:	MOVB	R0, -37(CCB)	
		B0	AB	BC	A3 00017		SUBW3	-68(CCB), -80(CCB), 34(CCB)	3119
		28	AB	BC	AB 0001E		MOVL	-68(CCB), 40(CCB)	3126
		FE	AB		08 8A 00023		BICB2	#8, -2(CCB)	3127
					5B DD 00027		PUSHL	CCB	3129
		00000000G	00		01 FB 00029		CALLS	#1, SYSSPUT	
			52		50 D0 00030		MOVL	R0, RMS_STATUS	
		00010651	8F		52 D1 00033		CMPL	RMS_STATUS, #67153	3131
					07 12 0003A		BNEQ	3\$	
		00000000G	00		00 FB 0003C		CALLS	#0, BAS\$\$SIGNAL_CTRL	3133
			07		52 E8 00043	3\$:	BLBS	RMS_STATUS, 4\$	3135
					7E D4 00046		CLRL	-(SP)	3137
		0000V	CF		01 FB 00048		CALLS	#1, PUT_ERROR	
			04		53 E9 0004D	4\$:	BLBC	R3, 5\$	3144
					50 D4 00050		CLRL	R0	
					03 11 00052		BRB	6\$	
			50		01 D0 00054	5\$:	MOVL	#1, R0	
		DA	AB		50 9B 00057	6\$:	MOVZBW	R0, -38(CCB)	
		B0	AB	EC	AB D0 0005B		MOVL	-20(CCB), -80(CCB)	3152
			50	D2	AB 3C 00060		MOVZWL	-46(CCB), R0	3153
		B4	AB	EC	BB40 9E 00064		MOVAB	@-20(CCB)[R0], -76(CCB)	
					0C BA 0006A		POPR	#*M<R2,R3>	3155
					05 0006C		RSB		

; Routine Size: 109 bytes, Routine Base: _BAS\$CODE + 0557

; 1878 3156 1

```
1880 3157 1 GLOBAL ROUTINE BASS$REC_RMFO ! Initialize read memory formatted
1881 3158 1 : JSB_RECO NOVALUE =
1882 3159 1
1883 3160 1 !+
1884 3161 1 FUNCTIONAL DESCRIPTION:
1885 3162 1
1886 3163 1 Pick up pointer to last major frame from ISB and initialize BUF_BEG,
1887 3164 1 BUF_PTR, and BUF_END to the values for the data area found in the
1888 3165 1 frame.
1889 3166 1
1890 3167 1 FORMAL PARAMETERS:
1891 3168 1
1892 3169 1 NONE
1893 3170 1
1894 3171 1 IMPLICIT INPUTS:
1895 3172 1
1896 3173 1 ISB$A_MAJ_F_PTR pointer to last Basic major frame
1897 3174 1
1898 3175 1 IMPLICIT OUTPUTS:
1899 3176 1
1900 3177 1 ROUTINE VALUE:
1901 3178 1
1902 3179 1 NONE
1903 3180 1
1904 3181 1 SIDE EFFECTS:
1905 3182 1
1906 3183 1 NONE
1907 3184 1
1908 3185 1 --
1909 3186 1
1910 3187 2 BEGIN
1911 3188 2
1912 3189 2 EXTERNAL REGISTER
1913 3190 2 CCB = K_CCB_REG : REF BLOCK [, BYTE];
1914 3191 2
1915 3192 2 LOCAL
1916 3193 2 BMF : REF BLOCK [0, BYTE] FIELD (BSF$MAJOR_FRAME);
1917 3194 2
1918 3195 2 !+
1919 3196 2 Reach back into the last major frame by picking up the value of R11 stored
1920 3197 2 in the ISB. Initialize BUF_PTR, BUF_END, BUF_BEG so that this will look
1921 3198 2 like a vanilla INPUT.
1922 3199 2 !-
1923 3200 2
1924 3201 2 BMF = .CCB [ISB$A_MAJ_F_PTR];
1925 3202 2 !+
1926 3203 2 If this cell is zero, then there was no DATA statement and an error should be
1927 3204 2 signalled.
1928 3205 2 !-
1929 3206 2
1930 3207 2 IF .BMF [BSF$A_CUR_DTA] EQLA 0 THEN BASS$STOP_IO (BASS$K_OUTOF_DAT);
1931 3208 2
1932 3209 2 CCB [LUB$A_BUF_BEG] = .BMF [BSF$A_CUR_DTA];
1933 3210 2 CCB [LUB$A_BUF_END] = .BMF [BSF$A_END_DTA];
1934 3211 2
1935 3212 2 !+
1936 3213 2 Subtract one from CUR_DATA for INPUT element transmitter compatibility.
```

BAS\$\$REC_PROC
1-095

F 8
16-Sep-1984 01:01:12
14-Sep-1984 11:56:35

VAX-11 Bliss-32 V4.0-742
[BASRTL.SRC]BASRECPRO.B32;1

Page 52
(20)

```
: 1937      3214  2    !-
: 1938      3215  2
: 1939      3216  2    (CB [LUB$A_BUF_PTR] = .BMF [BSF$A_CUR_DTA] - 1;
: 1940      3217  2    RETURN;
: 1941      3218  1    END;
```

```
                                0C  BB 00000 BAS$$REC RMF0::
                                PUSH  #^M<R2,R3>
                                52  FF48 CB D0 00002      MOVL  -184(CCB), BMF
                                53  0087 C2 D0 00007      MOVL  135(BMF), R3
                                0B  12 0000C      BNEQ  1$
                                7E      00G  8F 9A 0000E      MOVZBL #BAS$K_OUTOF_DAT, -(SP)
000000000G 00      01 FB 00012      CALLS  #1, BAS$$STOP_IO
                                BC  AB      53 D0 00019 1$:   MOVL  R3, -68(CCB)
                                B4  AB      C2 D0 0001D      MOVL  135(BMF), -76(CCB)
                                B0  AB      FF A3 9E 00023      MOVAB  -1(R3), -80(CCB)
                                0C      BA 00028      POPR   #^M<R2,R3>
                                05 0002A      RSB
                                : 3157
                                : 3201
                                : 3207
                                :
                                :
                                : 3209
                                : 3210
                                : 3216
                                : 3218
                                :
```

: Routine Size: 43 bytes, Routine Base: _BAS\$CODE + 05C4

: 1942 3219 1


```
: 1944      3220 1 GLOBAL ROUTINE BAS$$REC_MRE1          ! Mat Read element transmitter
: 1945      3221 1   : JSB_REC1 =
: 1946      3222 1
: 1947      3223 1   ++
: 1948      3224 1   FUNCTIONAL DESCRIPTION:
: 1949      3225 1
: 1950      3226 1       Since MAT READ just takes as much input data as it can get, it will just
: 1951      3227 1       return a failure here because there is no more data.
: 1952      3228 1
: 1953      3229 1   FORMAL PARAMETERS:
: 1954      3230 1
: 1955      3231 1       NONE
: 1956      3232 1
: 1957      3233 1   IMPLICIT INPUTS:
: 1958      3234 1
: 1959      3235 1       NONE
: 1960      3236 1
: 1961      3237 1   IMPLICIT OUTPUTS:
: 1962      3238 1
: 1963      3239 1       NONE
: 1964      3240 1
: 1965      3241 1   ROUTINE VALUE:
: 1966      3242 1
: 1967      3243 1       Returns failure - out of data.
: 1968      3244 1
: 1969      3245 1   SIDE EFFECTS:
: 1970      3246 1
: 1971      3247 1       As a result of the failure being returned, the MAT READ will stop
: 1972      3248 1       filling the matrix.
: 1973      3249 1
: 1974      3250 1   --
: 1975      3251 1
: 1976      3252 2   BEGIN
: 1977      3253 2   RETURN 0
: 1978      3254 1   END;                                ! end of BAS$$REC_MRE1
```

```
50 D4 00000 BAS$$REC_MRE1::
      CLRL R0
05 00002      RSB
```

```
: 3253
: 3254
```

: Routine Size: 3 bytes, Routine Base: _BAS\$CODE + 05EF

: 1979 3255 1

```
: 1981      3256 1 GLOBAL ROUTINE BAS$$REC_RMF1          ! Read element transmitter
: 1982      3257 1   : JSB_REC1 NOVALUE =
: 1983      3258 1
: 1984      3259 1   ++
: 1985      3260 1 FUNCTIONAL DESCRIPTION:
: 1986      3261 1
: 1987      3262 1     BAS$$REC_RMF1 should not be called in normal processing and will signal
: 1988      3263 1     an error (BAS$K_OUTOF_DAT) if it is called.
: 1989      3264 1
: 1990      3265 1 FORMAL PARAMETERS:
: 1991      3266 1
: 1992      3267 1     NONE
: 1993      3268 1
: 1994      3269 1 IMPLICIT INPUTS:
: 1995      3270 1
: 1996      3271 1     NONE
: 1997      3272 1
: 1998      3273 1 IMPLICIT OUTPUTS:
: 1999      3274 1
: 2000      3275 1 ROUTINE VALUE:
: 2001      3276 1
: 2002      3277 1     NONE
: 2003      3278 1
: 2004      3279 1 SIDE EFFECTS:
: 2005      3280 1
: 2006      3281 1     Signal - BAS$K_OUTOF_DAT - Out of Data
: 2007      3282 1
: 2008      3283 1   --
: 2009      3284 1
: 2010      3285 2 BEGIN
: 2011      3286 2 BAS$$SIGNAL (BAS$K_OUTOF_DAT);
: 2012      3287 2 RETURN;
: 2013      3288 1 END;                                ! end of BAS$$REC_RMF1
```

```
              7E      00G 8F 9A 00000 BAS$$REC_RMF1::
              00000000G 00      01 FB 00004 MOVZBL #BAS$K_OUTOF_DAT, -(SP)
              05 0000B CALLS #1, BAS$$SIGNAL
              RSB
```

```
: 3286
: 3288
```

: Routine Size: 12 bytes, Routine Base: _BAS\$CODE + 05F2

: 2014 3289 1


```
: 2016      3290 1 GLOBAL ROUTINE BAS$$REC_RMF9          ! Read IO_END
: 2017      3291 1   : JSB_REC9 NOVALUE =
: 2018      3292 1
: 2019      3293 1
: 2020      3294 1   ++
: 2021      3295 1   FUNCTIONAL DESCRIPTION:
: 2022      3296 1       Update the current data pointer in the last Basic major frame
: 2023      3297 1
: 2024      3298 1   FORMAL PARAMETERS:
: 2025      3299 1
: 2026      3300 1       NONE
: 2027      3301 1
: 2028      3302 1   IMPLICIT INPUTS:
: 2029      3303 1
: 2030      3304 1       NONE
: 2031      3305 1
: 2032      3306 1   IMPLICIT OUTPUTS:
: 2033      3307 1
: 2034      3308 1   ROUTINE VALUE:
: 2035      3309 1
: 2036      3310 1       NONE
: 2037      3311 1
: 2038      3312 1   SIDE EFFECTS:
: 2039      3313 1
: 2040      3314 1   --
: 2041      3315 1
: 2042      3316 2   BEGIN
: 2043      3317 2
: 2044      3318 2   EXTERNAL REGISTER
: 2045      3319 2       CCB = K_CCB_REG : REF BLOCK [0, BYTE];
: 2046      3320 2
: 2047      3321 2   LOCAL
: 2048      3322 2       BMF : REF BLOCK [0, BYTE] FIELD (BSF$MAJOR_FRAME);
: 2049      3323 2
: 2050      3324 2   ++
: 2051      3325 2       Set the current data pointer in the frame to BUF_PTR + 1.
: 2052      3326 2       The one is added because Input initialize will subtract one from BUF_PTR.
: 2053      3327 2       This whole matter is explained in IO_BEG.
: 2054      3328 2   --
: 2055      3329 2
: 2056      3330 2   BMF = .CCB [ISB$A MAJ_F_PTR];
: 2057      3331 2   BMF [BSF$A_CUR_DTA] = -.CCB [LUB$A_BUF_PTR] + 1;
: 2058      3332 2   RETURN;
: 2059      3333 1   END;                                     ! End of routine BAS$$REC_RMF9
```

```
          50      FF48  CB  D0 00000 BAS$$REC_RMF9::
0087  C0      B0  AB          01  C1 00005      MOVL  -184(CCB), BMF      : 3330
          05 0000C      ADDL3  #1, -80(CCB), 135(BMF)      : 3331
          RSB                                     : 3333
```

; Routine Size: 13 bytes, Routine Base: _BAS\$CODE + 05FE

BAS\$\$REC_PROC
1-095

: 2060

3334 1

J 8
16-Sep-1984 01:01:12
14-Sep-1984 11:56:35

VAX-11 Bliss-32 V4.0-742
[BASRTL.SRC]BASRECPRO.B32;1

Page 56
(23)

```
2062 3335 1 GLOBAL ROUTINE BAS$REC_GSE ( ; GET (sequential) a record
2063 3336 1 FOREIGN_BUFFER, ;
2064 3337 1 LOCK_FLAGS ;
2065 3338 1 ) : JSB_DO_READ NOVALUE =
2066 3339 1
2067 3340 1 !+
2068 3341 1 FUNCTIONAL DESCRIPTION:
2069 3342 1
2070 3343 1 Read one record. Update RECOUNT if successful.
2071 3344 1 If a foreign buffer is specified, then change RAB$RBF to point to the
2072 3345 1 "foreign buffer". Otherwise, signal a fatal error.
2073 3346 1
2074 3347 1 FORMAL PARAMETERS:
2075 3348 1
2076 3349 1 FOREIGN_BUFFER.rl.v points to CB of foreign buffer or 0
2077 3350 1 LOCK_FLAGS.rlu.v bits to set in RAB ROP for manual
2078 3351 1 record locking (0 if none)
2079 3352 1 IMPLICIT INPUTS:
2080 3353 1
2081 3354 1 RAB$W_USZ User buffer size of foreign buffer
2082 3355 1 RAB$R_UBF Pointer to user buffer for foreign buffer
2083 3356 1 LUB$R_WAIT_TIME Wait time for next input
2084 3357 1 WAIT The module level OWN WAIT
2085 3358 1
2086 3359 1 IMPLICIT OUTPUTS:
2087 3360 1
2088 3361 1 RAB$R_RAC Record access field
2089 3362 1 RECOUNT Own storage for RECOUNT function.
2090 3363 1 RAB$R_RBF Record pointer in RAB.
2091 3364 1 RAB$W_RSZ Number of bytes read (stored in RECOUNT)
2092 3365 1
2093 3366 1 ROUTINE VALUE:
2094 3367 1
2095 3368 1 NONE
2096 3369 1
2097 3370 1 SIDE EFFECTS:
2098 3371 1
2099 3372 1 RAB$W_USZ and RAB$W_UBF are altered while this routine is running,
2100 3373 1 but are restored before exit.
2101 3374 1 Reads next record from file on this logical unit.
2102 3375 1 SIGNALs any RMS errors
2103 3376 1 --
2104 3377 1
2105 3378 2 BEGIN
2106 3379 2
2107 3380 2 EXTERNAL REGISTER
2108 3381 2 (CB : REF BLOCK [, BYTE]);
2109 3382 2
2110 3383 2 MAP
2111 3384 2 FOREIGN_BUFFER : REF BLOCK [, BYTE];
2112 3385 2
2113 3386 2 LOCAL
2114 3387 2 RMS_STATUS,
2115 3388 2 SAVE_USZ, ; Save the USZ
2116 3389 2 ACTUAL_RSZ, ; Actual record size
2117 3390 2 WAIT_TIME; ; Current wait time
2118 3391 2 !+
```

```
2119 3392 2 : Save USZ in case it is modified. It is faster to always
2120 3393 2 : save and restore it, since that eliminates the test for foreign
2121 3394 2 : buffers and single-character mode at the end of this routine.
2122 3395 2 :
2123 3396 2 :   SAVE_USZ = .CCB [RAB$W_USZ];
2124 3397 2 :
2125 3398 2 :   If a timeout has been specified, store information in the RAB to tell
2126 3399 2 :   RMS about it. If no timeout has been specified, clear the TMO bit
2127 3400 2 :   in case there was an earlier timeout specified.
2128 3401 2 :
2129 3402 2 :
2130 3403 2 :
2131 3404 2 :   If WAIT is zero then use the LUB's wait. This is to provide upward compatibility
2132 3405 2 :   , i.e. existing EXE's can run with the LUB wait value in V2.2.
2133 3406 2 :
2134 3407 2 :   WAIT_TIME = ( IF ( .WAIT EQL 0 ) THEN .CCB [ LUB$L_WAIT_TIME ] ELSE .WAIT );
2135 3408 2 :
2136 3409 2 :   IF (.WAIT_TIME EQL 0)
2137 3410 2 :   THEN
2138 3411 2 :     CCB [RAB$V_TMO] = 0
2139 3412 2 :   ELSE
2140 3413 2 :     BEGIN
2141 3414 2 :       CCB [RAB$B_TMO] = .WAIT_TIME;
2142 3415 2 :       CCB [RAB$V_TMO] = 1;
2143 3416 2 :     END;
2144 3417 2 :
2145 3418 2 :
2146 3419 2 :
2147 3420 2 :   Set the Read-no-echo RMS bit based on the user's last call to
2148 3421 2 :   ECHO or NOECHO.
2149 3422 2 :
2150 3423 2 :   CCB [RAB$V_RNE] = .CCB [LUB$V_NOECHO];
2151 3424 2 :
2152 3425 2 :   Set the record pointer field in the RAB to the user buffer. This is
2153 3426 2 :   done on each element transmission and not just at OPEN because of RMS
2154 3427 2 :   Locate mode.
2155 3428 2 :   Fill the input buffer with Nulls. Basic semantics require null fill if
2156 3429 2 :   the record read is shorter than the buffer.
2157 3430 2 :   Set the record access field in the RAB to sequential. Perform the GET.
2158 3431 2 :   If RMS returns a failure status, signal the error. If the GET is
2159 3432 2 :   successful, then update recount.
2160 3433 2 :
2161 3434 2 :
2162 3435 2 :   IF (.FOREIGN_BUFFER NEQA 0)
2163 3436 2 :   THEN
2164 3437 2 :     BEGIN
2165 3438 2 :
2166 3439 2 :     A foreign buffer was specified. Save off RAB$L_usz of the "file" channel
2167 3440 2 :     and then substitute the appropriate values from the foreign channel into
2168 3441 2 :     the file channel to make the record go directly into the foreign buffer.
2169 3442 2 :
2170 3443 2 :     CCB [RAB$W_USZ] = .FOREIGN_BUFFER [RAB$W_USZ];
2171 3444 2 :
2172 3445 2 :
2173 3446 2 :
2174 3447 2 :   If the user has called ONECHR, shrink the effective size of the
2175 3448 2 :   buffer to one character, so he will get characters one at a time.
```

```
2176 3449 2 | The user must call ONECHR before each GET, so we clear the ONECHR
2177 3450 2 | flag here.
2178 3451 2 | -
2179 3452 2 |
2180 3453 3 | IF (.CCB [LUB$V_ONECHR])
2181 3454 3 | THEN
2182 3455 3 | BEGIN
2183 3456 3 | CCB [LUB$V_ONECHR] = 0;
2184 3457 3 | CCB [RAB$W_USZ] = 1;
2185 3458 2 | END;
2186 3459 2 |
2187 3460 2 | CCB [RAB$B_RAC] = RAB$C_SEQ;
2188 3461 2 |
2189 3462 2 | +
2190 3463 2 | Set bits in the RAB ROP (careful not to turn off ULK).
2191 3464 2 | -
2192 3465 2 |
2193 3466 2 | CCB [RAB$L_ROP] = .CCB [RAB$L_ROP] OR .LOCK_FLAGS;
2194 3467 2 |
2195 3468 2 | RMS_STATUS = $GET (RAB = .CCB);
2196 3469 2 |
2197 3470 2 | IF .RMS_STATUS EQL RMS$_CTRLC
2198 3471 2 | THEN
2199 3472 2 | BAS$$SIGNAL_CTRLC ();
2200 3473 2 |
2201 3474 2 | IF NOT .RMS_STATUS
2202 3475 2 | THEN
2203 3476 3 | BEGIN
2204 3477 3 | +
2205 3478 3 | We cannot call GET_ERROR because we must restore UBF and USZ.
2206 3479 3 | -
2207 3480 3 |
2208 3481 3 | WHILE (.CCB [RAB$L_STS] EQL RMS$_RSA) DO
2209 3482 4 | BEGIN
2210 3483 4 | $WAIT (RAB = .CCB);
2211 3484 4 | $GET (RAB = .CCB);
2212 3485 3 | END;
2213 3486 3 |
2214 3487 2 | END;
2215 3488 2 |
2216 3489 2 | +
2217 3490 2 | Clear RAB ROP bits so that a subsequent I/O operation does not
2218 3491 2 | inherit them.
2219 3492 2 | -
2220 3493 2 |
2221 3494 2 | CCB [RAB$L_ROP] = .CCB [RAB$L_ROP] XOR .LOCK_FLAGS;
2222 3495 2 |
2223 3496 2 | +
2224 3497 2 | This actual record size may or may not change below. If the file is a
2225 3498 2 | terminal device then it will get terminators tacked on to the record read.
2226 3499 2 | -
2227 3500 2 |
2228 3501 2 | ACTUAL_RSZ = .CCB [RAB$W_RSZ];
2229 3502 2 |
2230 3503 2 | +
2231 3504 2 | Tack on the terminators when a terminal device file, just like INPUT LINE
2232 3505 2 | -
```

```
2233 3506 2 IF .CCB[LUB$V_TERM_DEV]
2234 3507 2 THEN
2235 3508 2 BEGIN
2236 3509 2 LITERAL K_ESCAPE = %X'1B',
2237 3510 2 K_CR = %X'0D',
2238 3511 2 K_CRLF = %X'0A0D';
2239 3512 2
2240 3513 2
2241 3514 2 + STV0 is the escape character, STV2 is the number of terminating characters.
2242 3515 2 -
2243 3516 2 SELECTONEU .CCB [RAB$W_STV0] OF
2244 3517 2 SET
2245 3518 2 [K_ESCAPE] :
2246 3519 2 BEGIN
2247 3520 2
2248 3521 2 + If the length is one then escape is not at the end of the buffer and it
2249 3522 2 must be moved there, otherwise the escape sequence is at the end of the
2250 3523 2 buffer following the data.
2251 3524 2
2252 3525 2 IF .CCB [RAB$W_STV2] EQLU 1
2253 3526 2 THEN
2254 3527 2 BEGIN
2255 3528 2 IF .CCB [RAB$W_RSZ] GEQU .CCB [RAB$W_USZ]
2256 3529 2 THEN BAS$$STOP_IO (BAS$K_RECFLT00);
2257 3530 2 CH$MOVE (1,UPLIT(K_ESCAPE),.CCB [RAB$L_UBF] + .CCB [RAB$W_RSZ]);
2258 3531 2 ACTUAL_RSZ = .ACTUAL_RSZ + 1;
2259 3532 2 END
2260 3533 2 ELSE
2261 3534 2 ACTUAL_RSZ = .ACTUAL_RSZ + .CCB [RAB$W_STV2];
2262 3535 2 END;
2263 3536 2 [K_CR] :
2264 3537 2 BEGIN
2265 3538 2 IF .CCB [RAB$W_RSZ] + 2 GTRU .CCB [RAB$W_USZ]
2266 3539 2 THEN BAS$$STOP_IO (BAS$K_RECFLT00);
2267 3540 2 CH$MOVE (2,UPLIT(K_CRLF),.CCB [RAB$L_UBF] + .CCB [RAB$W_RSZ]);
2268 3541 2 ACTUAL_RSZ = .ACTUAL_RSZ + 2 ;
2269 3542 2 END;
2270 3543 2 [OTHERWISE] :
2271 3544 2 ;
2272 3545 2 TES;
2273 3546 2 END;
2274 3547 2
2275 3548 2 +
2276 3549 2 - If there are no errors, null pad the buffer.
2277 3550 2
2278 3551 2
2279 3552 2 IF (.CCB [RAB$W_USZ] GTR .ACTUAL_RSZ) AND .CCB [RAB$L_STS]
2280 3553 2 THEN
2281 3554 2 CH$FILL (%X'00',
2282 3555 2 .CCB [RAB$W_USZ] - .ACTUAL_RSZ, .CCB [RAB$L_UBF] + .ACTUAL_RSZ);
2283 3556 2
2284 3557 2 +
2285 3558 2 - Before checking for errors, restore UBF and USZ, and set RECOUNT.
2286 3559 2
2287 3560 2 CCB [RAB$L_UBF] = .CCB [LUB$A_UBF];
2288 3561 2 CCB [RAB$W_USZ] = .SAVE_USZ;
2289 3562 2 RECOUNT = .ACTUAL_RSZ;
```



```
: 2290 3563 2 1+
: 2291 3564 2 1- Any error remaining (which will be an error other than Record Stream
: 2292 3565 2 1- Active, RSA) is fatal.
: 2293 3566 2 1-
: 2294 3567 2 1-
: 2295 3568 2 1- IF ( NOT .CCB [RAB$L_STS]) THEN BAS$$STOP_IO (BAS$K_IOERR_REC);
: 2296 3569 2 1- CCB [LUB$A_RBUF_ADR] = .CCB [RAB$L_RBF];
: 2297 3570 2 1- RETURN;
: 2298 3571 2 1- END;
: 2299 3572 1 1- ! End of BAS$$REC_GSE
```

```
0000001B 0060B .BLKB 1
0000001B 0060C P.AAA: .LONG 27
00000A0D 00610 P.AAB: .LONG 2573
```

```
.EXTRN SYSS$WAIT
```

```
3C BB 00000 BAS$$REC_GSE::
SE 10 C2 00002 PUSHR #*M<R2,R3,R4,R5> 3335
54 51 D0 00005 SUBL2 #16, SP
08 AE 20 AB 9E 00008 MOVL R1, R4
04 AE 08 BE 3C 0000D MOVAB 32(CCB), 8(SP) 3396
51 00000000 EF 3C 00012 MOVZWL @8(SP), SAVE_USZ
04 12 00019 MOVZWL WAIT, R1 3407
51 CC AB D0 0001B BNEQ 1$
52 04 AB 9F 0001F 1$: MOVL -52(CCB), WAIT_TIME
51 D5 00023 MOVAB 4(CCB), R2 3411
06 12 00025 TSTL WAIT_TIME 3409
03 A2 02 8A 00027 BNEQ 2$ 3411
08 11 0002B BRB 3$
1F AB 51 90 0002D 2$: MOVB WAIT_TIME, 31(CCB) 3414
03 A2 02 88 00031 BISB2 #2, 3(R2) 3415
00 A0 AB F0 00035 3$: INSV -96(CCB), #0, #1, 3(R2) 3423
50 D5 0003C *STL FOREIGN_BUFFER 3435
05 13 0003E BEQL 4$
08 BE 20 A0 B0 00040 MOVW 32(Foreign Buffer), @8(SP) 3443
A0 AB 01 E1 00045 4$: BBC #1, -96(CCB), 5$ 3453
A0 AB 02 8A 0004A BICB2 #2, -96(CCB) 3456
08 BE 01 B0 0004E MOVW #1, @8(SP) 3457
62 1E AB 94 00052 5$: CLRB 30(CCB) 3460
54 C8 00055 BISL2 LOCK_FLAGS, (R2) 3466
5B DD 00058 PUSHL CCB 3468
00000000G 00 01 FB 0005A CALLS #1, SYSS$GET
53 50 D0 00061 MOVL R0, RMS_STATUS
00010651 8F 53 D1 00064 CMPL RMS_STATUS, #67153 3470
00000000G 00 07 12 0006B BNEQ 6$
00000000G 00 00 FB 0006D CALLS #0, BAS$$SIGNAL_CTRL C 3472
000182DA 8F 53 E8 00074 6$: BLBS RMS_STATUS, 8$ 3474
08 AB D1 00077 7$: CMPL 8(CCB), #99034 3481
14 12 0007F BNEQ 8$
5B DD 00081 PUSHL CCB 3483
00000000G 00 01 FB 00083 CALLS #1, SYSS$WAIT
5B DD 0008A PUSHL CCB 3484
00000000G 00 01 FB 0008C CALLS #1, SYSS$GET
```

: 2300 3573 1


```
2302 3574 1 GLOBAL ROUTINE BASS$REC_GIN ( ! GET (indexed) a record
2303 3575 1 KEY_NO, REL_OP, KEY, FOREIGN_BUFFER, LOCK_FLAGS) : JSB_REC_IND1 NOVALUE =
2304 3576 1
2305 3577 1 **
2306 3578 1 FUNCTIONAL DESCRIPTION:
2307 3579 1
2308 3580 1 Read one record. Update RECOUNT if successful.
2309 3581 1 If a foreign buffer is specified, then change RAB$RBF to point to the
2310 3582 1 "foreign buffer". Otherwise, signal a fatal error.
2311 3583 1
2312 3584 1 FORMAL PARAMETERS:
2313 3585 1
2314 3586 1 KEY_NO.rl.v key of reference number
2315 3587 1 REL_OP.rl.v relative relationship of the key
2316 3588 1 KEY.rt.dx key to search for
2317 3589 1 FOREIGN_BUFFER.rl.v points to CB of foreign buffer or 0
2318 3590 1 LOCK_FLAGS.rlu.v bits to set in RAB ROP to control manual record
2319 3591 1 locking (0 if none)
2320 3592 1
2321 3593 1 IMP_LICIT INPUTS:
2322 3594 1
2323 3595 1 RAB$W_USZ User buffer size of foreign buffer
2324 3596 1 RAB$L_UBF Pointer to user buffer for foreign buffer
2325 3597 1
2326 3598 1 IMPLICIT OUTPUTS:
2327 3599 1
2328 3600 1 RAB$B_RAC Record access field
2329 3601 1 RECOUNT Own storage for RECOUNT function.
2330 3602 1 RAB$L_RBF Record pointer in RAB.
2331 3603 1 RAB$W_USZ User buffer size for "file" buffer
2332 3604 1 RAB$L_UBF Pointer to user buffer for "file" buffer
2333 3605 1
2334 3606 1 ROUTINE VALUE:
2335 3607 1
2336 3608 1 NONE
2337 3609 1
2338 3610 1 SIDE EFFECTS:
2339 3611 1
2340 3612 1 Reads next record from file on this logical unit.
2341 3613 1 SIGNALs any RMS errors
2342 3614 1 --
2343 3615 1
2344 3616 2 BEGIN
2345 3617 2
2346 3618 2 EXTERNAL REGISTER
2347 3619 2 CCB : REF BLOCK [, BYTE];
2348 3620 2
2349 3621 2 MAP
2350 3622 2 KEY : REF BLOCK [8, BYTE], ! descriptor of the key
2351 3623 2 FOREIGN_BUFFER : REF BLOCK [, BYTE];
2352 3624 2
2353 3625 2 LITERAL
2354 3626 2 K_EQUAL = 0, ! keys should be equal
2355 3627 2 K_GREATER_EQUAL = 1, ! key should be greater than or equal
2356 3628 2 K_GREATER_THAN = 2; ! key should be greater than
2357 3629 2
2358 3630 2 LOCAL
```

```
2359 3631 2 RMS STATUS,
2360 3632 2 SAVE_USZ; ! Save the USZ
2361 3633 2
2362 3634 2
2363 3635 2 + Save USZ in case it is modified. It is faster to always
2364 3636 2 save and restore it, since that eliminates the test for foreign
2365 3637 2 buffers and single-character mode at the end of this routine.
2366 3638 2 -
2367 3639 2 SAVE_USZ = .CCB [RAB$W_USZ];
2368 3640 2
2369 3641 2 +
2370 3642 2 Set the record pointer field in the RAB to the user buffer. This is
2371 3643 2 done on each element transmission and not just at OPEN because of RMS
2372 3644 2 Locate mode.
2373 3645 2 Fill the input buffer with Nulls. Basic semantics require null fill if
2374 3646 2 the record read is shorter than the buffer.
2375 3647 2 Set the record access field in the RAB to sequential. Perform the GET.
2376 3648 2 If RMS returns a failure status, signal the error. If the GET is
2377 3649 2 successful, then update recount.
2378 3650 2 -
2379 3651 2
2380 3652 2 IF .FOREIGN_BUFFER NEQ 0
2381 3653 2 THEN
2382 3654 2 BEGIN
2383 3655 2 +
2384 3656 2 A foreign buffer was specified. Substitute the appropriate values from the foreign channel into
2385 3657 2 the file channel to make the record go directly into the foreign buffer.
2386 3658 2 -
2387 3659 2 CCB [RAB$L_UBF] = .FOREIGN_BUFFER [RAB$L_UBF];
2388 3660 2 CCB [RAB$W_USZ] = .FOREIGN_BUFFER [RAB$W_USZ];
2389 3661 2 END;
2390 3662 2
2391 3663 2 +
2392 3664 2 Set the record access field to key. Set KBF to the key. Set KSZ to the
2393 3665 2 the size of the key passed. Set the key of reference to the desired key.
2394 3666 2 Use a case statement to toggle KGT and KGE in the ROP.
2395 3667 2 -
2396 3668 2
2397 3669 2 CCB [RAB$B_RAC] = RAB$C_KEY;
2398 3670 2 CCB [RAB$L_KBF] = .KEY [DSC$A_POINTER];
2399 3671 2 CCB [RAB$B_KRF] = .KEY_NO;
2400 3672 2 CCB [RAB$B_KSZ] = (IF .KEY [DSC$B_DTYPE] NEQ DSC$K_DTYPE_P
2401 3673 2 THEN
2402 3674 2 .KEY [DSC$W_LENGTH]
2403 3675 2 ELSE
2404 3676 2 (.KEY [DSC$W_LENGTH]/2 + 1));
2405 3677 2
2406 3678 2 CASE .REL_OP FROM K_EQUAL TO K_GREATER_THAN OF
2407 3679 2 SET
2408 3680 2
2409 3681 2 [K_EQUAL] :
2410 3682 2 CCB [RAB$V_KGE] = CCB [RAB$V_KGT] = 0;
2411 3683 2
2412 3684 2 [K_GREATER_EQUAL] :
2413 3685 2 BEGIN
2414 3686 2 CCB [RAB$V_KGE] = 1;
2415 3687 2 CCB [RAB$V_KGT] = 0;
```

```
2416 3688 2      END;
2417 3689 2
2418 3690 2      [K_GREATER_THAN] :
2419 3691 2      BEGIN
2420 3692 2          CCB [RAB$V_KGT] = 1;
2421 3693 2          CCB [RAB$V_KGE] = 0;
2422 3694 2      END;
2423 3695 2      TES;
2424 3696 2
2425 3697 2      +
2426 3698 2      Set bits in RAB ROP without turning off ULK.
2427 3699 2      -
2428 3700 2
2429 3701 2      CCB [RAB$L_ROP] = .CCB [RAB$L_ROP] OR .LOCK_FLAGS;
2430 3702 2
2431 3703 2      RMS_STATUS = $GET (RAB = .CCB);
2432 3704 2
2433 3705 2      IF .RMS_STATUS EQL RMSS_CONTROLC
2434 3706 2      THEN
2435 3707 2          BAS$$SIGNAL_CTRLC ();
2436 3708 2
2437 3709 2      IF NOT .RMS_STATUS
2438 3710 2      THEN
2439 3711 2          BEGIN
2440 3712 2      +
2441 3713 2      We cannot call GET_ERROR because we must restore UBF and USZ.
2442 3714 2      -
2443 3715 2
2444 3716 2          WHILE (.CCB [RAB$L_STS] EQL RMSS_RSA) DO
2445 3717 2              BEGIN
2446 3718 2                  $WAIT (RAB = .CCB);
2447 3719 2                  $GET (RAB = .CCB);
2448 3720 2              END;
2449 3721 2
2450 3722 2          END;
2451 3723 2
2452 3724 2      +
2453 3725 2      Turn off bits in RAB ROP so that subsequent I/O operations can not
2454 3726 2      inherit them.
2455 3727 2      -
2456 3728 2
2457 3729 2      CCB [RAB$L_ROP] = .CCB [RAB$L_ROP] XOR .LOCK_FLAGS;
2458 3730 2
2459 3731 2      +
2460 3732 2      If there are no errors, null pad the buffer.
2461 3733 2      -
2462 3734 2
2463 3735 2      IF (.CCB [RAB$W_USZ] GTR .CCB [RAB$W_RSZ]) AND .CCB [RAB$L_STS]
2464 3736 2      THEN
2465 3737 2          CH$FILL ('X'00',
2466 3738 2              .CCB [RAB$W_USZ] - .CCB [RAB$W_RSZ], .CCB [RAB$L_UBF] + .CCB [RAB$W_RSZ]);
2467 3739 2
2468 3740 2      +
2469 3741 2      Before checking for errors, restore UBF and USZ, and set RECOUNT.
2470 3742 2      -
2471 3743 2      CCB [RAB$L_UBF] = .CCB [LUB$A_UBF];
2472 3744 2      CCB [RAB$W_USZ] = .SAVE_USZ;
```

```
2473 3745 2 RECOUNT = .CCB [RAB$W_RSZ];
2474 3746 2
2475 3747 2 *
2476 3748 2 Any error remaining (which will be an error other than Record Stream
2477 3749 2 Active, RSA) is fatal.
2478 3750 2
2479 3751 2 IF ( NOT .CCB [RAB$L_STS]) THEN BAS$$STOP_IO (BAS$K_IOERR_REC);
2480 3752 2
2481 3753 2 *
2482 3754 2 This is frosting on the cake. LUB$A RBUF_ADR points to the record buffer for
2483 3755 2 MOVE. The buffer may change due to RMS Locate Mode. Currently, Locate Mode
2484 3756 2 is not performed on files which UPDATE or PUT. However, in anticipation that
2485 3757 2 RMS may add such a capability, we point RBUF_ADR off to the buffer used by PUT.
2486 3758 2
2487 3759 2 CCB [LUB$A_RBUF_ADR] = .CCB [RAB$L_RBF];
2488 3760 2 RETURN;
2489 3761 1 END;
```

! End of BAS\$\$REC_GIN

			3C	BB	00000	BAS\$\$REC	GIN::			
							PUSHR	#^M<R2,R3,R4,R5>	3574	
	7E	20	AB	3C	00002		MOVZWL	32(CCB), SAVE_USZ	3639	
			53	D5	00006		TSTL	FOREIGN_BUFFER	3652	
			0A	13	00008		BEQL	1\$		
24	AB	24	A3	D0	0000A		MOVL	36(FOREIGN_BUFFER), 36(CCB)	3659	
20	AB	20	A3	80	0000F		MOVW	32(FOREIGN_BUFFER), 32(CCB)	3660	
1E	AB		01	90	00014	1\$:	MOVB	#1, 30(CCB)	3669	
30	AB	04	A2	D0	00018		MOVL	4(KEY), 48(CCB)	3670	
35	AB		50	90	0001D		MOVB	KEY_NO, 53(CCB)	3671	
	15	02	A2	91	00021		CMPB	2(KEY), #21	3672	
			05	13	00025		BEQL	2\$		
	52		62	3C	00027		MOVZWL	(KEY), R2	3674	
			08	11	0002A		BRB	3\$		
	52		62	3C	0002C	2\$:	MOVZWL	(KEY), R2	3676	
	52		02	C6	0002F		DIVL2	#2, R2		
			52	D6	00032		INCL	R2		
34	AB		52	90	00034	3\$:	MOVB	R2, 52(CCB)	3672	
	52	04	AB	9E	00038		MOVAB	4(CCB), R2	3682	
02	00		51	CF	0003C		CASEL	REL_OP, #0, #2	3678	
0018	000D		0006		00040	4\$:	.WORD	5\$-4\$,-		
								6\$-4\$,-		
								7\$-4\$,-		
	02	A2	40	8F	8A	00046	5\$:	BICB2	#64, 2(R2)	3682
				10	11	0004B		BRB	8\$	
	02	A2	20	88	0004D	6\$:	BISB2	#32, 2(R2)	3686	
	02	A2	40	8F	8A	00051		BICB2	#64, 2(R2)	3687
				09	11	00056		BRB	9\$	3678
	02	A2	40	8F	88	00058	7\$:	BISB2	#64, 2(R2)	3692
	02	A2		20	8A	0005D	8\$:	BICB2	#32, 2(R2)	3693
		62		54	C8	00061	9\$:	BISL2	LOCK_FLAGS, (R2)	3701
				5B	DD	00064		PUSHL	CCB	3703
00000000G	00		01	FB	00066		CALLS	#1, SYSSGET		
	53		50	D0	0006D		MOVL	R0, RMS_STATUS		
00010651	8F		53	D1	00070		CMPL	RMS_STATUS, #67153		3705

			07	12	00077	BNEQ	10\$		
			00	FB	00079	CALLS	#0, BAS\$\$SIGNAL_CTRL		3707
			53	E8	00080	BLBS	RMS STATUS, 12\$		3709
			AB	D1	00083	CMPL	8(CCB), #99034		3716
			14	12	00088	BNEQ	12\$		
			5B	DD	0008D	PUSHL	CCB		3718
			01	FB	0008F	CALLS	#1, SY\$\$WAIT		
			5B	DD	00096	PUSHL	CCB		3719
			01	FB	00098	CALLS	#1, SY\$\$GET		
			E2	11	0009F	BRB	11\$		3716
			54	CC	000A1	XORL2	LOCK_FLAGS, (R2)		3729
			AB	B1	000A4	CMPL	32(CCB), 34(CCB)		3735
			1D	1B	000A9	BLEQU	13\$		
			AB	E9	000AB	BLBC	8(CCB), 13\$		
			AB	3C	000AF	MOVZWL	32(CCB), R1		3738
			AB	3C	000B3	MOVZWL	34(CCB), R0		
			50	C2	000B7	SUBL2	R0, R1		
			AB	3C	000BA	MOVZWL	34(CCB), R0		
			AB	C0	000BE	ADDL2	36(CCB), R0		
			00	2C	000C2	MOVCS	#0, (SP), #0, R1, (R0)		
			60		000C7				
			AB	D0	000C8	MOVL	-100(CCB), 36(CCB)		3743
			6E	B0	000CD	MOVW	SAVE_USZ, 32(CCB)		3744
			AB	3C	000D1	MOVZWL	34(CCB), RECOUNT		3745
			AB	E8	000D9	BLBS	8(CCB), 14\$		3751
			01	CE	000DD	MNEGL	#1, -(SP)		
			01	FB	000E0	CALLS	#1, BAS\$\$STOP_10		
			AB	D0	000E7	MOVL	40(CCB), -20(CCB)		3759
			04	C0	000EC	ADDL2	#4, SP		3761
			3C	BA	000EF	POPR	#^M<R2,R3,R4,R5>		
			05		000F1	RSB			

: Routine Size: 242 bytes, Routine Base: _BAS\$CODE + 0766

: 2490 3762 1

```

: 2492 3763 1 GLOBAL ROUTINE BAS$$REC_GRE ( ! GET (relative) a record
: 2493 3764 1 FOREIGN_BUFFER, LOCK_FLAGS) : JSB_DO_READ NOVALUE =
: 2494 3765 1
: 2495 3766 1 !+
: 2496 3767 1 FUNCTIONAL DESCRIPTION:
: 2497 3768 1
: 2498 3769 1 Read one record from a relative file. Modify the RAB if necessary for
: 2499 3770 1 foreign buffers. Update RECOUNT if successful. Otherwise, signal a fatal error.
: 2500 3771 1
: 2501 3772 1 FORMAL PARAMETERS:
: 2502 3773 1
: 2503 3774 1 FOREIGN_BUFFER.rl.v The address of the CB of a foreign
: 2504 3775 1 buffer or 0
: 2505 3776 1 LOCK_FLAGS.rlu.v bits to set in the RAB ROP to control
: 2506 3777 1 manual record locking (0 if none)
: 2507 3778 1 IMPLICIT INPUTS:
: 2508 3779 1
: 2509 3780 1 RAB$W_RSZ record size for foreign buffer
: 2510 3781 1 RAB$L_UBF buffer address for foreign buffer
: 2511 3782 1
: 2512 3783 1 IMPLICIT OUTPUTS:
: 2513 3784 1
: 2514 3785 1 RAB$B_RAC Record access field
: 2515 3786 1 RECOUNT Own storage for RECOUNT function.
: 2516 3787 1 RAB$L_RBF Record pointer in RAB.
: 2517 3788 1 RAB$W_USZ record size of file buffer
: 2518 3789 1 RAB$L_UBF address of buffer for file buffer
: 2519 3790 1
: 2520 3791 1 ROUTINE VALUE:
: 2521 3792 1
: 2522 3793 1 NONE
: 2523 3794 1
: 2524 3795 1 SIDE EFFECTS:
: 2525 3796 1
: 2526 3797 1 SIGNALs any RMS errors
: 2527 3798 1 --
: 2528 3799 1
: 2529 3800 2 BEGIN
: 2530 3801 2
: 2531 3802 2 EXTERNAL REGISTER
: 2532 3803 2 CCB : REF BLOCK [, BYTE];
: 2533 3804 2
: 2534 3805 2 MAP
: 2535 3806 2 FOREIGN_BUFFER : REF BLOCK [, BYTE];
: 2536 3807 2
: 2537 3808 2 LOCAL
: 2538 3809 2 RMS STATUS,
: 2539 3810 2 SAVE_USZ; ! Save the USZ
: 2540 3811 2
: 2541 3812 2 !+
: 2542 3813 2 Save USZ in case it is modified. It is faster to always
: 2543 3814 2 save and restore it, since that eliminates the test for foreign
: 2544 3815 2 buffers and single-character mode at the end of this routine.
: 2545 3816 2 --
: 2546 3817 2 SAVE_USZ = .(CB [RAB$W_USZ]);
: 2547 3818 2
: 2548 3819 2 !+

```



```
2549 3820 2 | Set the record pointer field in the RAB to the user buffer. This is
2550 3821 2 | done on each element transmission and not just at OPEN because of RMS
2551 3822 2 | Locate mode.
2552 3823 2 | Fill the input buffer with Nulls. Basic semantics require null fill if
2553 3824 2 | the record read is shorter than the buffer.
2554 3825 2 | Set the record access field in the RAB to sequential. Perform the GET.
2555 3826 2 | If RMS returns a failure status, signal the error. If the GET is
2556 3827 2 | successful, then update recount.
2557 3828 2 |
2558 3829 2 |
2559 3830 2 | IF .FOREIGN_BUFFER NEQ 0
2560 3831 2 | THEN
2561 3832 2 | BEGIN
2562 3833 2 |
2563 3834 2 | + There is a foreign buffer. Modify the file buffer to point to the
2564 3835 2 | buffer associated with the foreign buffer's channel.
2565 3836 2 | -
2566 3837 2 | CCB [RAB$L_RBF] = CCB [RAB$L_UBF] = .FOREIGN_BUFFER [RAB$L_UBF];
2567 3838 2 | CCB [RAB$W_RSZ] = CCB [RAB$W_USZ] = .FOREIGN_BUFFER [RAB$W_USZ];
2568 3839 2 | END
2569 3840 2 | ELSE
2570 3841 2 | CCB [RAB$L_RBF] = .CCB [RAB$L_UBF];
2571 3842 2 |
2572 3843 2 | CCB [RAB$B_RAC] = RAB$C_KEY;
2573 3844 2 |
2574 3845 2 | +
2575 3846 2 | Set bits in RAB ROP without destroying ULK.
2576 3847 2 | -
2577 3848 2 |
2578 3849 2 | CCB [RAB$L_ROP] = .CCB [RAB$L_ROP] OR .LOCK_FLAGS;
2579 3850 2 |
2580 3851 2 | RMS_STATUS = $GET (RAB = .CCB);
2581 3852 2 |
2582 3853 2 | IF .RMS_STATUS EQL RMSS_CONTROLC
2583 3854 2 | THEN
2584 3855 2 | BAS$$SIGNAL_CTRLC ();
2585 3856 2 |
2586 3857 2 | IF NOT .RMS_STATUS
2587 3858 2 | THEN
2588 3859 2 | BEGIN
2589 3860 2 |
2590 3861 2 | + We cannot call GET_ERROR because we must restore UBF and USZ.
2591 3862 2 | -
2592 3863 2 |
2593 3864 2 | WHILE (.CCB [RAB$L_STS] EQL RMSS_RSA) DO
2594 3865 2 | BEGIN
2595 3866 2 | $WAIT (RAB = .CCB);
2596 3867 2 | $GET (RAB = .CCB);
2597 3868 2 | END;
2598 3869 2 |
2599 3870 2 | END;
2600 3871 2 |
2601 3872 2 | +
2602 3873 2 | Turn off bits in the RAB ROP so that subsequent I/O operations can not
2603 3874 2 | inherit them.
2604 3875 2 | -
2605 3876 2 |
```

```
: 2606      3877 2      CCB [RAB$L_ROP] = .CCB [RAB$L_ROP] XOR .LOCK_FLAGS;
: 2607      3878 2
: 2608      3879 2
: 2609      3880 2      * If there are no errors, null pad the buffer.
: 2610      3881 2      -
: 2611      3882 2
: 2612      3883 2      IF (.CCB [RAB$W_USZ] GTR .CCB [RAB$W_RSZ]) AND .CCB [RAB$L_STS]
: 2613      3884 2      THEN
: 2614      3885 2          CH$FILL (%X'00',
: 2615      3886 2              .CCB [RAB$W_USZ] - .CCB [RAB$W_RSZ], .CCB [RAB$L_UBF] + .CCB [RAB$W_RSZ]);
: 2616      3887 2
: 2617      3888 2      *
: 2618      3889 2      * Before checking for errors, restore UBF and USZ, and set RECOUNT.
: 2619      3890 2      -
: 2620      3891 2          CCB [RAB$L_UBF] = .CCB [LUB$A_UBF];
: 2621      3892 2          CCB [RAB$W_USZ] = .SAVE_USZ;
: 2622      3893 2          RECOUNT = .CCB [RAB$W_RSZ];
: 2623      3894 2      *
: 2624      3895 2      * Any error remaining (which will be an error other than Record Stream
: 2625      3896 2      * Active, RSA) is fatal.
: 2626      3897 2      -
: 2627      3898 2
: 2628      3899 2      IF ( NOT .CCB [RAB$L_STS]) THEN BAS$$STOP_IO (BAS$K_IOERR_REC);
: 2629      3900 2
: 2630      3901 2      *
: 2631      3902 2      * Set LUB$A_RBUF_ADR to point to the buffer used by RMS. It may move around
: 2632      3903 2      * due to Locate Mode.
: 2633      3904 2      -
: 2634      3905 2          CCB [LUB$A_RBUF_ADR] = .CCB [RAB$L_RBF];
: 2635      3906 2      RETURN;
: 2636      3907 1      END;
                                ! End of BAS$$REC_GRE
```

			3C	BB	00000	BAS\$\$REC GRE::		
						PUSHR	#*M<R2,R3,R4,R5>	3763
	52		51	D0	00002	MOVL	R1, R2	
	7E	20	AB	3C	00005	MOVZWL	32(CCB), SAVE_USZ	3817
			50	D5	00009	TSTL	FOREIGN_BUFFER	3830
			1A	13	0000B	BEQL	1\$	
	51	24	A0	D0	0000D	MOVL	36(FOREIGN_BUFFER), R1	3837
24	AB		51	D0	00011	MOVL	R1, 36(CCB)	
28	AB		51	D0	00015	MOVL	R1, 40(CCB)	
	50	20	A0	3C	00019	MOVZWL	32(FOREIGN_BUFFER), R0	3838
20	AB		50	B0	0001D	MOVW	R0, 32(CCB)	
22	AB		50	B0	00021	MOVW	R0, 34(CCB)	
			05	11	00025	BRB	2\$	3830
28	AB	24	AB	D0	00027	MOVL	36(CCB), 40(CCB)	3841
1E	AB		01	90	0002C	MOVB	#1, 30(CCB)	3843
04	AB		52	C8	00030	BISL2	LOCK_FLAGS, 4(CCB)	3849
			5B	DD	00034	PUSHL	CCB	3851
00000000G	00		01	FB	00036	CALLS	#1, SYS\$GET	
	53		50	D0	0003D	MOVL	R0, RMS_STATUS	
00010651	8F		53	D1	00040	CMPL	RMS_STATUS, #67153	3853
			07	12	00047	BNEQ	3\$	

00000000G	00	00	FB	00049	CALLS	#0, BASS\$SIGNAL_CTRL	:	3855
	1E	53	E8	00050	BLBS	RMS STATUS, 5\$	:	3857
000182DA	8F	08	AB	D1 00053	CMPL	8(CCB), #99034	:	3864
			14	12 0005B	BNEQ	5\$	:	
			5B	DD 0005D	PUSHL	CCB	:	3866
00000000G	00		01	FB 0005F	CALLS	#1, SYSS\$WAIT	:	
			5B	DD 00066	PUSHL	CCB	:	3867
00000000G	00		01	FB 00068	CALLS	#1, SYSS\$GET	:	
			E2	11 0006F	BRB	4\$	:	3864
	04		52	CC 00071	XORL2	LOCK FLAGS, 4(CCB)	:	3877
	22		AB	B1 00075	CMPW	32(CCB), 34(CCB)	:	3883
			1D	1B 0007A	BLEQU	6\$	:	
			AB	E9 0007C	BLBC	8(CCB), 6\$	:	
		08	AB	3C 00080	MOVZWL	32(CCB), R1	:	3886
		20	AB	3C 00084	MOVZWL	34(CCB), R0	:	
		22	AB	3C 00088	SUBL2	R0, R1	:	
			50	C2 0008B	MOVZWL	34(CCB), R0	:	
		22	AB	3C 0008B	ADDL2	36(CCB), R0	:	
		24	AB	C0 0008F	MOVZWL	36(CCB), R0	:	
51	00		00	2C 00093	ADDL2	#0, (SP), #0, R1, (R0)	:	
			60	00098	MOVZWL		:	
			AB	D0 00099	MOVZWL	-100(CCB), 36(CCB)	:	3891
	24		AB	D0 00099	MOVZWL	SAVE USZ, 32(CCB)	:	3892
	20		6E	B0 0009E	MOVZWL	34(CCB), RECOUNT	:	3893
00000000'	EF		AB	3C 000A2	BLBS	8(CCB), 7\$	:	3899
	0A		AB	E8 000AA	MNEGL	#1, -(SP)	:	
	7E		01	CE 000AE	CALLS	#1, BASS\$STOP_IO	:	
00000000G	00		01	FB 000B1	CALLS	#1, BASS\$STOP_IO	:	
	EC		AB	D0 000B8	MOVZWL	40(CCB), -20(CCB)	:	3905
		28	AB	D0 000B8	ADDL2	#4, SP	:	3907
			04	C0 000BD	POPR	#M<R2,R3,R4,R5>	:	
			3C	BA 000C0	RSB		:	
			05	000C2			:	

; Routine Size: 195 bytes, Routine Base: _BASS\$CODE + 0858

```
2638 3908 1 GLOBAL ROUTINE BAS$$REC_GRFA ( ! GET (by RFA) a record
2639 3909 1 FOREIGN_BUFFER, LOCK_FLAGS) : JSB_DO_READ NOVALUE =
2640 3910 1
2641 3911 1 !+
2642 3912 1 FUNCTIONAL DESCRIPTION:
2643 3913 1
2644 3914 1 Read one record from a file. Modify the RAB if necessary for
2645 3915 1 foreign buffers. Update RECOUNT if successful. Otherwise, signal a fatal error.
2646 3916 1
2647 3917 1 FORMAL PARAMETERS:
2648 3918 1
2649 3919 1 FOREIGN_BUFFER.rl.v The address of the CB of a foreign
2650 3920 1 buffer or 0
2651 3921 1 LOCK_FLAGS.rlu.v bits to set in the RAB ROP to control
2652 3922 1 manual record locking (0 if none)
2653 3923 1 IMPLICIT INPUTS:
2654 3924 1
2655 3925 1 RAB$W_RSZ record size for foreign buffer
2656 3926 1 RAB$L_UBF buffer address for foreign buffer
2657 3927 1
2658 3928 1 IMPLICIT OUTPUTS:
2659 3929 1
2660 3930 1 RAB$B_RAC Record access field
2661 3931 1 RECOUNT Own storage for RECOUNT function.
2662 3932 1 RAB$L_RBF Record pointer in RAB.
2663 3933 1 RAB$W_USZ record size of file buffer
2664 3934 1 RAB$L_UBF address of buffer for file buffer
2665 3935 1
2666 3936 1 ROUTINE VALUE:
2667 3937 1
2668 3938 1 NONE
2669 3939 1
2670 3940 1 SIDE EFFECTS:
2671 3941 1
2672 3942 1 SIGNALS any RMS errors
2673 3943 1 --
2674 3944 1
2675 3945 2 BEGIN
2676 3946 2
2677 3947 2 EXTERNAL REGISTER
2678 3948 2 CCB : REF BLOCK [, BYTE];
2679 3949 2
2680 3950 2 MAP
2681 3951 2 FOREIGN_BUFFER : REF BLOCK [, BYTE];
2682 3952 2
2683 3953 2 LOCAL
2684 3954 2 RMS_STATUS,
2685 3955 2 SAVE_USZ; ! Save the USZ
2686 3956 2
2687 3957 2 !+
2688 3958 2 Save USZ in case it is modified. It is faster to always
2689 3959 2 save and restore it, since that eliminates the test for foreign
2690 3960 2 buffers and single-character mode at the end of this routine.
2691 3961 2 --
2692 3962 2 SAVE_USZ = .CCB [RAB$W_USZ];
2693 3963 2
2694 3964 2 !+
```

```
2695 3965 2 | Set the record pointer field in the RAB to the user buffer. This is
2696 3966 2 | done on each element transmission and not just at OPEN because of RMS
2697 3967 2 | Locate mode.
2698 3968 2 | Fill the input buffer with Nulls. Basic semantics require null fill if
2699 3969 2 | the record read is shorter than the buffer.
2700 3970 2 | Set the record access field in the RAB to sequential. Perform the GET.
2701 3971 2 | If RMS returns a failure status, signal the error. If the GET is
2702 3972 2 | successful, then update recount.
2703 3973 2 |
2704 3974 2 |
2705 3975 2 | IF .FOREIGN_BUFFER NEQ 0
2706 3976 2 | THEN
2707 3977 2 | BEGIN
2708 3978 2 | +
2709 3979 2 | There is a foreign buffer. Modify the file buffer to point to the
2710 3980 2 | buffer associated with the foreign buffer's channel.
2711 3981 2 | -
2712 3982 2 | CCB [RAB$L_RBF] = CCB [RAB$L_UBF] = .FOREIGN_BUFFER [RAB$L_UBF];
2713 3983 2 | CCB [RAB$W_RSZ] = CCB [RAB$W_USZ] = .FOREIGN_BUFFER [RAB$W_USZ];
2714 3984 2 | END
2715 3985 2 | ELSE
2716 3986 2 | CCB [RAB$L_RBF] = .CCB [RAB$L_UBF];
2717 3987 2 |
2718 3988 2 | CCB [RAB$B_RAC] = RAB$C_RFA;
2719 3989 2 |
2720 3990 2 | +
2721 3991 2 | Set bits in RAB ROP without destroying ULK.
2722 3992 2 | -
2723 3993 2 |
2724 3994 2 | CCB [RAB$L_ROP] = .CCB [RAB$L_ROP] OR .LOCK_FLAGS;
2725 3995 2 |
2726 3996 2 | RMS_STATUS = $GET (RAB = .CCB);
2727 3997 2 |
2728 3998 2 | IF .RMS_STATUS EQL RMSS_CONTROLC
2729 3999 2 | THEN
2730 4000 2 | BAS$$SIGNAL_CTRLCL ();
2731 4001 2 |
2732 4002 2 | IF NOT .RMS_STATUS
2733 4003 2 | THEN
2734 4004 2 | BEGIN
2735 4005 2 | +
2736 4006 2 | We cannot call GET_ERROR because we must restore UBF and USZ.
2737 4007 2 | -
2738 4008 2 |
2739 4009 2 | WHILE (.CCB [RAB$L_STS] EQL RMSS_RSA) DO
2740 4010 2 | BEGIN
2741 4011 2 | $WAIT (RAB = .CCB);
2742 4012 2 | $GET (RAB = .CCB);
2743 4013 2 | END;
2744 4014 2 |
2745 4015 2 | END;
2746 4016 2 |
2747 4017 2 | +
2748 4018 2 | Turn off bits in the RAB ROP so that subsequent I/O operations can not
2749 4019 2 | inherit them.
2750 4020 2 | -
2751 4021 2 |
```

```
: 2752      4022 2      CCB [RAB$L_ROP] = .CCB [RAB$L_ROP] XOR .LOCK_FLAGS;
: 2753      4023 2
: 2754      4024 2 !+
: 2755      4025 2 ! If there are no errors, null pad the buffer.
: 2756      4026 2 !-
: 2757      4027 2
: 2758      4028 2      IF (.CCB [RAB$W_USZ] GTR .CCB [RAB$W_RSZ]) AND .CCB [RAB$L_STS]
: 2759      4029 2      THEN
: 2760      4030 2          CH$FILL ('X'00',
: 2761      4031 2              .CCB [RAB$W_USZ] - .CCB [RAB$W_RSZ], .CCB [RAB$L_UBF] + .CCB [RAB$W_RSZ]);
: 2762      4032 2
: 2763      4033 2 !+
: 2764      4034 2 ! Before checking for errors, restore UBF and USZ, and set RECOUNT.
: 2765      4035 2 !-
: 2766      4036 2      CCB [RAB$L_UBF] = .CCB [LUB$A_UBF];
: 2767      4037 2      CCB [RAB$W_USZ] = .SAVE_USZ;
: 2768      4038 2      RECOUNT = .CCB [RAB$W_RSZ];
: 2769      4039 2 !+
: 2770      4040 2 ! Any error remaining (which will be an error other than Record Stream
: 2771      4041 2 ! Active, RSA) is fatal.
: 2772      4042 2 !-
: 2773      4043 2
: 2774      4044 2      IF ( NOT .CCB [RAB$L_STS]) THEN BAS$$STOP_IO (BAS$K_IOERR_REC);
: 2775      4045 2
: 2776      4046 2 !+
: 2777      4047 2 ! Set LUB$A_RBUF_ADR to point to the buffer used by RMS. It may move around
: 2778      4048 2 ! due to Locate Mode.
: 2779      4049 2 !-
: 2780      4050 2      CCB [LUB$A_RBUF_ADR] = .CCB [RAB$L_RBF];
: 2781      4051 2      RETURN;
: 2782      4052 1      END;
```

! End of BAS\$\$REC_GRFA

			3C	BB	00000	BAS\$\$REC	GRFA::		
							PUSHR	#^M<R2,R3,R4,R5>	: 3908
	52		51	D0	00002		MOVL	R1, R2	
	7E	20	AB	3C	00005		MOVZWL	32(CCB), SAVE_USZ	: 3962
			50	D5	00009		TSTL	FOREIGN_BUFFER	: 3975
			1A	13	0000B		BEQL	1\$	
	51	24	A0	D0	0000D		MOVL	36(FOREIGN_BUFFER), R1	: 3982
24	AB		51	D0	00011		MOVL	R1, 36(CCB)	
28	AB		51	D0	00015		MOVL	R1, 40(CCB)	
	50	20	A0	3C	00019		MOVZWL	32(FOREIGN_BUFFER), R0	: 3983
20	AB		50	B0	0001D		MOVW	R0, 32(CCB)	
22	AB		50	B0	00021		MOVW	R0, 34(CCB)	
			05	11	00025		BRB	2\$	: 3975
28	AB	24	AB	D0	00027	1\$:	MOVL	36(CCB), 40(CCB)	: 3986
1E	AB		C2	90	0002C	2\$:	MOVB	#2, 30(CCB)	: 3988
04	AB		52	C8	00030		BISL2	LOCK_FLAGS, 4(CCB)	: 3994
			5B	DD	00034		PUSHL	CCB	: 3996
00000000G	00		01	FB	00036		CALLS	#1, SYSSGET	
	53		50	D0	0003D		MOVL	R0, RMS_STATUS	
00010651	8F		53	D1	00040		CMPL	RMS_STATUS, #67153	: 3998
			07	12	00047		BNEQ	3\$	

00000000G	00	00	FB	00049	CALLS	#0, BAS\$\$SIGNAL_CTRL	4000
000182DA	8F	08	AB	D1 00053	BLBS	RMS STATUS, 5\$	4002
			14	12 0005B	CMPL	8(CCB), #99034	4009
00000000G	00		5B	DD 0005D	BNEQ	5\$	4011
00000000G	00		01	FB 0005F	PUSHL	CCB	4012
			5B	DD 00066	CALLS	#1, SYSS\$WAIT	4009
			01	FB 00068	PUSHL	CCB	4022
			E2	11 0006F	CALLS	#1, SYSS\$GET	4028
04	AB		52	CC 00071	BRB	4\$	4031
22	AB	20	AB	B1 00075	XORL2	LOCK_FLAGS, 4(CCB)	
			1D	1B 0007A	CMPL	32(CCB), 34(CCB)	
			AB	E9 0007C	BLEQU	6\$	
		08	AB	3C 00080	BLBC	8(CCB), 6\$	
		20	AB	3C 00084	MOVZWL	32(CCB), R1	
		22	AB	3C 00088	MOVZWL	34(CCB), R0	
			50	C2 0008B	SUBL2	R0, R1	
		22	AB	3C 0008B	MOVZWL	34(CCB), R0	
		24	AB	C0 0C08F	ADDL2	36(CCB), R0	
51	00		00	2C 00093	MOVC5	#0, (SP), #0, R1, (R0)	
			60	00098			
		9C	AB	D0 00099	MOVL	-100(CCB), 36(CCB)	4036
			6E	B0 0009E	MOVW	SAVE_USZ, 32(CCB)	4037
00000000	EF	22	AB	3C 000A2	MOVZWL	34(CCB), RECOUNT	4038
	0A	08	AB	E8 000AA	BLBS	8(CCB), 7\$	4044
	7E		01	CE 000AE	MNEGL	#1, -(SP)	
00000000G	00		01	FB 000B1	CALLS	#1, BAS\$\$STOP_IO	
EC	AB	28	AB	D0 000B8	MOVL	40(CCB), -20(CCB)	4050
	5E		04	C0 000BD	ADDL2	#4, SP	4052
			3C	BA 000C0	POPR	#M<R2,R3,R4,R5>	
			05	000C2	RSB		

; Routine Size: 195 bytes, Routine Base: _BAS\$CODE + 091B

; 2783 4053 1
; 2784 4054 1

```
2786 4055 1 GLOBAL ROUTINE BAS$REC_PSE (
2787 4056 1     COUNT,
2788 4057 1     FOREIGN_BUFFER
2789 4058 1 ) : JSB_PUT NOVALUE =
2790 4059 1
2791 4060 1 ++
2792 4061 1 FUNCTIONAL DESCRIPTION:
2793 4062 1
2794 4063 1     Check for "foreign buffers" and point RAB$LSZ to foreign USZ if there.
2795 4064 1     Write one record. If successful then return; otherwise, signal a fatal
2796 4065 1     error.
2797 4066 1
2798 4067 1 FORMAL PARAMETERS:
2799 4068 1
2800 4069 1     COUNT.rl.v           No. of bytes to write
2801 4070 1     FOREIGN_BUFFER.rl.v  pointer to foreign buffer (B or 0)
2802 4071 1
2803 4072 1 IMPLICIT INPUTS:
2804 4073 1
2805 4074 1     RAB$W_RSZ             of foreign buffer
2806 4075 1     RAB$R_RBF             of foreign buffer
2807 4076 1     LUB$V_CCO             Cancel control 0
2808 4077 1
2809 4078 1 IMPLICIT OUTPUTS:
2810 4079 1
2811 4080 1     RAB$R_RBF             for "file" buffer
2812 4081 1     RAB$W_RSZ             length of record to write
2813 4082 1     LUB$R_LOG_RECNO       logical record number
2814 4083 1     RAB$B_RAC             record access field
2815 4084 1     RAB$V_CCO             Cancel control 0
2816 4085 1
2817 4086 1 ROUTINE VALUE:
2818 4087 1
2819 4088 1     NONE
2820 4089 1
2821 4090 1 SIDE EFFECTS:
2822 4091 1
2823 4092 1     SIGNALs any RMS errors
2824 4093 1 --
2825 4094 1
2826 4095 2 BEGIN
2827 4096 2
2828 4097 2 EXTERNAL REGISTER
2829 4098 2     CCB : REF BLOCK [, BYTE];
2830 4099 2
2831 4100 2 LOCAL
2832 4101 2     RMS_STATUS;
2833 4102 2
2834 4103 2 MAP
2835 4104 2     FOREIGN_BUFFER : REF BLOCK [, BYTE];
2836 4105 2
2837 4106 2 ++
2838 4107 2 Copy the current status of the cancel-control-o bit in the LUB
2839 4108 2 (possibly set by RCTRL0) into the RAB, and clear it from the
2840 4109 2 LUB. The net effect of this is that if the bit is set in the
2841 4110 2 LUB, then the CANCTRL0 modifier will be applied to this write
2842 4111 2 operation only.
```



```
2843 4112 2 :-
2844 4113 2
2845 4114 2 CCB [RAB$V_CCO] = .CCB [LUB$V_CCO];
2846 4115 2 CCB [LUB$V_CCO] = 0;
2847 4116 2
2848 4117 2
2849 4118 2 +
2850 4119 2 Set the recordsize field in the RAB based on COUNT.
2851 4120 2 Set the record address field in the RAB to the user buffer.
2852 4121 2 Perform the PUT.
2853 4122 2 If RMS returns a failure status, signal the error.
2854 4123 2 -
2855 4124 2 CCB [RAB$W_RSZ] = .COUNT;
2856 4125 2 CCB [RAB$B_RAC] = (IF .CCB [LUB$B_ORGAN] EQL LUB$K_ORG_INDEX THEN RAB$C_KEY ELSE RAB$C_SEQ);
2857 4126 2
2858 4127 2 IF .FOREIGN_BUFFER NEQA 0
2859 4128 2 THEN
2860 4129 2 +
2861 4130 2 There is a foreign buffer. Point RAB$L_UBF to it.
2862 4131 2 -
2863 4132 2 CCB [RAB$L_RBF] = CCB [RAB$L_UBF] = .FOREIGN_BUFFER [RAB$L_UBF]
2864 4133 2 ELSE
2865 4134 2 CCB [RAB$L_RBF] = .CCB [RAB$L_UBF];
2866 4135 2
2867 4136 2 RMS_STATUS = $PUT (RAB = .CCB);
2868 4137 2
2869 4138 2 IF .RMS_STATUS EQL RMSS_CONTROLC
2870 4139 2 THEN
2871 4140 2 BAS$$SIGNAL_CTRLC ();
2872 4141 2
2873 4142 2 IF NOT .RMS_STATUS
2874 4143 2 THEN
2875 4144 2 BEGIN
2876 4145 2 +
2877 4146 2 We cannot call PUT_ERROR because we must restore UBF and USZ.
2878 4147 2 -
2879 4148 2
2880 4149 2 WHILE (.CCB [RAB$L_STS] EQL RMSS_RSA) DO
2881 4150 2 BEGIN
2882 4151 2 $WAIT (RAB = .CCB);
2883 4152 2 $PUT (RAB = .CCB);
2884 4153 2 END;
2885 4154 2
2886 4155 2 END;
2887 4156 2
2888 4157 2 +
2889 4158 2 Restore RAB$L_UBF in case there was a foreign buffer.
2890 4159 2 -
2891 4160 2 CCB [RAB$L_UBF] = .CCB [LUB$A_UBF];
2892 4161 2 +
2893 4162 2 Point LUB$A_RBUF_PTR off to the buffer used by RMS.
2894 4163 2 -
2895 4164 2 CCB [LUB$A_RBUF_ADR] = .CCB [RAB$L_UBF];
2896 4165 2 +
2897 4166 2 Any error remaining (which will be an error other than Record Stream
2898 4167 2 Active, RSA) is fatal.
2899 4168 2 -
```

```

: 2900      4169  2
: 2901      4170  2
: 2902      4171  2
: 2903      4172  2
: 2904      4173  1
IF ( NOT .CCB [RAB$L_STS]) THEN BAS$$STOP_IO (BAS$K_IOERR_REC);
RETURN;
END;
' End of BAS$$REC_PSE

```

			5E	04	C2	00000	BAS\$\$REC_PSE::		
			01	02	EF	00003	SUBL2	#4, SP	: 4055
07	7E	A0	07	8E	F0	00009	EXTZV	#2, #1, -95(CCB), -(SP)	: 4114
	AB		AB	04	8A	0000F	INSV	(SP)+, #7, #1, 7(CCB)	
		A0	22	51	B0	00013	BICB2	#4, -96(CCB)	: 4115
			03	AB	91	00017	MOVW	COUNT, 34(CCB)	: 4124
				C4	05	12	CMPB	-60(CCB), #3	: 4125
			51	01	D0	0001D	BNEQ	1\$	
				02	11	00020	MOVL	#1, R1	
				51	D4	00022	BRB	2\$	
	1E	AB		51	90	00024	CLRL	R1	
				50	D5	00028	MOVB	R1, 30(CCB)	
				0E	13	0002A	TSTL	FOREIGN_BUFFER	: 4127
		50	24	A0	D0	0002C	BEQL	3\$	
	24	AB		50	D0	00030	MOVL	36(FOREIGN_BUFFER), R0	: 4132
	28	AB		50	D0	00034	MOVL	R0, 36(CCB)	
				05	11	00038	MOVL	R0, 40(CCB)	
	28	AB	24	AB	D0	0003A	BRB	4\$	
				5B	DD	0003F	MOVL	36(CCB), 40(CCB)	: 4134
				01	FB	00041	PUSHL	CCB	: 4136
00000000G		00		50	D0	00048	CALLS	#1, SYSSPUT	
		6E		6E	D1	0004B	MOVL	R0, RMS_STATUS	
00010651		8F		07	12	00052	CMPL	RMS_STATUS, #67153	: 4138
				00	FB	00054	BNEQ	5\$	
00000000G		00		6E	E8	0005B	CALLS	#0, BAS\$\$SIGNAL_CTRL	: 4140
		1E		AB	D1	0005E	BLBS	RMS_STATUS, 7\$	: 4142
000182DA		8F	08	14	12	00066	CMPL	8(CCB), #99034	: 4149
				5B	DD	00068	BNEQ	7\$	
				01	FB	0006A	PUSHL	CCB	: 4151
00000000G		00		5B	DD	00071	CALLS	#1, SYSSWAIT	
				01	FB	00073	PUSHL	CCB	: 4152
00000000G		00		E2	11	0007A	CALLS	#1, SYSSPUT	
	24	AB	9C	AB	D0	0007C	BRB	6\$	: 4149
	EC	AB	24	AB	D0	00081	MOVL	-100(CCB), 36(CCB)	: 4160
		0A	08	AB	E8	00086	MOVL	36(CCB), -20(CCB)	: 4164
		7E		01	CE	0008A	BLBS	8(CCB), 8\$	: 4170
00000000G		00		01	FB	0008D	MNEGL	#1, -(SP)	
		5E		04	C0	00094	CALLS	#1, BAS\$\$STOP_IO	
				05	00097	ADDL2	#4, SP		: 4173
						RSB			

; Routine Size: 152 bytes, Routine Base: _BAS\$CODE + 09DE

; 2905 4174 1


```
2907 4175 1 GLOBAL ROUTINE BAS$$REC_PRE (          | PUT (relative) a record
2908 4176 1     COUNT,                                | No. of bytes to write
2909 4177 1     FOREIGN_BUFFER,                        | pointer to foreign CB or 0
2910 4178 1     ) : JSB_PUT-NOVALUE -
2911 4179 1
2912 4180 1 ++
2913 4181 1 FUNCTIONAL DESCRIPTION:
2914 4182 1
2915 4183 1     Check for a foreign buffer and point to it if necessary.
2916 4184 1     Write one record. If successful then return; otherwise, signal a fatal
2917 4185 1     error.
2918 4186 1
2919 4187 1 FORMAL PARAMETERS:
2920 4188 1
2921 4189 1     COUNT.rl.v          No. of bytes to write
2922 4190 1     FOREIGN_BUFFER.rl.v  pointer to foreign CB or 0
2923 4191 1
2924 4192 1 IMPLICIT INPUTS:
2925 4193 1
2926 4194 1     RAB$$_UBF          for the foreign buffer (buffer pointer)
2927 4195 1     RAB$$_USZ          for the foreign buffer (buffer size)
2928 4196 1
2929 4197 1 IMPLICIT OUTPUTS:
2930 4198 1
2931 4199 1     RAB$$_RSZ          length of record to write (file buffer)
2932 4200 1     RAB$$_RBF          pointer to file CB
2933 4201 1     LUB$$_LOG_RECNO    logical record number
2934 4202 1     RAB$$_RAC          record access field
2935 4203 1
2936 4204 1 ROUTINE VALUE:
2937 4205 1
2938 4206 1     NONE
2939 4207 1
2940 4208 1 SIDE EFFECTS:
2941 4209 1
2942 4210 1     SIGNALs any RMS errors
2943 4211 1 --
2944 4212 1
2945 4213 2 BEGIN
2946 4214 2
2947 4215 2 EXTERNAL REGISTER
2948 4216 2     CCB : REF BLOCK [, BYTE];
2949 4217 2
2950 4218 2 LOCAL
2951 4219 2     RMS_STATUS;
2952 4220 2
2953 4221 2 MAP
2954 4222 2     FOREIGN_BUFFER : REF BLOCK [, BYTE];
2955 4223 2
2956 4224 2 ++
2957 4225 2     Set the recordsize field in the RAB based on COUNT.
2958 4226 2     Set the record address field in the RAB to the user buffer.
2959 4227 2     Set the record access field in the RAB to relative. Perform the PUT.
2960 4228 2     If RMS returns a failure status, signal the error.
2961 4229 2 --
2962 4230 2
2963 4231 2     CCB [RAB$$_RSZ] = .COUNT;
```

```

: 2964      4232 2      CCB [RAB$B_RAC] = RAB$C_KEY;
: 2965      4233 2
: 2966      4234 2      IF .FOREIGN_BUFFER NEQA 0
: 2967      4235 2      THEN
: 2968      4236 2
: 2969      4237 2      + There is a foreign buffer. Point off to the buffer but don't do the
: 2970      4238 2      size. A PUT with count would not work right, so the size is passed in.
: 2971      4239 2      -
: 2972      4240 2      CCB [RAB$L_UBF] = CCB [RAB$L_RBF] = .FOREIGN_BUFFER [RAB$L_UBF]
: 2973      4241 2      ELSE
: 2974      4242 2      CCB [RAB$L_RBF] = .CCB [RAB$L_UBF];
: 2975      4243 2
: 2976      4244 2      RMS_STATUS = $PUT (RAB = .CCB);
: 2977      4245 2
: 2978      4246 2      IF .RMS_STATUS EQL RMSS$_CONTROL
: 2979      4247 2      THEN
: 2980      4248 2      BAS$$SIGNAL_CTRL ();
: 2981      4249 2
: 2982      4250 2      IF NOT .RMS_ ATUS
: 2983      4251 2      THEN
: 2984      4252 2      BEGIN
: 2985      4253 2      +
: 2986      4254 3      We cannot call GET_ERROR because we must restore UBF and USZ.
: 2987      4255 3      -
: 2988      4256 3
: 2989      4257 3      WHILE (.CCB [RAB$L_STS] EQL RMSS$RSA) DO
: 2990      4258 4      BEGIN
: 2991      4259 4      $WAIT (RAB = .CCB);
: 2992      4260 4      $PUT (RAB = .CCB);
: 2993      4261 3      END;
: 2994      4262 3
: 2995      4263 2      END;
: 2996      4264 2
: 2997      4265 2      +
: 2998      4266 2      Restore RAB$L_UBF in case there was a foreign buffer.
: 2999      4267 2      -
: 3000      4268 2      CCB [RAB$L_UBF] = .CCB [LUB$A_UBF];
: 3001      4269 2      +
: 3002      4270 2      Point LUB$A_BUF_PTR off to the buffer used by RMS.
: 3003      4271 2      -
: 3004      4272 2      CCB [LUB$A_RBUF_ADR] = .CCB [RAB$L_UBF];
: 3005      4273 2      +
: 3006      4274 2      Any error remaining (which will be an error other than Record Stream
: 3007      4275 2      Active, RSA) is fatal.
: 3008      4276 2      -
: 3009      4277 2
: 3010      4278 2      IF ( NOT .CCB [RAB$L_STS]) THEN BAS$$STOP_IO (BAS$K_IOERR_REC);
: 3011      4279 2
: 3012      4280 2      RETURN;
: 3013      4281 1      END;
                                     ! End of BAS$$REC_PRE
```

22	AB		51	B0	00003	MOVW	COUNT, 34(CCB)	4231
1E	AB		01	90	00007	MOVB	#1, 30(CCB)	4232
			50	D5	0000B	TSTL	FOREIGN_BUFFER	4234
			0E	13	0000D	BEQL	1\$	
	50	24	A0	D0	0000F	MOVL	36(FOREIGN_BUFFER), R0	4240
28	AB		50	D0	00013	MOVL	R0, 40(CCB)	
24	AB		50	D0	00017	MOVL	R0, 36(CCB)	
			05	11	0001B	BRB	2\$	
28	AB	24	A8	D0	0001D	1\$: MOVL	36(CCB), 40(CCB)	4242
			5B	DD	00022	2\$: PUSHL	CCB	4244
00000000G	00		01	FB	00024	CALLS	#1, SYSS\$PUT	
	6E		50	D0	0002B	MOVL	R0, RMS_STATUS	
00010651	8F		6E	D1	0002E	CMPL	RMS_STATUS, #67153	4246
			07	12	00035	BNEQ	3\$	
00000000G	00		00	FB	00037	CALLS	#0, BAS\$\$SIGNAL_CTRL	4248
	1E		6E	E8	0003E	3\$: BLBS	RMS_STATUS, 5\$	4250
000182DA	8F	08	AB	D1	00041	4\$: CMPL	8(CCB), #99034	4257
			14	12	00049	BNEQ	5\$	
			5B	DD	0004B	PUSHL	CCB	4259
00000000G	00		01	FB	0004D	CALLS	#1, SYSS\$WAIT	
			5B	DD	00054	PUSHL	CCB	4260
00000000G	00		01	FB	00056	CALLS	#1, SYSS\$PUT	
			E2	11	0005D	BRB	4\$	4257
	24	9C	AB	D0	0005F	5\$: MOVL	-100(CCB), 36(CCB)	4268
	EC	24	AB	D0	00064	MOVL	36(CCB), -20(CCB)	4272
	0A	08	AB	E8	00069	BLBS	8(CCB), 6\$	4278
	7E		01	CE	0006D	MNEGL	#1, -(SP)	
00000000G	00		01	FB	00070	CALLS	#1, BAS\$\$STOP_10	
	5E		04	C0	00077	6\$: ADDL2	#4, SP	4281
			05	00	0007A	RSB		

: Routine Size: 123 bytes, Routine Base: _BAS\$CODE + 0A76

: 3014 4282 1

```
3016 4283 1 GLOBAL ROUTINE BASS$REC_FSE ( ! FIND (sequential) a record
3017 4284 1 LOCK_FLAGS
3018 4285 1 ) : JSB_REC2 NOVALUE =
3019 4286 1
3020 4287 1 !++
3021 4288 1 FUNCTIONAL DESCRIPTION:
3022 4289 1
3023 4290 1 Find next record. If successful then return; otherwise, signal a fatal
3024 4291 1 error.
3025 4292 1
3026 4293 1 FORMAL PARAMETERS:
3027 4294 1
3028 4295 1 LOCK_FLAGS.rlu.v bits to set in the RAB ROP to control manual
3029 4296 1 record locking (0 if none)
3030 4297 1
3031 4298 1 IMPLICIT INPUTS:
3032 4299 1
3033 4300 1 NONE
3034 4301 1
3035 4302 1 IMPLICIT OUTPUTS:
3036 4303 1
3037 4304 1 RAB$B_RAC record access field
3038 4305 1
3039 4306 1 ROUTINE VALUE:
3040 4307 1
3041 4308 1 NONE
3042 4309 1
3043 4310 1 SIDE EFFECTS:
3044 4311 1
3045 4312 1 Finds next record in file on this logical unit.
3046 4313 1 SIGNALs any RMS errors
3047 4314 1 !--
3048 4315 1
3049 4316 2 BEGIN
3050 4317 2
3051 4318 2 EXTERNAL REGISTER
3052 4319 2 CCB : REF BLOCK [, BYTE];
3053 4320 2
3054 4321 2 LOCAL
3055 4322 2 RMS_STATUS;
3056 4323 2
3057 4324 2 !+
3058 4325 2 Set the record access field in the RAB to sequential. Perform the FIND.
3059 4326 2 If RMS returns a failure status, signal the error.
3060 4327 2 !-
3061 4328 2
3062 4329 2 CCB [RAB$B_RAC] = RAB$C_SEQ;
3063 4330 2
3064 4331 2 !+
3065 4332 2 Set bits in RAB ROP without clearing ULK.
3066 4333 2 !-
3067 4334 2
3068 4335 2 CCB [RAB$L_ROP] = .CCB [RAB$L_ROP] OR .LOCK_FLAGS;
3069 4336 2
3070 4337 2 !+
3071 4338 2 perform the FIND.
3072 4339 2 !-
```

```
: 3073      4340  2
: 3074      4341  2
: 3075      4342  2
: 3076      4343  2
: 3077      4344  2
: 3078      4345  2
: 3079      4346  2
: 3080      4347  2
: 3081      4348  2
: 3082      4349  2
: 3083      4350  2
: 3084      4351  2
: 3085      4352  2
: 3086      4353  2
: 3087      4354  2
: 3088      4355  2
: 3089      4356  2
: 3090      4357  1

RMS_STATUS = $FIND (RAB = .CCB);
!+
! Turn off bits so that subsequent operations will not inherit them.
!-
CCB [RAB$L_ROP] = .CCB [RAB$L_ROP] XOR .LOCK_FLAGS;
!+
! signal if the FIND failed.
!-
IF NOT .RMS_STATUS
THEN
    BAS$$STOP_IO (BAS$K_IOERR_REC);

RETURN;
END;
```

! End of BAS\$\$REC_FSE

```
.EXTRN  SY$$FIND

52 DD 00000 BAS$$REC_FSE::
      52      50 D0 00002      PUSHL  R2
      1E      AB 94 00005      MOVL   R0, R2
      04 AB      52 C8 00008      CLRB   30(CCB)
      00000000G 00      5B DD 0000C      BISL2  LOCK_FLAGS, 4(CCB)
      04 AB      01 FB 0000E      PUSHL  CCB
      0A      52 CC 00015      CALLS  #1, SY$$FIND
      7E      50 E8 00019      XORL2  LOCK_FLAGS, 4(CCB)
      00000000G 00      01 CE 0001C      BLBS   RMS_STATUS, 1$
      01 FB 0001F      MNEGL  #1, -(SP)
      04 BA 00026 1$:      CALLS  #1, BAS$$STOP_IO
      05 00028      POPR   #^M<R2>
      RSB
```

; Routine Size: 41 bytes, Routine Base: _BAS\$CODE + 0AF1

```
3092 4358 1 GLOBAL ROUTINE BAS$$REC_FRFA ( ! FIND (by RFA) a record
3093 4359 1 LOCK_FLAGS
3094 4360 1 ) : JSB_REC2 NOVALUE =
3095 4361 1
3096 4362 1 ++
3097 4363 1 FUNCTIONAL DESCRIPTION:
3098 4364 1
3099 4365 1 Find record by RFA stored in the RAB. If successful then return; otherwise, signal a fatal
3100 4366 1 error.
3101 4367 1
3102 4368 1 FORMAL PARAMETERS:
3103 4369 1
3104 4370 1 LOCK_FLAGS.rlu.v bits to set in the RAB ROP to control manual
3105 4371 1 record locking (0 if none)
3106 4372 1
3107 4373 1 IMPLICIT INPUTS:
3108 4374 1
3109 4375 1 NONE
3110 4376 1
3111 4377 1 IMPLICIT OUTPUTS:
3112 4378 1
3113 4379 1 RAB$B_RAC record access field
3114 4380 1
3115 4381 1 ROUTINE VALUE:
3116 4382 1
3117 4383 1 NONE
3118 4384 1
3119 4385 1 SIDE EFFECTS:
3120 4386 1
3121 4387 1 Finds next record in file on this logical unit.
3122 4388 1 SIGNALs any RMS errors
3123 4389 1 --
3124 4390 1
3125 4391 2 BEGIN
3126 4392 2
3127 4393 2 EXTERNAL REGISTER
3128 4394 2 CCB : REF BLOCK [, BYTE];
3129 4395 2
3130 4396 2 LOCAL
3131 4397 2 RMS_STATUS;
3132 4398 2
3133 4399 2 ++
3134 4400 2 Set the record access field in the RAB to sequential. Perform the FIND.
3135 4401 2 If RMS returns a failure status, signal the error.
3136 4402 2 --
3137 4403 2
3138 4404 2 CCB [RAB$B_RAC] = RAB$C_RFA;
3139 4405 2
3140 4406 2 ++
3141 4407 2 Set bits in RAB ROP without clearing ULK.
3142 4408 2 --
3143 4409 2
3144 4410 2 CCB [RAB$L_ROP] = .CCB [RAB$L_ROP] OR .LOCK_FLAGS;
3145 4411 2
3146 4412 2 ++
3147 4413 2 perform the FIND.
3148 4414 2 --
```



```

: 3149      4415  2
: 3150      4416  2
: 3151      4417  2
: 3152      4418  2
: 3153      4419  2
: 3154      4420  2
: 3155      4421  2
: 3156      4422  2
: 3157      4423  2
: 3158      4424  2
: 3159      4425  2
: 3160      4426  2
: 3161      4427  2
: 3162      4428  2
: 3163      4429  2
: 3164      4430  2
: 3165      4431  2
: 3166      4432  1

RMS_STATUS = $FIND (RAB = .CCB);

!+
!- Turn off bits so that subsequent operations will not inherit them.
!-

CCB [RAB$L_ROP] = .CCB [RAB$L_ROP] XOR .LOCK_FLAGS;

!+
!- Signal if the FIND failed.
!-

IF NOT .RMS_STATUS
THEN
    BAS$$STOP_IO (BAS$K_IOERR_REC);

RETURN;
END;
! End of BAS$$REC_FRFA

```

		52	DD	00000	BAS\$\$REC_FRFA::			
					PUSHL	R2		: 4358
		50	D0	00002	MOVL	R0, R2		: 4404
1E	AB	02	90	00005	MOVB	#2, 30(CCB)		: 4410
04	AB	52	C8	00009	BISL2	LOCK_FLAGS, 4(CCB)		: 4416
		5B	DD	0000D	PUSHL	CCB		: 4422
00000000G	00	01	FB	0000F	CALLS	#1, SYSS\$FIND		: 4427
04	AB	52	CC	00016	XORL2	LOCK_FLAGS, 4(CCB)		: 4429
	0A	50	E8	0001A	BLBS	RMS_STATUS, 1\$		: 4432
	7E	01	CE	0001D	MNEGL	#1, -(SP)		
00000000G	00	01	FB	00020	CALLS	#1, BAS\$\$STOP_IO		
		04	BA	00027	POPR	#^M<R2>		
		05	00	0029	RSB			

: Routine Size: 42 bytes, Routine Base: _BAS\$CODE + 0B1A

```

: 3167      4433  1
: 3168      4434  1

```

```
3170 4435 1 GLOBAL ROUTINE BAS$$REC_FRE (          ! FIND (relative) a record
3171 4436 1     LOCK_FLAGS
3172 4437 1 ) : JSB_REC0 NOVALUE =
3173 4438 1
3174 4439 1 ++
3175 4440 1 FUNCTIONAL DESCRIPTION:
3176 4441 1
3177 4442 1     Find next record.  If successful then return; otherwise, signal a fatal
3178 4443 1     error.
3179 4444 1
3180 4445 1 FORMAL PARAMETERS:
3181 4446 1
3182 4447 1     LOCK_FLAGS.rlu.v      bits to set in the RAB ROP to control manual
3183 4448 1                          record locking (0 if none)
3184 4449 1
3185 4450 1 IMPLICIT INPUTS:
3186 4451 1
3187 4452 1     NONE
3188 4453 1
3189 4454 1 IMPLICIT OUTPUTS:
3190 4455 1
3191 4456 1     RAB$B_RAC              record access field
3192 4457 1
3193 4458 1 ROUTINE VALUE:
3194 4459 1
3195 4460 1     NONE
3196 4461 1
3197 4462 1 SIDE EFFECTS:
3198 4463 1
3199 4464 1     SIGNALs any RMS errors
3200 4465 1 --
3201 4466 1
3202 4467 2 BEGIN
3203 4468 2
3204 4469 2 EXTERNAL REGISTER
3205 4470 2     CCB : REF BLOCK [, BYTE];
3206 4471 2
3207 4472 2 LOCAL
3208 4473 2     RMS_STATUS;
3209 4474 2
3210 4475 2 ++
3211 4476 2     Set the record access field in the RAB to sequential.  Perform the FIND.
3212 4477 2     If RMS returns a failure status, signal the error.
3213 4478 2 --
3214 4479 2
3215 4480 2 CCB [RAB$B_RAC] = RAB$C_KEY;
3216 4481 2
3217 4482 2 ++
3218 4483 2     Set bits in the RAB ROP without clearing ULK.
3219 4484 2 --
3220 4485 2
3221 4486 2 CCB [RAB$L_ROP] = .CCB [RAB$L_ROP] OR .LOCK_FLAGS;
3222 4487 2
3223 4488 2 ++
3224 4489 2     perform the FIND.
3225 4490 2 --
3226 4491 2
```



```

: 3227      4492  2  RMS_STATUS = $FIND (RAB = .CCB);
: 3228      4493  2
: 3229      4494  2
: 3230      4495  2  !+
: 3231      4496  2  ! Turn off bits in the RAB ROP so that subsequent operations do not
: 3232      4497  2  ! inherit them.
: 3233      4498  2  !-
: 3234      4499  2  CCB [RAB$L_ROP] = .CCB [RAB$L_ROP] XOR .LOCK_FLAGS;
: 3235      4500  2
: 3236      4501  2  !+
: 3237      4502  2  ! Signal if the FIND failed.
: 3238      4503  2  !-
: 3239      4504  2  IF NOT .RMS_STATUS
: 3240      4505  2  THEN
: 3241      4506  2      BAS$$STOP_IO (BAS$V_IOERR_REC);
: 3242      4507  2
: 3243      4508  2  RETURN;
: 3244      4509  1  END;

```

! End of BAS\$\$REC_FRE

1E	AB	01	90 00000	BAS\$\$REC_FRE::		
				MOVB	#1, 30(CCB)	: 4480
04	AB	04	AE C8 00004	BISL2	LOCK_FLAGS, 4(CCB)	: 4486
			5B DD 00009	PUSHL	CCB	: 4492
00000000G	00		01 FB 0000B	CALLS	#1, SYSS\$FIND	: 4499
04	AB	04	AE CC 00012	XORL2	LOCK_FLAGS, 4(CCB)	: 4504
	0A		50 E8 00017	BLBS	RMS_STATUS, 1\$	: 4506
	7E		01 CE 0001A	MNEGL	#1, -(SP)	: 4509
00000000G	00		01 FB 0001D	CALLS	#1, BAS\$\$STOP_IO	
			05 00024 1\$:	RSB		

; Routine Size: 37 bytes, Routine Base: _BAS\$CODE + 0B44

; 3245 4510 1

```
3247 4511 1 GLOBAL ROUTINE BASS$REC_FIN (      ! FIND (indexed) a record
3248 4512 1     KEY_NO, REL_OP, KEY, LOCK_FLAGS) : JSB_REC_IND1 NOVALUE =
3249 4513 1
3250 4514 1  **
3251 4515 1  FUNCTIONAL DESCRIPTION:
3252 4516 1
3253 4517 1      Find indicated record.  If successful then return; otherwise, signal a fatal
3254 4518 1      error.
3255 4519 1
3256 4520 1  FORMAL PARAMETERS:
3257 4521 1
3258 4522 1      KEY_NO.rl.v      key of reference
3259 4523 1      REL_OP.rl.v      relational operator for key
3260 4524 1      KEY.rt.dx      key to search for
3261 4525 1      LOCK_FLAGS.rlu.v  bits to set in the RAB ROP to control
3262 4526 1                      manual record locking (0 if none)
3263 4527 1
3264 4528 1  IMPLICIT INPUTS:
3265 4529 1
3266 4530 1      NONE
3267 4531 1
3268 4532 1  IMPLICIT OUTPUTS:
3269 4533 1
3270 4534 1      RAB$K_KBF      pointer to the desired key value
3271 4535 1      RAB$K_KSZ      size of desired key value
3272 4536 1      RAB$K_KGE      relational in RAB$K_ROP indicating greater than
3273 4537 1                      or equal
3274 4538 1      RAB$K_KGT      relational in RAB$K_ROP indicating greater than
3275 4539 1      RAB$K_KRF      indicates key of reference
3276 4540 1      RAB$K_RAC      record access field
3277 4541 1
3278 4542 1  ROUTINE VALUE:
3279 4543 1
3280 4544 1      NONE
3281 4545 1
3282 4546 1  SIDE EFFECTS:
3283 4547 1
3284 4548 1      See RMS Reference manual for discussion on whether match will be exact,
3285 4549 1      generic, approximate, or generic-approximate.
3286 4550 1      SIGNALS any RMS errors
3287 4551 1  --
3288 4552 1
3289 4553 2  BEGIN
3290 4554 2
3291 4555 2  EXTERNAL REGISTER
3292 4556 2      (CB : REF BLOCK [, BYTE]);
3293 4557 2
3294 4558 2  MAP
3295 4559 2      KEY : REF BLOCK [8, BYTE];
3296 4560 2
3297 4561 2  LITERAL
3298 4562 2      K_EQUAL = 0,      ! search for key equal
3299 4563 2      K_GREATER_EQUAL = 1, ! search for key GEQ
3300 4564 2      K_GREATER_THAN = 2; ! search for key GTR
3301 4565 2
3302 4566 2  LOCAL
3303 4567 2      RMS_STATUS;
```

```
3304 4568 2
3305 4569 2
3306 4570 2
3307 4571 2
3308 4572 2
3309 4573 2
3310 4574 2
3311 4575 2
3312 4576 2
3313 4577 2
3314 4578 2
3315 4579 3
3316 4580 3
3317 4581 3
3318 4582 3
3319 4583 2
3320 4584 2
3321 4585 2
3322 4586 2
3323 4587 2
3324 4588 2
3325 4589 2
3326 4590 2
3327 4591 2
3328 4592 3
3329 4593 3
3330 4594 3
3331 4595 2
3332 4596 2
3333 4597 2
3334 4598 3
3335 4599 3
3336 4600 3
3337 4601 2
3338 4602 2
3339 4603 2
3340 4604 2
3341 4605 2
3342 4606 2
3343 4607 2
3344 4608 2
3345 4609 2
3346 4610 2
3347 4611 2
3348 4612 2
3349 4613 2
3350 4614 2
3351 4615 2
3352 4616 2
3353 4617 2
3354 4618 2
3355 4619 2
3356 4620 2
3357 4621 2
3358 4622 2
3359 4623 2
3360 4624 2
```

```
+
Set the key buffer field, the key size field, the key of reference,
and the relational bits in the ROP.
Set the record access field in the RAB to key. Perform the FIND.
If RMS returns a failure status, signal the error.
-
```

```
CCB [RAB$B_RAC] = RAB$C_KEY;
CCB [RAB$L_KBF] = .KEY [DSC$A_POINTER];
CCB [RAB$B_KRF] = .KEY_NO;
CCB [RAB$B_KSZ] = (IF .KEY [DSC$B_DTYPE] NEQ DSC$K_DTYPE_P
THEN
    .KEY [DSC$W_LENGTH]
ELSE
    (.KEY [DSC$W_LENGTH]/2 + 1));
```

```
CASE .REL_OP FROM K_EQUAL TO K_GREATER_THAN OF
SET
```

```
[K_EQUAL] :
    CCB [RAB$V_KGE] = CCB [RAB$V_KGT] = 0;
```

```
[K_GREATER_EQUAL] :
    BEGIN
        CCB [RAB$V_KGE] = 1;
        CCB [RAB$V_KGT] = 0;
    END;
```

```
[K_GREATER_THAN] :
    BEGIN
        CCB [RAB$V_KGT] = 1;
        CCB [RAB$V_KGE] = 0;
    END;
```

```
TES;
```

```
+
Set bits in the RAB ROP without clearing ULK.
-
```

```
CCB [RAB$L_ROP] = .CCB [RAB$L_ROP] OR .LOCK_FLAGS;
```

```
+
perform the FIND.
-
```

```
RMS_STATUS = $FIND (RAB = .CCB);
```

```
+
Turn off bits in the RAB ROP so that subsequent operations do not
inherit them.
-
```

```
CCB [RAB$L_ROP] = .CCB [RAB$L_ROP] XOR .LOCK_FLAGS;
```

```
+
Signal if the FIND failed.
```

```
: 3361      4625  2      !-
: 3362      4626  2      IF NOT .RMS_STATUS
: 3363      4627  2      THEN
: 3364      4628  2      BAS$$STOP_IO (BAS$K_IOERR_REC);
: 3365      4629  2
: 3366      4630  2      RETURN;
: 3367      4631  1      END;
```

! End of BAS\$\$REC_FIN

			52	DD	00000	BAS\$\$REC_FIN::			
						PUSHL	R2	: 4511	
	1E	AB		01	90	00002	MOVB	#1, 30(CCB)	: 4576
	30	AB	04	A2	D0	00006	MOVL	4(KEY), 48(CCB)	: 4577
	35	AB		50	90	0000B	MOVB	KEY NO, 53(CCB)	: 4578
		15	02	A2	91	0000F	CMPB	2(KEY), #21	: 4579
				05	13	00013	BEQL	1\$	
		52		62	3C	00015	MOVZWL	(KEY), R2	: 4581
				08	11	00018	BRB	2\$	
		52		62	3C	0001A	MOVZWL	(KEY), R2	: 4583
		52		02	C6	0001D	DIVL2	#2, R2	
				52	D6	00020	INCL	R2	
	34	AB		52	90	00022	MOVW	R2, 52(CCB)	: 4579
		52	04	AB	9E	00026	MOVAB	4(CCB), R2	: 4589
		00		51	CF	0002A	CASEL	REL OP, #0, #2	: 4585
02						0002E	.WORD	4\$-3\$,-	
0018		000D	0006					5\$-3\$,-	
								6\$-3\$	
	02	A2	40	8F	8A	00034	BICB2	#64, 2(R2)	: 4589
				10	11	00039	BRB	7\$	
	02	A2		20	88	0003B	BISB2	#32, 2(R2)	: 4593
	02	A2	40	8F	8A	0003F	BICB2	#64, 2(R2)	: 4594
				09	11	00044	BRB	8\$	: 4585
	02	A2	40	8F	88	00046	BISB2	#64, 2(R2)	: 4599
	02	A2		20	8A	0004B	BICB2	#32, 2(R2)	: 4600
		62		53	C8	0004F	BISL2	LOCK_FLAGS, (R2)	: 4608
				5B	DD	00052	PUSHL	CCB	: 4614
00000000G	00			01	FB	00054	CALLS	#1, SYSS\$FIND	
	62			53	CC	0005B	XORL2	LOCK_FLAGS, (R2)	: 4621
	0A			50	E8	0005E	BLBS	RMS_STATUS, 9\$	: 4626
	7E			01	CE	00061	MNEGL	#1, -(SP)	: 4628
00000000G	00			01	FB	00064	CALLS	#1, BAS\$\$STOP_IO	
			04	BA	0006B	9\$:	POPR	#^M<R2>	: 4631
				05	0006D		RSB		

: Routine Size: 110 bytes, Routine Base: _BAS\$CODE + 0B69

: 3368 4632 1

```

: 3370 4633 1 GLOBAL ROUTINE BAS$$REC_DSE . DELETE (sequential) a record
: 3371 4634 1 : JSB_RECO NOVALUE =
: 3372 4635 1
: 3373 4636 1 +
: 3374 4637 1 FUNCTIONAL DESCRIPTION:
: 3375 4638 1
: 3376 4639 1 Delete current record. If successful then return; otherwise, signal a fatal
: 3377 4640 1 error.
: 3378 4641 1
: 3379 4642 1 FORMAL PARAMETERS:
: 3380 4643 1
: 3381 4644 1 NONE
: 3382 4645 1
: 3383 4646 1 IMPLICIT INPUTS:
: 3384 4647 1
: 3385 4648 1 NONE
: 3386 4649 1
: 3387 4650 1 IMPLICIT OUTPUTS:
: 3388 4651 1
: 3389 4652 1 RAB$B_RAC record access field
: 3390 4653 1
: 3391 4654 1 ROUTINE VALUE:
: 3392 4655 1
: 3393 4656 1 NONE
: 3394 4657 1
: 3395 4658 1 SIDE EFFECTS:
: 3396 4659 1
: 3397 4660 1 SIGNALS any RMS errors
: 3398 4661 1 --
: 3399 4662 1
: 3400 4663 2 BEGIN
: 3401 4664 2
: 3402 4665 2 EXTERNAL REGISTER
: 3403 4666 2 CCB : REF BLOCK [, BYTE];
: 3404 4667 2
: 3405 4668 2 +
: 3406 4669 2 Set the record access field in the RAB to sequential. Perform the DELETE.
: 3407 4670 2 If RMS returns a failure status, signal the error.
: 3408 4671 2 -
: 3409 4672 2
: 3410 4673 2 CCB [RAB$B_RAC] = RAB$C_SEQ;
: 3411 4674 2
: 3412 4675 2 IF NOT $DELETE (RAB = .CCB) THEN BAS$$STOP_IO (BAS$K_IOERR_REC);
: 3413 4676 2
: 3414 4677 2 RETURN;
: 3415 4678 1 END; ! End of BAS$$REC_DSE

```

.EXTRN SYS\$DELETE

```

1E AB 04 0000 BAS$$REC_DSE::
          5B DD 00003 CLR 30(CCB)
          01 FB 00005 PUSH  CCB
          50 E8 0000C CALLS #1, SYS$DELETE
          01 CE 0000F BLBS  R0, 1$
          MNEGL #1, -(SP)
00000000G 00
          0A
          7E

```

```

: 4673
: 4675
:
:
:

```

BAS\$\$REC_PROC
1-095

G 11
16-Sep-1984 01:01:12 VAX-11 Bliss-32 V4.0-742
14-Sep-1984 11:56:35 [BASRTL.SRC]BASRECPRO.B32;1

Page 92
(34)

00000000G 00

01 FB 00012 CALLS #1, BAS\$\$STOP_IO
05 00019 1s. RSB

:
: 4678

: Routine Size: 26 bytes, Routine Base: _BAS\$CODE + 0BD7

: 3416 4679 1


```
3418 4680 1 GLOBAL ROUTINE BAS$$REC_UNL ! UNLOCK a record
3419 4681 1 : JSB_RECO NOVALUE =
3420 4682 1
3421 4683 1 !++
3422 4684 1 FUNCTIONAL DESCRIPTION:
3423 4685 1
3424 4686 1 Unlock the current record. If successful or no records locked,
3425 4687 1 then return; otherwise, signal a fatal error.
3426 4688 1
3427 4689 1 FORMAL PARAMETERS:
3428 4690 1
3429 4691 1 NONE
3430 4692 1
3431 4693 1 IMPLICIT INPUTS:
3432 4694 1
3433 4695 1 NONE
3434 4696 1
3435 4697 1 IMPLICIT OUTPUTS:
3436 4698 1
3437 4699 1 RAB$B_RAC record access field
3438 4700 1
3439 4701 1 ROUTINE VALUE:
3440 4702 1
3441 4703 1 NONE
3442 4704 1
3443 4705 1 SIDE EFFECTS:
3444 4706 1
3445 4707 1 -- SIGNALs any RMS errors
3446 4708 1 --
3447 4709 1
3448 4710 2 BEGIN
3449 4711 2
3450 4712 2 EXTERNAL REGISTER
3451 4713 2 CCB : REF BLOCK [, BYTE];
3452 4714 2
3453 4715 2 !+
3454 4716 2 Set the record access field in the RAB to sequential. Perform the UNLOCK.
3455 4717 2 If RMS returns a failure status, signal the error.
3456 4718 2 !-
3457 4719 2
3458 4720 2 CCB [RAB$B_RAC] = RAB$C_SEQ;
3459 4721 2
3460 4722 3 IF NOT $RELEASE (RAB = .CCB)
3461 4723 2 THEN
3462 4724 2
3463 4725 2 IF .CCB [RAB$L_STS] NEQ RMS$_RNL
3464 4726 2 THEN
3465 4727 2 !+
3466 4728 2 An error was returned, check for 'record not locked'.
3467 4729 2 !-
3468 4730 2 BAS$$STOP_IO (BAS$K_IOERR_REC);
3469 4731 2
3470 4732 2 RETURN;
3471 4733 1 END; ! End of BAS$$REC_UNL
```

.EXTRN SYSS\$RELEASE

	1E	AB	94	00000	BAS\$\$REC	UNL::		
		5B	DD	00003		CLRB	30(CCB)	: 4720
00000000G	00	01	FB	00005		PUSHL	CCB	: 4722
		50	E8	0000C		CALLS	#1, SYSS\$RELEASE	:
000181A0	8F	08	AB	D1 0000F		BLBS	R0, 1\$	:
		0A	13	00017		CMPL	8(CCB), #98720	: 4725
	7E	01	CE	00019		BEQL	1\$	:
00000000G	00	01	FB	0001C		MNEGL	#1, -(SP)	: 4730
		05	00023	1\$:		CALLS	#1, BAS\$\$STOP_IO	:
						RSB		: 4733

: Routine Size: 36 bytes, Routine Base: _BAS\$CODE + 0BF1

: 3472 4734 1


```
: 3474 4735 1 GLOBAL ROUTINE BAS$$REC_FEE ! FREE all locked records
: 3475 4736 1 : JSB_REC0 NOVALUE =
: 3476 4737 1
: 3477 4738 1 !++
: 3478 4739 1 FUNCTIONAL DESCRIPTION:
: 3479 4740 1
: 3480 4741 1 Free all locked records. If successful or no records locked,
: 3481 4742 1 then return; otherwise, signal a fatal error.
: 3482 4743 1
: 3483 4744 1 FORMAL PARAMETERS:
: 3484 4745 1
: 3485 4746 1 NONE
: 3486 4747 1
: 3487 4748 1 IMPLICIT INPUTS:
: 3488 4749 1
: 3489 4750 1 NONE
: 3490 4751 1
: 3491 4752 1 IMPLICIT OUTPUTS:
: 3492 4753 1
: 3493 4754 1 RAB$B_RAC record access field
: 3494 4755 1
: 3495 4756 1 ROUTINE VALUE:
: 3496 4757 1
: 3497 4758 1 NONE
: 3498 4759 1
: 3499 4760 1 SIDE EFFECTS:
: 3500 4761 1
: 3501 4762 1 SIGNALs any RMS errors
: 3502 4763 1 --
: 3503 4764 1
: 3504 4765 2 BEGIN
: 3505 4766 2
: 3506 4767 2 EXTERNAL REGISTER
: 3507 4768 2 CCB : REF BLOCK [, BYTE];
: 3508 4769 2
: 3509 4770 2 !+
: 3510 4771 2 Set the record access field in the RAB to sequential. Perform the FREE.
: 3511 4772 2 If RMS returns a failure status, signal the error.
: 3512 4773 2 !-
: 3513 4774 2
: 3514 4775 2 CCB [RAB$B_RAC] = RAB$C_SEQ;
: 3515 4776 2
: 3516 4777 3 IF NOT $FREE (RAB = .CCB)
: 3517 4778 2 THEN
: 3518 4779 2
: 3519 4780 2 IF .CCB [RAB$L_STS] NEQ RMS$_RNL
: 3520 4781 2 THEN
: 3521 4782 2 !+
: 3522 4783 2 An error was returned, check for "record not locked".
: 3523 4784 2 !-
: 3524 4785 2 BAS$$STOP_IO (BAS$K_IOERR_REC);
: 3525 4786 2
: 3526 4787 2 RETURN;
: 3527 4788 1 END; ! End of BAS$$REC_FEE
```

.EXTRN SYSS\$FREE

	1E	AB	94	00000	BAS\$\$REC_FEE::		
		5B	DD	00003	CLRB	30(CCB)	: 4775
00000000G	00	01	FB	00005	PUSHL	CCB	: 4777
	14	50	E8	0000C	CALLS	#1, SYSS\$FREE	:
000181A0	8F	08	AB	D1 0000F	BLBS	R0, 1\$	:
	7E		0A	13 00017	CMPL	8(CCB), #98720	: 4780
00000000G	00		01	CE 00019	BEQL	1\$	:
			01	FB 0001C	MNEGL	#1, -(SP)	: 4785
			05	00023 1\$:	CALLS	#1, BAS\$\$STOP_10	:
					RSB		: 4788

; Routine Size: 36 bytes, Routine Base: _BAS\$CODE + 0C15

; 3528 4789 1

```

3530 4790 1 GLOBAL ROUTINE BAS$$REC_UPD ( ! UPDATE a record
3531 4791 1 COUNT ! No. of bytes in the record
3532 4792 1 ) : JSB_DO_WRITE NOVALUE =
3533 4793 1
3534 4794 1 ++
3535 4795 1 FUNCTIONAL DESCRIPTION:
3536 4796 1
3537 4797 1 Update current record. If successful then return; otherwise, signal a fatal
3538 4798 1 error.
3539 4799 1
3540 4800 1 FORMAL PARAMETERS:
3541 4801 1
3542 4802 1 COUNT.rl.v No. of bytes in record to update
3543 4803 1
3544 4804 1 IMPLICIT INPUTS:
3545 4805 1
3546 4806 1 NONE
3547 4807 1
3548 4808 1 IMPLICIT OUTPUTS:
3549 4809 1
3550 4810 1 RAB$B_RAC record access field
3551 4811 1 RAB$W_RSZ record size
3552 4812 1
3553 4813 1 ROUTINE VALUE:
3554 4814 1
3555 4815 1 NONE
3556 4816 1
3557 4817 1 SIDE EFFECTS:
3558 4818 1
3559 4819 1 Update current record in file on this logical unit.
3560 4820 1 SIGNALs any RMS errors
3561 4821 1 --
3562 4822 1
3563 4823 2 BEGIN
3564 4824 2
3565 4825 2 EXTERNAL REGISTER
3566 4826 2 CCB : REF BLOCK [, BYTE];
3567 4827 2
3568 4828 2 !+
3569 4829 2 Point RBF to the user buffer.
3570 4830 2 Set the record access field in the RAB to sequential. Perform the UPDATE.
3571 4831 2 If RMS returns a failure status, signal the error.
3572 4832 2 !-
3573 4833 2 CCB [RAB$L_RBF] = .CCB [RAB$L_UBF];
3574 4834 2 CCB [RAB$W_RSZ] = .COUNT;
3575 4835 2 CCB [RAB$B_RAC] = RAB$C_SEQ;
3576 4836 2
3577 4837 2 IF NOT $UPDATE (RAB = .CCB) THEN BAS$$STOP_IO (BAS$K_ICERR_REC);
3578 4838 2
3579 4839 2 !+
3580 4840 2 Point LUB$A_RBUF_ADR to the buffer used by RMS for MOVE.
3581 4841 2 !-
3582 4842 2 CCB [LUB$A_RBUF_ADR] = .CCB [RAB$L_UBF];
3583 4843 2 RETURN;
3584 4844 1 END; ! End of BAS$$REC_UPD

```

					.EXTRN SYSSUPDATE	
28	AB	24	AB	D0 00000	BAS\$\$REC UPD::	
					MOVL 36(CCB), 40(CCB)	: 4833
22	AB		5C	B0 00005	MOVW COUNT, 34(CCB)	: 4834
		1E	AB	94 00009	CLRB 30(CCB)	: 4835
			5B	DD 0000C	PUSHL CCB	: 4837
00000000G	00		01	FB 0000E	CALLS #1, SYSSUPDATE	:
	0A		50	E8 00015	BLBS R0, 1\$	:
	7E		01	CE 00018	MNEGL #1, -(SP)	:
00000000G	00		01	FB 0001B	CALLS #1, BAS\$\$STOP IO	:
	EC	24	AB	D0 00022 1\$:	MOVL 36(CCB), -20(CCB)	: 4842
			05	00027	RSB	: 4844

; Routine Size: 40 bytes, Routine Base: _BAS\$CODE + 0C39

; 3585 4845 1

```

: 3587      4846 1 GLOBAL ROUTINE BAS$$REC_RSE      ! RESTORE (sequential) to beginning of file
: 3588      4847 1 : JSB_RECO NOVALUE =
: 3589      4848 1
: 3590      4849 1 ++
: 3591      4850 1 FUNCTIONAL DESCRIPTION:
: 3592      4851 1
: 3593      4852 1     Rewind the file.  If successful then return; otherwise, signal a fatal
: 3594      4853 1     error.
: 3595      4854 1
: 3596      4855 1 FORMAL PARAMETERS:
: 3597      4856 1
: 3598      4857 1     NONE
: 3599      4858 1
: 3600      4859 1 IMPLICIT INPUTS:
: 3601      4860 1
: 3602      4861 1     NONE
: 3603      4862 1
: 3604      4863 1 IMPLICIT OUTPUTS:
: 3605      4864 1
: 3606      4865 1     RAB$B_RAC      record access field
: 3607      4866 1
: 3608      4867 1 ROUTINE VALUE:
: 3609      4868 1
: 3610      4869 1     NONE
: 3611      4870 1
: 3612      4871 1 SIDE EFFECTS:
: 3613      4872 1
: 3614      4873 1     SIGNALs any RMS errors
: 3615      4874 1 --
: 3616      4875 1
: 3617      4876 2 BEGIN
: 3618      4877 2
: 3619      4878 2 EXTERNAL REGISTER
: 3620      4879 2     CCB : REF BLOCK [, BYTE];
: 3621      4880 2
: 3622      4881 2 ++
: 3623      4882 2     Set the record access field in the RAB to sequential.  Perform the REWIND.
: 3624      4883 2     If RMS returns a failure status, signal the error.
: 3625      4884 2 --
: 3626      4885 2
: 3627      4886 2 CCB [RAB$B_RAC] = RAB$C_SEQ;
: 3628      4887 2
: 3629      4888 2 IF NOT $REWIND (RAB = .CCB) THEN BAS$$STOP_IO (BAS$K_IOERR_REC);
: 3630      4889 2
: 3631      4890 2 RETURN;
: 3632      4891 1 END;      ! End of BAS$$REC_RSE
```

.EXTRN SYSSREWIND

```

1E AB 94 00000 BAS$$REC_RSE::
                                CLR B 30(CCB)
                                PUSHL CCB
                                CALLS #1, SYSSREWIND
                                BLBS R0, 1$
                                MNEGL #1, -(SP)
```

```

00000000G 00
           0A
           7E
```

```

: 4886
: 4888
:
:
```

BAS\$\$REC_PROC
1-095

B 12
16-Sep-1984 0:01:12 VAX-11 Bliss-32 V4.0-742
14-Sep-1984 11:56:35 [BASRTL.SRC]BASRECPRO.B32;1

Page 100
(38)

00000000G 00

01 FB 00012 CALLS #1, BAS\$\$STOP_IO
05 00019 1\$: RSB

: 4891

; Routine Size: 26 bytes, Routine Base: _BAS\$CODE + 0C61

; 3633 4892 1


```
3635 4893 1 GLOBAL ROUTINE BAS$$REC_RIN (                ! RESTORE (indexed) to beginning of file
3636 4894 1     KEY_NO) : JSB_REC_IND NOVALUE =
3637 4895 1
3638 4896 1 ++
3639 4897 1 FUNCTIONAL DESCRIPTION:
3640 4898 1
3641 4899 1     Rewind the file.  If successful then return; otherwise, signal a fatal
3642 4900 1     error.
3643 4901 1
3644 4902 1 FORMAL PARAMETERS:
3645 4903 1
3646 4904 1     KEY_NO.rl.v                                key of reference
3647 4905 1
3648 4906 1 IMPLICIT INPUTS:
3649 4907 1
3650 4908 1     NONE
3651 4909 1
3652 4910 1 IMPLICIT OUTPUTS:
3653 4911 1
3654 4912 1     RAB$B_KRF                                key of reference
3655 4913 1     RAB$B_RAC                                record access field
3656 4914 1
3657 4915 1 ROUTINE VALUE:
3658 4916 1
3659 4917 1     NONE
3660 4918 1
3661 4919 1 SIDE EFFECTS:
3662 4920 1
3663 4921 1     SIGNALs any RMS errors
3664 4922 1 --
3665 4923 1
3666 4924 2 BEGIN
3667 4925 2
3668 4926 2 EXTERNAL REGISTER
3669 4927 2     (CB : REF BLOCK [, BYTE];
3670 4928 2
3671 4929 2 ++
3672 4930 2     Set the key of reference .
3673 4931 2     Set the record access field in the RAB to key.  Perform the REWIND.
3674 4932 2     If RMS returns a failure status, signal the error.
3675 4933 2     -
3676 4934 2
3677 4935 2     (CB [RAB$B_KRF] = .KEY_NO;
3678 4936 2     (CB [RAB$B_RAC] = RAB$C_KEY;
3679 4937 2
3680 4938 2 IF NOT $REWIND (RAB = .CCB) THEN BAS$$STOP_IO (BAS$K_IOERR_REC);
3681 4939 2
3682 4940 2 RETURN;
3683 4941 1 END;                                ! End of BAS$$REC_RIN
```

```
35 AB          50 90 00000 BAS$$REC_RIN::
1E AB          01 90 00004      MOVB KEY_NO, 53(CCB)
                                MOVB #1, -30(CCB)
```

```
: 4935
: 4936
```

BAS\$\$REC_PROC
1-095

D 12
16-Sep-1984 01:01:12
14-Sep-1984 11:56:35

VAX-11 Bliss-32 V4.0-742
[BASRTL.SRC]BASREC PRO.B32;1

Page 102
(39)

00000000G	00	5B	DD	00008	PUSHL	CCB
	0A	01	FB	0000A	CALLS	#1, SYSSREWIND
	7E	50	E8	00011	BLBS	R0, 1\$
00000000G	00	01	CE	00014	MNEGL	#1, -(SP)
		01	FB	00017	CALLS	#1, BAS\$\$STOP_10
		05	0001E	1\$:	RSB	

: 4938

: 4941

: Routine Size: 31 bytes, Routine Base: _BAS\$CODE + 0C7B

: 3684 4942 1


```

: 3686      4943 1 GLOBAL ROUTINE BAS$$REC_SSE                ! SCRATCH (sequential) a record
: 3687      4944 1   : JSB_RECO NOVALUE =
: 3688      4945 1
: 3689      4946 1
: 3690      4947 1 ++
: 3691      4948 1 FUNCTIONAL DESCRIPTION:
: 3692      4949 1     Truncate this file.  If successful then return; otherwise, signal a fatal
: 3693      4950 1     error.
: 3694      4951 1
: 3695      4952 1 FORMAL PARAMETERS:
: 3696      4953 1
: 3697      4954 1     NONE
: 3698      4955 1
: 3699      4956 1 IMPLICIT INPUTS:
: 3700      4957 1
: 3701      4958 1     NONE
: 3702      4959 1
: 3703      4960 1 IMPLICIT OUTPUTS:
: 3704      4961 1
: 3705      4962 1     RAB$B_RAC                record access field
: 3706      4963 1
: 3707      4964 1 ROUTINE VALUE:
: 3708      4965 1
: 3709      4966 1     NONE
: 3710      4967 1
: 3711      4968 1 SIDE EFFECTS:
: 3712      4969 1
: 3713      4970 1     SIGNALs any RMS errors
: 3714      4971 1 --
: 3715      4972 1
: 3716      4973 2 BEGIN
: 3717      4974 2
: 3718      4975 2 EXTERNAL REGISTER
: 3719      4976 2     CCB : REF BLOCK [, BYTE];
: 3720      4977 2
: 3721      4978 2 ++
: 3722      4979 2     Set the record access field in the RAB to sequential.  Perform the TRUNCATE.
: 3723      4980 2     If RMS returns a failure status, signal the error.
: 3724      4981 2     -
: 3725      4982 2
: 3726      4983 2 CCB [RAB$B_RAC] = RAB$C_SEQ;
: 3727      4984 2
: 3728      4985 2 IF NOT $TRUNCATE (RAB = .CCB) THEN BAS$$STOP_IO (BAS$K_IOERR_REC);
: 3729      4986 2
: 3730      4987 2 RETURN;
: 3731      4988 1 END;                                ! End of BAS$$REC_SSE
```

.EXTRN SYS\$TRUNCATE

```

1E AB 94 00000 BAS$$REC_SSE::
                                CLR 30(CCB)
                                PUSH CCB
                                CALL #1, SYS$TRUNCATE
                                BLBS R0, 1$
                                MNEGL #1, -(SP)
```

00000000G	00	5B	DD	00003
	0A	01	FB	00005
	7E	50	E8	0000C
		01	CE	0000F

: 4983
: 4985
:
:

BAS\$\$REC_PROC
1-095

F 12
16-Sep-1984 01:01:12 VAX-11 Bliss-32 V4.0-742
14-Sep-1984 11:56:35 [BASRTL.SRC]BASRECPRO.B32;1

Page 104
(40)

00000000G 00

01 FB 00012 CALLS #1, BAS\$\$STOP_IO
05 00019 1\$: RSB

:
: 4988

; Routine Size: 26 bytes, Routine Base: _BAS\$CODE + 0C9A

; 3732 4989 1

```
3734 4990 1 ROUTINE PUT_ERROR (          ! Here on error in $PUT
3735 4991 1     SIGNAL_OR_STOP          ! specifies whether to signal or stop
3736 4992 1     ) : CALL_CCB NOVALUE =
3737 4993 1
3738 4994 1 !++
3739 4995 1 ! FUNCTIONAL DESCRIPTION:
3740 4996 1
3741 4997 1     Here on $PUT errors, check for Record stream active error (RMS$_RSA)
3742 4998 1     If this error, WAIT until not active and try $PUT again.
3743 4999 1     This recovers from AST I/O which can occur out of the middle
3744 5000 1     of synchronous I/O at non-AST level.
3745 5001 1
3746 5002 1 ! CALLING SEQUENCE:
3747 5003 1
3748 5004 1     PUT_ERROR (signal_or_stop)
3749 5005 1
3750 5006 1 ! FORMAL PARAMETERS:
3751 5007 1
3752 5008 1     SIGNAL_OR_STOP.rl.v          whether to signal or stop
3753 5009 1
3754 5010 1 ! IMPLICIT INPUTS:
3755 5011 1
3756 5012 1     CCB                          Adr. of current LUB/ISB/RAB
3757 5013 1
3758 5014 1 ! IMPLICIT OUTPUTS:
3759 5015 1
3760 5016 1     LUB$V_OUTBUF_DR              Cleared to indicate clean buffer
3761 5017 1
3762 5018 1 ! ROUTINE VALUE:
3763 5019 1
3764 5020 1     NONE
3765 5021 1
3766 5022 1 ! SIDE EFFECTS:
3767 5023 1
3768 5024 1     $WAITs and then tries $PUT again, until success or any error
3769 5025 1     except record stream active.
3770 5026 1 --
3771 5027 1
3772 5028 2 BEGIN
3773 5029 2
3774 5030 2 EXTERNAL REGISTER
3775 5031 2     CCB : REF BLOCK [, BYTE];
3776 5032 2
3777 5033 2 WHILE .CCB [RAB$L_STS] EQL RMS$_RSA DO
3778 5034 3     BEGIN
3779 5035 3         $WAIT (RAB = .CCB);
3780 5036 4         $PUT (RAB = .CCB)
3781 5037 2     END;
3782 5038 2
3783 5039 2 IF NOT .CCB [RAB$L_STS]
3784 5040 2 THEN
3785 5041 3     BEGIN
3786 5042 3 !+
3787 5043 3 ! Clear the buffer dirty bit so if there is anything there BAS$CLOSE won't
3788 5044 3 ! get confused, and try to do another PUT.
3789 5045 3 --
3790 5046 3     CCB [LUB$V_OUTBUF_DR] = 0;
```

```

: 3791      5047 3
: 3792      5048 3
: 3793      5049 3
: 3794      5050 3
: 3795      5051 3
: 3796      5052 3
: 3797      5053 3
: 3798      5054 2
: 3799      5055 2
: 3800      5056 1

```

```

IF .SIGNAL_OR_STOP EQL K_SIGNAL
THEN
    BAS$$SIGNAL_IO (BAS$K_IOERR_REC)
ELSE
    BAS$$STOP_IO (BAS$K_IOERR_REC);

END;
RETURN;
END;

```

! End of PUT_ERROR

0000 00000 PUT_ERROR:						
000182DA	8F	08	AB D1 00002 1\$:	.WORD	Save nothing	: 4990
			14 12 0000A	CMPL	8(CCB), #99034	: 5033
			5B DD 0000C	BNEQ	2\$	
00000000G	00		01 FB 0000E	PUSHL	CCB	: 5035
			5B DD 00015	CALLS	#1, SYSSWAIT	
00000000G	00		01 FB 00017	PUSHL	CCB	: 5036
			E2 11 0001E	CALLS	#1, SYSSPUT	
	1F	08	AB E8 00020 2\$:	BRB	1\$	
FE	AB		08 8A 00024	BLBS	8(CCB), 4\$	: 5039
	01	04	AC D1 00028	BICB2	#8, -2(CCB)	: 5046
			0B 12 0002C	CMPL	SIGNAL_OR_STOP, #1	: 5048
	7E		01 CE 0002E	BNEQ	3\$	
00000000G	00		01 FB 00031	MNEGL	#1, -(SP)	: 5050
			04 00038	CALLS	#1, BAS\$\$SIGNAL_IO	
	7E		01 CE 00039 3\$:	RET		
00000000G	00		01 FB 0003C	MNEGL	#1, -(SP)	: 5052
			04 00043 4\$:	CALLS	#1, BAS\$\$STOP_IO	
				RET		: 5056

; Routine Size: 68 bytes, Routine Base: _BAS\$CODE + 0CB4

```
3802 5057 1 ROUTINE GET_ERROR (          ! Here on error on $GET
3803 5058 1     SIGNAL_OR_STOP          ! parameter to signal(continue) or stop
3804 5059 1     ) : CALL_CCB NOVALUE =
3805 5060 1
3806 5061 1 ++
3807 5062 1 FUNCTIONAL DESCRIPTION:
3808 5063 1
3809 5064 1     Here on $GET errors, check for Record stream active error (RMS$RSA)
3810 5065 1     If this error, WAIT until not active and try $GET again.
3811 5066 1     This recovers from AST I/O which can occur out of the middle
3812 5067 1     of synchronous I/O at non-AST level.
3813 5068 1
3814 5069 1 CALLING SEQUENCE:
3815 5070 1
3816 5071 1     JSB GET_ERROR ( )
3817 5072 1
3818 5073 1 FORMAL PARAMETERS:
3819 5074 1
3820 5075 1     NONE
3821 5076 1
3822 5077 1 IMPLICIT INPUTS:
3823 5078 1
3824 5079 1     CCB                      Adr. of current LUB/ISB/RAB
3825 5080 1
3826 5081 1 IMPLICIT OUTPUTS:
3827 5082 1
3828 5083 1 ROUTINE VALUE:
3829 5084 1
3830 5085 1     NONE
3831 5086 1
3832 5087 1 SIDE EFFECTS:
3833 5088 1
3834 5089 1     If this is an INPUT LINE and a ^Z error, then just return and it will
3835 5090 1     be handled above.
3836 5091 1     $WAITS and then tries $GET again, until success or any error
3837 5092 1     except record stream active.
3838 5093 1 --
3839 5094 1
3840 5095 2 BEGIN
3841 5096 2
3842 5097 2 EXTERNAL REGISTER
3843 5098 2     CCB : REF BLOCK [, BYTE];
3844 5099 2
3845 5100 2 ++
3846 5101 2 Set the prompt buffer length to zero so that error followed by RESUME will not
3847 5102 2 keep concatenating the prompt buffer.
3848 5103 2 --
3849 5104 2     CCB [RAB$B_PSZ] = 0;
3850 5105 2 ++
3851 5106 2 Is this INPUT LINE and only a ^Z in the record?
3852 5107 2 --
3853 5108 2
3854 5109 2 IF .CCB [ISB$B_STYM TYPE] EQL ISB$K_ST_TY_INL AND .CCB [RAB$W_RSZ] EQLU 1 AND .(CCB [RAB$L_RBF])<0, 8>
3855 5110 2     EQLU BAS$K_CONTROL_Z
3856 5111 2 THEN
3857 5112 2     RETURN;
3858 5113 2
```

```
: 3859      5114  2  WHILE .CCB [RAB$L_STS] EQL RMSS_RSA DO
: 3860      5115  3      BEGIN
: 3861      5116  3          $WAIT (RAB = .CCB);
: 3862      5117  4          $GET (RAB = .CCB)
: 3863      5118  2          END;
: 3864      5119  2
: 3865      5120  2  IF NOT .CCB [RAB$L_STS]
: 3866      5121  2  THEN
: 3867      5122  2
: 3868      5123  2      !+
: 3869      5124  2      ! Check the input parameter to see if we should signal or stop.
: 3870      5125  2      !-
: 3871      5126  2
: 3872      5127  2      IF .SIGNAL_OR_STOP EQL K_SIGNAL
: 3873      5128  2      THEN
: 3874      5129  2          BAS$$SIGNAL_IO (BAS$K_IOERR_REC)
: 3875      5130  2      ELSE
: 3876      5131  2          BAS$$STOP_IO (BAS$K_IOERR_REC);
: 3877      5132  2
: 3878      5133  2  RETURN;
: 3879      5134  1  END;
```

! End of GET_ERROR

0000 00000 GET_ERROR:						
		34	AB 94 00002	.WORD	Save nothing	: 5057
			CB 91 00005	CLRB	52(CCB)	: 5104
20	FF71		0C 12 0000A	CMPB	-143(CCB), #32	: 5109
01	22		AB B1 0000C	BNEQ	1\$	
			06 12 00010	CMPL	34(CCB), #1	
1A	28		BB 91 00012	BNEQ	1\$	
			3D 13 00016	CMPB	240(CCB), #26	: 5110
000182DA	8F	08	AB D1 00018 1\$:	BEQL	4\$	
			14 12 00020	CMPB	8(CCB), #99034	: 5114
			5B DD 00022	BNEQ	2\$	
00000000G	00		01 FB 00024	PUSHL	CCB	: 5116
			5B DD 0002B	CALLS	#1, SYSSWAI1	
00000000G	00		01 FB 0002D	PUSHL	CCB	: 5117
			E2 11 00034	CALLS	#1, SYSSGET	
	1B	08	AB E8 00036 2\$:	BRB	1\$	
	01	04	AC D1 0003A	BLBS	8(CCB), 4\$	: 5120
			0B 12 0003E	CMPL	SIGNAL_OR_STOP, #1	: 5127
	7E		01 CE C0040	BNEQ	3\$	
00000000G	00		01 FB 00043	MNEGL	#1, -(SP)	: 5129
			04 0004A	CALLS	#1, BAS\$\$SIGNAL_IO	
	7E		01 CE 0004B 3\$:	RET		
00000000G	00		01 FB 0004E	MNEGL	#1, -(SP)	: 5131
			04 00055 4\$:	CALLS	#1, BAS\$\$STOP_IO	
				RET		: 5134

: Routine Size: 86 bytes. Routine Base: _BAS\$CODE + 0CF8

```
: 3880      5135  1  END
: 3881      5136  1
```


BAS\$\$REC_PROC
1-095

K 12
16-Sep-1984 01:01:12
14-Sep-1984 11:56:35

VAX-11 Bliss-32 V4.0-742
[BASRTL.SRC]BASRECPRO.B32;1

Page 109
(42)

: 3882 5137 0 ELUDOM

BAS\$\$REC_WF9== BAS\$\$REC_WSL9
BAS\$\$REC_WF1== BAS\$\$REC_WSL1
BAS\$\$REC_WF0== BAS\$\$REC_WSL0

PSECT SUMMARY

Name	Bytes	Attributes
:_BAS\$DATA	6	NOVEC, WRT, RD, NOEXE, NOSHR, LCL, REL, CON, PIC, ALIGN(2)
:_BAS\$CODE	3406	NOVEC, NOWRT, RD, EXE, SHR, LCL, REL, CON, PIC, ALIGN(2)

Library Statistics

File	----- Total	Symbols Loaded	----- Percent	Pages Mapped	Processing Time
:_\$255\$DUA28:[SYSLIB]STARLET.L32;1	9776	44	0	581	00:01.2

COMMAND QUALIFIERS

: BLISS/CHECK=(FIELD,INITIAL,OPTIMIZE)/NOTRACE/LIS=LISS\$:BASRECPRO/OBJ=OBJ\$:BASRECPRO MSRC\$:BASRECPRO/UPDATE=(ENH\$:BASRECPRO
:)

: Size: 3397 code + 15 data bytes
: Run Time: 01:16.8
: Elapsed Time: 02:50.9
: Lines/CPU Min: 4014
: Lexemes/CPU-Min: 26026
: Memory Used: 249 pages
: Compilation Complete

0030 AH-BT13A-SE
VAX/VMS V4.0

DIGITAL EQUIPMENT CORPORATION
CONFIDENTIAL AND PROPRIETARY

