

.TITLE XADRIVER - VAX/VMS DR11-W DRIVER
.IDENT 'V04-001'

* COPYRIGHT (c) 1978, 1980, 1982, 1984 BY *
* DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS. *
* ALL RIGHTS RESERVED. *

* THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED *
* ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE *
* INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER *
* COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY *
* OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY *
* TRANSFERRED. *

* THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE *
* AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT *
* CORPORATION. *

* DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS *
* SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL. *

++
FACILITY:

VAX/VMS Executive, I/O Drivers

ABSTRACT:

This module contains the DR11-W driver:

- Tables for loading and dispatching
- Controller initialization routine
- FDT routine
- The start I/O routine
- The interrupt service routine
- Device specific Cancel I/O
- Error logging register dump routine

ENVIRONMENT:

Kernal Mode, Non-paged

AUTHOR:

C. A. Sameulson 10-JAN-79

MODIFIED BY:

V04-001 JLV0395 Jake VanNoy 6-SEP-1984
Add AVL bit to DEVCHAR.

V03-006 TMK0001 Todd M. Katz 07-Dec-1983
Fix a broken branch.

V03-005 JLV0304 Jake VanNoy 24-AUG-1983
Several bug fixes. All word writes to XA_CSR now have
ATTN set so as to prevent lost interrupts. Attention
AST list is synchronized at device IPL in DEL_ATTNAST.
Correct status is returned on a set mode ast that
is returns through EXESFINISHIO. REQCOM's are always
done at FIPL. Signed division that prevented full size
transfers has been fixed.

V03-004 KDM0059 Kathleen D. Morse 14-Jul-1983
Change time-wait loops to use new TIMEDWAIT macro.
Add \$DEVDEF.

V03-003 KDM0002 Kathleen D. Morse 28-Jun-1982
Added \$DYNDEF, \$DCDEF, and \$SSDEF.

.SBTTL External and local symbol definitions

: External symbols

```

$ACBDEF      : AST control block
$CRBDEF      : Channel request block
$DCDEF       : Device types
$DDBDEF      : Device data block
$DEVDEF      : Device characteristics
$DPTDEF      : Driver prolog table
$DYNDEF      : Dynamic data structure types
$EMBDEF      : EMB offsets
$IIDBDEF     : Interrupt data block
$IODEF       : I/O function codes
$IPLDEF      : Hardware IPL definitions
$IIRPDEF     : I/O request packet
$IPRDEF      : Internal processor registers
$PRIDEF      : Scheduler priority increments
$SSDEF       : System status codes
$UCBDEF      : Unit control block
$VECDEF      : Interrupt vector block
$XADEF       : Define device specific characteristics

```

: Local symbols

: Argument list (AP) offsets for device-dependent QIO parameters

```

P1      = 0      : First QIO parameter
P2      = 4      : Second QIO parameter
P3      = 8      : Third QIO parameter
P4      = 12     : Fourth QIO parameter
P5      = 16     : Fifth QIO parameter
P6      = 20     : Sixth QIO parameter

```

: Other constants

```

XA_DEF_TIMEOUT = 10      : 10 second default device timeout
XA_DEF_BUFSIZ  = 65535   : Default buffer size
XA_RESET_DELAY = <<2+9>/10> : Delay N microseconds after RESET
                                     : (rounded up to 10 microsec intervals)

```

: DR11-W definitions that follow the standard UCB fields

```
: *** N O T E *** ORDER OF THESE UCB FIELDS IS ASSUMED
```

```

$DEFINI UCB
.=UCBSL_DPC+4
SDEF UCBSL_XA_ATTEN      : Attention AST listhead
      .BLKL 1
SDEF UCBSW_XA_CSRTMP    : Temporary storage of CSR image
      .BLKW 1
SDEF UCBSW_XA_BARTMP    : Temporary storage of BAR image
      .BLKW 1
SDEF UCBSW_XA_CSR       : Saved CSR on interrupt
      .BLKW 1
SDEF UCBSW_XA_EIR       : Saved EIR on interrupt

```

```

SDEF UCBSW_XA_IDR .BLKW 1 ; Saved IDR on interrupt
SDEF UCBSW_XA_BAR .BLKW 1 ; Saved BAR register on interrupt
SDEF UCBSW_XA_WCR .BLKW 1 ; Saved WCR register on interrupt
SDEF UCBSW_XA_ERROR .BLKW 1 ; Saved device status flag
SDEF UCBSL_XA_DPR .BLKW 1 ; Data Path Register contents
SDEF UCBSL_XA_FMPR .BLKL 1 ; Final Map Register contents
SDEF UCBSL_XA_PMPR .BLKL 1 ; Previous Map Register contents
SDEF UCBSW_XA_DPRN .BLKW 1 ; Saved Datapath Register Number
; And Datapath Parity error flag

; Bit positions for device-dependent status field in UCB
$VFIELD UCB_0,<-
  <ATTNAST,,M>,- ; UCB device specific bit definitions
  <UNEXPT,,M>,- ; ATTN AST requested
  > ; Unexpected interrupt received

UCBSK_SIZE=
$DEFEND UCB

; Device register offsets from CSR address
SDEF $DEFINI XA ; Start of DR11-W definitions
XA_WCR ; Word count
SDEF XA_BAR .BLKW 1 ; Buffer address
SDEF XA_CSR .BLKW 1 ; Control/status

; Bit positions for device control/status register
$EQUList XASK,,0,1,<- ; Define CSR FNCT bit values
  <FNCT1,2>-
  <FNCT2,4>-
  <FNCT3,8>-
  <STATUSA,2048>- ; Define CSR STATUS bit values
  <STATUSB,1024>-
  <STATUSC,512>-
>

$VFIELD XA_CSR,0,<- ; Control/status register
  <GD,,M>,- ; Start device
  <FNCT,3,M>,- ; CSR FNCT bits
  <XBA,2,M>,- ; Extended address bits
  <IE,,M>,- ; Enable interrupts
  <RDY,,M>,- ; Device ready for command
  <CYCLE,,M>,- ; Starts slave transmit
  <STATUS,3,M>,- ; CSR STATUS bits

```

```

      <MAINT,,M>,-      ; Maintenance bit
      <ATTN,,M>,-      ; Status from other processor
      <NEX,,M>,-       ; Nonexistent memory flag
      <ERROR,,M>,-    ; Error or external interrupt
>
$DEF   KA_EIR          ; Error information register
; Bit positions for error information register
$VIELD KA_EIR,0,<-    ; Error information register
      <REGFLG,,M>,-   ; Flags whether EIR or CSR is accessed
      <SPARE,,M>,-   ; Unused - spare
      <BURST,,M>,-   ; Burst mode transfer occurred
      <DLT,,M>,-     ; Time-out for successive burst xfer
      <PAR,,M>,-     ; Parity error during DATI/P
      <ACLO,,M>,-    ; Power fail on this processor
      <MULTI,,M>,-   ; Multi-cycle request error
      <ATTN,,M>,-    ; ATTN - same as in CSR
      <NEX,,M>,-     ; NEX - same as in CSR
      <ERROR,,M>,-  ; ERROR - same as in CSR
>
      .BLKW 1
$DEF   KA_IDR          ; Input Data Buffer register
$DEF   KA_ODR          ; Output Data Buffer register
      .BLKW 1
$DEFEND KA            ; End of DR11-W definitions

```

.SBTTL Device Driver Tables

; Driver prologue table

```

DPTAB - ; DPT-creation macro
      END=XA END,- ; End of driver label
      ADAPTER=UBA,- ; Adapter type
      FLAGS=DPTSM_SVP,- ; Allocate system page table
      UCBSIZE=UCBSK_SIZE,- ; UCB size
      NAME=XADRIVER ; Driver name
DPT_STORE INIT ; Start of load
      ; initialization table
DPT_STORE UCB,UCBSB_FIPL,B,8 ; Device fork IPL
DPT_STORE UCB,UCBSB_DIPL,B,22 ; Device interrupt IPL
DPT_STORE UCB,UCBSL_DEVCHAR,L,<- ; Device characteristics
      DEVSM_AVL!- ; Available
      DEVSM_RTM!- ; Real Time device
      DEVSM_ELG!- ; Error Logging enabled
      DEVSM_IDV!- ; input device
      DEVSM_ODV> ; output device
DPT_STORE UCB,UCBSB_DEVCLASS,B,DC$ REALTIME ; Device class
DPT_STORE UCB,UCBSB_DEVTYPE,B,DT$ DR11W ; Device Type
DPT_STORE UCB,UCBSW_DEVBUFSIZ,W,- ; Default buffer size
      XA DEF BUFSIZ
DPT_STORE REINIT ; Start of reload
      ; initialization table
DPT_STORE DDB,DDBSL_DDT,D,XASDDT ; Address of DDT
DPT_STORE CRB,CRBSL_INTD+4,D,- ; Address of interrupt
      XA INTERRUPT ; service routine
DPT_STORE CRB,CRBSL_INTD+VECSL_INITIAL,- ; Address of controller
      D,XA CONTROL_INIT ; initialization routine
DPT_STORE END ; End of initialization
      ; tables

```

; Driver dispatch table

```

DDTAB - ; DDT-creation macro
      DEVNAM=XA,- ; Name of device
      START=XA START,- ; Start I/O routine
      FUNCTB=XA FUNCTABLE,- ; FDT address
      CANCEL=XA_CANCEL,- ; Cancel I/O routine
      REGDMP=XA_REGDUMP,- ; Register dump routine
      DIAGBF=<<13*4>><<3+5+1>*4>>,- ; Diagnostic buffer size
      ERLGBF=<<13*4>><<1*4>><EMBSL_DV_REGSAV>> ; Error log buffer size

```

; Function dispatch table

```

XA_FUNCTABLE: ; FDT for driver
FUNCTAB - ; Valid I/O functions
      <READPBLK,READLBLK,READVBLK,WRITEPBLK,WRITELBLK,WRITEVBLK,-
      SETMODE,SETCHAR,SENSEMODE,SENSECHAR>
FUNCTAB ; No buffered functions
FUNCTAB XA READ WRITE,- ; Device-specific FDT
      <READPBLK,READLBLK,READVBLK,WRITEPBLK,WRITELBLK,WRITEVBLK>
FUNCTAB +EXESREAD,<READPBLK,READLBLK,READVBLK>

```

FUNCTAB +EX\$WRITE,<WRITEPBLK,WRITELBLK,WRITEVBLK>
FUNCTAB XA SETMODE,<SETMODE,SETCHAR>
FUNCTAB +EX\$SENSEMODE,<SENSEMODE,SENSECHAR>

.SBTTL KA_CONTROL_INIT, Controller initialization

++
 KA_CONTROL_INIT, Called when driver is loaded, system is booted, or power failure recovery.

Functional Description:

- 1) Allocates the direct data path permanently
- 2) Assigns the controller data channel permanently
- 3) Clears the Control and Status Register
- 4) If power recovery, requests device time-out

Inputs:

R4 = address of CSR
 R5 = address of IDB
 R6 = address of DDB
 R8 = address of CRB

Outputs:

VECSV_PATHLOCK bit set in CRBSL_INTD+VECSB_DATAPATH
 UCB address placed into IDBSL_OWNER

KA_CONTROL_INIT:

```

MOVL  IDBSL_UCBLST(R5),R0      ; Address of UCB
MOVL  R0,IDBSL_OWNER(R5)      ; Make permanent controller owner
BISW  #UCBSM_ONLINE,UCBSW_STS(R0) ; Set device status "on-line"

```

: If powerfail has occurred and device was active, force device time-out.
 : The user can set his own time-out interval for each request. Time-
 : out is forced so a very long time-out period will be short circuited.

```

BBS   #UCBSV_POWER,UCBSW_STS(R0),10$ ; Branch if powerfail
BISB  #VECSM_PATHLOCK,CRBSL_INTD+VECSB_DATAPATH(R8) ; Permanently allocate direct datapath

```

10\$:

```

BSBW  KA_DEV_RESET           ; Reset DR11W
RSB   ; Done

```

.SBTTL XA_READ_WRITE, FDT for device data transfers

++ XA_READ_WRITE, FDT for READLBLK, READVBLK, READPBLK, WRITELBLK, WRITEVBLK,
WRITEPBLK

Functional description:

- 1) Rejects QUEUE I/O's with odd transfer count
- 2) Rejects QUEUE I/O's for BLOCK MODE request to UBA Direct Data PATH on odd byte boundary
- 3) Stores request time-out count specified in P3 into IRP
- 4) Stores FNCT bits specified in P4 into IRP
- 5) Stores word to write into ODR from P5 into IRP
- 6) Checks block mode transfers for memory modify access

Inputs:

R3 = Address of IRP
 R4 = Address of PCB
 R5 = Address of UCB
 R6 = Address of CCB
 R8 = Address of FDT routine
 AP = Address of P1
 P1 = Buffer Address
 P2 = Buffer size in bytes
 P3 = Request time-out period (conditional on IOSM_TIMED)
 P4 = Value for CSR FNCT bits (conditional on IOSM_SETFNCT)
 P5 = Value for ODR (conditional on IOSM_SETFNCT)
 P6 = Address of Diagnostic Buffer

Outputs:

R0 = Error status if odd transfer count
 IRPSL_MEDIA = Time-out count for this request
 IRPSL_SEGVBN = FNCT bits for DR11-W CSR and ODR image

```
XA_READ_WRITE:
BLBC      P2(AP),10$           ; Branch if transfer count even
2$:      MOVZWL #SS$_BADPARAM,R0 ; Set error status code
5$:      JMP     G^EXESABORT;O ; Abort request
10$:     MOVZWL IRPSW_FUNC(R3),R1 ; Fetch I/O function code
        MOVL   P3(AP),IRPSL_MEDIA(R3) ; Set request specific time-out count
        BBS   #IOSV_TIMED,R1,15$ ; Branch if time-out specified
        MOVL  #XA_DEF_TIMEOUT,IRPSL_MEDIA(R3)
15$:     BBC   #IOSV_DIAGNOSTIC,R1,20$ ; Else set default timeout value
        EXTZV #IOSV_FCODE,#IOSS_FCODE,R1,R1 ; AND out all function modifiers
        CMPB  #IOS_READPBLK,R1 ; If maintenance function, must be
        ; physical I/O read or write
        BEQL 20$
        CMPB #IOS_WRITEPBLK,R1
        BEQL 20$
        MOVZWL #SS$_NOPRIV,R0 ; No privilege for operation
```

```

20$:   BRB      5$                ; Abort request
      EXTZV   #0,#3,P4(AP),R0    ; Get value for FNCT bits
      ASHL    #XA(CSRSV FNCT,R0,IRPSL_SEGVBN(R3)) ; Shift into position for CSR
      MOVW    P5(AP),IRPSL_SEGVBN+2(R3) ; Store ODR value for later

```

```

: If this is a block mode transfer, check buffer for modify access
: whether or not the function is read or write. The DR11-W does
: not decide whether to read or write, the users device does.
: For word mode requests, return to read check or write check.
:

```

```

: If this is a BLOCK MODE request and the UBA Direct Data Path is
: in use, check the data buffer address for word alignment. If buffer
: is not word aligned, reject the request.

```

```

      BBS     #IOSV_WORD,IRPSW_FUNC(R3),30$ ; Branch if word mode transfer
      BBS     #XASV_DATAPATH,UCBSL_DEVDEPEND(R5),25$ ; Branch if Buffered Data Path in use
25$:   BLBS    P1(AP),2$                ; DDP, branch on bad alignment
      JMP     G^EXESMODIFY             ; Check buffer for modify access
30$:   RSB
      ; Return

```

.SBTTL XA_SETMODE, Set Mode, Set characteristics FDT

++ XA_SETMODE, FDT routine to process SET MODE and SET CHARACTERISTICS

Functional description:

If IOSM_ATTNAST modifier is set, queue attention AST for device
 If IOSM_DATAPATH modifier is set, queue packet.
 Else, finish I/O.

Inputs:

R3 = I/O packet address
 R4 = PCB address
 R5 = UCB address
 R6 = CCB address
 R7 = Function code
 AP = QIO Parameter list address

Outputs:

If IOSM_ATTNAST is specified, queue AST on UCB attention AST list.
 If IOSM_DATAPATH is specified, queue packet to driver.
 Else, use exec routine to update device characteristics

XA_SETMODE:

MOVZWL IRPSW_FUNC(R3),R0 ; Get entire function code
 BBC #IOSV_ATTNAST,R0,20\$; Branch if not an ATTN AST

; Attention AST request

PUSHR #*M<R4,R7>
 MOVAB UCBSL_XA_ATT(R5),R7 ; Address of ATTN AST control block list
 JSB G^COM\$SETATTNAST ; Set up attention AST
 POPR #*M<R4,R7>
 BLBC R0,50\$; Branch if error
 BISW #UCBSM_ATTNAST,UCBSW_DEVSTS(R5) ; Flag ATTN AST expected.
 BBC #UCBSV_UNEXPT,UCBSW_DEVSTS(R5),10\$; Deliver AST if unsolicited interrupt

10\$: BSBW DEL_ATTNAST
 MOVZBL #SS\$ NORMAL,R0 ; Set status
 JMP G^EXE\$FINISHIOC ; Thats all for now (clears R1)

; If modifier IOSM DATAPATH is set,
 ; queue packet. The data path is changed at driver level to preserve
 ; order with other requests.

20\$: BBS S^#IOSV_DATAPATH,R0,30\$; If BDP modifier set, queue packet
 JMP G^EXE\$SETCHAR ; Set device characteristics

; This is a request to change data path usage, queue packet

```
30$:  CMPL  #IOS_SETCHAR,R7      ; Set characteristics?
      BNEQ  45$                  ; No, must have the privilege
      JMP   G^EXE$SETMODE       ; Queue packet to start I/O

; Error, abort IO

45$:  MOVZWL #SS$_NOPRIV,R0      ; No priv for operation
50$:  CLRL  R1
      JMP   G^EXE$ABORTIO       ; Abort IO on error
```

```
.SBTTL XA_START, Start I/O routines
```

```
++
XA_START - Start a data transfer, set characteristics, enable ATTN AST.
```

```
Functional Description:
```

```
This routine has two major functions:
```

- 1) Start an I/O transfer. This transfer can be in either word or block mode. The FNCTN bits in the DR11-W CSR are set. If the transfer count is zero, the STATUS bits in the DR11-W CSR are read and the request completed.
- 2) Set Characteristics. If the function is change data path, the new data path flag is set in the UCB.

```
Inputs:
```

```
R3 = Address of the I/O request packet
R5 = Address of the UCB
```

```
Outputs:
```

```
R0 = final status and number of bytes transferred
R1 = value of CSR STATUS bits and value of input data buffer register
Device errors are logged
Diagnostic buffer is filled
```

```
--
.ENABL LSB
```

```
XA_START:
```

```
; Retrieve the address of the device CSR
```

```
ASSUME IDBSL_CSR EQ 0
MOVL   UCBSL_CRB(R5),R4      ; Address of CRB
MOVL   @CRBSL_INTD+VECSL_IDB(R4),R4 ; Address of CSR
```

```
; Fetch the I/O function code
```

```
MOVZWL IRPSW_FUNC(R3),R1      ; Get entire function code
MOVW   R1,UCBSW_FUNC(R5)      ; Save FUNC in UCB for Error Logging
EXTZV  #IOSV_FCODE,#IOSS_FCODE,R1,R2 ; Extract function field
```

```
; Dispatch on function code. If this is SET CHARACTERISTICS, we will
; select a data path for future use.
; If this is a transfer function, it will either be processed in word
; or block mode.
```

```
CMPB   #IOS_SETCHAR,R2      ; Set characteristics?
BNEQ   3$
```

```
++
SET CHARACTERISTICS - Process Set Characteristics QIO function
```

: INPUTS:

XA_DATAPATH bit in Device Characteristics specifies which data path to use. If bit is a one, use buffered data path. If zero, use direct datapath.

: OUTPUTS:

CRB is flagged as to which datapath to use.
 DEVDEPEND bits in device characteristics is updated
 XA_DATAPATH = 1 -> buffered data path in use
 XA_DATAPATH = 0 -> direct data path in use

```

MOV  UCBSL_CRB(R5),R0          ; Get CRB address
MOVQ IRPSL_MEDIA(R3),UCBSB_DEVCLASS(R5) ; Set device characteristics
BISB #VECSM_PATHLOCK,CRBSL_INTD+VECSB_DATAPATH(R0)
BBC   #XASV_DATAPATH,UCBSL_DEVDEPEND(R5),2$ ; Were we right?
BICB  #VECSM_PATHLOCK,CRBSL_INTD+VECSB_DATAPATH(R0) ; Set buffered datapath
2$:   CLRL  R1                  ; Return Success
      MOVZWL #SS$_NORMAL,R0
      REQCOM
  
```

: If subfunction modifier for device reset is set, do one here

```

3$:   BBC   S^#IOSV_RESET,R1,4$ ; Branch if not device reset
      BSBW  XA_DEV_RESET        ; Reset DR11-W
  
```

: This must be a data transfer function - i.e. READ OR WRITE
 : Check to see if this is a zero length transfer.
 : If so, only set CSR FNCT bits and return STATUS from CSR

```

4$:   TSTW  UCBSW_BCNT(R5)      ; Is transfer count zero?
      BNEQ  10$                ; No, continue with data transfer
      BBC   S^#IOSV_SETFNCT,R1,6$ ; Set CSR FNCT specified?
      DSBINT
      MOVW  IRPSL_SEGVBN+2(R3),XA_ODR(R4)
                               ; Store word in ODR
      MOVZWL XA_CSR(R4),R0
      BICW  #<XA_CSRSM_FNCT!XA_CSRSM_ERROR>,R0
      BISW  IRPSL_SEGVBN(R3),R0
      BISW  #XA_CSRSM_ATTN,R0   ; Force ATTN on to prevent lost interrupt
      MOVW  R0,XA_CSR(R4)
      BBC   #XASV_LINK,UCBSL_DEVDEPEND(R5),5$ ; Link mode?
      BICW3 #XASK_FNCT2,R0,XA_CSR(R4) ; Make FNCT bit 2 a pulse
  
```

5\$: ENBINT

```

6$:   BSBW  XA_REGISTER        ; Fetch DR11-W registers
      BLBS  R0,7$             ; If error, then log it
      JSB  G^ERL$DEVICERR     ; Log a device error
7$:   JSB  G^IOC$DIAGBUFILL    ; Fill diagnostic buffer if specified
      MOVL  UCBSW_XA_CSR(R5),R1 ; Return CSR and EIR in R1
      MOVZWL UCBSW_XA_ERROR(R5),R0 ; Return status in R0
  
```

```

BISB #XA_CSRSM_IE,XA_CSR(R4) ; Enable device interrupts
REQCOM ; Request done

```

```

; Build CSR image in R0 for later use in starting transfers

```

```

10$:

```

```

MOVZWL UCBSW_BCNT(R5),R0 ; Fetch byte count
DIVL3 #2,R0,UCBSL_XA_DPR(R5) ; Make byte count into word count
; Set up UCBSW_CSRTMP used for loading CSR later

```

```

MOVZWL XA_CSR(R4),R0
BICW #<XA_CSRSM_FNCT>,R0
BISW #XA_CSRSM_IET,XA_CSRSM_ATTN,R0 ; Set Interrupt Enable and ATTN
BBC S^#IOSV_SETFNCT,R1,20$ ; Set FNCT bits in CSR?
BICW #<XA_CSRSM_FNCT>,R0 ; Yes, Clear previous FNCT bits
BISB IRPSC_SEGVBN(R3),R0 ; OR in new value
20$: BBC S^#IOSV_DIAGNOSTIC,R1,23$ ; Check for maintenance function
BISW #XA_CSRSM_MAINT,R0 ; Set maintenance bit in CSR image

```

```

; Is this a word mode or block mode request?

```

```

23$: MOVW R0,UCBSW_XA_CSRTMP(R5) ; Save CSR image in UCB
BBC S^#IOSV_WORD,R1,BLOCK_MODE ; Check if word or block mode
BRW WORD_MODE ; Branch to handle word mode

```



```

MNEGW UCBSL_XA_DPR(R5),XA_WCR(R4)
MOVW R1,XA_BAR(R4) ; Load negative of transfer count
MOVW R0,XA_CSR(R4) ; Load low 16 bits of bus address
BBC #XASV_LINK,UCBSL_DEVDEPEND(R5),26$ ; Load CSR image less "GO" and "CYCLE"
MOVW R2,XA_CSR(R4) ; Link mode?
BRB 126$ ; Yes, load CSR image less "FNCT" bit 2
; Only if link mode in dev characteristics
26$: MOVW UCBSW_XA_CSRTMP(R5),XA_CSR(R4) ; Move all bits to CSR
; Wait for transfer complete interrupt, powerfail, or device time-out
126$: WFIKPBH XA_TIME_OUT,IRPSL_MEDIA(R3) ; Wait for interrupt
; Device has interrupted, FORK
IOFORK ; FORK to lower IPL
; Handle request completion, release UBA resources, check for errors
MOVZWL #SS$ NORMAL,-(SP) ; Assume success, store code on stack
CLRW UCBSW_XA_DPRN(R5) ; Clear DPR number and DPR error flag
PURDPR ; Purge UBA buffered data path
BLBS R0,27$ ; Branch if no datapath error
MOVZWL #SS$ PARITY,(SP) ; Flag parity error on device
INCB UCBSW_XA_DPRN+1(R5) ; Flag PDR error for log
27$: MOVL R1,UCBSL_XA_DPR(R5) ; Save data path register in UCB
EXTZV #VECSV_DATAPATH,- ; Get Datapath register no.
#VECS$ DATAPATH,- ; For Error Log
CRBSL_INTD+VECS$ DATAPATH(R3),R0
MOVB R0,UCBSW_XA_DPRN(R5) ; Save for later in UCB
EXTZV #9,#7,UCBSW_XA_BAR(R5),R0 ; Low bits, final map register no.
EXTZV #4,#2,UCBSW_XA_CSR(R5),R1 ; Hi bits of map register no.
INSV R1,#7,#2,R0 ; Entire map register number
CMPW R0,#496 ; Is map register number in range?
BGTR 28$ ; No, forget it - compound error
MOVL (R2)[R0],UCBSL_XA_FMPR(R5) ; Save map register contents
CLRL UCBSL_XA_PMPR(R5) ; Assume no previous map register
DECL R0 ; Was there a previous map register?
CMPV #VECSV_MAPREG,#VECS$ MAPREG,- ;
CRBSL_INTD+VECS$ MAPREG(R3),R0
BGTR 28$ ; No if gtr
28$: MOVL (R2)[R0],UCBSL_XA_FMPR(R5) ; Save previous map register contents
RELMPR ; Release UBA resources
RELDPR
; Check for errors and return status
TSTW UCBSW_XA_WCR(R5) ; All words transferred?
BEQL 30$ ; Yes
MOVZWL #SS$ OPINCOMPL,(SP) ; No, flag operation not complete
30$: BBC #XA_CSR$V_ERROR,UCBSW_XA_CSR(R5),35$ ; Branch on CSR error bit
MOVZWL UCBSW_XA_ERROR(R5),(SP) ; Flag for controller/drive error status
BSBW XA_DEV_RESET ; Reset DR11-W
35$: BLBS (SP),40$ ; Any errors after all this?

```

```
408: JSB      G^ERLSDEVICERR      : Yes, log them
      BSBW    DEL_ATTNAST        : Deliver outstanding ATTN AST's
      JSB      G^I0CSDIAGBUFILL  : Fill diagnostic buffer
      MOVL    (SP)+,R0           : Get final device status
      MULW3   #2,UCBSW_XA_WCR(R5),R1 : Calculate final transfer count
      ADDW    UCBSW_BCNT(R5),R1
      INSV    R1,#16,#16,R0      : Insert into high byte of IOSB
      MOVL    UCBSW_XA_CSR(R5),R1 : Return CSR and EIR in IOSB
      BISB    #XA_CSR&M_IE,XA_CSR(R4) : Enable interrupts
      REQCOM
```

.DSABL LSB

++
: WORD MODE -- Process word mode (interrupt per word) transfer

: FUNCTIONAL DESCRIPTION:

: Data is transferred one word at a time with an interrupt for each word.
: The request is handled separately for a write (from memory to DR11-W
: and a read (from DR11-W to memory).

: For a write, data is fetched from memory, loaded into the ODR of the
: DR11-W and the system waits for an interrupt. For a read, the system
: waits for a DR11-W interrupt and the IDR is transferred into memory.

: If the unsolicited interrupt flag is set, the first word is transferred
: directly into memory without waiting for an interrupt.

--
: .ENABL LSB
WORD_MODE:

: Dispatch to separate loops on READ or WRITE

 CMPB #IOS_READPBLK,R2 ; Check for read function
 BEQL 30\$

++
: WORD MODE WRITE -- Write (output) in word mode

: FUNCTIONAL DESCRIPTION:

: Transfer the requested number of words from user memory to
: the DR11-W ODR one word at a time, wait for interrupt for each
: word.

--
10\$:
 BSBW MOVFRUSER ; Get two bytes from user buffer
 DSBINT ; Lock out interrupts
 ; Flag interrupt expected
 MOVW R1,XA_ODR(R4) ; Move data to DR11-W
 MOVW UCBSW_XA_CSRTMP(R5),XA_CSR(R4) ; Set DR11-W CSR
 BBC #XASV_LINK,UCBSL_DEVDEPEND(R5),15\$; Link mode?
 BICW3 #XASK_FNCT2,UCBSQ_XA_CSRTMP(R5),XA_CSR(R4) ; Clear interrupt FNCT bit 2
 ; Only if Link mode specified

15\$:
: Wait for interrupt, powerfail, or device time-out

 WFIKPB XA_TIME_OUTW,IRPSL_MEDIA(R3)

: Check for errors, decrement transfer count, and loop til complete

 IOFORK ; Fork to lower IPL
 BITW #XA_EIRSM_NEX!-
 XA_EIRSM_MULTI!-

```

                XA_EIRSM_ACLO!-
                XA_EIRSM_PAR!-
                XA_EIRSM_DLT,UCBSW_XA_EIR(R5) ; Any errors?
20$: BEQL      20$                ; No, continue
      BRW      40$                ; Yes, abort transfer.
      DECV     UCBSL_XA_DPR(R5)    ; All words trnasferred?
      BNEQ     10$                ; No, loop until finished.

```

```

; Transfer is done, clear iterrupt expected flag and FORK
; All words read or written in WORD MODE. Finish I/O.

```

RETURN_STATUS:

```

      JSB      G^IOC$DIAGBUFILL    ; Fill diagnostic buffer if present
      BSBW     DEL_ATTNA$T         ; Deliver outstanding ATTN AST's
22$: MOVZWL    #SS$ NORMAL,R0      ; Complete success status
      MULW3    #2,UCBSL_XA DPR(R5),R1 ; Calculate actual bytes xfered
      SUBW3    R1,UCBSW_BCNT(R5),R1 ; From requested number of bytes
      INSV     R1,#16,#16,R0       ; And place in high word of R0
      MOVL     UCBSW_XA_CSR(R5),R1 ; Return CSR and EIR status
      BISB     #XA_CSRSM_IE,XA_CSR(R4) ; Enable device interrupts
      REQCOM

```

```

; **
; WORD MODE READ -- Read (input) in word mode

```

FUNCTIONAL DESCRIPTION:

```

; Transfer the requested number of wrods from the DR11-W IDR into
; user memory one word at a time, wait for interrupt for each word.
; If the unexpected (unsolicited) interrupt bit is set, transfer the
; first (last received) word to memory without waiting for an
; interrupt.
; --

```

```

30$: DSBINT UCBSB_DIPL(R5)        ; Lock out interrupts

```

```

; If an unexpected (unsolicited) interrupt has occured, assume it
; is for this READ request and return value to user buffer without
; waiting for an interrupt.

```

```

      BBCC     #UCBSV UNEXPT,-
            UCBSW_DEVSTS(R5),32$ ; Branch if no unexpected interrupt
      ENBINT
      BRB      37$                ; Enable interrupts
            ; continue

```

```

32$: SETIPL #IPL$_POWER
35$:

```

```

; Wait for interrupt, powerfail, or device time-out

```

```

      WFIKPCX XA_TIME_OUTW,IRP$L_MEDIA(R3)

```

```

; Check for errors, decrement transfer count and loop until done

```

```

37$: IOFORK                ; Fork to lower IPL
      BITW   #XA_EIRSM_NEX!-
           XA_EIRSM_MULTI!-
           XA_EIRSM_ACLO!-
           XA_EIRSM_PAR!-
           XA_EIRSM_DLT,UCBSW_XA_EIR(R5) ; Any errors?
      BNEQ   40$           ; Yes, abort transfer.
      BSBW   MOVTOUSER     ; Store two bytes into user buffer
; Send interrupt back to sender. Acknowledge we got last word.
      DSBINT
      MOVW   UCBSW_XA_CSRTMP(R5),XA_CSR(R4)
      BBC    #XASV_LINK,UCBSL_DEVDEPEND(R5),38$ ; Link mode?
      BICW3  #XASK_FNCT2,UCBSW_XA_CSRTMP(R5),XA_CSR(R4) ; Yes, clear FNCT 2
38$:  DECW   UCBSL_XA_DPR(R5)           ; Decrement transfer count
      BNEQ   35$           ; Loop until all words transferred
      ENBINT
      BRW    RETURN_STATUS           ; Finish request in common code
; Error detected in word mode transfer
40$:  BSBW   DEL_ATTNAST           ; Deliver ATTN AST's
      BSBW   XA_DEV_RESET           ; Error, reset DR11-W
      JSB   G*IOC$DIAGBUFILL       ; Fill diagnostic buffer if presetn
      JSB   G*ERL$DEVICERR         ; Log device error
      MOVZWL UCBSW_XA_ERROR(R5),R0   ; Set controller/drive status in R0
      BRW   22$
      .DSABL LSB
;: MOVFRUSER - Routine to fetch two bytes from user buffer.
;: INPUTS:
;: R5 = UCB address
;: OUTPUTS:
;: R1 = Two bytes of data from users buffer
;: Buffer descriptor in UCB is updated.
;: .ENABL LSB
MOVFRUSER:
      MOVAL  -(SP),R1           ; Address of temporary stack loc
      MOVZBL #2,R2             ; Fetch two bytes
      JSB   G*IOC$MOVFRUSER     ; Call exec routine to do the deed
      MOVL  (SP)+,R1           ; Retrieve the bytes
      BRB   20$               ; Update UCB buffer pointers
;: MOVTOUSER - Routine to store two bytes into users buffer.
;:

```

: INPUTS:

R5 = UCB address
UCBSW_XA_IDR(R5) = Location where two bytes are saved

: OUTPUTS:

Two bytes are stored in user buffer and buffer descriptor in
UCB is updated.

MOVTOUSER:

```

MOVAB UCBSW_XA_IDR(R5),R1      ; Address of internal buffer
MOVZBL #2,R2
JSB G^1OC$MOVTOUSER          ; Call exec
20$: ADDW #2,UCBSW_BOFF(R5)      ; Update buffer pointers in UCB
      BICW #^C<^X01FF>,UCBSW_BOFF(R5) ; Add two to buffer descriptor
      BNEQ 30$                  ; Modulo the page size
      ADDL #4,UCB$L_SVAPTE(R5)  ; If NEQ, no page boundary crossed
      ; Point to next page
30$: RSB
: .DSABL LSB

```

```
.PAGE
.SBTTL DR11-W DEVICE TIME-OUT
```

```
++
: DR11-W device TIME-OUT
: If a DMA transfer was in progress, release UBA resources,
: For DMA or WORD mode, deliver ATTN AST's, log a device timeout error,
: and do a hard reset on the controller.
```

```
: Clear DR11-W CSR
: Return error status
```

```
: Power failure will appear as a device time-out
```

```
--
.ENABL LSB
XA_TIME_OUT: ; Time-out for DMA transfer

SETIPL UCBSB_FIPL(R5) ; Lower to FORK IPL
PURDPR ; Purge buffered data path in UBA
RELMR ; Release UBA map registers
RELDPR ; Release UBA data path
BRB 10$ ; continue

XA_TIME_OUTW: ; Time-out for WORD mode transfer

10$: SETIPL UCBSB_FIPL(R5) ; Lower to FORK IPL
MOVL UCBSL_CRB(R5),R4 ; Fetch address of CSR
MOVL @CRBSL_INTD+VECSL_IDB(R4),R4
BSBW XA_REGISTER ; Read DR11-W registers
JSB G^TOCS$DIAGBUFILL ; Fill diagnostic buffer
JSB G^ERLS$DEVICTMO ; Log device time out
BSBW DEL ATTNAST ; And deliver the AST's
BSBW XA DEV RESET ; Reset controller
MOVZWL #SS$ TIMEOUT,R0 ; Assume error status
BBC #UCBSV_CANCEL,- ; Branch if not cancel
UCBSW_STS(R5),20$ ; Set status

20$: MOVZWL #SS$_CANCEL,R0
CLRL R1
CLRW UCBSW_DEVSTS(R5) ; Clear ATTN AST flags
BICW #<UCBSM_TIM!UCBSM_INT!UCBSM_TIMEOUT!UCBSM_CANCEL!UCBSM_POWER>,-
UCBSW_STS(R5) ; Clear unit status flags
REQCOM ; Complete I/O in exec
.DSABL LSB
.PAGE
```

.SBTTL XA_INTERRUPT, Interrupt service routine for DR11-W

++ XA_INTERRUPT, Handles interrupts generated by DR11-W

Functional description:

This routine is entered whenever an interrupt is generated by the DR11-W. It checks that an interrupt was expected. If not, it sets the unexpected (unsolicited) interrupt flag. All device registers are read and stored into the UCB. If an interrupt was expected, it calls the driver back at its Wait For Interrupt point. Deliver ATTN AST's if unexpected interrupt.

Inputs:

00(SP) = Pointer to address of the device IDB
 04(SP) = saved R0
 08(SP) = saved R1
 12(SP) = saved R2
 16(SP) = saved R3
 20(SP) = saved R4
 24(SP) = saved R5
 28(SP) = saved PSL
 32(SP) = saved PC

Outputs:

The driver is called at its Wait For Interrupt point if an interrupt was expected.
 The current value of the DR11-W CSR's are stored in the UCB.

```

--
XA_INTERRUPT:                ; Interrupt service for DR11-W
    MOVL    @(SP)+,R4        ; Address of IDB and pop SP
    MOVQ    (R4),R4         ; CSR and UCB address from IDB

; Read the DR11-W device registers (WCR, BAR, CSR, EIR, IDR) and store
; into UCB.
    BSBW    XA_REGISTER     ; Read device registers

; Check to see if device transfer request active or not
; If so, call driver back at Wait for Interrupt point and
; Clear unexpected interrupt flag.
20$:    BBCC    #UCBSV_INT,UCBSW_STS(R5),25$ ; If clear, no interrupt expected

; Interrupt expected, clear unexpected interrupt flag and call driver
; back.
    BICW    #UCBSM_UNEXPT,UCBSW_DEVSTS(R5) ; Clear unexpected interrupt flag
    MOVL    UCBSL_FR3(R5),R3 ; Restore drivers R3
    JSB    @UCBSI_FPC(R5)   ; Call driver back
  
```

BRB 30\$

; Deliver ATTN AST's if no interrupt expected and set unexpected
; interrupt flag.

25\$:

BISW #UCBSM_UNEXPT,UCBSW_DEVSTS(R5) ; Set unexpected interrupt flag
BSBW DEL_ATTNAST ; Deliver ATTN AST's
BISB #XA_CSRSM_IE,XA_CSR(R4) ; Enable device interrupts

; Restore registers and return from interrupt

30\$:

POPR #^M<R0,R1,R2,R3,R4,R5> ; Restore registers
REI ; Return from interrupt

```
.PAGE
.SBTTL  XA_REGISTER - Handle DR11-W CSR transfers
```

```
++
XA_REGISTER - Routine to handle DR11-W register transfers
```

```
INPUTS:
```

```
R4 - DR11-W CSR address
R5 - UCB address of unit
```

```
OUTPUTS:
```

```
CSR, EIR, WCR, BAR, IDR, and status are read and stored into UCB.
The DR11-W is placed in its initial state with interrupts enabled.
```

```
RO - .true. if no hard error
     .false. if hard error (cannot clear ATTN)
```

```
If the CSR ERROR bit is set and the associated condition can be cleared, then
the error is transient and recoverable. The status returned is SSS_DRVERR.
If the CSR ERROR bit is set and cannot be cleared by clearing the CSR, then
this is a hard error and cannot be recovered. The returned status is
SSS_CTRLERR.
```

```
RO,R1 - destroyed, all other registers preserved.
```

```
--
XA_REGISTER:
```

```

MOVZWL #SS$ NORMAL,RO          ; Assume success
MOVZWL XA_CSR(R4),R1           ; Read CSR
MOVW   R1,UCBSW_XA_CSR(R5)     ; Save CSR in UCB
BBC    #XA_CSR$V_ERROR,R1,55$  ; Branch if no error
MOVZWL #SS$ DRVERR,RO         ; Assume "drive" error
55$:  BICW #^C<XA_CSR$M_FNCT>,R1 ; Clear all uninteresting bits for later
      BISB #<XA_CSR$M_ERROR/256>,XA_CSR+1(R4) ; Set EIR flag
      MOVW XA_EIR(R4),UCBSW_XA_EIR(R5) ; Save EIR in UCB
      MOVW R1,XA_CSR(R4)         ; Clear EIR flag and errors
      MOVW XA_CSR(R4),R1         ; Read CSR back
      BBC  #XA_CSR$V_ATTN,R1,60$ ; If attention still set, hard error
60$:  MOVZWL #SS$ CTRLERR,RO     ; Flag hard controller error
      MOVW XA_IDR(R4),UCBSW_XA_IDR(R5) ; Save IDR in UCB
      MOVW XA_BAR(R4),UCBSW_XA_BAR(R5)
      MOVW XA_WCR(R4),UCBSW_XA_WCR(R5)
      MOVW RO,UCBSW_XA_ERROR(R5) ; Save status in UCB
      RSB
```

.SBTTL XA_CANCEL, Cancel I/O routine

XA_CANCEL, Cancels an I/O operation in progress

Functional description:

Flushes Attention AST queue for the user.
If transfer in progress, do a device reset to DR11-W and finish the request.
Clear interrupt expected flag.

Inputs:

R2 = negated value of channel index
R3 = address of current IRP
R4 = address of the PCB requesting the cancel
R5 = address of the device's UCB

Outputs:

```

XA_CANCEL:                                ; Cancel I/O
      BBCC    #UCBSV_ATTNAST,-
           UCBSW_DEVSTS(R5),20$    ; ATTN AST enabled?
; Finish all ATTN AST's for this process.
      PUSHR   #^M<R2,R6,R7>
      MOVL   R2,R6                ; Set up channel number
      MOVAB  UCBSL_XA_ATTNAST(R5),R7 ; Address of listhead
      JSB    G^COMB_FLUSHATTNS    ; Flush ATTN AST's for process
      POPR   #^M<R2,R6,R7>
; Check to see if a data transfer request is in progress
; for this process on this channel
20$:
      DSBINT UCBSB_DIPL(R5)        ; Lock out device interrupts
      JSB    G^IOCS_CANCELIO      ; Check if transfer going
      BBC    #UCBSV_CANCEL,-
           UCBSW_STS(R5),30$    ; Branch if not for this guy
; Force timeout
      CLRL   UCBSL_DUETIM(R5)      ; clear timer
      BISW   #UCBSM_TIM,UCBSW_STS(R5) ; set timed
      BICW   #UCBSM_TIMEOUT,-
           UCBSW_STS(R5)        ; Clear timed out
30$:
      ENBINT
      RSB    ; Lower to FORK IPL
           ; Return

```

.PAGE
 .SBTTL DEL_ATTNAST, Deliver ATTN AST's

++
 DEL_ATTNAST, Deliver all outstanding ATTN AST's

Functional description:

This routine is used by the DR11-W driver to deliver all of the outstanding attention AST's. It is copied from COMSDELATTNAST in the exec. In addition, it places the saved value of the DR11-W CSR and Input Data Buffer Register in the AST parameter.

Inputs:

R5 = UCB of DR11-W unit

Outputs:

R0,R1,R2 Destroyed
 R3,R4,R5 Preserved

```

--
DEL_ATTNAST:
DSBINT UCBSB DIPL(R5)          ; Device IPL
BBCC   #UCBSV_ATTNAST,UCBSW_DEVSTS(R5),30$
                                ; Any ATTN AST's expected?
10$:  PUSHR  #^M<R3,R4,R5>      ; Save R3,R4,R5
      MOVL  8(SP),R1           ; Get address of UCB
      MOVAB UCBSL_XA_ATTNA(R1),R2 ; Address of ATTN AST listhead
      MOVL  (R2),R5           ; Address of next entry on list
      BEQL  20$              ; No next entry, end of loop
      BICW  #UCBSM_UNEXPT,UCBSW_DEVSTS(R1) ; Clear unexpected interrupt flag
      MOVL  (R5),(R2)         ; Close list
      MOVW  UCBSW_XA_IDR(R1),ACBSL_KAST+6(R5)
                                ; Store IDR in AST parameter
      MOVW  UCBSW_XA_CSR(R1),ACBSL_KAST+4(R5)
                                ; Store CSR in AST parameter
      PUSHAB B^10$           ; Set return address for FORK
      FORK                                     ; FORK for this AST

; AST fork procedure
      MOVQ  ACBSL_KAST(R5),ACBSL_AST(R5)
                                ; Re-arrange entries
      MOVB  ACBSL_KAST+8(R5),ACBSB_RMOD(R5)
      MOVL  ACBSL_KAST+12(R5),ACBSL_PID(R5)
      CLRL  ACBSL_KAST(R5)
      MOVZBL #PRI$_IOCOM,R2    ; Set up priority increment
      JMP   G^SCH$QAST         ; Queue the AST

20$:  POPR  #^M<R3,R4,R5>      ; Restore registers
30$:  ENBINT
      RSB                                     ; Return
  
```

```
.PAGE
.SBTTL XA_REGDUMP - DR11-W register dump routine
```

```
++
XA_REGDUMP - DR11-W Register dump routine.
```

```
This routine is called to save the controller registers in a specified
buffer. It is called from the device error logging routine and from the
diagnostic buffer fill routine.
```

Inputs:

```
R0 - Address of register save buffer
R4 - Address of Control and Status Register
R5 - Address of UCB
```

Outputs:

The controller registers are saved in the specified buffer.

```
CSRTMP - The last command written to the DR11-W CSR by
          by the driver.
BARTMP - The last value written into the DR11-W BAR by
          the driver during a block mode transfer.
CSR - The CSR image at the last interrupt
EIR - The EIR image at the last interrupt
IDR - The IDR image at the last interrupt
BAR - The BAR image at the last interrupt
WCR - Word count register
ERROR - The system status at request completion
PDRN - UBA Datapath Register number
DPR - The contents of the UBA Data Path register
FMPR - The contents of the last UBA Map register
PMRP - The contents of the previous UBA Map register
DPRF - Flag for purge datapath error
       0 = no purger datapath error
       1 = parity error when datapath was purged
```

Note that the values stored are from the last completed transfer operation. If a zero transfer count is specified, then the values are from the last operation with a non-zero transfer count.

XA_REGDUMP:

```
MOVZBL #11,(R0)+ ; Eleven registers are stored.
MOVAB UCBSW_XA_CSRTMP(R5),R1 ; Get address of saved register images
MOVZBL #8,R2 ; Return 8 registers here
10$: MOVZWL (R1)+,(R0)+
SOBGR R2,10$ ; Move them all
MOVZBL UCBSW_XA_DPRN(R5),(R0)+ ; Save Datapath Register number
MOVZBL #3,R2 ; And 3 more here
20$: MOVL (R1)+,(R0)+ ; Move UBA register contents
SOBGR R2,20$
MOVZBL UCBSW_XA_DPRN+1(R5),(R0)+ ; Save Datapath Parity Error Flag
RSB
```


The image displays a dense grid of small, illegible text fragments, likely representing a large document or code page. The text is arranged in a regular pattern across the page. Some larger, faint text is visible, including "XDRIVER MAR", "CONTERR LIS", and "NORTVER LIS". The overall appearance is that of a high-resolution scan of a document with very small characters.