


```
XTITLE 'EVLIBRARY Symbol Definition Library'  
'MODULE EVLIBRARY (  
    LANGUAGE (BLISS32),  
    IDENT = 'V04-000'  
    ) =
```

```
BEGIN
```

```
*****  
*  
* COPYRIGHT (c) 1978, 1980, 1982, 1984 BY  
* DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.  
* ALL RIGHTS RESERVED.  
*  
* THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED  
* ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE  
* INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER  
* COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY  
* OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY  
* TRANSFERRED.  
*  
* THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE  
* AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT  
* CORPORATION.  
*  
* DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS  
* SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.  
*  
*****
```

```
♦♦  
FACILITY: DECnet Event Logging (EVL)  
ABSTRACT:  
    Event Logging Library of Common Definitions  
ENVIRONMENT: VAX/VMS Operating System  
AUTHOR: Darrell Duffy , CREATION DATE: 15-June-1980  
MODIFIED BY:  
    V001 TMH0001 Tim Halvorsen 25-Jun-1981  
    Remove some obsolete definitions  
--
```

```
%SBTTL 'Definitions'
```

```
Structure declarations used for system defined structures to  
save typing. These structures are byte sized.  
(Thanks to A. Goldstein)
```

```
STRUCTURE  
  BBLOCK [O, P, S, E; N] =  
    [N]  
    (BBLOCK+O)<P,S,E>,  
  BBLOCKVECTOR [I, O, P, S, E; N, BS] =  
    [N*BS]  
    ((BBLOCKVECTOR+I*BS)+O)<P,S,E>  
  ;
```

```
Macro to create a bit id value for net control qio macros
```

```
$BITID  
(  
Component prefix LNI, NDI, OBI, DLI, ...  
Type of parameter V, L, S  
Identifier for bit  
)
```

```
MACRO
```

```
$BITID (COMP, TYP, ID) =  
(  
( %NAME (COMP, 'SC', TYP, 'MASK') ) ^16 +  
( %BITPOSITION (%NAME (COMP, 'SV_', TYP, '_', ID) ) )  
)  
%;
```


