



\*\*FILE\*\*ID\*\*DAPDEF

K 14

DDDDDDDD	AAAAAA	PPPPPPP	DDDDDDDD	EEEEEEEEE	FFFFFFFFF
DDDDDDDD	AAAAAA	PPPPPPP	DDDDDDDD	EEEEEEEEE	FFFFFFFFFF
DD DD	AA AA	AA PP	DD DD	EE EE	FF
DD DD	AA AA	AA PP	DD DD	EE EE	FF
DD DD	AA AA	AA PP	DD DD	EE EE	FF
DD DD	AA AA	AA PPPPPP	DD DD	EEEEE	FFFFFFF
DD DD	AA AA	AA PPPPPP	DD DD	EEEEE	FFFFFFF
DD DD	AAAAAAA	PP	DD DD	EE EE	FF
DD DD	AAAAAAA	PP	DD DD	EE EE	FF
DD DD	AA AA	AA PP	DD DD	EE EE	FF
DD DD	AA AA	AA PP	DD DD	EE EE	FF
DDDDDDDD	AA AA	PP	DDDDDDDD	EEEEEEEEE	FF
DDDDDDDD	AA AA	PP	DDDDDDDD	EEEEEEEEE	FF

....  
....  
....  
....

MM	MM	DDDDDDDD	LL
MM	MM	DDDDDDDD	LL
MMMM	MMMM	DD	DD LL
MMMM	MMMM	DD	DD LL
MM	MM	DD	DD LL
MM	MM	DD	DD LL
MM	MM	DD	DD LL
MM	MM	DD	DD LL
MM	MM	DD	DD LL
MM	MM	DD	DD LL
MM	MM	DD	DD LL
MM	MM	DD	DD LL
MM	MM	DDDDDDDD	LLLLLLLLL
MM	MM	DDDDDDDD	LLLLLLLLL

:TITLE \$DAPDEF - DATA ACCESS PROTOCOL DEFINITIONS  
:IDENT 'V04-000'

\*\*\*\*\*  
\* COPYRIGHT (c) 1978, 1980, 1982, 1984 BY  
\* DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.  
\* ALL RIGHTS RESERVED.

THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED  
ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE  
INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER  
COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY  
OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY  
TRANSFERRED.

THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE  
AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT  
CORPORATION.

DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS  
SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.

++ Facility: DAP (Data Access Protocol)

Abstract:

This module defines the DAP control block. It is both an input and  
output control structure for the FAL\$DECODE\_MSG and NT\$DECODE\_MSG  
subroutines in FAL and RMS, respectively.

Environment:

The MDL translator must be used to convert DAPDEF.MDL into  
DAPDEF.MAR (and DAPDEF.B32).

Author: James A. Krycka. Creation Date: 17-OCT-1977

Modified By:

V03-007 JEJ0018 J E Johnson 27-Mar-1984  
Correct double assignment of DAP\$V\_POS caused in V03-006; now  
P/OS will be identified as DAP\$V\_P\_OS and DAP\$K\_P\_OS.  
Remove no longer used DAP buffer size constants:  
DAP\$K\_INIBUFSIZ, DAP\$K\_MINBUFSIZ, and DAP\$K\_MAXBUFSIZ.

V03-006 JAK0124 J A Krycka 06-SEP-1983  
Define operating system class bits analogous to DAP\$V\_VAXVMS  
(VAXELAN, TOPS10, TOPS20, RT11, RSTS, RSX, IAS, and POS).  
Define DAP\$B\_X\_FIELD containing flags from DAP\$Q\_DCODE\_FLG.

Rearrange order of DAP\$Q\_DCODE\_FLG bits.

- V03-005 JAK0112 J A Krycka 22-JUN-1983  
Define DAP\$V\_GEQ\_V71.  
Define DAP\$V\_VMS\_XPF1 thru VMS\_XPF4.
- V03-004 JAK0111 J A Krycka 17-JUN-1983  
Upgrade definitions to correspond to DAP V7.0 specification:  
Define DAP\$K\_VAXELAN and DAP\$K\_RMS32S.  
Define new SYSCAP bit (OCTALVER).  
Define DAP\$K\_IN8 and DAP\$K\_BN8.
- V03-003 KRM0102 K Malik 09-May-1983  
Define new SYSCAP field bits (MODATTCRE, NAM3PART, CHGATTRN,  
CHGTIMREN, CHGPROREN, BLKCNT).  
Rename SYSCAP bits (CHGATT to CHGATTCLS, CHGTIM to CHGTIMCLS,  
CHGPRO to CHGPROCLS, CHGNAM to CHGNAMCLS).  
Define DAP\$V\_BLKCNT, DAP\$B\_BLKCNT, and DAPS\_BLKCNT.  
Define DAP\$V\_DSP\_3NAM.  
Define DAP\$K\_QUIT.
- V03-002 KRM0081 K Malik 23-Mar-1983  
Define DAP\$V\_GEQ\_V70.  
Rename DAP\$B\_SOFTVER to DAP\$B\_DECVER.  
Rename DAP\$B\_USRSOFT to DAP\$K\_USRVER.  
Define DAP\$K\_STMLF and DAP\$K\_STMCR.
- V03-001 KRM0065 K Malik 23-NOV-1982  
Change DAP\$K\_SYSCAP2\_V and DAP\$K\_VALID\_R2F values to support  
rename operation.
- V02-047 JAK0070 J A Krycka 27-JAN-1982  
Remove all "DAP\$V\_..." symbols from expressions and eliminate  
the use of ":" in symbol names to aid in future conversion of  
this MDL file into SDL format.
- V02-046 JAK0063 J A Krycka 24-AUG-1981  
Cleanup:  
Rearrange sections defined by \$DAPPLGDEF.  
Expand several menu fields from one byte to two bytes in length  
(DAP\$W\_CTLMENU, DAP\$W\_TIMENU, DAP\$W\_PROMENU, DAP\$W\_SUMENU).  
For consistency, denote fields that exist in two messages as  
DAP\$S\_name1 and DAP\$S\_name2 (FOP, ALQ, DEQ, DISPLAY, RECNUM).  
Remove unused system specific fields (DAP\$L\_FOP, DAP\$L\_ROP, and  
DAP\$L\_CTX).  
Rename SYSCAP bits (RANREC to RANRRN, MULKEY to IDXORG, and  
BITCOUNT to BITOPT).
- V02-045 JAK0063 J A Krycka 21-AUG-1981  
Upgrade definitions to correspond to DAP V6.0 specification:  
Define DAP\$V\_GEQ\_V60.  
Define DAP\$V\_EXTEND and DAP\$V\_DISPLAY.  
Define new SYSCAP field bits (EXTEND, DISPLAY, GNGOPT, CHGATT,  
CHGTIM, CHGPRO, and CHGNAM).  
Define new FOP field bit (DIR).  
Define new ROP field bits (ROPWAT, RRL, and REA).

Define DAP\$K\_EXTEND\_B and DAP\$K\_EXTEND\_E; remove DAP\$K\_EXTEND.  
Define DAP\$K\_CHANGE\_B, DAP\$K\_CHANGE\_E, and DAP\$K\_TERMINATE.  
Rename DAP\$K\_PURGE to DAP\$K\_RESET.  
Define DAP\$Q\_STX and DAP\$ STX.  
Define DAP\$V\_PDT, DAP\$Q\_PDT, and DAP\$ PDT.  
Define DAP\$V\_ADT, DAP\$Q\_ADT, and DAP\$ ADT.  
Modify value of DAP\$K\_SYSACP1\_V (set EXTEND and DISPLAY bits).  
Modify value of DAP\$K\_SYSACP2\_V (set CHGTIM and CHGPRO bits).

- V02-044 JAK0061 J A Krycka 17-JUL-1981  
Define DAP\$K\_INIBUFSIZ, DAP\$K\_MINBUFSIZ, and DAP\$K\_MAXBUFSIZ.  
Remove DAP\$K\_BUFSIZ\_F and DAP\$K\_BUFSIZ\_R.
- V02-043 JAK0060 J A Krycka 23-JUN-1981  
Define DAP\$K\_TOPS10, and DAP\$K\_TOPS10F.  
Define DAP\$V\_BDT, DAP\$Q\_BDT, and DAP\$ BDT.  
Modify value of DAP\$K\_Flags\_U (remove LEN256 bit).  
Modify value of DAP\$K\_SYSACP1\_V (set RANRFA and BIGBLK bits).
- V02-042 JAK0050 J A Krycka 22-NOV-1980  
Define DAP\$V\_RMS and DAP\$V\_FCS.  
Fix bug in definition of reserved bit in FOP field.  
Change DAP\$K\_BUFSIZ\_F value from <4096+256> to <4096+32>.  
Modify value of DAP\$K\_SYSACP2\_V (include WILDCARD bit).
- V02-041 REFORMAT J A Krycka 26-JUL-1980

++  
Define the overall structure of the DAP control block and symbols related  
to its prologue section.

Note: Longword and quadword fields are longword aligned within the control  
block. Fields longer than 8 bytes are not stored within. Instead a  
descriptor is stored in the control block that points to an external  
buffer where the field data is located.

--

\$STRUCT DAP,PLGDEF ; DAP control block prologue

-----  
Parameter and status section  
-----

F DCODE\_FLG,Q

S VERSION,4,W

S PARTNER,6,W

V <

,32

GEO\_V41

GEO\_V42

GEO\_V52

GEO\_V54

GEO\_V56

GEO\_V60

GEO\_V70

GEO\_V71

,4

VMS\_XPF1

VMS\_XPF2

VMS\_XPF3

VMS\_XPF4

RMS

FCS

STM\_ONLY

,1

VAXVMS

VAXELAN

TOPS10

TOPS20

RT11

RSTS

RSX

IAS

P\_OS

,3

>

F MSG\_BUFI,Q

F MSG\_BUFI,Q

On input, descriptor of message string  
to decode

On output, descriptor of string remaining  
after message just decoded

On input, ignored

```

F DCODE_STS,L ; On output, descriptor of message just
    S ,0,B     decoded; same as MSG_BUG1 on input if
    S DCODE_FID,1,B no blocked message follows
    S DCODE_MSG,2,B Message decode status codes
    S DCODE_MAC,3,B (output from message decode subroutine)
    F MSG_MASR,L Message decode success/fail (1/0) status flag
                    On error, DAP field ID code; else 0
                    Message type (0 if invalid)
                    On error, DAP MACCODE error code; else 0
                    Bit mask of valid messages to receive
                    (input to message decode subroutine)
                    (bit offsets are derived from message type
                     values, e.g., offset for Data message is
                     <1@DAP$K DAT_MSG>)
                    Current CRC resultant value
                    Explicit field found in message flags field
                    Meaning:
                    Message explicitly contained RECNUM field
                    Message explicitly contained CHECK field
                    Spare
                    Spare
-----Message decode section (part 1)-----
F ,L,2 ; Configuration message save section
        (space for DAP$Q SYSCAP bit mask field
         defined by the $DAPCNFDEF macro)
-----Message decode section (parts 2 and 3)-----
F CMWA,L,20 ; Current message work area
    K CMWA,<20*4>
    S ,0,L,4   Current message work area size
-----Message header section
        (space for current message header fields
         defined by the $DAPHDRDEF macro)
-----Message operand section
        (space for current message operand fields
         defined by the $DAPxxxDEF macros, where xxx
         represents the 15 DAP message mnemonics)
        ***** offset = ^X80 = 128 *****
-----Message decode section (parts 4 and 5)-----
F SSPWA,L,4 ; System specific work area
    K SSPWA,<4*4>
    S ,0,L,4   System specific work area size
-----System specific section
        (space for system specific fields
         defined by the $DAPSSPDEF macro)
-----Temporary work area
-----Temporary work area size
-----Spare
-----Define length of DAP control block
E

```

;++  
Define symbols related to the DAP message header.  
;--

```
$STRUCT DAP,HDRDEF      ; DAP message header
F ,L,12                  ; Position to message header section
                           ; of DAP control block
F TYPE,B                 ; DAP message type field (1) : B
K <
  CNF_MSG,1               ; DAP message type:
  ATT_MSG,2               ; Configuration message
  ACC_MSG,3               ; Attributes message
  CTL_MSG,4               ; Access message
  CON_MSG,5               ; Control message
  CON_MSG,5               ; Continue Transfer message
  ACK_MSG,6               ; Acknowledge message
  CMP_MSG,7               ; Access Complete message
  DAT_MSG,8               ; Data message
  STS_MSG,9               ; Status message
  KEY_MSG,10              ; Key Definition Attributes message
  ALL_MSG,11              ; Allocation Attributes message
  SUM_MSG,12              ; Summary Attributes message
  TIM_MSG,13              ; Date and Time Attributes message
  PRO_MSG,14              ; Protection Attributes message
  NAM_MSG,15              ; Name message
  >                      ; (16) reserved for ACL Attributes message
  K VALID R2F,-           ; Mask of DAP messages valid for RMS to send:
  <^X0000EDBE>          ; CNF, ATT, ACC, CTL, CON, CMP, DAT, KEY, ALL,
                           ; TIM, PRO, NAM
  K VALID F2R,-           ; Mask of DAP messages valid for FAL to send:
  <^X0000OFFC6>          ; CNF, ATT, ACK, CMP, DAT, STS, KEY, ALL, SUM,
                           ; TIM, PRO, NAM
F FLAGS,B                ; DAP message flags field (EX-5) : BM
V <M
  STREAMID
  LENGTH
  LEN256
  BITCNT
  TMP1$,1
  SYSPEC
  SEGMENT
  TMP2$,1
  >
  K FLAGS I,<-            ; Define flags options that are invalid:
  <DAP$M_TMP1$>!-          ; Reserved
  <DAP$M_TMP2$>!-          ; Reserved
  0>
  K FLAGS U,<-            ; Define flags options unsupported by VAX:
  <DAP$M_BITCNT>!-          ; BITCNT
  <DAP$M_SEGMENT>!-          ; SEGMENT
  F STREAMID,B             ; Data stream identification field (1) : B
  F LENGTH,B               ; Length (of rest of message) field (1) : B
```

```
F LEN256,B      ; Length extension field (1) : B
F BITCNT,B     ; Bit count field (1) : B
F B,2          ; Padding
F SYSPEC,Q     ; Descriptor pointing to the
E              ; System specific field (I-255) : B
```

++  
Define symbols related to the system specific field (mini-message)  
contained in the DAP message header.  
--

\$STRUCT DAP,SSPDEF      System specific field  
F ,L,32                  Position to system specific section  
F SSP\_MENU,W              of DAP control block  
V <M                    System specific menu field (EX-5) : B  
SSP\_CAP                  Menu of fields to follow:  
SSP\_FLG                 Extended system capabilities  
TMP1\$,14                Extended flags  
>                        Reserved  
K SSP\_MEN\_I,<-          Define SSP\_MENU options that are invalid:  
<DAP\$M\_TMP1\$>!-        Reserved  
0>                         
K SSP\_MEN\_U,<-          Define SSP\_MENU options unsupported by VAX:  
0>                         
F ,W                      Padding  
F SSP\_FLG,L              System specific flags field (EX-5) : B  
V <M                    Meaning:  
LOAD                     Load image modifier for open function  
TMP1\$,31                Reserved  
>                         
K SSP\_FLG\_I,<-          Define SSP\_FLG options that are invalid:  
<DAP\$M\_TMP1\$>!-        Reserved  
0>                         
K SSP\_FLG\_U,<-          Define SSP\_FLG options unsupported by VAX:  
0>                         
F SSP\_CAP,L              System specific capabilities field (EX-5) : B  
V <M                    Partner node supports:  
LOADIM                  Load image function  
.31                      Reserved  
>                         
K SSP\_CAP\_V,<-          Define SSP\_CAP options supported by VAX:  
<DAP\$M\_LOADIM>!-        LOADIM  
0>                         
F ,L,1                   Spare  
E

++  
Define symbols related to the Configuration message (TYPE=1).  
--

\$STRUCT DAP,CNFDEF : DAP Configuration message  
  
M 1  
F ,L,16 Position to message operand section  
of DAP control block  
F BUFSIZ,W Buffer size field (2) : B  
(This is DAP buffer size value from partner)  
F OSTYPE,B Operating system type field (1) : B  
K < Operating system type:  
RT11,1 RT-11  
RSTS,2 RSTS/E  
RSX11S,3 RSX-11S  
RSX11M,4 RSX-11M  
RSX11D,5 RSX-11D  
IAS,6 IAS  
VAXVMS,7 VAX/VMS  
TOPS20,8 TOPS-20  
TOPS10,9 TOPS-10  
RTS8,10 RTS-8  
OS8,11 OS-8  
RSX11MP,12 RSX-11M-PLUS  
COPOS11,13 TOPS-20 (using 2050/2060 front end)  
P OS,14 P/OS  
VAXELAN,15 VAXELAN  
>  
F FILESYS,B File system type field (1) : B  
K < File system type:  
RMS11,1 RMS-11  
RMS20,2 RMS-20  
RMS32,3 RMS-32  
FCS11,4 FCS-11  
RT11FS,5 RT-11  
NO FS,6 No file system present  
TOPS20FS,7 TOPS-20  
TOPS10FS,8 TOPS-10  
OS8FS,9 OS-8  
RMS32S,10 RMS-32 subset  
>  
F VERNUM,B DAP version number field (1) : B  
K VERNUM\_V,7 Value for VAX/VMS V4.0  
F ECONUM,B ECO version number field (1) : B  
K ECONUM\_V,0 Value for VAX/VMS V4.0  
F USRNUM,B User protocol version number field (1) : B  
K USRNUM\_V,0 Value for VAX/VMS V4.0  
F DECVER,B DEC software version number field (1) : B  
K DECVER\_V,4 Value for VAX/VMS V4.0  
F USRVER,B User software version number field (1) : B  
K USRVER\_V,0 Value for VAX/VMS V4.0  
F ,B,3 Padding  
F ,L,13 Spare  
P 1  
F ,L,10 Position to Configuration message save section

```

F SYSCAP,Q          : System capabilities field (EX-12) : BM
V <
  FILALL           : Partner node supports:
  SEQORG           :   Allocation of space at file creation
  RELORG           :   Sequential file organization
  ,1               :   Relative file organization
  EXTEND           :   Reserved for HSHORG
  SEQFIL            :   Manual file extension
  RANRRN           :   Sequential file access (file transfer mode)
  RANVBN           :   Random access by relative record number
  RANKEY           :   Random access by virtual block number
  ,1               :   Random access by key value
  RANRFA            :   Reserved for RANHSH
  IDXORG           :   Random access by record file address
  SWMODE            :   Multi-keyed indexed file organization
  APPEND            :   Dynamic switching of access modes
  SUBMIT            :   Append records to end-of-file
  ,1               :   Command file submission/execution
  MDS               :   Reserved for COMPRESS (data compression)
  DISPLAY           :   Multiple data streams per file
  MSGBLK            :   Display of file attributes on request
  UNRBLK            :   Blocking of DAP messages up to response
  BIGBLK            :       using a 1-byte length field (LENGTH)
  DAPCRC            :   Unrestricted blocking of DAP messages
  KEYXAB            :   Blocking of DAP messages up to response
  ALLXAB            :       using a 2-byte length field (LEN256,LENGTH)
  SUMXAB            :   DAP message CRC checksum
  DIRECTORY         :   Key Definition XAB message
  TIMXAB            :   Allocation XAB message
  PROXAB            :   Summary XAB message
  ,1               :   Directory list operation
  FOPSPL            :   Date and Time XAB message
  FOPSCF            :   File Protection XAB messsage
  FOPDLT            :   Reserved for ACLXAB
  >
  ,32              :   Spool file on close FOP option
  ,1               :   Execute command file on close FOP option
  SEQRAC            :   Delete file on close FOP option

V <
  ,1               : Partner node supports:
  (skip over bits defined above)
  ,1               : Reserved for DFTFIL (default file spec)
  SEQRAC           : Sequential record access
  ,1               : Reserved for RECOVERY
  BITOPT           : Bit count option in the FLAGS field
  WARNING          : Warning Status message and associated error
                     : recovery message exchange
  RENAME            : File rename operation
  WILDCARD          : Wildcard operations (excluding directory)
  GNGOPT            : Go/Nogo option in the ACCOPT field
  NAMMSG            : Name message
  SEGMSG            : Segmented DAP messages
  CHGATTCLS        : Changing file attributes on close via ATT msg
  CHGTIMCLS        : Changing file attributes on close via TIM msg
  CHGPROCLS        : Changing file attributes on close via PRO msg
  CHGNAMCLS        : Changing file attributes on close via NAM msg
                     : (i.e., rename of file)
  MODATTCRE        : Modified attributes returned on create

```

NAM3PART  
CHGATTRREN  
CHGTIMREN  
CHGPROREN  
BLKCNT  
OCTALVER  
.11  
>  
K SYSCAP1 V,-  
<^XEFF67DF7>  
  
K SYSCAP2 V,-  
<^X0000T962>  
E

3-part Name message format in DISPLAY field  
of both Access and Control messages  
Changing file attributes on rename via ATT msg  
Changing file attributes on rename via TIM msg  
Changing file attributes on rename via PRO msg  
BLKCNT field in Control message  
Octal version numbers only in file specs  
(bit is valid only for DAP V7.0 or later)  
Reserved  
  
Define supported SYSCAP options (bits 00-31):  
FILALL, SEQORG, RELORG, EXTEND, SEQFIL,  
RANRRN, RANVBN, RANKEY, RANRFA, IDXORG, SWMODE,  
APPEND, SUBMIT, DISPLAY, MSGBLK, BIGBLK,  
DAPCRC, KEYXAB, ALLXAB, SUMXAB, DIRECTORY,  
TIMXAB, PROXAB, FOPSPL, FOPSCF, FOPDLT  
Define supported SYSCAP options (bits 32-63):  
SEQRAC, RENAME, WILDCARD, NAMMSG, CHGTIMCLS,  
CHGPROCLS

;+  
; Define symbols related to the Attributes message (TYPE=2).  
;--

```
$STRUCT DAP,ATTDEF      : DAP Attributes message
F ,L,16                  : Position to message operand section
                            : of DAP control block
F ATTMENU,L               : Attributes menu field (EX-6) : BM
V <M                      : Menu of fields to follow:
    DATATYPE              : Data type
    ORG                     : File organization
    RFM                     : Record format
    RAT                     : Record attributes
    BLS                     : Block size
    MRS                     : Maximum record size
    ALQ1                   : Allocation quantity
    BKS                     : Bucket size
    FSZ                     : Fixed control area size
    MRN                     : Maximum record number
    RUNSYS                 : Run-time system identification
    DEQ1                   : Default extension quantity
    FOP1                   : File options
    BSZ                     : Byte size field
    DEV                     : Device characteristics
    TMP1$,1                : Reserved for SDC
    LRL                     : Longest record length
    HBK                     : Highest virtual block number
    EBK                     : End-of-file block number
    FFB                     : First free byte in end-of-file block
    SBN                     : Starting logical block number
    TMP2$,11               : Reserved
>
K ATTMENU_I,<-           : Define ATTMENU options that are invalid:
<DAPSM_TMP1$>!-          : Reserved
<DAPSM_TMP2$>!-          : Reserved
0>
K ATTMENU_U,<-           : Define ATTMENU options unsupported by VAX:
0>
F DATATYPE,B              : Data type field (EX-2) : BM
V <M                      : Define offsets and masks:
    ASCII                  : Data in ASCII format
    IMAGE                  : Data in IMAGE format
    TMP1$,1                : Reserved for EBCDIC
    CMPFMT                : Compressed format
    EXEC                   : File contains executable code
    PRIV                   : File contains privileged code
    TMP2$,1               : Reserved (ignore if received)
    ZERO                   : (this was attributes match flag in DAP V4.1)
                           : Zero file on erase file operation
>
K DATATYP_I,<-            : Define DATATYPE options that are invalid:
<DAPSM_TMP1$>!-          : Reserved
0>
K DATATYP_U,<-            : Define DATATYPE options unsupported by VAX:
<DAPSM_CMPFMT>!-          : CMPFMT
```

```

<DAPSM_ZERO>!-
0>
K DATATYP D,<-
<DAPSM_IMAGE>!-
0>
F ORG,B
K <
SEQ,0
REL,16
IDX,32
>
K ORG_D,DAP$K_SEQ
F RFM,B
K <
UDF,0
FIX,1
VAR,2
VFC,3
STM,4
STMLF,5
STMCR,6
>
K RFM_D,DAP$K_FIX
F RAT,B
V <M
FTN
CR
PRN
BLK
EMBEDDED
TMP1$,1
LSA
MACY11
>
K RAT_I,<-
<DAPSM_TMP1$>!-
0>
K RAT_U,<-
<DAPSM_LSA>!-
<DAPSM_MACY11>!-
0>
K RAT_D,<-
<DAPSM_EMBEDDED>!-
0>

F BLS,W
K BLS_D,512
F MRS_W
F ALQ1,L
F BKS,B
F FSZ,B
F BSZ,B
K BSZ_D,8

```

ZERO  
Define default DATATYPE value  
IMAGE

File organization field (1) : B  
File organization:  
Sequential  
Relative  
Indexed  
(48) reserved for hash

Define default ORG value  
Record format field (1) : B  
Record format:  
Undefined  
Fixed length  
Variable length  
Variable length with fixed control  
Stream ASCII  
Stream LF  
Stream CR

Define default RFM value  
Record attributes field (EX-3) : BM  
Meaning:  
Fortran carriage control  
Implied (LF-Record-(CR) carriage control  
Print file format  
Records do not cross block boundaries  
Records have embedded control characters  
Reserved  
Line sequenced ASCII  
MACY11 format

Define RAT options that are invalid:  
Reserved

Define RAT options unsupported by VAX:  
LSA  
MACY11

Define default RAT value  
EMBEDDED

\*\*\*\*\* No default value is stated in the  
\*\*\*\*\* DAP spec although some systems  
\*\*\*\*\* treat EMBEDDED as the default  
Block size field (2) : B  
Define default BLS value  
Maximum record size field (2) : B  
Allocation quantity field (I-5) : B  
Bucket size field (1) : B  
Fixed control area size field (1) : B  
Byte size field (1) : B  
Define default BSZ value

F ,B	Padding
F DEQ1,W	Default extension quantity field (2) : B
F ,B,2	Padding
F MRN,L	Maximum record number field (I-5) : B
F RUNSYS,Q	Descriptor pointing to the Run-time system field (I-40) : A
F FOP1,L	File options field (EX-6) : BM
V <CM	Options:
RWO	Rewind magtape on open
RWC	Rewind magtape on close
TMP1\$,1	Reserved
POS	Position magtape past last created file
DLK	Do not lock file if improperly closed
DIR	Directory file
FLK	File locked
CTG	Contiguous space allocation
SUP	Supersede existing file on create
NEF	Inhibit positioning magtape to end-of-file
TMP	Create temporary file
TMD	Create temporary file and mark for delete
TMP2\$,1	Reserved
DMO	Dismount magtape on close
WCK	Enable write checking
RCK	Enable read checking
CIF	Create if no file present else open file
TMP3\$,1	Reserved for LKO
SQO	Sequential access only
MXV	Maximize version number
SPL	Spool file on close
SCF	Submit command file on close
DLT	Delete file on close (used stand-alone or as a suboption to SCF or SPL)
CBT	Contiguous-best-try space allocation
TMP4\$,1	Reserved for WAT
DFW	Deferred write (REL and IDX files)
TEF	Truncate at EOF on close (SEQ files)
OFP	Output file parse
TMP5\$,4	Reserved
>	
K FOP_I,<-	Define FOP options that are invalid: (This is used for both FOP1 and FOP2 fields)
<DAPSM_TMP1\$> -	Reserved
<DAPSM_TMP2\$> -	Reserved
<DAPSM_TMP3\$> -	Reserved
<DAPSM_TMP4\$> -	Reserved
<DAPSM_TMP5\$> -	Reserved
0>	
K FOP_U,<-	Define FOP options unsupported by VAX: (This is used for both FOP1 and FOP2 fields)
<DAPSM_DMO> -	DMO Note: allow DLK, DIR, and FLK
0>	Device characteristics field (EX-6) : BM
F DEV,L	Meaning:
V <	Device is record oriented
DEVREC	Carriage control device
DEVCCL	

DEVTRM : Device is a terminal  
DEVDIR : Device is directory structured  
DEVSDI : Device is single directory structured  
DEVSQD : Seq. block oriented device (e.g., magtape)  
TMP1\$,1,,M Reserved  
DEVFOD : Files oriented device (e.g., disk, magtape)  
DEVSHR : Device is sharable  
DEVSPL : Device is being spooled  
DEVMNT : Device is mounted  
DEVDMT : Device is marked for dismount  
DEVALL : Device is allocated  
DEVIDV : Device is capable of providing input  
DEVODV : Device is capable of providing output  
DEVSWL : Device is software write locked  
DEVALV : Device is available  
DEVELG : Device has error logging enabled  
DEVMBX : Device is a mailbox  
DEVRTM : Device is realtime in nature  
DEVRND : Device allows random access  
DEVRCK : Device has read checking enabled  
DEVWCK : Device has write checking enabled  
DEVFOR : Device is mounted as foreign (not files-11)  
DEVNET : Network device  
DEVGEN : Generic device  
TMP2\$,6,,M Reserved  
>  
K DEV\_I,<-  
<DAPSM\_TMP1\$>|-  
<DAPSM\_TMP2\$>|-  
O>  
K DEV\_U,<-  
O>  
F ,L,1  
F LRL,W  
F FFB,W  
F HBK,L  
F EBK,L  
F SBN,L  
E

Define DEV options that are invalid:  
Reserved  
Reserved

Define DEV options unsupported by VAX:  
Reserved for SDC  
Longest record length field (2) : B  
First free byte in EOF block field (2) : B  
Highest virtual block number field (I-5) : B  
End-of-file block number field (I-5) : B  
Starting logical block number field (I-5) : B

```
++ Define symbols related to the Access message (TYPE=3).
--
```

\$STRUCT DAP,ACCDEF	DAP Access message
F ,L,16	Position to message operand section of DAP control block
F ACCFUNC,B	Access function field (1) : B
K <	Access function:
OPEN,1	Open a file
CREATE,2	Create a file
RENAME,3	Rename a file
ERASE,4	Erase (delete) a file
(5) reserved	(5) reserved
DIR LIST,6	Return directory list
SUBMIT,7	Submit (copy and execute) a command file
EXECUTE,8	Execute a command file
LOAD,255	Load image file--for internal use by FAL
>	
F ACCOPT,B	Access options field (EX-5) : BM
V <M	Meaning:
NONFATAL	I/O errors are not fatal
TMP1\$,2	Reserved--used to be STS_STORE and STS_RETRV
RET_CRC	Return CRC value with each DAP message
GO_NOGO	Go/nogo option
TMP2\$,3	Reserved
>	
K ACCOPT_I,<- <DAP\$M_TMP2\$>!- 0>	Define ACCOPT options that are invalid: Reserved
K ACCOPT_U,<- <DAP\$M_TMP1\$>!- <DAP\$M_GO_NOGO>!- 0>	Define ACCOPT options unsupported by VAX: Reserved--was defined in DAP V5.4 GO_NOGO
F FAC,B	File access field (EX-3) : BM
V <M	Access for:
PUT	Put record
GET	Get record
DEL	Delete record
UPD	Update record
TRN	Truncate file
BIO	Block I/O operations only
BRO	Mixed record and block I/O operations
APP	Append record
>	
K FAC_I,<- 0>	Define FAC options that are invalid:
K FAC_U,<- 0>	Define FAC options unsupported by VAX: Note: allow APP
K FAC_D,<- <DAP\$M_GET>!- 0>	Define default FAC value GET
F SHR,B	File sharing field (EX-3) : BM
V <M	Shared access for:
SHRPUT	Put record

SHRGET : Get record  
SHRDEL : Delete record  
SHRUPD : Update record  
MSE : Multiple record streams enabled  
UPI : User provided interlocking  
NIL : No shared access allowed  
TMP1\$,1 : Reserved  
>  
K SHR\_I,<- : Define SHR options that are invalid:  
<DAP\$M\_TMP1\$>!-  
0>  
K SHR\_U,<- : Define SHR options unsupported by VAX:  
<DAP\$M\_MSE>!-  
0>  
K SHR\_D,<- : Define default SHR value  
0>  
F FILESPEC,Q : \*\*\*\*\* This is contrary to the DAP spec  
F DISPLAY1,W : \*\*\*\*\* which says that DAP\$M\_GET is the default  
V <M : Descriptor pointing to the  
DSP\_ATT : File specification field (I-255) : A  
DSP\_KEY : Display attributes field (EX-4) : BM  
DSP\_ALL : Return the following:  
DSP\_SUM : Attributes message  
DSP\_TIM : Key Definition Attributes message  
DSP\_PRO : Allocation Attributes message  
TMPT\$,2 : Summary Attributes message  
TMPT\$,2 : Date and Time Attributes message  
TMPT\$,2 : Protection Attributes message  
TMPT\$,2 : Reserved  
TMPT\$,2 : Reserved for ACL Attributes message  
DSP\_NAM : Name message  
DSP\_3NAM : 3-part Name message  
TMP2\$,6 : Reserved  
>  
K DISPLAY\_I,<- : Define DISPLAY options that are invalid:  
<DAP\$M\_TMP1\$>!-  
<DAP\$M\_TMP2\$>!-  
0>  
K DISPLAY\_U,<- : Define DISPLAY options unsupported by VAX:  
<DAP\$M\_DSP\_3NAM>!-  
0>  
F W : (This is used for both DISPLAY1 and DISPLAY2)  
F PASSWORD,Q : Reserved  
F .L,10 : 3-Part Name message  
E : Padding  
F : Descriptor pointing to the  
F : Password field (I-40) : B  
F : Spare

;++ Define symbols related to the Control message (TYPE=4).  
;--

```
$STRUCT DAP,CTLDEF      : DAP Control message
F ,L,16                  Position to message operand section
                           of DAP control block
F CTLFUNC,B               Control function field (1) : B
K <
  GET READ,1              Control function:
  CONNECT,2
  UPDATE,3
  PUT WRITE,4
  DELETE,5
  REWIND,6
  TRUNCATE,7
  RELEASE,9
  FREE,10
  EXTEND_B,11
  FLUSH,T2
  FIND,14
  EXTEND_E,15
  DISPLAY,16
  SPACE_FW,17
  SPACE_BW,18
>
F ,B,3                  Padding
F CTLMENU,W              Control menu field (EX-4) : BM
V <M
  RAC
  KEY
  KRF
  ROP
  TMP1$,1
  DISPLAY2
  BLKCNT
  TMP2$,9
>
K CTLMENU_I,<-           Define CTLMENU options that are invalid:
  <DAPSM_TMP1$>!-
  <DAPSM_TMP2$>!-
  0>
K CTLMENU_U,<-           Define CTLMENU options unsupported by VAX:
  <DAPSM_BLKCNT>!-
  0>
F RAC,B                  Record access field (1) : B
K <
  SEQ_ACC,0
  KEY_ACC,1
  RFA_ACC,2
>
                           Record access type:
                           Sequential record access
                           Random access by key value or record number
                           Random access by RFA
```

SEQ_FILE,3	: Sequential file transfer mode
BLK_VBN,4	Block I/O access by VBN
BLK_FILE,5	Block I/O file transfer mode
>	
K RAC_D,DAP\$K_SEQ_ACC	Define default RAC value
F KRF,B	Key of reference field (1) : B
F KEY,Q	Descriptor pointing to the Key field (I-255) : B
F ROP_L	Record options field (EX-6) : BM
V <M	Meaning:
EOF	Position to end-of-file
FDL	Fast record delete
UIF	Convert put to update function as required
TMP1\$,1	Reserved for HSH
LOA	Load buckets according to bucket fill size
ULK	Enable manual unlocking of records; disable automatic unlocking
TPT	Truncate put; write EOF then put (SEQ files)
RAH	Read ahead
WBH	Write behind
KGE	Key value is greater than or equal
KGT	Key value is greater than
NLK	Do not lock record
RLK	Read of locked record allowed
ROPBIO	Connect for block I/O operations only
LIM	Compare for key limit reached
NXR	Non-existent record processing
ROPWAT	Wait until locked record becomes available
RRL	Read record regardless of lock
REA	Lock record but allow others to read it
TMP2\$,13	Reserved
>	
K ROP_I,<- <DAP\$M_TMP1\$> - <DAP\$M_TMP2\$> - 0>	Define ROP options that are invalid: Reserved Reserved
K ROP_U,<- 0>	Define ROP options unsupported by VAX:
F DISPLAY2,W	Display attributes field (EX-4) : BM (see DISPLAY1 field of Access message for bit definitions)
F BLKCNT,B	Block count field
F ,B	Padding
F ,L,10	Spare
E	

;+++  
; Define symbols related to the Continue Transfer message (TYPE=5).  
;--

```
$STRUCT DAP,CONDEF      ; DAP Continue Transfer message
F ,L,16                  ; Position to message operand section
F CONFUNC,B              ; of DAP control block
K <                     ; Continue transfer function field (1) : B
    RETRY,1               ; Recovery action:
    SKIP REC,2            ; Try access function again
    ABORT,3                ; Skip record in error and continue
    RESUME,4               ; Abort request
    QUIT,5                 ; Resume operation
    >                      ; Terminate file processing
    F ,B,3
    F ,L,15
E
```

```
;++  
; Define symbols related to the Acknowledge message (TYPE=6).  
;--
```

```
$STRUCT DAP,ACKDEF      ; DAP Acknowledge message  
F ,L,16                  ; Position to message operand section  
F ,L,16                  ; of DAP control block  
E                         ; Spare
```

;++  
; Define symbols related to the Access Complete message (TYPE=7).  
;--

```
$STRUCT DAP,CMPDEF      : DAP Access Complete message
F ,L,16                  : Position to message operand section
                            : of DAP control block
F CMPFUNC,B               : Access complete function field (1) : B
K <
  CLOSE,1                 : Access complete function:
  RESPONSE,2              : Close file
  RESET,3                 : Response to partner's CMPFUNC request
  DISCONN,4                : Close file and restore it to initial state
  SKIP_FILE,5              : (this used to be named PURGE)
  CHANGE_B,6               : Disconnect record stream
  CHANGE_E,7               : Skip to next file (i.e., close this file
                            : and open next file)
  TERMINATE,8              : Close file and change its file attributes
                            : (beginning message of sequence)
  >                      : Close file and change its file attributes
                            : (ending message of sequence)
  >                      : Terminate (abort) operation and re-initialize
F ,B                      : Padding
F CHECK,W                 : CRC Checksum field (2) : B
F FOP2,L                 : File options field (EX-6) : BM
                            : (see FOP1 field of Attributes message
                            : for bit definitions)
F ,L,14                  : Spare
E
```

```
++  
Define symbols related to the Data message (TYPE=8).  
--  
$STRUCT DAP,DATDEF      ; DAP Data message  
F ,L,16                  ; Position to message operand section  
                           ; of DAP control block  
F RECNUM1,L               ; Record number field (I-8) : B  
F FILEDATA,Q              ; Descriptor pointing to the  
                           ; File data field (rest-of-message) : B  
F ,L,13                  ; Spare  
E
```

++  
Define symbols related to the Status message (TYPE=9).  
--

```
$STRUCT DAP,STSDEF      ; DAP Status message
F ,L,16                  Position to message operand section
F STSCODE,W              of DAP control block
V <M                    DAP status code field (2) : B
MICCODE,12                Subfields:
MACCODE,4                 Micro status code
>                         Macro status code
K <,S                   MACCODE field status code classes:
PENDING,0                Operation in progress
SUCCESS,1                Operation completed successfully
UNSUPPORT,2              DAP implementation does not support request
                          (3) reserved
FILE_OPEN,4               Error related to opening a file
FILE_XFER,5              Error encountered while file was open
                          (i.e., during record access)
WARNING,6                Warning error condition
FILE_CLOS,7              Error related to closing a file
FORMAT,8                 Parse error caused by incorrect format
INVALID,9                Invalid DAP field value
MSG_SYNC,10              DAP message received out-of-order
>
F RFA,W,3                Record file address field (I-8) : B
F RECNUM2,L              Record number field (I-8) : B
F STV,L                  Secondary status field (I-8) : B
F STX,Q                  Descriptor pointing to the
                          Secondary status text field (I-255) : A
F ,L,10                  Spare
E
```

```

:+++
: Define symbols related to the Key Definition Attributes message (TYPE=10).
:--



$STRUCT DAP,KEYDEF      : DAP key definition Attributes message
F ,L,16                  : Position to message operand section
                           : of DAP control block
F KEYMENU,L               : Key definition menu field (EX-6) : BM
V <M                      : Menu of fields to follow:
   FLG
   DFL
   IFL
   NSG
   REF
   KNM
   NUL
   IAN
   LAN
   DAN
   DTP
   RVB
   TMP1$,1
   DVB
   DBS
   IBS
   LVL
   TKS
   MRL
   TMP2$,13
   >
   K KEYMENU_I,<-
     <DAPSM_TMP1$>!-
     <DAPSM_TMP2$>!-
     0>
   K KEYMENU_U,<-
     0>
   F DFL,W
   F IFL,W
   F FLG,B
   V <M
     DUP
     CHG
     NUL CHR
     TMPTS$,5
   >
   K FLG_I,<-
     <DAPSM_TMP1$>!-
     0>
   K FLG_U,<-
     0>
   F NSG,B
   F POS TMP,W
   S SIZ TMP,0,B
   F POS,D,8
   S POS0,0,W
                           : Reserved for HAL
                           : DVB
                           : DBS
                           : IBS
                           : LVL
                           : TKS
                           : MRL
                           : Reserved
                           : Define KEYMENU options that are invalid:
                           : Reserved
                           : Reserved
                           : Define KEYMENU options unsupported by VAX:
                           : Data bucket fill quantity field (2) : B
                           : Index bucket fill quantity field (2) : B
                           : Key options field (EX-3) : BM
                           : Meaning:
                           : Duplicate key values allowed
                           : Key field may change on update (alt key)
                           : Null key character defined (alt key)
                           : Reserved
                           : Define key options (FLG) that are invalid:
                           : Reserved
                           : Define key options (FLG) unsupported by VAX:
                           : Number of key segments field (1) : B
                           : Temporary work space for POS field processing
                           : Temporary work space for SIZ field processing
                           : Key segment position field (2) : B
                           : Segment 0

```

```
S POS1,2,W : Segment 1
S POS2,4,W : Segment 2
S POS3,6,W : Segment 3
S POS4,8,W : Segment 4
S POS5,10,W : Segment 5
S POS6,12,W : Segment 6
S POS7,14,W : Segment 7
F SIZ,B,8 : Key segment size field (1) : B
S SIZ0,0,B : Segment 0
S SIZ1,1,B : Segment 1
S SIZ2,2,B : Segment 2
S SIZ3,3,B : Segment 3
S SIZ4,4,B : Segment 4
S SIZ5,5,B : Segment 5
S SIZ6,6,B : Segment 6
S SIZ7,7,B : Segment 7
F KNM,Q : Descriptor pointing to the
            Key name field (I-40) : A
F REF,B : Key of reference field (1) : B
F NUL,B : Null key character field (1) : B
F IAN,B : Index area number field (1) : B
F LAN,B : Lowest level index area number field (1) : B
F DAN,B : Data area number field (1) : B
F DTP,B : Key data type field (1) : B
K < : Data type:
      STG,0 : String
      IN2,1 : Signed 2-byte integer
      BN2,2 : Unsigned 2-byte integer (binary)
      IN4,3 : Signed 4-byte integer
      BN4,4 : Unsigned 4-byte integer (binary)
      PAC,5 : Packed decimal (0-31 digits plus sign)
      IN8,6 : Signed 8-byte integer
      BN8,7 : Unsigned 8-byte integer (binary)
      >
K DTP_D,DAP$K_STG : Define default DTP value
F MRL,W : Minimum record length to contain key field (2) : B
F RVB,L : Root bucket start VBN field (I-8) : B
F DVB,L : First data bucket start VBN field (I-8) : B
F DBS,B : Data bucket fill size field (1) : B
F IBS,B : Index bucket fill size field (1) : B
F LVL,B : Level of root buckets field (1) : B
F TKS,B : Total key size field (1) : B
E
```

++  
Define symbols related to the Allocation Attributes message (TYPE=11).  
--

```
$STRUCT DAP,ALLDEF      ; DAP Allocation Attributes message
F ,L,16
F ALLMENU,W             ; Position to message operand section
V <M                   ; of DAP control block
                         ; Allocation menu field (EX-6) : BM
                         ; Menu of fields to follow:
                         ; VOL
                         ; ALN
                         ; AOP
                         ; LOC
                         ; TMP1$,1
                         ; ALQ2
                         ; AID
                         ; BKZ
                         ; DEQ2
                         ; TMP2$,7
                         ;
K ALLMENU_I,<-          ; Define ALLMENU options that are invalid:
<DAPSM_TMP1$>!-        ; Reserved
<DAPSM_TMP2$>!-        ; Reserved
0>
K ALLMENU_U,<-          ; Define ALLMENU options unsupported by VAX:
0>
F VOL,W                 ; Relative volume number field (2) : B
F ALN,B                 ; Alignment options field (EX-4) : BM
K <
ANY,0                   ; Alignment types:
CYL,1                   ; Any allocation placement is ok
LBN,2                   ; Align on cylinder boundary
VBN,3                   ; Align on specified logical block
RFI,4                   ; Allocate near specified virtual block
                         ; Allocate near specified related file
                         ;
F AOP,B                 ; Allocation options field (EX-4) : BM
V <M                   ; Options:
HRD                     ; Return error if requested allocation fails
CTG2                    ; Contiguous space allocation
CBT2                    ; Contiguous-best-try space allocation
ONC                     ; Allocate space on cylinder boundary
TMP1$,4
                         ;
K AOP_I,<-              ; Define AOP options that are invalid:
<DAPSM_TMP1$>!-        ; Reserved
0>
K AOP_U,<-              ; Define AOP options unsupported by VAX:
0>
F ,B,2
F LOC_L                ; Padding
F ALQ2,L               ; Starting location field (I-8) : B
F AID,B                ; Allocation quantity field (I-5) : B
F BKZ,B                ; Area identification field (1) : B
F DEQ2,W               ; Bucket size field (1) : B
F ,L,11                 ; Default extension quantity field (2) : B
                         ; Spare
```

DAPDEF.MDL;1

16-SEP-1984 16:38:17.80 M 16 Page 28

E

:

```
:++  
: Define symbols related to the Summary Attributes message (TYPE=12).  
:--  
  
$STRUCT DAP,SUMDEF      : DAP summary Attributes message  
  
F .L,16                  : Position to message operand section  
F SUMENU,W               : of DAP control block  
V <M                     : Summary menu field (EX-6) : BM  
  NOK  
  NOA  
  NOR  
  PVN  
  TMP1$,12  
  >  
K SUMENU_I,<-             : Menu of fields to follow:  
  <DAP$M_TMP1$>!-  
  O>  
K SUMENU_U,<-             : NOK  
  O>  
F PVN,W                  : NOA  
F NOK,B                  : NOR  
F NOA,B                  : PVN  
F NOR,B                  : Reserved  
F .B                      :  
F .L,14                  :  
E                         ;  
  
                           Define SUMENU options that are invalid:  
                           Reserved  
  
                           Define SUMENU options unsupported by VAX:  
                           Note: allow NOR  
                           Prologue version number field (1) : B  
                           Number of keys field (1) : B  
                           Number of allocation areas field (1) : B  
                           Number of record descriptors field (1) : B  
                           Padding  
                           Spare
```

++  
Define symbols related to the Date and Time Attributes message (TYPE=13).  
--

\$STRUCT DAP,TIMDEF : DAP date and time Attributes message  
F ,L,16 Position to message operand section  
of DAP control block  
F TIMENU,W Date and time menu field (EX-6) : BM  
V <M Menu of fields to follow:  
CDT  
RDT  
EDT  
RVN  
BDT  
PDT  
ADT  
TMP1\$,9  
>  
K TIMENU\_I,<- Define TIMENU options that are invalid:  
<DAP\$M\_TMP1\$>!- Reserved  
0>  
K TIMENU\_U,<- Define TIMENU options unsupported by VAX:  
0> Note: allow PDT and ADT  
F RVN,W Revision number field (2) : B  
F ,L Padding  
F CDT,Q Creation date and time field (18) : A  
(stored in DAP control block as a  
64-bit time value per VMS convention)  
F RDT,Q Revision date and time field (18) : A  
(stored in DAP control block as a  
64-bit time value per VMS convention)  
F EDT,Q Expiration date and time field (18) : A  
(stored in DAP control block as a  
64-bit time value per VMS convention)  
F BDT,Q Backup date and time field (18) : A  
(stored in DAP control block as a  
64-bit time value per VMS convention)  
F PDT,Q Physical creation date and time field (18) : A  
(stored in DAP control block as a  
64-bit time value per VMS convention)  
F ADT,Q Accessed date and time field (18) : A  
(stored in DAP control block as a  
64-bit time value per VMS convention)  
F ,L,2 Spare  
E

++  
: Define symbols related to the Protection Attributes message (TYPE=14).  
--

\$STRUCT DAP,PRODEF : DAP protection Attributes message  
F ,L,16 Position to message operand section  
of DAP control block  
F PROMENU,W Protection menu field (EX-6) : BM  
V <M Menu of fields to follow:  
OWNER  
PROSYS  
PROOWN  
PROGRP  
PROWLD  
TMP1\$,11  
>  
K PROMENU\_I,<- Define PROMENU options that are invalid:  
<DAPSM\_TMP1\$>!-  
0>  
K PROMENU\_U,<- Define PROMENU options unsupported by VAX:  
0>  
F ,W,3 Padding  
F OWNER,Q Descriptor pointing to the  
File owner field (I-40) : A  
F PROSYS,W System protection field (EX-3) : BM  
V <M Meaning:  
RED\_ACC Deny read access  
WRT\_ACC Deny write access  
EXE\_ACC Deny execute access  
DLT\_ACC Deny delete access  
APP\_ACC Deny append access  
DIR\_ACC Deny directory access  
UPD\_ACC Deny update access  
CHG\_ACC Deny change protection access  
EXT\_ACC Deny extend access  
TMPT\$,7 Reserved  
>  
K PROTECT\_I,<- Define protection options that are invalid:  
<DAPSM\_TMP1\$>!-  
0>  
K PROTECT\_U,<- This mask applies to PROSYS, PROOWN, PROGRP,  
0> and PROWLD fields  
Define protection options unsupported by VAX:  
This mask applies to PROSYS, PROOWN, PROGRP,  
and PROWLD fields  
Note: allow APP\_ACC, DIR ACC, UPD\_ACC,  
CHG ACC, and EXT ACC  
F PROOWN,W Owner protection field (EX-3) : BM  
F PROGRP,W Group protection field (EX-3) : BM  
F PROWLD,W World protection field (EX-3) : BM  
F ,L,10 Spare  
E

;++  
; Define symbols related to the Name Attributes message (TYPE=15).  
;--

```
$STRUCT DAP,NAMDEF      ; DAP name Attributes message
F ,L,16                  ; Position to message operand section
                           ; of DAP control block
F NAMETYPE,B              ; Name type field (EX-3) : BM
V <M
  FILSPEC
  FILNAME
  DIRNAME
  VOLNAME
  DFTSPEC
  TMP1$,1
  TMP2$,2
>
F ,B,3                  ; Type:
K NAMETYP_I,<-           ; Primary file specification
<DAP$M_TMP1$>!-          ; File name
<DAP$M_TMP2$>!-          ; Directory name
0>                         ; Volume or structure name
K NAMETYP_U,<-           ; Default file specification
<DAP$M_DFTSPEC>!-        ; Reserved for RELSPEC
0>                         ; Reserved
F NAMESPEC,Q              ; Padding
F ,L,13                  ; Define NAMETYPE options that are invalid:
                           ; Reserved
                           ; Reserved
F NAMESPEC,Q              ; Define NAMETYPE options unsupported by VAX:
                           ; DFTSPEC
F ,L,13                  ; Descriptor pointing to the
                           ; Name field (I-255) : A
                           ; Spare
```

++  
Define symbols related to DAP message CRC checksum computation.  
The CRC polynomial function (order T6) used is:

X\*\*16 + X\*\*15 + X\*\*13 + X\*\*7 + X\*\*4 + X\*\*2 + X\*\*1 + 1

--\$STRUCT DAP,CRCDEF : DAP message CRC checksum symbol definitions

K CRC\_INIT,<^X0000FFFF> : Initial CRC value  
K CRC\_POLY,<^X0000E905> : CRC polynomial representation used as  
: input to LIB\$CRC\_TABLE to generate  
: the CRC polynomial table below:  
K CRC\_TBL0,<^X00000000> : Table entry 0  
K CRC\_TBL1,<^X000053E3> : Table entry 1  
K CRC\_TBL2,<^X0000A7C6> : Table entry 2  
K CRC\_TBL3,<^X0000F425> : Table entry 3  
K CRC\_TBL4,<^X00009D87> : Table entry 4  
K CRC\_TBL5,<^X0000CE64> : Table entry 5  
K CRC\_TBL6,<^X00003A41> : Table entry 6  
K CRC\_TBL7,<^X000069A2> : Table entry 7  
K CRC\_TBL8,<^X0000E905> : Table entry 8  
K CRC\_TBL9,<^X0000BAE6> : Table entry 9  
K CRC\_TBLA,<^X00004EC3> : Table entry 10  
K CRC\_TBLB,<^X00001D20> : Table entry 11  
K CRC\_TBLC,<^X00007482> : Table entry 12  
K CRC\_TBLD,<^X00002761> : Table entry 13  
K CRC\_TBLE,<^X0000D344> : Table entry 14  
K CRC\_TBLF,<^X000080A7> : Table entry 15

E

++  
\$DAPFIDDEF defines DAP field identification code symbols.  
These are used to identify a field in a DAP Status message.  
--

\$STRUCT DAP,FIDDEF ; DAP field ID codes

K <,\$  
UNKNOWN,0  
TYPE,8  
>  
K <,\$  
FLAGS,8  
STREAMID,9  
LENGTH,10  
LEN256,11  
BITCNT,12  
SYSPEC,14  
SSP\_MENU,14  
SSP\_CAP,14  
SSP\_FLG,14  
>  
K <,\$  
BUFSIZ,16  
OSTYPE,17  
FILESYS,18  
VERNUM,19  
ECONUM,20  
USRNUM,21  
DECVER,22  
USRVER,23  
SYSCAP,24  
>  
K <,\$  
ATTRMENU,16  
DATATYPE,17  
ORG,18  
RFM,19  
RAT,20  
BLS,21  
MRS,22  
ALQ1,23  
BKS,24  
FSZ,25  
MRN,26  
RUNSYS,27  
DEQ1,28  
FOP1,29  
BSZ,30  
DEV,31  
LRL,33  
HBK,34  
EBK,35

; Miscellaneous field codes:  
Unknown field  
DAP message type field

; Message header field codes:  
DAP message flags field  
Data stream identification field  
Length field  
Length extension field  
Bit count field  
(13) reserved  
System specific field  
whose subfields use the same code:  
System specific menu field  
System specific capabilities field  
System specific flags field

; Configuration message field codes:  
Buffer size field  
Operating system type field  
File system type field  
DAP version number field  
ECO version number field  
User protocol version number field  
DEC software version number field  
User software version number field  
System capabilities field

; Attributes message field codes:  
Attributes menu field  
Data type field  
File organization field  
Record format field  
Record attributes field  
Block size field  
Maximum record size field  
Allocation quantity field  
Bucket size field  
Fixed control area size field  
Maximum record number field  
Run-time system field  
Default extension quantity field  
File options field  
Byte size field  
Device characteristics field  
(32) reserved for SDC field  
Longest record length field  
Highest virtual block number field  
End-of-file block number field

FFB,36  
SBN,37  
>  
K <,\$  
ACC FUNC,16  
ACCOPT,17  
FILESPÉC,18  
FAC,19  
SHR,20  
DISPLAY1,21  
PASSWORD,22  
>  
K <,\$  
CTL FUNC,16  
CTL MENU,17  
RAC,18  
KEY,19  
KRF,20  
ROP,21  
DISPLAY2,23  
BLKCNT,24  
>  
K <,\$  
CONFUNC,16  
>  
  
K <,\$  
CMP FUNC,16  
TOP2,17  
CHECK,18  
>  
K <,\$  
RÉCNUM1,16  
FILEDATA,17  
>  
K <,\$  
STSCODE,16  
  
RFA,18  
RECNUM2,19  
STV,20  
STX,21  
>  
K <,\$  
KEY MENU,16  
FLG,17  
DFL,18  
IFL,19  
NSG,20  
POS,21  
POS TMP,21  
SIZ,22  
SIZ TMP,22

: First free byte in EOF block field  
: Starting logical block number field

: Access message field codes:  
: Access function field  
: Access options field  
: File specification field  
: File access field  
: File sharing field  
: Display attributes field  
: Password field

: Control message field codes:  
: Control function field  
: Control menu field  
: Record access field  
: Key field  
: Key of reference field  
: Record options field  
: (22) reserved for HSH field  
: Display attributes field  
: Block count field

: Continue Transfer message field codes:  
: Continue transfer function field

: Acknowledge message field codes:  
: none

: Access Complete message field codes:  
: Access complete function field  
: File options field  
: CRC Checksum field

: Data message field codes:  
: Record number field  
: File data field

: Status message field codes:  
: Status code field used for both:  
: MACCODE,16  
: MICCODE,17  
: Record file address field  
: Record number field  
: Secondary status value field  
: Secondary status text field

: Key definition attributes message field codes:  
: Key definition menu field  
: Key options field  
: Data bucket fill quantity field  
: Index bucket fill quantity field  
: Number of key segments field  
: Key segment position field  
: (alias for POS)  
: Key segment size field  
: (alias for SIZ)

REF,23	: Key of reference field	
KNM,24	: Key name field	
NUL,25	: Null key character field	
IAN,26	: Index area number field	
LAN,27	: Lowest level index area number field	
DAN,28	: Data area number field	
DTP,29	: Key data type field	
RVB,30	: Root bucket start VBN field (31) reserved for HAL field	
DVB,32	: First data bucket start VBN field	DI
DBS,33	: Data bucket fill size field	
IBS,34	: Index bucket fill size field	
LVL,35	: Level of root buckets field	
TKS,36	: Total key size field	
MRL,37	: Minimum record length to contain key field	
>		
K <,\$	Allocation attributes message field codes:	
ALLMENU,16	: Allocation menu field	DI
VOL,17	: Relative volume number field	
ALN,18	: Alignment options field	
AOP,19	: Allocation options field	
LOC,20	: Starting location field (21) reserved for RFI field	
ALQ2,22	: Allocation quantity field	
AID,23	: Area identification field	
BKZ,24	: Bucket size field	
DEQ2,25	: Default extension quantity field	
>		
K <,\$	Summary attributes message field codes:	LA
SUMENU,16	: Summary menu field	
NOK,17	: Number of keys field	
NOA,18	: Number of allocation areas field	
NOR,19	: Number of record descriptors field	
PVN,20	: Prologue version number field	
>		
K <,\$	Date and time attributes message field codes:	
TIMENU,16	: Date and time menu field	
CDT,17	: Creation date and time field	
RDT,18	: Revision date and time field	
EDT,19	: Expiration date and time field	
RVN,20	: Revision number field	
BDT,21	: Backup date and time field	
PDT,22	: Physical creation date and time field	
ADT,23	: Accessed date and time field	
>		
K <,\$	Protection attributes message field codes:	
PROMENU,16	: Protection menu field	
OWNER,17	: File owner field	
PROSYS,18	: System protection field	
PROOWN,19	: Owner protection field	
PROGRP,20	: Group protection field	
PROWLD,21	: World protection field	
>		
K <,\$	Name message field codes:	
NAMETYPE,16	: Name type field	
NAMESPEC,17	: Name field	

E >

: End of module

0173 AH-BT13A-SE  
VAX/VMS V4.0

DIGITAL EQUIPMENT CORPORATION  
CONFIDENTIAL AND PROPRIETARY

SND SMB  
LIS

SWEDER  
LTD

FAL

四  
三

0174 AH-BT13A-SE  
VAX/VMS V4.0

DIGITAL EQUIPMENT CORPORATION  
CONFIDENTIAL AND PROPRIETARY

FALACTON  
LIS

FALADERS  
LIS

FALMACROS  
MAR

FALBLOXAB  
LIS

FALDEF  
MOL

FALBLOSTS  
LIS

FALACTINI  
LIS

FALOPTIO  
LIS

FALACTMSG  
LIS