		BBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBB	RRRRRRRRRRRRRRRRRRRRRRRRRRRRRRRRRRRRRR		
LLL	HH				
LLL	III	BBB BBB BBB	RRR RRR	111	iii
illillillillill	1111111111	BBBBBBBBBBB	RRR RRR	TTT	IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII
LLLLLLLLLLLLLLLLLLLLLLLLLLLLLLLLLLLLLLL		88888888888 88888888888	RRR RRR	III	

LI

000000 00 00 00 00		\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$	UU	BBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBB	
\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$	DDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDD				

{ REQUIRE file for Logical Unit Block (LUB) { File: OTSLUB.SDL Edit: MDL2005

COPYRIGHT (c) 1978, 1980, 1982, 1984 BY DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS. ALL RIGHTS RESERVED.

THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY TRANSFERRED.

THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT CORPORATION.

DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.

Author: T. Hastings Change history:
[Previous edit history removed. SBL 24-Aug-1982] 1-048 - Give LUB\$A_ASSOC_VAR another name LUB\$L_ALQ, this is to hold the allocation quantity for files in BASIC. FM 1-Oct-1980 1-049 - Add a flag to request ANSI processing. PLL 22-Jul-1982
2-001 - Convert to SDL. SBL 24-Aug-1982
2-002 - Don't depend on names for sub-structures. SBL 29-Sep-1982
2-003 - Change aggregate name to LUB for better fieldset name. SBL 26-Oct-1982
2-004 - Add fields for RFA cacheing. SBL 2-June-1983
2-005 - add field to indicate FIELDing. MDL 29-Mar-1984

{ The LUB contains OTS OWN data associated with a particular logical unit which is needed between I/O statements. OWN data which is needed for several calls within a single I/O statement is allocated in the I/O Statement Block (ISB). Data which is needed during a single call is always LOCAL.

LUB definition (-11 OTS equivalents are indicated in parens) Symbols are of the form: LUB\$t_symbol where t is A,B,W,L,T,or V.

MODULE \$LUBDEF; AGGREGATE LUB STRUCTURE PREFIX LUB\$ ORIGIN end_of_lub;

Define some constants that are used to set the organization field of the LUB

LIB

! \$! n

MAC

```
16-SEP-1984 16:41:41.68 Page 2
 OTSLUB.SDL:1
 {-
 CONSTANT (
              ORG_SEQUE, { Organizations of the control of the co
                                                        { Organization sequential { Organization relative
                                                        { Organization indexed
{ Organization termina
{ Organization virtual
                                                               Organization indexed sequential
                                                               Organization terminal format
 {+
{ Define the symbols for the special LUNs with negative numbers.
 CONSTANT (
                                                        { Logical unit for BASIC PRINT { Logical unit no. for BASIC INPUT { Logical unit for BASIC READ { Logical unit for FORTRAN ENCODE/DECODE { Logical unit no. for FORTRAN READ { Logical unit no. for FORTRAN ACCEPT { Logical unit no. for FORTRAN TYPE { Logical unit no. for FORTRAN PRINT INCREMENT 1:
              LUN_BPRI,
LUN_INPU,
LUN_BREAD,
               LUN_ENCD,
               LUN READ,
LUN ACCE,
               LUN TYPE,
LUN PRIN
               ) EQUALS -8 INCREMENT 1;
                                                                                    EQUALS LUB$K_LUN_BPRI;
EQUALS LUB$K_LUN_READ;
EQUALS LUB$K_LUN_PRIN;
EQUALS 0;
                                                                                                                                                                        { Min LUN (for LUN table)
{ Min default-OPEN LUN for FORTRAN
{ Max default-OPEN LUN for FORTRAN
 CONSTANT ILUN_MIN
 CONSTANT DLUN MIN
                                                                                                                                                                         ( Min. explicit FORTRAN OPEN LUN & BASIC limit is .GT. this.
 CONSTANT LUN MIN
                                                                                                                                                                         { Max. explicit or implicit LUN
 CONSTANT LUN_MAX
                                                                                    EQUALS 119:
Define a symbol for the default value of the right margin. This value ( is used only by BASIC.
                                                                                                                                { default right margin for files
 CONSTANT D_MARGIN
                                                                                    EQUALS 72:
{+
{ Define a symbol for the maximum length of the prompt buffer.
{ This much space is allocated whenever a sequential file is opened
 { in case we are to prompt for input from it. {-
 CONSTANT PBUF_SIZ
                                                                                    EQUALS 80:
                                                                                                                                                                    { Size of prompt buffer
 { Lay out the storage of the LUB
                                                                                                                                            { define negative length of LUB { RMS User Buffer.
               CONSTANT NEG_BLN EQUALS . ;
               UBF ADDRESS:
               UNIT_STT3 WORD UNSIGNED;
                                                                                                                                            { more flags
                             UNIT_STT3_STRUCT STRUCTURE;
```

LIB

!+

MAC

MAC

! E

```
BLS WORD UNSIGNED:
```

END union_1;

OTSLUB.SDL:1

NOECHO BITFIELD:

ONECHR BITFIELD:

FIND_LAST BITFIELD:

AST_GUARD BITFIELD:

NOMARGIN BITFIELD:

USEROPEN BITFIELD: NOTSEQUE BITFIELD:

END UNIT_STT3_STRUCT;

ANSI BITFIELD:

CCO BITFIELD:

PTA BITFIELD:

CR BITFIELD; FTN BITFIELD: PEN BITFIELD:

The following address, if non-zero, points to a routine to be called just before the LUB is CLOSEd. This is used by the BASIC File Array support to write out the last buffer.

CLOSE ADDRESS:

{+
{ The following quadword is used to link the LUB to the LUB table
{ maintained by OTSCCB.
{-

QUEUE QUADWORD UNSIGNED:

{ Link for INSQUE and REMQUE instructions

{ LUB Locations used by all User Data Formatted (UDF) level Procedures { which are: FOR\$\$UDF_{R,W}{F,U,L} and BAS\$\$UDF_{RW}_L

BUF_PTR ADDRESS:

{ (FOR-BLBUF) Adr. of next byte in buffer to be { filled or emptied with user data { (FOR-EOLBUF) Adr.+1 of last byte in buffer

BUF_END ADDRESS:

**!

```
16-SEP-1984 16:41:41.68 Page
OTSLUB.SDL:1
                                                        { to be filled or emptied with user data.
{ This is the buddy pointer for BASIC I/O. For all units except 0, it
( should point to itself. For unit 0, the Print CCB will point to the
{ Input CCB and vice versa
                                                        { pointer to the complementary CCB for Print and { Input. Needed for recursive and continued I/O
     BUDDY_PTR ADDRESS:
   LUB Locations used solely by the input or output dependent
{ Formatted User Data Formatters .
     BUF_BEG ADDRESS:
                                                           (FOR-LNBUF) Adr. of first byte in buffer (FOR-used
                                                           for T format).
                                                           (FOR-TSPECP) Adr. of highest byte filled in
     BUF_HIGH ADDRESS:
                                                           buffer during format processing (FOR-needed
                                                          because In format can move backwards).
{ LUB locations set by OPEN, default OPEN, CALL FI DEFINE FILE, and checked on every I/O statement
  LUB locations set by OPEN, default OPEN, CALL FDBSET, or
     ORGAN BYTE UNSIGNED:
                                                           (BAS-If.BLK-If.TRF) File organization:
                                                           virtual block, sequential, relative, indexed
                                                           sequential or terminal format.
                                                          Bucket size, from FAB$B_BKS
      BKS BYTE UNSIGNED:
                                                           Logical unit number (0:99)
     LUN WORD:
                                                          Note: signed! Negative LUNS used for: INPUT and PRINT
     union 1A UNION FILL:
           PRINT_POS LONGWORD UNSIGNED;
                                                          (BAS-POSITN) printhead position
                                                          PRINT statements may end in a semicolon or a comma requiring the printhead position to be maintained to the next PRINT statement.
                                                          This is a longword because the longest string (65K) may be put in the longest buffer (65K). First allocated byte of RFA cache (FOR)
           RFA_CACHE_BEG ADDRESS;
     END union 1A;
union 1B UNION FILL;
WAIT TIME LONGWORD UNSIGNED;
RFA CACHE PTR ADDRESS;
END union 1B;
IFI WORD UNSIGNED;
                                                        { (BAS-WATIM) Wait time to a white (FOR) { Pointer to current RFA cache entry (FOR)
                                                          (BAS-WATIM) Wait time for a WAIT operation
                                                           RMS internal file id, needed
                                                           until $CLOSE
      RBUF_SIZE WORD UNSIGNED;
                                                           Record buffer size in bytes
                                                           Set by OPEN, default open, or DEFINE FILE. Used to allocate record buffer at open.
                                                          Read by record level of abstraction FOR$$REC_{R,W}{f,U,L} (BAS-new) the right margin for a terminal format file. The default is 72 for terminal format files, set to terminal
      R_MARGIN WORD UNSIGNED:
```

LIE

. *1

*

```
16-SEP-1984 16:41:41.68 Page 5
OTSLUB.SDL:1
                                                        width otherwise. Not the same as
                                                        buffer size because of embedded carriage control characters. For terminal format files,
                                                        when the cursor position exceeds this value the record is PUI.
     D_MARGIN WORD UNSIGNED:
                                                     { Default right margin.
     LANGUAGE BYTE UNSIGNED:
                                                        The language that opened the LUN, as follows:
                               EQUALS 0;
EQUALS 0;
EQUALS 1;
EQUALS 2;
EQUALS 2;
     CONSTANT LANG MIN CONSTANT LANG NONE
                                                        Minimum language code
                                                       None (probably not open yet)
VAX-11 BASIC-PLUS-2
VAX-11 FORTRAN-IV PLUS
     CONSTANT LANG BAS CONSTANT LANG FOR CONSTANT LANG MAX
                                                     { Maximum language code
     RFM BYTE UNSIGNED:
                                                     { Record format, from FAB$B_RFM
    union_2 UNION;
BAS_VFC WORD UNSIGNED;
                                                        (BAS-new) fixed control block for carriage control
                                                        This is pointed to by the RAB so it is a part
                                                       of the RMS interface. As a result, it is only
                                                     { written to by the REC level.
         BAS_VFC_STRUCT STRUCTURE;
BAS_VFC1 BYTE UNSIGNED;
BAS_VFC2 BYTE UNSIGNED;
END BAS_VFC_STRUCT;
END union_2;
                                                     { overlay first byte of VFC
                                                     { overlay second byte of VFC
    union_3 UNION:
          ASSOC_VAR ADDRESS:
                                                     { Adr. of ASSOCIATEVARIABLE or 0 if none
                                                       Set by OPEN or DEFINEFILE.
                                                     { LUB$V_ASS_VAR_L specifies word/longword
          ALQ LONGWORD UNSIGNED:
                                                     { Allocation quantity for files, also used in assoc_var
          END union_3;
    LOG_RECNO LONGWORD UNSIGNED;
                                                        current or next Logical (or segmented)
                                                        record number for sequential access files
                                                        (needed for BACKSPACE of segmented records). Current or next
                                                        record number for
                                                        FORTRAN direct access files (0=1=first record)
                                                        Direct access maximum record number
    REC_MAX LONGWORD UNSIGNED;
                                                        (RMS doesn't keep for Sequential organization files). Set by DEFINE FILE or OPEN.
Address of FAB allocated by CALL ASSIGN,
CALL FDBSET, DEFINEFILE or OPEN.
0 = ASSIGN, FDBSET, DEFINEFILE or
    FAB ADDRESS:
                                                       LUB not done.
NOTE: This field cannot move from an offset
                                                        of -24 due to fortran compatibility routines
Size in bytes of record buffer (includes
     RBUF_ADR ADDRESS;
                                                        any FORTRAN information kept in the record) three words to hold directory ID from OPEN
     DID WORD UNSIGNED DIMENSION 3;
     RAT BYTE UNSIGNED;
RSL BYTE UNSIGNED;
                                                        The record attributes, from FAB$B_RAT.
                                                        size of resultant name string (0 = no string allocated)
     RSN ADDRESS:
                                                        address of resultant name string
    union_4 UNION;
```

LIE

SWI

! F

XIF XTH

LIE

PSE

! E

```
**
```

(FOR-D.STAT) Unit attribute bits which are needed between I/O statements. UNIT ATTR WORD UNSIGNED:

NOTE: Some of these bits are in fixed positions as noted.

UNIT_ATTR_STRUCT STRUCTURE: OPENED BITFIELD:

(FOR-DV.OPN) LUB has been successfully opened by OPEN or default OPEN.
Cleared by CLOSE or error during OPEN NOTE: cannot be moved from offset -4,0 due to fortran compatibility.
(FOR--) An I/O statement is active on this logical unit. Set to 0 on an error or end of I/O list. Used to prevent recursive I/O on the same logical unit.
(FOR-DV.RDO) No writes will (can) be done to this file.
Set by CALL FDBSET or OPEN 'READONLY'.
NOTE: cannot be moved from offset -4,2 due to fortran compatibility.
(FOR-DV.OLD) Old (existing) file required.do OPEN not CREATE. Set by TYPE='OLD' or FDBSET 'OLD'.
NOTE: cannot be moved from offset -4,3 due to

IO_ACTIVE BITFIELD;

READ_ONLY BITFIELD:

OLD_FILE BITFIELD:

DIRECT BITFIELD:

NOTE: cannot be moved from offset -4,3 due to

Fortran compatibility.

(FOR-DV.DFD) FORTRAN direct access file.
Set by ACCESS='DIRECT' or DEFINEFILE.
Note: this bit is independent of RMS

file organization (Sequential or Relative).

Can not be moved from -4,4 unless FOR\$\$IO_BEG is modified. (FOR-DV.SCR) TYPE='SCRATCH' specified. (FOR-DV.DEL) OPEN DISP='DELETE' specified. SCRATCH BITFIELD: DELETE BITFIELD:

Checked at CLOSE (FOR-DV.SPL) OPEN DISPOSE='PRINT' causes PRINT BITFIELD:

spooling at CLOSE.
(FOR-DV.FMP) File is FORTRAN formatted.
OPEN FORM='FORMATTED' FORMATTED BITFIELD:

0 = unspecified.

NOTE: Can not be moved from -4,8 unless FOR\$\$10_BEG is modified.

(FOR-DV.UFP) File is FORTRAN unformatted.

0 = unspecified. Set by DEFINE FILE or OPEN.

Note: LUB\$V_FORMATTED and LUB\$V_UNFORMAT can both be 0 on default OPEN done for END FILE since the format may be either.

Can not be moved from -4,9 unless FOR\$\$10_REG is modified. UNFORMAT BITFIELD:

FOR\$\$10_BEG is modified.

(FOR--) 1 = Record format is RMS fixed (FLR).

OPEN RECORDTYPE='FIXED' FIXED BITFIELD:

0 = Record format is RMS variable
(VLR or VLRM, i.e., VLR on Relative
Organization file. OPEN RECORDTYPE='VARIABLE'
(FDR--) Segmented (unformatted) records are

to be used. Otherwise only one record (VLR or FLR) is to be read or

SEGMENTED BITFIELD:

```
16-SEP-1984 16:41:41.68 Page 7
OTSLUB.SDL:1
                                                                                                   written with no segmented control info.
RECORDTYPE = 'SEGMENTED' in OPEN or TYPE not specified for sequential unformatted file.
(FOR-DV.AI4) ASSOCIATEVARIABLE is a longword
                            ASS_VAR_L BITFIELD:
                                                                                                    0 = ASSOCIATEVARIABLE is a word or not
                                                                                                  O = ASSOCIATEVARIABLE is a word or not present. Set by OPEN or DEFINE FILE. See LUBSA_ASSOC_VAR (FOR-DV.APD) File was opened ACCESS = 'APPEND' also used as state bit (LOG_RECNO is undefined) NOTE: cannot be moved from offset -4,13 due to Fortran compatibilty.

1 if ACCESS='SEQUENTIAL' (FORTRAN)
Note: Can not be moved from -4,14
unless FOR$$IO_BEG is modified.

1 if ACCESS='KEYED' (FORTRAN)
Note: Can not be moved from -4.15
                            APPEND BITFIELD:
                            SEQUENTIA BITFIELD:
                            KEYED BITFIELD:
                                                                                                    Note: Can not be moved from -4,15
                                                                                                   unless FOR$$10 BEG is modified.
                            END UNIT_ATTR_STRUCT;
                  END union 4:
   Bits set by OPEN, default OPEN, CALL FDBSET, or
   DEFINEFILE, and checked on every I/O statement
       UNIT_STT2 WORD UNSIGNED;
UNIT_STT2_STRUCT STRUCTURE;
UNIT_RSN_BITFIELD;
                                                                                               { Second word of bits
                                                                                                   indicates that RSN points to dynamic memory
                                                                                                   not local storage
File was implicitly opened to do ENDFILE
When first I/O is done, there are a few
defaults which will be specified:
LUB$V_FORMATTED or LUB$V_UNFORMAT
LUB$V_SEGMENTED
                            ENDFILOPN BITFIELD:
                                                                                                   Then [UB$V_ENDFIL_OPN is cleared.

(BAS-new) The last output element transmitter ended in a comma or semicolon.

(BAS-IF.WRT) the PRINT buffer already has something in it and should be dumped before continuing. Set by BAS$$DO_WRITE

Used for same purpose by BASIC file Array support (BAS-IF.TRF) terminal format file on any unit including 0 Set by OPEN info from user. = 1, term-
                           FORM_CHAR BITFIELD;
                            OUTBUF_DR BITFIELD;
                            TERM_FOR BITFIELD:
                                                                                                    inal format (BAS-IF.TRM) terminal device on any unit including 0 Set by OPEN info from RMS. = 1, term-
                            TERM_DEV BITFIELD:
                                                                                                   inal device
(BAS-IF.FRC) forcible device on any unit including 0
Set by OPEN info from RMS. = 1, term-
inal or line printer device
(BAS-new?) terminal device - unit 0
Set by Default OPEN for PRINT and INPUT
(BAS-IF.VIR) marks a files first usage as a
                            FORCIBLE BITFIELD:
                            UNIT_O BITFIELD;
                            VA_USE BITFIELD:
                                                                                                   virtual array. Once used as virtual, it cannot be used for block I/O. (BAS-BIO) Marks a file's first use as block
                            BLK_USE BITFIELD;
```

OTS

...

*

* * * * * *

* *

.

.

.

* * * *

.

*

LIT

```
16-SEP-1984 16:41:41.68 Page 8
OTSLUB.SDL:1
                                                                                               { I/O. Once used as block I/O , it cannot be { used for virtual I/O. { (BAS-IF.CON) File is multistream connected. { File is (or was) connected to.
                            M_STREAM BITFIELD:
M_STR_C BITFIELD:
         { The following bit is set by CLOSE to indicate that the LUB should be { deallocated as soon as all recursive or nested I/O on it has { completed. It is cleared (in effect) by OTS$$POP_CCB deallocating the { storage. While it is set the LUN may not be OPENed since there is { I/O outstanding which should be allowed to fail. {-
                                                                                              { Can deallocate this LUB 
 { FORTRAN DISP='SUBMIT' if set. 
 { FORTRAN BLANK='ZERO' if clear, 
 { BLANK='NULL' if set. 
 { If 1, the record buffer was allocated 
 { by the user, don't deallocate it at 
 { CLOSE time.
                            DEALLOC BITFIELD:
SUBMIT BITFIELD;
                            NULLBLNK BITFIELD;
                            USER_RBUF BITFIELD:
                            END UNIT_STT2_STRUCT;
                   END union_5;
         CONSTANT LUB_LEN EQUALS :;
                                                                                              { Length of LUB
         end_of_lub BYTE FILL TAG $$; END_LUB;
END_MODULE $LUBDEF;
{ End of file OTSLUB.SDL
```

OTS

STF

FIE

1

0202 AH-BT13A-SE

DIGITAL EQUIPMENT CORPORATION CONFIDENTIAL AND PROPRIETARY

