

A large, stylized letter 'A' is formed using the characters 'S' and 'Y'. The left and right vertical strokes are composed of 'S' characters, while the central vertical stroke and the diagonal strokes are composed of 'Y' characters. The 'A' is symmetrical and has a bold, blocky appearance.

[illegible]

(1) 66
(1) 97

CANCEL TIMER REQUEST
CANCEL WAKEUP

SYSC
Sym

ARG
CTL
EXE
EXE
EXE
PCB
PRV
PRV
PSL
ROU
SF\$
SS\$

PSE

· E
\$AE

Pha

Ini
Com
Pas
Sym
Pas
Sym
Pse
Cro
Ass

The
335
The
131
12

Mac

-\$
-\$
TOT
761


```
0000 1 .TITLE SYSCANEVT - SYSTEM SERVICES TO CANCEL EVENTS
0000 2 .IDENT 'V04-000'
0000 3
0000 4
0000 5 *****
0000 6 *
0000 7 * COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
0000 8 * DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
0000 9 * ALL RIGHTS RESERVED.
0000 10 *
0000 11 * THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
0000 12 * ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
0000 13 * INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
0000 14 * COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
0000 15 * OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
0000 16 * TRANSFERRED.
0000 17 *
0000 18 * THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
0000 19 * AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
0000 20 * CORPORATION.
0000 21 *
0000 22 * DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
0000 23 * SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.
0000 24 *
0000 25 *
0000 26 *****
0000 27
0000 28 D. N. CUTLER 4-OCT-76
0000 29
0000 30 SYSTEM SERVICES TO CANCEL EVENTS
0000 31
0000 32 CANCEL TIMER
0000 33 CANCEL WAKEUP
0000 34
0000 35 MODIFICATION HISTORY:
0000 36
0000 37 V03-001 KDM0002 Kathleen D. Morse 28-Jun-1982
0000 38 Add $IPLDEF.
0000 39
0000 40
0000 41 MACRO LIBRARY CALLS
0000 42
0000 43
0000 44 $IPLDEF ;DEFINE INTERRUPT PRIORITY LEVELS
0000 45 $PCBDEF ;DEFINE PCB OFFSETS
0000 46 $PRDEF ;DEFINE PROCESS REGISTER NUMBERS
0000 47 $SSDEF ;DEFINE SYSTEM STATUS VALUES
0000 48 $TQEDEF ;DEFINE TQE OFFSETS
0000 49
0000 50
0000 51 LOCAL SYMBOLS
0000 52
0000 53 ARGUMENT LIST OFFSET DEFINITIONS FOR CANCEL TIMER
0000 54
0000 55
00000004 0000 56 REQIDT=4 ;REQUEST IDENTIFICATION
00000008 0000 57 ACMODE=8 ;ACCESS MODE
```

	0000	58	
	0000	59	:
	0000	60	: ARGUMENT LIST OFFSET DEFINITIONS FOR CANCEL WAKEUP
	0000	61	:
	0000	62	:
00000004	0000	63	PIDADR=4
00000008	0000	64	LOGNAM=8

:ADDRESS OF PROCESS IDENTIFICATION
:ADDRESS OF PROCESS NAME STRING DESCRIPTOR


```
0000 66 .SBTTL CANCEL TIMER REQUEST
0000 67 :+
0000 68 : EXESCANTIM - CANCEL TIMER REQUEST
0000 69 :
0000 70 : THIS SERVICE PROVIDES THE CAPABILITY TO CANCEL ALL OR A SPECIFIED SUBSET
0000 71 : OF TIMERS THAT WERE PREVIOUSLY ESTABLISHED.
0000 72 :
0000 73 : INPUTS:
0000 74 :
0000 75 : REQIDT(AP) = REQUEST IDENTIFICATION (ZERO IMPLIES ALL).
0000 76 : ACMODE(AP) = ACCESS MODE (ALL EQUAL AND HIGHER ACCESS MODES).
0000 77 :
0000 78 : R4 = CURRENT PROCESS PCB ADDRESS.
0000 79 :
0000 80 : OUTPUTS:
0000 81 :
0000 82 : R0 LOW BIT SET INDICATES SUCCESSFUL COMPLETION.
0000 83 :
0000 84 : R0 = SSS_NORMAL - NORMAL COMPLETION.
0000 85 :-
0000 86 :
0000 87 .ENABL LSB
0000 88 .ENTRY EXESCANTIM,^M<R2,R3,R4,R5>
0002 89 EXTZV #0,#2,ACMODE(AP),R0 ;GET SPECIFIED ACCESS MODE
0008 90 JSB EX$MAXACMODE ;MAXIMIZE ACCESS MODE WITH PREVIOUS MODE
000E 91 MOVL PCB$PID(R4),R5 ;SET PROCESS ID
0012 92 MOVZBL #TQESCTMSNGL,R4 ;SET TYPE OF ENTRY
0015 93 MOVL REQIDT(AP),R3 ;SET REQUEST IDENTIFICATION
0019 94 MOVL R0,R2 ;SET CANCELLATION ACCESS MODE
001C 95 BRB 10$ ;FINISH IN COMMON CODE
```

50 08 AC 02 00 003C 0000 88
00000000 EF 16 0002 89
55 60 A4 D0 000E 91
54 00 9A 0012 92
53 04 AC D0 0015 93
52 50 D0 0019 94
OE 11 001C 95

```
001E 97 .SBTTL CANCEL WAKEUP
001E 98 :+
001E 99 : EXE$CANWAK - CANCEL WAKEUP
001E 100 :
001E 101 : THIS SERVICE PROVIDES THE CAPABILITY TO CANCEL ALL WAKE UP REQUESTS FOR
001E 102 : A SPECIFIED PROCESS.
001E 103 :
001E 104 : INPUTS:
001E 105 :
001E 106 :     PIDADR(AP) = ADDRESS OF PROCESS IDENTIFICATION.
001E 107 :     LOGNAM(AP) = ADDRESS OF PROCESS NAME STRING DESCRIPTOR.
001E 108 :
001E 109 :     R4 = CURRENT PROCESS PCB ADDRESS.
001E 110 :
001E 111 : OUTPUTS:
001E 112 :
001E 113 :     R0 LOW BIT CLEAR INDICATES FAILURE TO CANCEL WAKE UP REQUESTS.
001E 114 :
001E 115 :         R0 = SS$ ACCVIO - PROCESS NAME STRING OR PROCESS NAME
001E 116 :             STRING DESCRIPTOR CANNOT BE READ BY CALLING ACCESS
001E 117 :             MODE, OR PROCESS IDENTIFICATION CANNOT BE WRITTEN
001E 118 :             BY CALLING ACCESS MODE.
001E 119 :
001E 120 :         R0 = SS$ IVLOGNAM - ZERO OR GREATER THAN MAXIMUM LENGTH
001E 121 :             PROCESS NAME STRING SPECIFIED.
001E 122 :
001E 123 :         R0 = SS$ NONEXPR - NONEXISTENT PROCESS OF INVALID PROCESS
001E 124 :             IDENTIFICATION SPECIFIED.
001E 125 :
001E 126 :         R0 = SS$ NOPRIV - PROCESS DOES NOT HAVE PRIVILEGE TO WAKE
001E 127 :             SPECIFIED PROCESS.
001E 128 :
001E 129 :     R0 LOW BIT SET INDICATES SUCCESSFUL COMPLETION.
001E 130 :
001E 131 :         R0 = SS$_NORMAL - NORMAL COMPLETION.
001E 132 : -
001E 133 :
001E 134 .ENTRY EXE$CANWAK, ^M<R2,R3,R4,R5>
0020 135 BSBW EXE$NAMPID :GET TARGET PROCESS ID
0023 136 BLBC R0,20$ :IF LBC INVALID ARGUMENT
0026 137 MOVZBL #TQESC_WKSNGL,R4 :SET TYPE OF ENTRY
0029 138 MOVL R1,R5 :SET TARGET PROCESS ID
002C 139 10$: SETIPL #IPL$ TIMER :RAISE IPL TO TIMER LEVEL
002F 140 BSBW EXE$RMVTIMQ :REMOVE ENTRIES FROM TIMER QUEUE
0032 141 MOVZWL #SS$_NORMAL,R0 :SET NORMAL COMPLETION STATUS
0035 142 20$: SETIPL #0 :ALLOW INTERRUPTS
0038 143 RET :
0039 144 .DSABL LSB
0039 145
0039 146 .END
```

FFDD' 003C 30
OF 50 E9
54 02 9A
55 51 D0
FFCE' 30
50 01 3C
04

SYSCANEVT
Symbol table

- SYSTEM SERVICES TO CANCEL EVENTS^{H 4}

16-SEP-1984 01:46:23 VAX/VMS Macro V04-00
5-SEP-1984 03:49:17 [SYS.SRC]SYSCANEVT.MAR;1

Page 5
(1)

ACMODE	= 00000008		
EXESCANTIM	00000000	RG	01
EXESCANWAK	0000001E	RG	01
EXESMAXACMODE	*****	X	01
EXESNAMPID	*****	X	01
EXESRMVTIMQ	*****	X	01
IPL\$ TIMER	= 00000008		
LOGNAM	= 00000008		
PCBSL PID	= 00000060		
PIDADR	= 00000004		
PR\$ IPL	= 00000012		
REQIDT	= 00000004		
SS\$ NORMAL	= 00000001		
TQESC_TMSNGL	= 00000000		
TQESC_WKSNGL	= 00000002		

+-----+
! Psect synopsis !
+-----+

PSECT name	Allocation	PSECT No.	Attributes															
. ABS .	00000000 (0.)	00 (0.)	NOPIC	USR	CON	ABS	LCL	NOSHR	NOEXE	NORD	NOWRT	NOVEC	BYTE					
. BLANK .	00000039 (57.)	01 (1.)	NOPIC	USR	CON	REL	LCL	NOSHR	EXE	RD	WRT	NOVEC	BYTE					
\$AB\$\$	00000000 (0.)	02 (2.)	NOPIC	USR	CON	ABS	LCL	NOSHR	EXE	RD	WRT	NOVEC	BYTE					

+-----+
! Performance indicators !
+-----+

Phase	Page faults	CPU Time	Elapsed Time
Initialization	36	00:00:00.07	00:00:01.14
Command processing	126	00:00:00.53	00:00:04.16
Pass 1	236	00:00:05.88	00:00:17.99
Symbol table sort	0	00:00:01.00	00:00:02.50
Pass 2	42	00:00:01.02	00:00:03.95
Symbol table output	4	00:00:00.03	00:00:00.04
Psect synopsis output	1	00:00:00.02	00:00:00.02
Cross-reference output	0	00:00:00.00	00:00:00.00
Assembler run totals	447	00:00:08.56	00:00:29.80

The working set limit was 1350 pages.
32963 bytes (65 pages) of virtual memory were used to buffer the intermediate code.
There were 40 pages of symbol table space allocated to hold 670 non-local and 2 local symbols.
146 source lines were read in Pass 1, producing 18 object records in Pass 2.
13 pages of virtual memory were used to define 12 macros.

+-----+
! Macro library statistics !
+-----+

Macro library name

Macros defined

\$255\$DUA28:[SYS.OBJ]LIB.MLB;1
\$255\$DUA28:[SYSLIB]STARLET.MLB;2
TOTALS (all libraries)

4
5
9

746 GETS were required to define 9 macros.

There were no errors, warnings or information messages.

MACRO/LIS=LIS\$:SYSCANEVT/OBJ=OBJ\$:SYSCANEVT MSRC\$:SYSCANEVT/UPDATE=(ENH\$:SYSCANEVT)+EXECML\$/LIB

0382 AH-BT13A-SE
VAX/VMS V4.0

DIGITAL EQUIPMENT CORPORATION
CONFIDENTIAL AND PROPRIETARY

SYSCANEVT
LIS

SYSCREPRO
LIS

SYSCHKPRO
LIS

SYSCREDEL
LIS

SYSCANCEL
LIS

SYSCOMMON
LIS

SYSCHGMOD
LIS