





(1)	136	DECLARATIONS
(1)	287	REGISTER DEFINITIONS
(1)	346	CONTROLLER INITIALIZATION
(1)	427	UNIT INITIALIZATION
(1)	512	MAINTENANCE ROUTINES
(1)	577	OUTPUT MODEM CONTROL
(1)	631	DZ-11 MODEM POLLER
(1)	717	RECEIVER INTERRUPT SERVICE
(1)	891	START I/O ROUTINE
(1)	943	PORT ROUTINES STOP, RESUME, XON, XOFF
(1)	1085	OUTPUT INTERRUPT SERVICE
(1)	1348	SET SPEED, PARITY PARAMETERS
(1)	1400	INITIALIZE DZ-11 MODEM POLLING

```

0000 1 .if df DZV
0000 2 .TITLE DZVDRIVER - Port Driver for DZV-11 support
0000 3 .iff
0000 4 .TITLE DZDRIVER - Port Driver for DZ-11 support
0000 5 .endc
0000 6 .IDENT 'V04-000'
0000 7
0000 8
0000 9 *****
0000 10 *
0000 11 * COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
0000 12 * DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
0000 13 * ALL RIGHTS RESERVED.
0000 14 *
0000 15 * THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
0000 16 * ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
0000 17 * INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
0000 18 * COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
0000 19 * OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
0000 20 * TRANSFERRED.
0000 21 *
0000 22 * THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
0000 23 * AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
0000 24 * CORPORATION.
0000 25 *
0000 26 * DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
0000 27 * SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.
0000 28 *
0000 29 *
0000 30 *****
0000 31
0000 32 ++
0000 33 FACILITY:
0000 34
0000 35 VAX/VMS TERMINAL DRIVER
0000 36
0000 37 ABSTRACT:
0000 38
0000 39 DZ PORT DRIVER
0000 40 This module functions as a port driver for DZ11 and DZ32 terminal
0000 41 controllers. It contains hardware specific port level service
0000 42 routines.
0000 43
0000 44 AUTHOR:
0000 45
0000 46 RICK SPITZ
0000 47
0000 48 Revision history:
0000 49
0000 50 V03-028 MIRO480 Michael I.Rosenblum 8-Aug-1984
0000 51 Fix bugs found in testing the DZ-32 and reported in
0000 52 QAR 1126 (FT1).
0000 53
0000 54 V03-027 LMP0275 L. Mark Pilant, 12-Jul-1984 21:01
0000 55 Initialize the ACL info in the ORB to be a null descriptor
0000 56 list rather than an empty queue. This avoids the overhead
0000 57 of locking and unlocking the ACL mutex, only to find out

```

```

0000 58 : that the ACL was empty.
0000 59 :
0000 60 : V03-026 EMD0090 Ellen M. Dusseault 30-Apr-1984
0000 61 : Add DEV$M_NNM characteristic to DEVCHAR2 so that these
0000 62 : devices will have the 'node$' prefix.
0000 63 :
0000 64 : V03-025 LMP0221 L. Mark Pilant, 7-Apr-1984 13:37
0000 65 : Change UCBSL_OWNUIC to ORBSL_OWNER and UCBSW_VPROT to
0000 66 : ORBSW_PROT.
0000 67 :
0000 68 : V03-024 JLV0321 Jake VanNoy 5-JAN-1984
0000 69 : Minor enhancements to DZV11 support. Comment out
0000 70 : DPT_STORE for parity, must fix a restriction.
0000 71 :
0000 72 : V03-023 MIR0055 Michael I. Rosenblum 30-June-1983
0000 73 : Remove code from unit and controler-init routines
0000 74 : and make insert calls to class driver macros
0000 75 : Add DZV11 support.
0000 76 :
0000 77 : V03-022 RKS0022 RICK SPITZ 14-MAR-1983
0000 78 : ADD ENHANCEMENTS TO SUPPORT LOGICAL UCB.
0000 79 :
0000 80 : V03-021 MIR0022 Michael I. Rosenblum 19-Jan-1982
0000 81 : Change references to UCBSB_ERTCNT to use UCBSW_IT_UNITBIT
0000 82 : to be more maintainable.
0000 83 : Replace old vector table with new vector table macro.
0000 84 : Remove references to UCBSL_DEVDEPEND and UCBSQ_IT_STATE
0000 85 : move these references into the class driver jacket routines
0000 86 :
0000 87 : V03-020 MIR0021 Michael I. Rosenblum 17-Jan-1983
0000 88 : Fix DZ32 DZ_SET table entry.
0000 89 :
0000 90 : V03-019 RKSOC19 RICK SPITZ 13-JAN-1983
0000 91 : Repair problem with port vector macro
0000 92 :
0000 93 : V03-018 MIR0019 Michael I. Rosenblum 11-Jan-1982
0000 94 : Fix undefined symbol created by MIR0018.
0000 95 :
0000 96 : V03-017 MIR0018 Michael I. Rosenblum 07-Jan-1983
0000 97 : Change the port vector table to use the $VEC macros
0000 98 :
0000 99 : V03-J16 MIR0017 Michael I. Rosenblum 05-Jan-1983
0000 100 : Add powerfail check in the Unit init routine to allow the
0000 101 : terminal class drier to take positive action on powerfail.
0000 102 : Change code to accept a byte value as returns from the
0000 103 : GETNXT and PUTNXT class survices, this will removes this
0000 104 : information from the condition codes.
0000 105 :
0000 106 : V03-015 MIR0016 Michael I. Rosenblum 29-Dec-1982
0000 107 : Replace time calculation code with TIMSET macro call
0000 108 :
0000 109 : V03-014 MIR0015 Michael I. Rosenblum 20-Dec-1982
0000 110 : Remove entry point to reflect the redefinition of the PORT_DISCONNec
0000 111 : entry point.
0000 112 :
0000 113 : V03-013 MIR0014 Michael I. Rosenblum 17-Dec-1982
0000 114 : Remove code to calculate flow control characters from

```

```
0000 115 : port XON and XOFF routines and move that code into
0000 116 : the class driver.
0000 117 :
0000 118 : V03-012 RKS0012 RICK SPITZ 16-SEP-1982
0000 119 : Check reference count in unit init to determine if
0000 120 : modem control should be initialized or hungup. This
0000 121 : is needed to insure that a hangup ^Y is posted on
0000 122 : powerfail for modem lines.
0000 123 :
0000 124 : V03-011 JLV0211 Jake VanNoy 2-JUL-1982
0000 125 : Remove check for powerfail in unit init that prevents
0000 126 : SETUP_UCB from being called. This insures that UCB fields
0000 127 : are initialized correctly when Unit init is called for
0000 128 : use with CSS unibus switch.
0000 129 :
0000 130 : V03-010 KDM0002 Kathleen D. Morse 28-Jun-1982
0000 131 : Added $DEVDEF, $IPLDEF, $PRDEF, and $SSDEF.
0000 132 :
0000 133 :
0000 134 :--
```

```

0000 136          .SBTTL  DECLARATIONS
0000 137
0000 138          :
0000 139          : EXTERNAL DEFINITIONS:
0000 140          :
0000 141          $ACBDEF          : DEFINE ACB
0000 142          $CRBDEF          : DEFINE CRB
0000 143          $DCDEF           : DEVICE DEFINITIONS
0000 144          $DDBDEF          : DEFINE DDB
0000 145          $DEVDEF          : DEFINE DEVICE TYPES
0000 146          $DYNDEF          : DYNAMIC STRUCTURE DEFINITIONS
0000 147          $IDBDEF          : DEFINE IDB OFFSETS
0000 148          $IODEF           : DEFINE I/O FUNCTION CODES
0000 149          $IPLDEF          : DEFINE INTERRUPT PRIORITY LEVELS
0000 150          $IRPDEF          : IRP DEFINITIONS
0000 151          $ORBDEF          : DEFINE OBJECT'S RIGHTS BLOCK OFFSETS
0000 152          $PRDEF           : DEFINE PROCESSOR REGISTERS
0000 153          $SSDEF           : DEFINE SYSTEM STATUS CODES
0000 154          $TTYDEF          : DEFINE TERMINAL DRIVER SYMBOLS
0000 155          $TTDEF           : DEFINE TERMINAL TYPES
0000 156          $TT2DEF          : DEFINE EXTENDED DEFINITIONS
0000 157          $TQEDEF          : DEFINE TIMER QUEUE OFFSETS
0000 158          $UCBDEF          : DEFINE UCB
0000 159          $UBADEF          : DEFINE UBA
0000 160          $VECDEF          : DEFINE VECTOR FOR CRB
0000 161          $TTYMACS         : DEFINE TERMINAL DRIVER MACROS
0000 162          $TTYDEFS         : DEFINE TERMINAL DRIVER SYMBOLS
0000 163          $TTYMODEM        : DEFINE MODEM DEFINITIONS
0000 164
0000 165
0000 166          :
0000 167          : LOCAL STORAGE
0000 168          :
0000 169          .PSECT $$$105_PROLOGUE
0000 170
0000 171          :
0000 172          : Driver prologue table:
0000 173          :
0000 174
0000 175 DZSDPT::          : DRIVER START
0000 176 .IF DF DZV
0000 177     DPTAB          -          : DRIVER PROLOGUE TABLE
0000 178     END=DZ$END,-          : End and offset to INIT's vectors
0000 179     UCBSIZE=UCB$C TT LENGTH,- : SIZE OF UCB
0000 180     FLAGS=DPT$M_NOUNLOAD,-    : DO NOT ALLOW UNLOAD
0000 181     ADAPTER=UBA,-              : ADAPTER TYPE
0000 182     DEFUNITS=4,-              : DZV has 4 units
0000 183     NAME=DZDRIVER,-            : NAME OF DRIVER
0000 184     VECTOR=PORT_VECTOR        : PORT DRIVER VECTOR TABLE
0000 185 .IFF
0000 186     DPTAB          -          : DRIVER PROLOGUE TABLE
0000 187     END=DZ$END,-          : End and offset to INIT's vectors
0000 188     UCBSIZE=UCB$C TT LENGTH,- : SIZE OF UCB
0000 189     FLAGS=DPT$M_NOUNLOAD,-    : DO NOT ALLOW UNLOAD
0000 190     ADAPTER=UBA,-              : ADAPTER TYPE
0000 191     DEFUNITS=8,-              : Number of units to create
0000 192     NAME=DZDRIVER,-            : NAME OF DRIVER

```

```

0000 193 VECTOR=PORT_VECTOR ; PORT DRIVER VECTOR TABLE
0038 194 .ENDC
0038 195 DPT_STORE INIT
0038 196 DPT_STORE UCB,UCB$B_FIPL,B,8 ; FORK IPL
003C 197 DPT_STORE UCB,UCB$B_DEVCHAR,L,<- ; CHARACTERISTICS
003C 198 DEVSM_REC!-
003C 199 DEVSM_AVL!-
003C 200 DEVSM_IDV!-
003C 201 DEVSM_ODV!-
003C 202 DEVSM_TRM!-
003C 203 DEVSM_CCL>
0043 204 DPT_STORE UCB,UCB$B_DEVCHAR2,L,- ; Device Characteristics
0043 205 <DEVSM_NNM> ; prefix with 'node$'
004A 206 DPT_STORE UCB,UCB$B_DEVCLASS,B,DC$ TERM;
004E 207 DPT_STORE UCB,UCB$B_TT_DETYPE,B,TT$ UNKNOWN ; TYPE
0052 208 DPT_STORE UCB,UCB$W_TT_DESIZE,@W,TTY$GW_DEFBUF ; BUFFER SIZE
0059 209 DPT_STORE UCB,UCB$B_TT_DECHAR,@L,TTY$GL_DEFCHAR ; DEFAULT CHARACTERS
0060 210 DPT_STORE UCB,UCB$B_TT_DECHA1,@L,TTY$GL_DEFCHAR2; DEFAULT CHARACTERS
0067 211 DPT_STORE UCB,UCB$W_TT_DESPEE,@B,TTY$GB_DEFSPEED; DEFAULT SPEED
006E 212 DPT_STORE UCB,UCB$W_TT_DESPEE+1,@B,TTY$GB_RSPEED; DEFAULT SPEED
0075 213 DPT_STORE UCB,UCB$B_TT_DEPARI,@B,TTY$GB_PARITY ; DEFAULT PARITY
007C 214 ; DPT_STORE UCB,UCB$B_TT_PARITY,@B,TTY$GB_PARITY ; DEFAULT PARITY
007C 215 DPT_STORE UCB,UCB$B_DEVTYPE,B,TT$ UNKNOWN ; TYPE
0080 216 DPT_STORE UCB,UCB$W_DEVBUFSIZ,@W,TTY$GW_DEFBUF ; BUFFER SIZE
0087 217 DPT_STORE UCB,UCB$B_DEVDEPEND,@L,TTY$GL_DEFCHAR ; DEFAULT CHARACTERS
008E 218 DPT_STORE UCB,UCB$B_DEVDEPND2,@L,TTY$GL_DEFCHAR2; DEFAULT CHARACTERS
0095 219 DPT_STORE UCB,UCB$W_TT_SPEED,@B,TTY$GB_DEFSPEED ; DEFAULT SPEED
009C 220 DPT_STORE UCB,UCB$W_TT_SPEED+1,@B,TTY$GB_RSPEED ; DEFAULT SPEED
00A3 221 DPT_STORE UCB,UCB$B_DIPL,B,21 ; DEVICE IPL
00A7 222 DPT_STORE UCB,UCB$B_TT_WFLINK,L,0 ; Zero write queue.
00AE 223 DPT_STORE UCB,UCB$B_TT_WBLINK,L,0 ; Zero write queue.
00B5 224 DPT_STORE UCB,UCB$B_TT_RTIMOU,L,0 ; Zero read timed out disp.
00BC 225 DPT_STORE ORB,ORB$B_FLAGS,B,- ; Protection block flags
00BC 226 <ORB$M_PROT_16> ; SOGW protection word
00C0 227 DPT_STORE ORB,ORB$W_PROT,@W,TTY$GW_PROT ; Default allocation protection
00C7 228 DPT_STORE ORB,ORB$B_OWNER,@L,TTY$GL_OWNUIC ; Default owner UIC
00CE 229 DPT_STORE DDB,DDB$B_DDT,D,DZ$DDT
00D3 230
00D3 231 DPT_STORE REINIT
00D3 232 DPT_STORE CRB,CRB$B_INTD+VECSL_INITIAL,D,DZ$INITIAL ; CONTROLLER INIT
00D8 233 DPT_STORE CRB,CRB$B_INTD+VECSL_UNITINIT,D,DZ$INITLINE; UNIT INIT
00DD 234 DPT_STORE END
0000 235
0000 236 DDTAB DEVNAM = DZ,- ; DUMMY DZ PORT DRIVER DISPATCH TABLE
0000 237 START = 0,-
0000 238 FUNCTB = 0
0038 239
00000038 240 .PSECT $$$115_DRIVER
0038 241
0038 242 ;
0038 243 ; THE ASSOCIATED CLASS DRIVER USES THIS TABLE TO COMMAND THE PORT DRIVER.
0038 244 ; THE ADDRESS OF THIS TABLE IS CONTAINED IN THE TERMINAL UCB EXTENSION AREA.
0038 245 ; THE OFFSET DEFINITIONS ARE DEFINED BY TTYDEFS.
0038 246 ;
0038 247
0038 248 PORT_VECTOR:
0038 249

```



```

0038 250 :
0038 251 : DZ-11 SPECIFIC DISPATCH TABLE
0038 252 :
0038 253 $VECINI DZ11,DZ$NULL
0070 254 $VEC STARTIO,DZ11$STARTIO
003C 255 $VEC SET_LINE,DZ$SET_LINE
0044 256 $VEC DS_SET,DZ11$DS_SET
0048 257 $VEC XON,DZ11$XON
004C 258 $VEC XOFF,DZ11$XOFF
0050 259 $VEC STOP,DZ$STOP
0054 260 $VEC ABORT,DZ$ABORT
005C 261 $VEC RESUME,DZ11$RESUME
0060 262 $VEC SET_MODEM,DZ11$SET_MODEM
0064 263 $VEC MAINT,DZ11$MAINT
006C 264 .IF NDF DZV
006C 265 $VECEND END=NO
0070 266 :
0070 267 : DZ-32 SPECIFIC DISPATCH TABLE
0070 268 :
0070 269 :
0070 270 $VECINI DZ32,DZ$NULL
00A8 271 $VEC STARTIO,DZ32$STARTIO ; START NEW OUTPUT
0074 272 $VEC SET_LINE,DZ$SET_LINE ; SET NEW PARITY/SPEED
007C 273 $VEC DS_SET,DZ32$DS_SET ; SET NEW OUTPUT MODEM SIGNALS
0080 274 $VEC XON,DZ32$XON ; SEND XON
0084 275 $VEC XOFF,DZ32$XOFF ; SEND XOFF
0088 276 $VEC STOP,DZ$STOP ; STOP CURRENT OUTPUT
008C 277 $VEC ABORT,DZ$ABORT ; ABORT CURRENT OUTPUT
0094 278 $VEC RESUME,DZ32$RESUME ; RESUME STOPPED OUTPUT
0098 279 $VEC MAINT,DZ32$MAINT ; INVOKE MAINTENANCE FUNCTIONS
00A4 280 .ENDC
00A4 281 $VECEND
05 00AC 282 DZ$NULL: ; NULL PORT ROUTINE
00AD 283 RSB
00AD 284
00AD 285

```

```

00AD 287      .SBTTL REGISTER DEFINITIONS
00AD 288
00AD 289
00AD 290      : CSR BIT DEFINITIONS ( CSR ) ( READ/WRITE )
00AD 291      :
00AD 292      $VIELD DZCSR,0,<-
00AD 293      <MODE,1,M>,-      : DZ32 - MODE/ DZ11 - UNUSED
00AD 294      <DS_ENAB,1,M>,- : DZ32 - DATA SET INTERRUPT ENABLE
00AD 295      <,1>,-          : UNUSED
00AD 296      <MAINT,1,M>,-   : LINE TURNAROUND
00AD 297      <CLEAR,1,M>,-  : MASTER RESET
00AD 298      <MASTENAB,1,M>,- : MASTER SCAN ENABLE
00AD 299      <RCVINT,1,M>,-  : RECEIVER INTERRUPT ENABLE
00AD 300      <RCVRDY,1,M>,-  : RECEIVER READY
00AD 301      <LINE,3,M>,-   : LINE NUMBAE ( 0 - 7)
00AD 302      <DS_CHG,1,M>,- : DZ32 - DATA SET INTERRUPT
00AD 303      <,2>,-          : UNUSED
00AD 304      <SNDINT,1,M>,-  : TRANSMIT INTERRUPT ENABLE
00AD 305      <SNDRDY,1,M>-  : TRANSMITTER READY
00AD 306      >
00AD 307      :
00AD 308      : RECEIVER BUFFER ( CSR+2 ) ( READ ONLY )
00AD 309      :
00AD 310      $VIELD DZRCV,0,<-
00AD 311      <BUF,8,M>,-      : RECEIVER DATA
00AD 312      <LINE,3,M>,-   : LINE NUMBER ( 0 - 7)
00AD 313      <,1>,-          :
00AD 314      <PARERR,1,M>,-  : PARITY ERROR
00AD 315      <FRAMER,1,M>,-  : FRAME ERROR
00AD 316      <OVERRUN,1,M>,- : OVERRUN ERROR
00AD 317      <VALID,1,M>-   : DATA VALID
00AD 318      >
00AD 319      :
00AD 320      : LINE PARAMETER REGISTER ( CSR+2 ) ( WRITE ONLY )
00AD 321      :
00AD 322      :
00AD 323      $VIELD DZLPR,0,<-
00AD 324      <LINE,3,M>,-   : LINE NUMBER (0-7)
00AD 325      <SIZE,2,M>,-   : CHARACTER SIZE
00AD 326      <STOP,1,M>,-   : NUMBER STOP BITS
00AD 327      <PARITY,1,M>,-  : PARITY ENABLE
00AD 328      <ODD,1,M>,-    : ODD PARITY
00AD 329      <SPEED,4,M>,-  : LINE SPEED
00AD 330      <CLOCK,1,M>,-  : RECEIVER CLOCK
00AD 331      <SPLIT,1,M>,-  : DZ32 - SPLIT SPEED
00AD 332      >
00AD 333      :
00AD 334      :
00AD 335      : DZ-32 SPECIFIC MODEM CONTROL
00AD 336      :
00AD 337      :
00AD 338      $VIELD DZLCS1,8,<-
00AD 339      <,7>,-          :
00AD 340      <ACK,1,M>,-    : READY FOR COMMAND/ UPDATE OUTPUT MODEM
00AD 341      >
00AD 342
00AD 343

```

DZDRIVER  
V04-000

- Port Driver for DZ-11 support L 12  
REGISTER DEFINITIONS

00AD 344

16-SEP-1984 02:24:50 VAX/VMS Macro V04-00  
5-SEP-1984 04:15:55 [TTDRVR.SRC]DZDRIVER.MAR;1

Page 8  
(1)

DZ  
V0

```

00AD 346          .SBTTL  CONTROLLER INITIALIZATION
00AD 347
00AD 348
00AD 349
00AD 350
00AD 351 :++
00AD 352 : DZ$INITIAL - INITIALIZE INTERFACE
00AD 353 : FUNCTIONAL DESCRIPTION:
00AD 354 :
00AD 355 : THIS ROUTINE IS ENTERED AT SYSTEM STARTUP AND POWER RECOVERY.
00AD 356 :
00AD 357 : INPUTS:
00AD 358 :
00AD 359 :     R4 = ADDRESS OF THE UNIT CSR
00AD 360 :     R5 = IDB OF UNIT
00AD 361 :     R8 = ADDRESS OF THE UNIT CRB
00AD 362 :
00AD 363 : OUTPUTS:
00AD 364 :
00AD 365 :     R2 is destroyed.
00AD 366 :
00AD 367 : IMPLICIT INPUTS:
00AD 368 :
00AD 369 :     IPL = IPL$_POWER
00AD 370 :
00AD 371 :--
00AD 372 DZ$INITIAL::          : INITIALIZE DZ UNIT
00AD 373
00AD 374 :
00AD 375 : SET UP CONTROLLER
00AD 376 :
00AD 377 :     class_ctrl_init dz$dpt,port_vector
00DA 378
00DA 379 25$:  MOVW    #DZCSRSM_CLEAR,(R4)    ; INIT CONTROLLER RESET
00DD 380
00DD 381 :
00DD 382 :     WAIT TILL CONTROLLER INIIALIZATION IS COMPLETE
00DD 383 :
00DD 384 :     TIMEWAIT    #500,#DZCSRSM_CLEAR,(R4),W,.FALSE.
0104 385
0104 386  MOVW    #<<DZCSRSM_MASTENAB>!--    ;
0109 387          <DZCSRSM_RCVINT>!--      ; ENABLE RECEIVER INTERRUPTS
0109 388          <DZCSRSM_SNDINT>!--      ; ENABLE TRANSMITTER INTERRUPTS
0109 389          <DZCSRSM_DS_ENAB>!--     ; ENABLE DZ-32 DATA SET INTERRUPTS
0109 390          <DZCSRSM_MODE>>,(R4)    ; ENABLE ENHANCED MODE ON DZ-32
0109 391  BLBC    R0,DZ$CTRL_ERROR
010C 392
010C 393  MOVW    (R4),R2                      ; GET NEW STATUS
010F 394  BBS     #DZCSR$V_MODE,R2,110$      ; BRANCH IF DZ-32 CONTROLLER
0113 395
0113 396 100$:  MOVB    #DTS_DZ11,CRB$B_TT_TYPE(R8); CONTROLLER IS DZ11
0118 397
0118 398 :
0118 399 : INIT DZ-11 INTERRUPT VECTORS
0118 400 :     THIS IS DONE HERE TO ALLOW THE DRIVER TO SERVICE INTERUPTS
0118 401 :     FOR BOTH THE DZ-11 AND DZ-32 BETWEEN CONTROLLER AN UNIT INIT.
0118 402 :

```

```

28 A8 000003E9'EF DE 0118 403          MOVAL  DZ11$INTINP,CRBSL_INTD+4(R8)  ; INIT RECEIVER VECTOR
4C A8 000006E9'EF DE 0120 404          MOVAL  DZ11$INTOUT,CRBSL_INTD2+4(R8) ; INIT TRANSMITTER VECTOR
                                0128 405
                                1C A8 B4 0128 406          CLRW   CRBSB_DZ_RING(R8)           ; RESET CURRENT DZ-11 MODEM STATE
                                05 012B 407          RSB
                                012C 408
                                012C 409 110$: ;DZ-32 CONTROLLER SPECIFIC INIT
                                012C 410 .if ndf DZV
                                012C 411
                                0B A8 43 8F 90 012C 412          MOVB   #DTS_DZ32,CRBSB_TT_TYPE(R8)   ; CONTROLLER IS DZ-32
                                07 A4 0E A5 94 0131 413          CLRB   IDBSB_TT_ENABLE(R5)         ; RESET DZ-32 LINE ENABLE
                                07 A4 0E A5 90 0134 414          MOVB   IDBSB_TT_ENABLE(R5),7(R4)   ; RESET TRANSMIT LINE ENABLES
                                0139 415          ;
                                0139 416          ; INIT DZ-32 ALTERNATE INTERRUPT VECTORS
                                0139 417          ;
28 A8 00000477'EF DE 0139 418          MOVAL  DZ32$INTINP,CRBSL_INTD+4(R8)  ; INIT RECEIVER VECTOR
4C A8 000007A3'EF DE 0141 419          MOVAL  DZ32$INTOUT,CRBSL_INTD2+4(R8) ; INIT TRANSMITTER VECTOR
                                0149 420 .endc
                                05 0149 421          RSB
                                014A 422
                                014A 423 DZ$CTRL_ERROR:
                                05 014A 424          RSB
                                014B 425

```

```

014B 427 .SBTTL UNIT INITIALIZATION
014B 428 :++
014B 429 : DZ$INITLINE - UNIT INITIALIZATION
014B 430 :
014B 431 : FUNCTIONAL DESCRIPTION:
014B 432 :
014B 433 : THIS ROUTINE PERFORMS A SIMPLE UNIT INITIALIZATION.
014B 434 :
014B 435 : INPUTS:
014B 436 :
014B 437 : R5 = UCB ADDRESS
014B 438 :
014B 439 : OUTPUTS:
014B 440 :
014B 441 : R2,R5 ARE PRESERVED.
014B 442 :--
014B 443 :
014B 444 DZ$INITLINE::
014B 445
54 24 A5 D0 014B 446 MOVL UCBSL_CRB(R5),R4 ; GET CRB ADDRESS
014F 447
014F 448 .IF NDF DZV ; IF NOT DZV
014F 449
50 FF1D CF DE 014F 450 MOVAL DZ32$VEC,R0 ; SET DZ-32 PORT VECTOR TABLE
OB A4 43 8F 91 0154 451 CMPB #DTS_DZ32,CRBSB_TT_TYPE(R4) ; IS IT DZ-32 ?
05 13 0159 452 BEQL 5$ ; YES
015B 453
015B 454 .ENDC ; END OF DZ32 CODE
015B 455
50 FED9 CF DE 015B 456 MOVAL DZ11$VEC,R0 ; SET DZ-11 PORT VECTOR TABLE
0160 457 5$: CLASS_UNIT_INIT
53 64 A5 10 AE 01A9 458 B1SW #UCBSM_ONLINE,UCBSW_STS(R5); SET ONLINE
01 54 A5 78 01AD 459 10$: ASHL UCBSW_UNIT(R5),#1,R3 ; BUILD UNIT'S BIT MASK
0106 C5 53 B1 01B2 460 MOVW R3,UCBSW_TT_UNITBIT(R5) ; SAVE IT
51 0114 C5 D1 01B7 461 MOVL UCBSL_TT_CLASS(R5),R1 ; ADDRESS CLASS VECTOR TABLE
08 B1 16 01BC 462 JSB @CLASS_SETUP_UCB(R1) ; INIT UCB FIELDS
01BF 463 20$:
00000864'EF 16 01BF 464 JSB DZ$SET_LINE ; INIT SPEED/PARITY
01C5 465
54 24 A5 D0 01C5 466 MOVL UCBSL_CRB(R5),R4 ; GET CRB ADDRESS
01C9 467
01C9 468 .IF NDF DZV ; IF NOT DZV
01C9 469
OB A4 42 8F 91 01C9 470 CMPB #DTS_DZ11,CRBSB_TT_TYPE(R4) ; CONTROLLER DZ11?
69 13 01CE 471 BEQL 25$ ; YES
01D0 472
01D0 473
01D0 474 :
01D0 475 : INIT RECEIVER MODEM STATUS FOR DZ-32
01D0 476 :
54 2C B4 D0 01D0 477 MOVL @CRBSL_INTD+VEC$I_IDB(R4),R4 ; GET CSR ADDRESS
01D4 478
01D4 479 : WAIT TILL MODEM CONTROL READY FOR COMMAD
01D4 480
01D4 481 TIMEWAIT #500,#DZLCS1$M_ACK,4(R4),W,.TRUE.
04 A4 56 50 E9 01FE 482 BLBC R0,DZ$UNIT_ERROR
54 A5 B0 0201 483 MOVW UCBSW_UNIT(R5),4(R4) ; REQUEST STATUS ON LINE

```

```

0206 484
0206 485 ; WAIT FOR COMPLETION
0206 486
0206 487 TIMEWAIT #500,#DZLCS1$M_ACK,4(R4),W,.TRUE.
0124 C5 24 50 E9 0230 488 BLBC R0,DZ$UNIT_ERROR
04 A4 90 0233 489 MOVB 4(R4),UCB$B_TT_DS_RCV(R5) ; UPDATE RECEIVER MODEM STATUS
0239 490
0239 491 25$:
0239 492 .ENDC ; END OF DZ32 CODE
0239 493
0239 494 PUSHL R2
50 51 00 9A 023B 495 MOVZBL #MODEM$C_INIT,R1 ; ASSUME INIT MODEM PROTOCOL
0114 C5 D0 023E 496 MOVL UCB$L_TT_CLASS(R5),R0 ; ADDRESS CLASS VECTOR TABLE
OC B0 16 0243 497 JSB @CLASS_DS_TRAN(R0) ; INVOKE TO INIT MODEM PROTOCOL
52 8ED0 0246 498 POPL R2
0249 499 30$:
08 64 A5 05 E1 0249 500 BBC #UCB$V_POWER,UCB$W_STS(R5),40$; DID WE DETECT A POWER FAIL
50 0114 C5 D0 024E 501 MOVL UCB$L_TT_CLASS(R5),R0 ; GET THE CLASS VECTOR TABLE ADDRESS
20 B0 17 0253 502 JMP @CLASS_POWERFAIL(R0) ; AND GOTO THE POWERFAIL CODE
05 0256 503 40$:
0257 504 ;
0257 505 ; ERROR DETECTED DURING INITIALIZATION
0257 506 ;
0257 507
0257 508 DZ$UNIT_ERROR:
64 A5 10 AA 0257 509 BICW #UCB$M_ONLINE,UCB$W_STS(R5) ; UNIT NOT ON LINE
05 025B 510 RSB

```

```

025C 512 .SBTTL MAINTENANCE ROUTINES
025C 513 :++
025C 514 : DZ$MAINT - MAINTENANCE FUNCTIONS
025C 515 :
025C 516 : FUNCTIONAL DESCRIPTION:
025C 517 :
025C 518 : THIS ROUTINE PERFORMS MAINTENANCE FUNCTIONS FOR THE DZ .
025C 519 :
025C 520 :
025C 521 : INPUTS:
025C 522 :
025C 523 : R5 = UBC ADDRESS
025C 524 : UCBSB_TT_MAINT = FUNCTION TO BE PERFORMED
025C 525 :
025C 526 : OUTPUTS:
025C 527 :
025C 528 :--
025C 529 .IF NDF DZV
025C 530 DZ32$MAINT:
012A 01 93 025C 531 BITB #IOSM_LOOPa-7,- ; LOOPBACK FUNCTION
012A C5 025E 532 UCBSB_TT_MAINT(R5)
52 40 06 13 0261 533 BEQL 5$ ; NO
012A 8F 9A 0263 534 MOVZBL #^X40,R2 ; SPECIFY LOOPBACK CODE
012A 0C 11 0267 535 BRB 10$
0269 536 5$:
012A 02 93 0269 537 BITB #IOSM_UNLOOPa-7,- ; RESET LOOPBACK FUNCTION
012A C5 026B 538 UCBSB_TT_MAINT(R5)
52 7200 0F 13 026E 539 BEQL 15$ ; NO
012A 8F 3C 0270 540 MOVZWL #^X7200,R2 ; SPECIFY UNLOOP CODE (BOTH)
000002ED'EF 16 0275 541 10$: JSB DZ32$DS_SET ; UPDATE CONTROLLER
50 01 9A 027B 543 MOVZBL #1,R0 ; INDICATE SUCCESS
027E 544 RSB
027F 545 15$:
012A 20 93 027F 546 BITB #IOSM_LOOP_EXTa-7,- ; LOOPBACK FUNCTION
012A C5 0281 547 UCBSB_TT_MAINT(R5)
52 72 06 13 0284 548 BEQL 20$ ; NO
012A 8F 9A 0286 549 MOVZBL #^X72,R2 ; SPECIFY LOOPBACK CODE
012A E9 11 028A 550 BRB 10$
028C 551
028C 552 20$: ; CHECK OTHER FUNCTIONS
028C 553 .ENDC
028C 554 DZ11$MAINT:
012A 04 93 028C 555 BITB #IOSM_LINE_OFFa-7,- ; LINE OFF
012A C5 028E 556 UCBSB_TT_MAINT(R5)
80 08 13 0291 557 BEQL 10$ ; NO
012A 8F 88 0293 558 BISB #UCBSM_TT_DSBL,- ; DISABLE LINE
012A C5 0296 559 UCBSB_TT_MAINT(R5)
012A 0D 11 0299 560 BRB 20$
029B 561 10$:
012A 10 93 029B 562 BITB #IOSM_LINE_ONa-7,- ; LINE ON
012A C5 029D 563 UCBSB_TT_MAINT(R5)
80 10 13 02A0 564 BEQL 30$ ; NO
012A 8F 8A 02A2 565 BICB #UCBSM_TT_DSBL,- ; REENABLE LINE
012A C5 02A5 566 UCBSB_TT_MAINT(R5)
00000864'EF 16 02A8 567 20$: JSB DZ$SET_LINE ; IMPLEMENT FUNCTION
02A8 568

```



DZDRIVER  
V04-000

- Port Driver for DZ-11 support E 13  
MAINTENANCE ROUTINES

16-SEP-1984 02:24:50 VAX/VMS Macro V04-00  
5-SEP-1984 04:15:55 [TTDRVR.SRC]DZDRIVER.MAR;1

Page 14  
(1)

DZ  
VO

50	01	9A	02AE	569	MOVZBL	#1,R0
		05	02B1	570	RSB	
			02B2	571		
	50	D4	02B2	572	CLRL	R0
		05	02B4	573	RSB	
			02B5	574		
			02B5	575		

```

02B5 577 .SBTTL OUTPUT MODEM CONTROL
02B5 578 :++
02B5 579 : DZ$DS_SET - SET OUTPUT MODEM SIGNALS
02B5 580 :
02B5 581 : FUNCTIONAL DESCRIPTION:
02B5 582 :
02B5 583 : THIS ROUTINE OUTPUTS THE OUTPUT MODEM SIGNALS FOR THE SPECIFIED UNIT
02B5 584 :
02B5 585 : INPUTS:
02B5 586 :
02B5 587 : R2 = LOW BYTE - SIGNALS TO ACTIVATE
02B5 588 : HIGH BYTE- SIGNALS TO DEACTIVATE
02B5 589 :
02B5 590 : R5 = UBC ADDRESS
02B5 591 :
02B5 592 : OUTPUTS:
02B5 593 :
02B5 594 : R0-R3 ARE USED.
02B5 595 :--
02B5 596 :
02B5 597 DZ11$DS_SET:
02B5 598 PUSHL R4 ; SAVE
52 0125 C5 52 88 02B7 599 BISB R2,UCB$B TT_DS_TX(R5) ; SET NEW OUTPUT SIGNALS
52 52 F8 8F 78 02BC 600 ASHL #-8,R2,R2 ; ACCESS SIGNALS TO RESET
0125 C5 52 8A 02C1 601 BICB R2,UCB$B TT_DS_TX(R5) ; RESET THEM
54 24 A5 D0 02C6 602 MOVL UCB$C CRB(R5),R4 ; GET CRB ADDRESS
53 2C B4 D0 02CA 603 MOVL @CRB$C_INTD+VECSL_IDB(R4),R3 ;
02CE 604 ; GET CSR ADDRESS
51 0125 C5 01 01 EF 02CE 605 EXTZV #TT$V_DS_DTR,#1,UCB$B TT_DS_TX(R5),R1 ;
02D5 606 ; GET CURRENT DTR FOR LINE
51 51 54 A5 78 02D5 607 ASHL UCB$W_UNIT(R5),R1,R1 ; SHIFT TO RELATIVE LINE POSITION
1E A4 0106 C5 8A 02DA 608 BICB UCB$W_UNITBIT(R5),CRB$B DZ_DTR(R4) ;
02E0 609 ; RESET CURRENT DTR FOR THAT LINE
1E A4 51 88 02E0 610 BISB R1,CRB$B DZ_DTR(R4) ; SET IT IF NEED BE
05 A3 1E A4 90 02E4 611 MOVB CRB$B_DZ_DTR(R4),5(R3) ; UPDATE DTR STATUS FOR LINES
54 8ED0 02E9 612 POPL R4
05 02EC 613 RSB
02ED 614 .IF NDF DZV
02ED 615 DZ32$DS_SET:
02ED 616 PUSHL R4 ; SAVE
52 0125 C5 52 88 02EF 617 BISB R2,UCB$B TT_DS_TX(R5) ; SET NEW OUTPUT SIGNALS
52 52 F8 8F 78 02F4 618 ASHL #-8,R2,R2 ; ACCESS SIGNALS TO RESET
0125 C5 52 8A 02F9 619 BICB R2,UCB$B TT_DS_TX(R5) ; RESET THEM
54 24 A5 D0 02FE 620 MOVL UCB$C CRB(R5),R4 ; GET CRB ADDRESS
53 2C B4 D0 0302 621 MOVL @CRB$C_INTD+VECSL_IDB(R4),R3 ;
0306 622 TIMEWAIT #100,#DZLCS1$M ACK,4(R3),W,.TRUE. ; WAIT FOR READY
7E 0124 C5 3C 0330 623 MOVZWL UCB$B TT_DS_TX-T(R5),-(SP) ; CREATE TEMP LOCATION
6E 54 A5 90 0335 624 MOVB UCB$W_UNIT(R5),(SP) ; SET UNIT NUMBER
6E 8000 8F AB 0339 625 BISW #DZLCS1$M ACK,(SP) ; ENABLE NEW OUTPUT SIGNALS
04 A3 8E F7 033E 626 CVTLW (SP)+,4(R3) ; SET NEW OUTPUT MODEM SIGNALS
54 8ED0 0342 627 POPL R4
05 0345 628 RSB
0346 629 .ENDC

```

```

0346 631 .SBTTL DZ-11 MODEM POLLER
0346 632 :++
0346 633 : DZ$TIMER - POLL FOR DZ-11 MODEM TRANSITIONS
0346 634 :
0346 635 : FUNCTIONAL DESCRIPTION:
0346 636 :
0346 637 : THIS ROUTINE CHECKS FOR DZ-11 CONTROLLER MODEM
0346 638 : TRANSITION. IT UPDATES THE INPUT MODEM STATUS FOR EACH
0346 639 : LINE AND CALLS THE CLASS TRANSITION ROUTINE FOR EACH LINE WITH
0346 640 : A CHANGE.
0346 641 :
0346 642 : INPUTS:
0346 643 :
0346 644 : R5 - TQE ADDRESS
0346 645 :
0346 646 : OUTPUTS:
0346 647 :
0346 648 : R0 - R4 DESTROYED
0346 649 :
0346 650 :--
0346 651 :
0346 652 DZ$TIMER:
54 0060 8F BB 0346 653 PUSHR #^M<R5,R6>
00000000'EF DE 034A 654 MOVAL DZ$L_DIALUP,R4 ; GET DZ TIMER LIST HEAD
54 64 DO 0351 655 5$:
05 12 0351 656 MOVL (R4),R4 ; GET NEXT CRB ADDRESS
0060 8F BA 0354 657 BNEQ 15$ ; PROCESS LINES FOR THIS CRB
05 05 0356 658 POPR #^M<R5,R6> ; RESTORE REGISTERS
035A 659 RSB ; RETURN FROM TIMER INTERRUPT
035B 660 :
035B 661 : TEST LINES ON THIS CONTROLLER FOR A TRANSITION
035B 662 :
035B 663 :
035B 664 15$:
54 DD 035B 665 PUSHL R4 ; SAVE TIMER THREAD
54 18 C2 035D 666 SUBL #CRB$L_DZ MODEM,R4 ; GET ACTUAL CRB ADDRESS
06 53 2C B4 DO 0360 667 MOVL @CRB$L_INTD+VEC$L_IDB(R4),R3 ; GET CSR ADDRESS
A3 1C A4 B1 0364 668 CMPW CRB$B_DZ_RING(R4),6(R3) ; ANY TRANSITIONS
78 13 0369 669 BEQL 60$ ; NONE
036B 670 :
036B 671 : FIND WHICH SIGNALS CHANGED AND UPDATE THEM
036B 672 :
50 52 06 A3 90 036B 673 MOVB 6(R3),R2 ; GET NEW RING
1C A4 52 8D 036F 674 XORB3 R2,CRB$B_DZ_RING(R4),R0 ; FIND TRANSITIONED LINES
1C A4 52 90 0374 675 MOVB R2,CRB$B_DZ_RING(R4) ; UPDATE CURRENT RING
52 07 A3 90 0378 676 MOVB 7(R3),R2 ; GET NEW CARRIER
56 1D A4 52 8D 037C 677 XORB3 R2,CRB$B_DZ_CARRIER(R4),R6
50 50 56 88 0381 678 BISB R6,R0 ; FLAG LINES WITH TRANSITIONED CARRIER
1D A4 52 90 0384 679 MOVB R2,CRB$B_DZ_CARRIER(R4) ; UPDATE CURRENT CARRIER
0388 680 :
0388 681 : PROCESS TRANSITIONED LINES
0388 682 :
0388 683 :
51 50 08 00 EA 0388 684 50$:
00 50 54 13 038D 685 BEQL 60$ ; FIND NEXT LINE NEEDING SERVICE
00 50 51 E5 038F 686 BBCC R1,R0,55$ ; DONE
0393 687 55$: ; RESET ATTENTION BIT FOR THIS LINE

```

```

56 2C A4 DO 0393 688
55 18 A641 DO 0397 689
EA 13 039C 690
E5 44 A5 15 E1 039E 691
03A3 692
03A3 693
56 1C A4 01 51 EF 03AA 694
01 06 56 FO 03B0 695
0124 C5 03B4 696
56 1D A4 01 51 EF 03B7 697
01 05 56 FO 03BD 698
0124 C5 03C1 699
90 8F 88 03C4 700
0124 C5 03C7 701
52 0124 C5 90 03CA 702
51 03 9A 03CF 703
56 0114 C5 DO 03D2 704
1F BB 03D7 705
OC B6 16 03D9 706
1F BA 03DC 707
A5 11 03DE 708
03E1 709
03E3 710
03E3 711 60$:
54 8ED0 03E3 712
FF68 31 03E6 713
03E9 714
03E9 715

```

```

MOVL CRBSL_INTD+VECSL_IDB(R4),R6
MOVL IDBSL_UCBLST(R6)[R1],R5 ; GET UCB FOR THAT LINE
BEQL 50$ ; NONE
BBC #TT$V_MODEM,UCBSL_DEVDEPEND(R5),50$ ; SKIP IF NOT MODEM LINE
DSBINT UCBSB_DIPL(R5) ; RAISE TO DEVICE IPL
EXTZV R1,#1-CRBSB_DZ_RING(R4),R6 ; GET RING FOR THAT LINE
INSV R6,#TT$V_DS_RING,#1,- ; UPDATE IT IN UCB
UCBSB_TT_DS_RCV(R5)
EXTZV R1,#1-CRBSB_DZ_CARRIER(R4),R6 ; GET CD FOR THAT LINE
INSV R6,#TT$V_DS_CARRIER,#1,- ; UPDATE IT IN UCB
UCBSB_TT_DS_RCV(R5)
BISB #<TT$M_DS_DSR!TT$M_DS_CTS>,- ; ASSUME CTS AND DSR ALWAYS SET
UCBSB_TT_DS_RCV(R5)
MOVBL UCBSB_TT_DS_RCV(R5),R2 ; GET CURRENT RECV MODEM STATUS
MOVZBL #MODEM$C_DATASET,R1 ; SIGNAL DATASET TRANSITION
MOVL UCBSL_TT_CLASS(R5),R6 ; GET CLASS VECTOR TABLE
PUSHR #^M<R0,RT,R2,R3,R4> ; SAVE VOLITAL REGISTERS
JSB @CLASS_DS_TRAN(R6) ; SIGNAL TRANSITION
POPR #^M<R0,R1,R2,R3,R4> ; RESTORE REGISTERS
ENBINT ; RESTORE IPL
BRB 50$

POPL R4 ; RESTORE TIMER THREAD
BRW 5$

```

```

03E9 717 .SBTTL RECEIVER INTERRUPT SERVICE
03E9 718 :++
03E9 719 : DZ$INTINP - DZ RECEIVER READY INTERRUPTS
03E9 720 :
03E9 721 : FUNCTIONAL DESCRIPTION:
03E9 722 :
03E9 723 : THIS ROUTINE IS ENTERED WHEN A CHARACTER IS AVAILABLE IN THE UNIT'S
03E9 724 : SILO. THE CHARACTER IS EXTRACTED AND IS PASSED TO THE ASSOCIATED
03E9 725 : CLASS DRIVER. IF THE CLASS DRIVER RETURNS CHARACTER(S) THEN NEW
03E9 726 : OUTPUT IT INITIATED (NORMALLY ECHO).
03E9 727 :
03E9 728 : INPUTS:
03E9 729 :
03E9 730 : OO(SP) = ADDRESS OF IDB
03E9 731 :
03E9 732 : IMPLICIT INPUTS:
03E9 733 :
03E9 734 : R0,R1,R2,R3,R4,R5 ARE SAVED ON STACK.
03E9 735 :
03E9 736 : OUTPUTS:
03E9 737 :
03E9 738 : THE INTERRUPT IS DISMISSED WHEN THE SILO IS EMPTY.
03E9 739 :
03E9 740 :--
03E9 741 DZ11$INTINP:: : DZ-11 INPUT INTERRUPTS
03E9 742 :
03E9 743 : GET THE CSR ADDRESS
03E9 744 :
54 9E D0 03E9 745 MOVL @ (SP)+,R4 : GET THE IDB ADDRESS
50 54 DD 03EC 746 PUSHL R4 : SAVE IDB ADDRESS
50 64 D0 03EE 747 MOVL (R4),R0 : GET THE CSR ADDRESS
03F1 748 :
03F1 749 : GET THE CHARACTER FROM THE INTERFACE
03F1 750 :
53 02 A0 B0 03F1 751 25$: MOVW 2(R0),R3 : GET THE CHARACTER,ERRORS AND LINE NUMBER
73 18 03F5 752 BGEQ 100$ : SILO EMPTY
53 7000 8F B3 03F7 753 BITW #<DZRCV$M_PARERR>!-
03FC 754 <DZRCV$M_OVERRUN>!-
03FC 755 <DZRCV$M_FRAMER>,R3 : ERRORS?
52 53 FB 8F 12 03FC 756 BNEQ 50$ : YES,PROCESS THEM
52 FFFFFFFF 8F CA 0403 757 27$: ASHL #-8,R3,R2 : GET THE LINE NUMBER
55 18 A442 D0 040A 759 MOVZBL R3,R3 : CLEAR THE HIGH BYTES OF CHARACTER
0110 D5 16 040D 760 MOVL IDB$$_UCBLST(R4)[R2],R5 : GET THE UCB FOR THAT LINE
010B C5 95 0412 761 BEQL 25$ : IF EQL THEN NOT THERE
010B C5 17 0414 762 JSB @UCB$$_TT_PUTNXT(R5) : BUFFER THE CHARACTER
010B C5 53 90 0418 763 TSTB UCB$$_TT_OUTYPE(R5) : DID HE RETURN ANYTHING TO OUTPUT
04 A0 0106 C5 A8 041C 764 BLEQ 40$ : NONE OR STRING OUTPUT
0400 8F A8 041E 765 MOVW R3,UCB$$_TT_HOLD(R5) : SAVE THE CHARACTER IN TANK
0108 C5 0423 766 BISW #TTY$$_TANK_HOLD,- : SIGNAL CHARACTER IN TANK
0400 8F A8 0427 767 UCBSW_TT_HOLD(R5)
04 A0 0106 C5 A8 042A 768 BISW UCBSW_TT_UNITBIT(R5),4(R0) : ENABLE LINE
54 6E D0 0430 769 30$: MOVL (SP),R4 : GET IDB ADDRESS
BC 11 0433 770 BRB 25$ : CONTINUE
0435 771 40$:
0800 F9 13 0435 772 BEQL 30$ : NO CHARACTER
0800 8F A8 0437 773 BISW #TTY$$_TANK_BURST,- : SIGNAL BURST

```

```

04 A0 0108 C5 043B 774 UCBSW_TT_HOLD(R5)
04 A0 0106 C5 A8 043E 775 BISW UCBSW_TT_UNITBIT(R5),4(R0) ; ENABLE LINE
EA 11 0444 776 BRB 30$
0446 777 :
0446 778 : SILO EMPTY OR CHARACTER IN ERROR
0446 779 :
0446 780 50$:
0446 781 :
0446 782 : PROCESS PARITY, FRAME OR OVERRUN ERROR
0446 783 :
52 53 F8 8F 78 0446 784 ASHL #-8,R3,R2 ; GET LINE NUMBER
52 FFFFFFFF 8F CA 044B 785 BICL #^C<7>,R2 ;
55 18 A442 D0 0452 786 MOVL IDB$L_UCBLST(R4)[R2],R5; GET UCB ADDRESS
0A 13 0457 787 BEQL 70$ ; IF EQL THEN NO UCB
52 0114 C5 D0 0459 788 MOVL UCBSL_TT_CLASS(R5),R2 ; GET CLASS DISPATCH
045E 789
14 B2 16 045E 790 60$: JSB @CLASS_READERROR(R2) ; SIGNAL ERROR
9B 12 0461 791 BNEQ 27$ ; BRANCH WITH CHARACTER TO MAIN PATH
60 0080 8F B3 0463 792 70$: BITW #^X080,(R0) ; VALID CHARACTER IN SILO NOW?
C6 12 0468 793 BNEQ 30$ ; IF NEQ THEN YES
5E 04 C0 046A 794 100$: ADDL #4,SP ; REMOVE IDB ADDRESS
50 8E 7D 046D 795 MOVQ (SP)+,R0 ; RESTORE REGISTERS
52 8E 7D 0470 796 MOVQ (SP)+,R2 ;
54 8E 7D 0473 797 MOVQ (SP)+,R4 ;
02 0476 798 REI ;
0477 799

```

```

0477 801 .IF NDF DZV
0477 802 :
0477 803 : DZ-32 INPUT INTERRUPT SERVICE
0477 804 :
0477 805 :
0477 806 DZ32$INTINP:: : DZ-32 INPUT INTERRUPTS
0477 807 :
0477 808 : GET THE CSR ADDRESS
0477 809 :
54 9E D0 0477 810 MOVL @ (SP)+,R4 : GET THE IDB ADDRESS
DD 047A 811 PUSHL R4 : SAVE IDB ADDRESS
50 64 D0 047C 812 MOVL (R4),R0 : GET THE CSR ADDRESS
AA 047F 813 BICW #<<DZCSR$M_RCVINT>!- : DISABLE RECEIVER INTERRUPTS
0480 814 <DZCSR$M_DS_ENAB>>,- : DISABLE DZ-32 DATA SET INTERRUPTS
60 0042 8F 0480 815 (R0) : DZ-32 during the interrupt service routine
0484 816 :
0484 817 : GET THE CHARACTER FROM THE INTERFACE
0484 818 :
53 02 A0 B0 0484 819 25$: MOVW 2(R0),R3 : GET THE CHARACTER, ERRORS AND LINE NUMBER
75 18 0488 820 BGEQ 100$ : SILO EMPTY
53 7000 8F B3 048A 821 BITW #<DZRCV$M_PARERR>!- :
048F 822 <DZRCV$M_OVERRUN>!- : ERRORS?
048F 823 <DZRCV$M_FRAMER>,R3 : ERRORS?
52 53 F8 8F 78 048F 824 BNEQ 50$ : YES, PROCESS THEM
52 FFFFFFFF 8F CA 0496 825 27$: ASHL #-8,R3,R2 : GET THE LINE NUMBER
53 53 9A 049D 827 MOVZBL R3,R3 :
55 18 A4 42 D0 04A0 828 MOVL IDB$L_UCBLST(R4)[R2],R5 : CLEAR THE HIGH BYTES OF CHARACTER
DD 13 04A5 829 BEQL 25$ : GET THE UCB FOR THAT LINE
0110 D5 16 04A7 830 JSB @UCB$L_TT_PUTNXT(R5) : IF EQL THEN NOT THERE
010B C5 95 04AB 831 TSTB UCBSB_TT_OUTYPE(R5) : BUFFER THE CHARACTER
0108 C5 53 90 04AF 832 BLEQ 40$ : DID HE RETURN ANYTHING TO OUTPUT
0400 8F A8 04B1 833 MOVW R3,UCBSW_TT_HOLD(R5) : NONE OR STRING OUTPUT
0108 C5 04B6 834 BISW #TTY$M_TANK_HOLD,- : SAVE THE CHARACTER IN TANK
04BA 835 UCBSW_TT_HOLD(R5) : SIGNAL CHARACTER IN TANK
04BD 836 28$:
54 6E D0 04BD 837 MOVL (SP),R4 : RESTORE IDB ADDRESS
0106 C5 88 04C0 838 BISB UCBSW_TT_UNITBIT(R5),- : ENABLE LINE
OE A4 04C4 839 IDBSB_TT_ENABLE(R4)
07 A0 OE A4 90 04C6 840 MOVW IDBSB_TT_ENABLE(R4),7(R0)
54 6E D0 04CB 841 30$: MOVL (SP),R4 : GET IDB ADDRESS
B4 11 04CE 843 BRB 25$ : CONTINUE
04D0 844 40$:
0800 8F A8 04D2 845 BEQL 30$ : NO CHARACTER
0108 C5 04D6 846 BISW #TTY$M_TANK_BURST,- : SIGNAL BURST
E2 11 04D9 847 UCBSW_TT_HOLD(R5)
04DB 848 BRB 28$
04DB 849 :
04DB 850 : SILO EMPTY OR CHARACTER IN ERROR
04DB 851 :
04DB 852 50$:
04DB 853 :
04DB 854 : PROCESS PARITY, FRAME OR OVERRUN ERROR
04DB 855 :
52 53 F8 8F 78 04DB 856 ASHL #-8,R3,R2 : GET LINE NUMBER
52 FFFFFFFF 8F CA 04E0 857 BICL #^C<7>,R2 :

```

```

55 18 A442 D0 04E7 858      MOVL  IDB$$_UCBLST(R4)[R2],R5 ; GET UCB ADDRESS
      OA 13 04EC 859      BEQL  70$                    ; IF EQL THEN NO UCB
52 0114 C5 D0 04EE 860      MOVL  UCB$$_TT_CLASS(R5),R2  ; GET CLASS DISPATCH
      14 B2 16 04F3 861
      99 12 04F6 862 60$:   JSB   @CLASS_READERROR(R2) ; SIGNAL ERROR
60 0080 8F B3 04F8 863      BNEQ  27$                    ; BRANCH WITH CHARACTER TO MAIN PATH
      CC 12 04FD 864 70$:   BITW  #^X080,(R0) ; VALID CHARACTER IN SILO NOW?
      53 60 B0 04FF 865      BNEQ  30$                    ; IF NEQ THEN YES
      12 53 0B E0 0502 866 100$: MOVW (R0),R3 ; TEST FOR MODEM TRANSITION
      53 0B AB 0506 867      BBS   #DZCSR$V_DS_CHG,R3,200$ ; BRANCH IF MODEM TRANSITION
      50 0507 868      BISW  #<<DZCSR$M_RCVINT>!- ; ENABLE RECEIVER INTERRUPTS
60 0042 8F 0507 870      <DZCSR$M_DS_ENAB>>,- ; ENABLE DZ-32 DATA SET INTERRUPTS
      SE 04 C0 050B 871      (R0) ; DZ-32 BEFORE EXITING
      50 8E 7D 050E 872      ADDL  #4,SP ; REMOVE IDB ADDRESS
      52 8E 7D 0511 873      MOVQ  (SP)+,R0 ; RESTORE REGISTERS
      54 8E 7D 0514 874      MOVQ  (SP)+,R2
      02 0517 875      MOVQ  (SP)+,R4
      50 DD 0518 876      REI
52 53 53 06 A0 90 051A 877 200$: PUSHL R0 ; SAVE R0
      FFFFFFFF 8F CB 051E 878      MOVB  6(R0),R3 ; GET NEW RECEIVE MODEM SIGNALS
      55 18 A442 D0 0526 879      BICL3 #^C<7>,R3,R2 ; ISOLATE UNIT NUMBER
      13 13 052B 880      MOVL  IDB$$_UCBLST(R4)[R2],R5 ; GET ASSOCIATED UCB
0124 C5 53 90 052D 881      BEQL  110$ ; NONE
      52 53 9A 0532 882      MOVB  R3,UCB$$_TT_DS_RCV(R5) ; UPDATE INPUT MODEM SIGNALS
      51 03 9A 0535 883      MOVZBL R3,R2 ; LOAD ARGUMENT
53 0114 C5 D0 0538 884      MOVZBL #MODEM$C_DATASET,R1 ; MODEM TRANSITION
      0C B3 16 053D 885      MOVL  UCB$$_TT_CLASS(R5),R3 ; ACCESS CLASS VECTORS
      50 8ED0 0540 886      JSB   @CLASS_DS_TRAN(R3) ; SIGNAL TRANSITION
      FF85 31 0543 887 110$: POPL  R0 ; RESTORE R0
      0546 888      BRW  30$ ; DISMISS INTERRUPT
      889 .ENDC

```



```

0546 891 .SBTTL START I/O ROUTINE
0546 892 :++
0546 893 : DZ$STARTIO - START I/O OPERATION ON DZ
0546 894 :
0546 895 : FUNCTIONAL DESCRIPTION:
0546 896 :
0546 897 : THIS ROUTINE IS ENTERED FROM THE DEVICE INDEPENDENT TERMINAL STARTIO
0546 898 : ROUTINE TO ENABLE OUTPUT INTERRUPTS ON AN IDLE DZ UNIT.
0546 899 :
0546 900 : INPUTS:
0546 901 :
0546 902 : R3 = CHARACTER AND CC = PLUS
0546 903 : ADDRESS AND CC = NEGATIVE
0546 904 :
0546 905 : R5 = UCB ADDRESS
0546 906 :
0546 907 : OUTPUTS:
0546 908 :
0546 909 : R5 = UCB ADDRESS
0546 910 :--
0546 911 DZ11$STARTIO:: : START I/O ON UNIT
0546 912 BGEQ 20$ : SINGLE CHARACTER
0546 913 BISW #TTY$M_TANK_BURST,- : SIGNAL BURST ACTIVE
0546 914 UCBSW_TT_HOLD(R5)
0546 915 10$: MOVL UCBSL_CRB(R5),R1 : GET CRB OF UNIT
0546 916 MOVL @CRB$C_INTD+VEC$SL_IDB(R1),R1 : GET CSR
0546 917 BISW UCBSW_TT_UNITBIT(R5),4(R1) : ENABLE LINE
0546 918 RSB : RETURN TO CALLER
0546 919 20$:
0546 920 MOVB R3,UCBSW_TT_HOLD(R5) : SAVE OUTPUT CHARACTER
0546 921 BISW #TTY$M_TANK_HOLD,- : SIGNAL CHARACTER IN TANK
0546 922 UCBSW_TT_HOLD(R5)
0546 923 BRB 10$
0546 924
0546 925 .IF NDF DZV
0546 926 DZ32$STARTIO:: : START I/O ON UNIT
0546 927 BGEQ 20$ : SINGLE CHARACTER SPECIFIED
0546 928 BISW #TTY$M_TANK_BURST,- : SIGNAL BURST ACTIVE
0546 929 UCBSW_TT_HOLD(R5)
0546 930 10$: MOVL UCBSL_CRB(R5),R1 : GET CRB OF UNIT
0546 931 MOVL CRB$C_INTD+VEC$SL_IDB(R1),R4 : GET IDB ADDRESS
0546 932 MOVL (R4),R1 : GET CSR ADDRESS
0546 933 BISB UCBSW_TT_UNITBIT(R5),IDB$B_TT_ENABLE(R4)
0546 934 MOVB IDB$B_TT_ENABLE(R4),7(R1)
0546 935 RSB : RETURN TO CALLER
0546 936 20$:
0546 937 MOVB R3,UCBSW_TT_HOLD(R5) : SAVE OUTPUT CHARACTER
0546 938 BISW #TTY$M_TANK_HOLD,- : SIGNAL CHARACTER IN TANK
0546 939 UCBSW_TT_HOLD(R5)
0546 940 BRB 10$
0546 941 .ENDC

```







```

06DC 1085      .SBTTL OUTPUT INTERRUPT SERVICE
06DC 1086      :++
06DC 1087      : DZ$INTOUT - DZ-11 OUTPUT INTERRUPT SERVICE
06DC 1088      :
06DC 1089      : FUNCTIONAL DESCRIPTION:
06DC 1090      :
06DC 1091      : THIS ROUTINE IS ENTERED WHEN THE DZ-11 FINDS A LINE ENABLED
06DC 1092      : AND AN EMPTY UART. THE CORRESPONDING UCB IS FOUND AND
06DC 1093      : ANY OUTSTANDING PORT OUTPUT IS DONE. WHEN ALL OUTSTANDING PORT
06DC 1094      : OUTPUT IS COMPLETED, THE CLASS DRIVER IS CALLED TO RETURN THE NEXT
06DC 1095      : CHARACTER OR STRING TO BE OUTPUT. IF NO MORE OUTPUT IS FOUND, THEN
06DC 1096      : THE LINE IS DISBALED.
06DC 1097      :
06DC 1098      : INPUTS:
06DC 1099      :
06DC 1100      :     SP(00) = ADDRESS OF THE IDB
06DC 1101      :
06DC 1102      : IMPLICIT INPUTS:
06DC 1103      :
06DC 1104      :     R0,R1,R2,R3,R4,R5 SAVED ON THE STACK.
06DC 1105      :
06DC 1106      : OUTPUTS:
06DC 1107      :
06DC 1108      :     THE INTERRUPT IS DISMISSED.
06DC 1109      :
06DC 1110      :--
06DC 1111      DZ11_OUT_EXIT:
06DC 1112      ADDL    #4,SP          ; EXIT OUTPUT INTERRUPT
5E   04   C0   06DC 1112      ADDL    #4,SP          ; REMOVE IDB ADDRESS
50   8E   7D   06DF 1113      MOVQ   (SP)+,R0          ; RESTORE REGISTERS
52   8E   7D   06E2 1114      MOVQ   (SP)+,R2
54   8E   7D   06E5 1115      MOVQ   (SP)+,R4
02   06E8 1116      REI
06E9 1117      : DISMISS INTERRUPT
06E9 1118      DZ11$INTOUT::
06E9 1119      : DZ-11 OUTPUT INTERRUPT SERVICE
54   00   BE   D0   06E9 1120      DZ11_OUT_LOOP:
50   64   D0   06E9 1121      MOVL   @ (SP),R4        ; GET THE IDB ADDRESS
06ED 1122      MOVL   (R4),R0       ; GET THE CSR ADDRESS
06F0 1123      :
06F0 1124      : GET THE LINE INFO FROM THE CSR
06F0 1125      :
06F0 1126      :
52   60   B0   06F0 1127      MOVW   (R0),R2         ; GET THE CSR VALUE
52   E7   18   06F3 1128      BGEQ   DZ11_OUT_EXIT  ; NO MORE LINES
52   F8   8F   78   06F5 1129      ASHL   #-8,R2,R2      ; GET THE LINE NUMBER
52   F8   8F   CA   06FA 1130      BICL   #^C<7>,R2
55   18   A4  D0   0701 1131      MOVL   IDB$UCBLST(R4)[R2],R5 ; GET THE UCB ADDRESS
0706 1132      BEQL   DZ11_OUT_LOOP  ; IF EQL THEN DISMISS
0708 1133      :
0708 1134      : CHECK FOR BURST ACTIVE ON LINE
0708 1135      :
0109 08   91   0708 1136      CMPB   #TTY$M_TANK_BURST@-8,- ; ONLY BURST ACTIVE?
070A 1137      UCBSW TT HO[D+1](R5)
070D 1138      BEQL   DZ11_BURST    ; YES, CONTINUE BURST
070F 1139      :
070F 1140      : LOOK FOR NEXT OUTPUT STATE IN TANK
070F 1141      :

```

```

53 0109 C5 06 00 EA 070F 1142
070F 1143 FFS #0,#6,UCBSW_TT_HOLD+1(R5),R3
0716 1144 CASE R3,TYPE=B,<= ; DISPATCH
0716 1145 DZ11_PREMPT,- ; SEND PREMPT CHARACTER
0716 1146 DZ11_STOP,- ; STOP OUTPUT
0716 1147 DZ11_CHAR,- ; CHAR IN TANK
0716 1148 DZ11_BURST,- ; BURST IN PROGRESS
0716 1149 >
0722 1150 :
0722 1151 : NO PENDING DATA - LOOK FOR NEXT CHARACTER
0722 1152 :
64 A5 03 8A 0722 1153 BICB #UCBSM_TIM!UCBSM_INT,UCBSW_STS(R5); CLEAR TIMEOUT AND EXPECTED
0726 1154 :
0726 1155 : CALL CLASS DRIVER FOR MORE OUTPUT
0726 1156 :
01 FF 8F 010C D5 16 0726 1157 JSB @UCBSL_TT_GETNXT(R5) ; GET THE NEXT CHARACTER
010B C5 8F 072A 1158 CASEB UCBSB_TT_OUTTYPE(R5),#-1,#1; OPTIMIZE FOR THE SINGLE
0731 1159 : CHARACTER CASE BY SETTING THE
0731 1160 : LIMIT TO 1
0017' 0731 1161 1$: .WORD DZ11_START_BURST-1$ ; BURST SPECIFIED
000A' 0733 1162 .WORD 50$-T$ ; NONE
0735 1163 :
0735 1164 : OUTPUT A CHARACTER TO THE DZ-11
0735 1165 :
06 A0 53 9B 0735 1166 20$: MOVZBW R3,6(R0) ; OUTPUT CHARACTER
AE 11 0739 1167 BRB DZ11_OUT_LOOP
073B 1168 :
073B 1169 : DISABLE OUTPUT ON THIS LINE
073B 1170 :
073B 1171 50$:
A9 64 A5 01 E0 073B 1172 BBS #UCBSV_INT,- ; IF INT EXP, THEN DON'T RESET,
073D 1173 UCBSW_STS(R5),DZ11_OUT_LOOP ; COULD HAVE BEEN SET DURING CALLBACK
0740 1174 :
0740 1175 :
04 A0 0106 C5 AA 0740 1176 BICW UCBSW_TT_UNITBIT(R5),4(R0) ; RESET THE OUTPUT ENABLE
A1 11 0746 1177 BRB DZ11_OUT_LOOP
0748 1178 :
0748 1179 :
0800 8F AB 0748 1180 DZ11_START_BURST:
0108 C5 0748 1181 BISW #TTY$M_TANK_BURST,- ; SIGNAL BURST ACTIVE
074C 1182 UCBSW_TT_HOLD(R5)
074F 1183 :
074F 1184 : CONTINUE BURST OUTPUT
074F 1185 :
074F 1186 DZ11_BURST:
011C D5 90 074F 1187 MOVB @UCBSL_TT_OUTADR(R5),- ; OUTPUT NEXT BYTE
06 A0 0753 1188 6(R0)
011C C5 D6 0755 1189 INCL UCBSL_TT_OUTADR(R5) ; UPDATE POINTER
0120 C5 B7 0759 1190 DECW UCBSW_TT_OUTLEN(R5) ; UPDATE COUNT
8A 12 075D 1191 BNEQ DZ11_OUT_LOOP ; NOT LAST CHARACTER
0800 8F AA 075F 1192 BICW #TTY$M_TANK_BURST,- ; RESET BURST ACTIVE
0108 C5 0763 1193 UCBSW_TT_HOLD(R5)
FF80 31 0766 1194 BRW DZ11_OUT_LOOP
0769 1195 :
0769 1196 : OUTPUT SINGLE CHARACTER
0769 1197 :
0769 1198 DZ11_CHAR:

```

```

06 A0 0108 C5 90 0769 1199      MOVB   UCBSW TT_HOLD(R5),6(R0) ; OUTPUT CHAR IN TANK
      0400 8F AA 076F 1200      BICW   #TTYSM TANK_HOLD,-      ; SHOW TANK EMPTY
      0108 C5      0773 1201      UCBSW TT_HOLD(R5)
      FF70 31 0776 1202      BRW   DZ11_OUT_LOOP
      0779 1203      :
      0779 1204      : STOP THE OUTPUT
      0779 1205      :
      0779 1206      DZ11_STOP:
      03 8A 0779 1207      BICB   #UCBSM_INT!UCBSM_TIM,-
      64 A5 077B 1208      UCBSW_STS(R5)
04 A0 0106 C5 AA 077D 1209      BICW   UCBSW TT_UNITBIT(R5),4(R0) ; RESET OUTPUT ACTIVE
      FF63 31 0783 1210      BRW   DZ11_OUT_LOOP
      0786 1211      :
      0786 1212      .ENABLE LSB
      0786 1213      :
      0786 1214      : SEND XON OR XOFF CHARACTER
      0786 1215      :
      0786 1216      :
      0786 1217      DZ11_PREMPT:
      0100 8F AA 0786 1218      BICW   #TTYSM TANK_PREMPT,-      . RESET XOFF STATE
      0108 C5      078A 1219      UCBSW TT_HOLD(R5)
06 A0 010A C5 90 078D 1220      MOVB   UCBSB TT_PREMPT(R5),6(R0); OUTPUT CHARACTER
      FF53 31 0793 1221      BRW   DZ11_OUT_LOOP
      0796 1222      .DISABLE      CSB
      0796 1223

```

```

0796 1225 .IF NDF DZV
0796 1226 :
0796 1227 : DZ-32 OUTPUT INTERRUPT SERVICE CODE
0796 1228 :
0796 1229 :
0796 1230 DZ32_OUT_EXIT: : EXIT OUTPUT INTERRUPT
5E 04 C0 0796 1231 ADDL #4,SP : REMOVE IDB ADDRESS
50 8E 7D 0799 1232 MOVQ (SP)+,R0 : RESTORE REGISTERS
52 8E 7D 079C 1233 MOVQ (SP)+,R2 :
54 8E 7D 079F 1234 MOVQ (SP)+,R4 :
02 07A2 1235 REI : DISMISS INTERRUPT
07A3 1236 :
07A3 1237 DZ32$INTOUT:: : DZ-32 OUTPUT INTERRUPT SERVICE
07A3 1238 DZ32_OUT_LOOP: :
54 00 BE D0 07A3 1239 MOVL @ (SP),R4 : GET THE IDB ADDRESS
50 64 D0 07A7 1240 MOVL (R4),R0 : GET THE CSR ADDRESS
07AA 1241 :
07AA 1242 : GET THE LINE INFO FROM THE CSR
07AA 1243 :
07AA 1244 :
52 60 B0 07AA 1245 MOVW (R0),R2 : GET THE CSR VALUE
52 E7 18 07AD 1246 BGEQ DZ32_OUT_EXIT
52 52 FB 8F 78 07AF 1247 ASHL #-8,R2,R2 : GET THE LINE NUMBER
52 FFFFFFFF 8F CA 07B4 1248 BICL #^C<7>,R2 :
55 18 A442 D0 07BB 1249 MOVL IDB$L_UCBLST(R4)[R2],R5; GET THE UCB ADDRESS
E1 13 07C0 1250 BEQL DZ32_OUT_LOOP : IF EQL THEN DISMISS
07C2 1251 :
07C2 1252 : CHECK FOR BURST ACTIVE ON LINE
07C2 1253 :
0109 08 91 07C2 1254 CMPB #TTY$M_TANK_BURST@-8,- : ONLY BURST ACTIVE?
C5 07C4 1255 UCBSW TT_HOLD+1(R5)
4B 13 07C7 1256 BEQL DZ32_BURST : YES, CONTINUE BURST
07C9 1257 :
07C9 1258 : LOOK FOR NEXT OUTPUT STATE IN TANK
07C9 1259 :
53 0109 C5 06 00 EA 07C9 1260 FFS #0,#6,UCBSW_TT_HOLD+1(R5),R3
G7D0 1262 CASE R3,TYPE=B,<= : DISPATCH
07D0 1263 DZ32_PREMPT,- : SEND PREMPT CHARACTERS
07D0 1264 DZ32_STOP,- : STOP OUTPUT
07D0 1265 DZ32_CHAR,- : CHAR IN TANK
07D0 1266 DZ32_BURST,- : BURST IN PROGRESS
07D0 1267 >
07DC 1268 :
07DC 1269 : NO PENDING DATA - LOOK FOR NEXT CHARACTER
07DC 1270 :
64 A5 03 8A 07DC 1271 BICB #UCBSM_TIM!UCBSM_INT,UCBSW_STS(R5); CLEAR TIMEOUT AND EXPECTED
07E0 1272 :
07E0 1273 : CALL CLASS DRIVER FOR MORE OUTPUT
07E0 1274 :
01 FF 8F 010C D5 16 07E0 1275 JSB @UCBSL_TT_GETNXT(R5) : GET THE NEXT CHARACTER
010B C5 8F 07E4 1276 CASEB UCBSB_TT_OUTTYPE(R5),#-1,#1 : OPTIMIZE FOR THE SINGLE
07EB 1277 : CHARACTER CASE BY SETTING THE
07EB 1278 : LIMIT TO 1
0022' 07EB 1279 1$: .WORD DZ32_START_BURST-1$ : BURST SPECIFIED
000B' 07ED 1280 .WORD 50$-1$ : NONE
07EF 1281 :

```



```

07EF 1282 : OUTPUT A CHARACTER TO THE DZ-32
07EF 1283 :
06 A0 53 90 07EF 1284 20$: MOVB R3,6(R0) ; OUTPUT CHARACTER
FFAD 31 07F3 1285 BRW DZ32_OUT_LOOP
07F6 1286 :
07F6 1287 :
07F6 1288 : DISABLE OUTPUT ON THIS LINE
07F6 1289 :
07F6 1290 50$:
07F6 1291 BBS #UCBSV_INT,- ; IF INT EXP, THEN DON'T RESET,
A8 64 01 E0 07F8 1292 UCBSW_STS(R5),DZ32_OUT_LOOP
A5 07FB 1293 ; COULD HAVE BEEN SET DURING CALLBACK
07FB 1294
54 00 BE D0 07FB 1295 MOVL @(SP),R4 ; GET IDB ADDRESS
0106 C5 8A 07FF 1296 BICB UCBSW_TT_UNITBIT(R5),- ; RESET THE OUTPUT ENABLE
0E A4 0803 1297 IDBSB_TT_ENABLE(R4)
07 A0 0E A4 90 0805 1298 MOVB IDBSB_TT_ENABLE(R4),7(R0)
FF96 31 080A 1299 BRW DZ32_OUT_LOOP
080D 1300
080D 1301
080D 1302 DZ32_START BURST:
080D 1303 BISW #TTYSM_TANK_BURST,- ; SIGNAL BURST ACTIVE
0108 C5 A8 0811 1304 UCBSW_TT_HOLD(R5)
0814 1305 DZ32_BURST:
0814 1306 MOVB @UCBSL_TT_OUTADR(R5),- ; OUTPUT NEXT BYTE
06 A0 0818 1307 6(R0)
011C C5 D6 081A 1308 INCL UCBSL_TT_OUTADR(R5) ; UPDATE POINTER
0120 C5 B7 081E 1309 DECB UCBSW_TT_OUTLEN(R5) ; UPDATE COUNT
07 12 0822 1310 BNEQ 60$ ; NOT LAST CHARACTER
0800 8F AA 0824 1311 BICW #TTYSM_TANK_BURST,- ; RESET BURST ACTIVE
0108 C5 0828 1312 UCBSW_TT_HOLD(R5)
FF75 31 082B 1313 60$: BRW DZ32_OUT_LOOP
082E 1314 :
082E 1315 : OUTPUT SINGLE CHARACTER
082E 1316 :
082E 1317 DZ32_CHAR:
06 A0 0108 C5 90 082E 1318 MOVB UCBSW_TT_HOLD(R5),6(R0) ; OUTPUT CHAR IN TANK
0400 8F AA 0834 1319 BICW #TTYSM_TANK_HOLD,- ; SHOW TANK EMPTY
0108 C5 0838 1320 UCBSW_TT_HOLD(R5)
FF65 31 083B 1321 BRW DZ32_OUT_LOOP
083E 1322 :
083E 1323 : STOP OUTPUT
083E 1324 :
083E 1325 DZ32_STOP:
03 8A 083E 1326 BICB #UCBSM_INT!UCBSM_TIM,-
64 A5 0840 1327 UCBSW_STS(R5) ; RESET OUTPUT ACTIVE
54 00 BE D0 0842 1328 MOVL @(SP),R4 ; GET IDB ADDRESS
0106 C5 8A 0846 1329 BICB UCBSW_TT_UNITBIT(R5),- ; RESET THE OUTPUT ENABLE
0E A4 084A 1330 IDBSB_TT_ENABLE(R4)
07 A0 0E A4 90 084C 1331 MOVB IDBSB_TT_ENABLE(R4),7(R0)
FF4F 31 0851 1332 BRW DZ32_OUT_LOOP
0854 1333
0854 1334 .ENABLE LSB
0854 1335 :
0854 1336 : SEND XON OR XOFF
0854 1337 :
0854 1338 DZ32_PREMPT:

```

```
06 A0 0100 8F AA 0854 1339 BICW #TTYSM TANK PREMPT,- ; RESET XOFF STATE
0108 C5 0858 1340 UCBSW TT_HO[D(R5)
010A C5 90 085B 1341 MOV B UCBSB-TT-PREMPT(R5),6(R0); OUTPUT CHARACTER
FF3F 31 0861 1342 BRW DZ32_OUT_LOOP
0864 1343
0864 1344
0864 1345
0864 1346 .ENDC .DISABLE LSB
```

```

0864 1348 .SBTTL SET SPEED, PARITY PARAMETERS
0864 1349
0864 1350 :++
0864 1351 : DZ$SET_LINE - RESET SPEED, PARITY
0864 1352 :
0864 1353 : FUNCTIONAL DESCRIPTION:
0864 1354 :
0864 1355 : INPUTS:
0864 1356 :
0864 1357 : R5 - UCB ADDRESS
0864 1358 :
0864 1359 : OUTPUTS:
0864 1360 :
0864 1361 : R4 USED
0864 1362 :--
0864 1363
0864 1364 DZ$SET_LINE:
01 AE 54 24 A5 D0 0864 1365 MOVL UCB$$_CRB(R5),R4 ; ADDRESS CRB
0868 1366 :
0868 1367 : SET UP LINE SPEED AND PARITY
0868 1368 :
01 AE 54 2C B4 D0 0868 1369 MOVL @CRB$_INTD+VEC$_IDB(R4),R4 ; GET THE CSR ADDRESS VIA CRB
086C 1370 CLRL -(SP) ; RESET A TEMPORARY LOCATION
00F4 C5 01 D4 086C 1370 SUBB3 #1,UCB$_TT_SPEED(R5),1(SP) ; ADJUST DATA BASE SPEED
6E 00F8 C5 90 0875 1371 MOVB UCB$_TT_PARITY(R5),(SP) ; SET PARITY, STOP, CHARACTER SIZE
6E F007 8F AA 087A 1373 BICW #^XF007,(SP) ; CLEAR SPECIAL FIELDS
07 E0 087F 1374 BBS #UCB$_TT_DSBL,- ; SKIP CLOCK ENABLE IF LINE DISABLED
05 012A C5 0881 1375 UCB$_TT_MAINT(R5),3$
6E 1000 8F AB 0885 1376 BISW #<DZLPR$_CLOCK>,(SP)
088A 1377 3$:
6E 54 A5 AB 088A 1378 BISW UCB$_UNIT(R5),(SP) ; SET LINE NUMBER
64 01 B3 088E 1379 BITW #DZCSR$_MODE,(R4) ; DZ32 CONTROLLER?
05 12 0891 1380 BNEQ 10$ ; YES
0893 1381 5$:
02 A4 8E F7 0893 1382 CVTLW (SP)+,2(R4) ; INSERT AS LINE PARAMETER
05 0897 1383 RSB
0898 1384
0898 1385 : HANDLE DZ-32 SPECIFIC FUNCTIONS
0898 1386 10$:
00F4 C5 91 0898 1387 CMPB UCB$_TT_SPEED(R5),- ; TRANSMIT/RECEIVE THE SAME
00F5 C5 089C 1388 UCB$_TT_SPEED+1(R5)
089F 1389 BEQL 5$ ; YES, NO SPLIT SPEED
00F5 C5 95 08A1 1390 TSTB UCB$_TT_SPEED+1(R5) ; RECEIVE SPEED SPECIFIED?
EC 13 08A5 1391 BEQL 5$ ; NO, NO SPLIT SPEED
08A7 1392
08A7 1393 : SET SPLIT SPEED
08A7 1394
6E 2000 8F AB 08A7 1395 BISW #DZLPR$_SPLIT,(SP) ; SET SPLIT SPEED BIT
E5 11 08AC 1396 BRB 5$ ; COMPLETE SETUP
08AE 1397

```

```

08AE 1399
08AE 1400      .SBTTL INITIALIZE DZ-11 MODEM POLLING
08AE 1401
08AE 1402 :++
08AE 1403 : DZ$SET_MODEM - INIT MODEM POLLING
08AE 1404 :
08AE 1405 : FUNCTIONAL DESCRIPTION:
08AE 1406 :
08AE 1407 : INIT DZ-11 MODEM TRANSITION POLLING IF NOT ALREADY ACTIVE. LINK CRB
08AE 1408 : FOR CURRENT LINE INTO MODEM TRANSITION POLLING LIST
08AE 1409 :
08AE 1410 : INPUTS:
08AE 1411 :
08AE 1412 :      R5 - UCB ADDRESS
08AE 1413 :
08AE 1414 : OUTPUTS:
08AE 1415 :
08AE 1416 :      R0-R4 USED
08AE 1417 :--
08AE 1418
08AE 1419 DZ11$SET MODEM:
54 24 A5 D0 08AE 1420      MOVL      UCBS$L_CRB(R5),R4      : ADDRESS CRB
00000000'EF D5 08B2 1421      TSTL      DZ$L_DIALUP      : DZ-11 POLLING ALREADY ACTIVE?
18 12 08B8 1422      BNEQ      5$      : YES, SKIP STARTUP
38 BB 08BA 1423      PUSHR     #*M<R3,R4,R5>
55 00000004'EF DE 08BC 1424      MOVAL     DZ$TIMQUENT,R5      : ADDRESS OF TIMER ENTRY
0B A5 06 90 08C3 1425      MOV      #IPL$_QUEUEAST,TQESB_RQTYPE(R5) ; SET FORK IPL
000008D0'EF 9F 08C7 1426      PUSHAB   4$      : RETURN ADDRESS
0021 31 08CD 1427      BRW      30$      : QUEUE FORK
38 BA 08D0 1428 4$:      POPR      #*M<R3,R4,R5>
53 18 A4 DE 08D2 1429 5$:
51 00000000'EF DE 08D2 1430      MOVAL     CRB$L_DZ_MODEM(R4),R3 : ADDRESS OF DZ CRB THREAD
52 51 D0 08D6 1431      MOVAL     DZ$L_DIALUP,R1      : ADDRESS OF DZ TIMER LIST HEAD
08DD 1432      MOVL      R1,R2
08E0 1433 :
08E0 1434 : LINK CRB INTO DZ-11 MODEM POLLER LIST IF NEEDED
08E0 1435 :
08E0 1436 10$:
53 62 D1 08E0 1437      CMPL     (R2),R3      : IS CRB ON LIST
0B 13 08E3 1438      BEQL     20$      : YES, DONE
52 62 D0 08E5 1439      MOVL     (R2),R2      : POINT TO NEXT CRB
F6 12 08E8 1440      BNEQ     10$      : LOOK FOR NEXT
63 61 D0 08EA 1441      MOVL     (R1),(R3)    : LINK CRB AT LIST HEAD
61 53 D0 08ED 1442      MOVL     R3,(R1)
08F0 1443 20$:
05 08F0 1444      RSB
08F1 1445 30$:
00000000'GF 16 08F1 1446      JSB      G^EXES$FORK      : FORK TO QUEUE TIMER ENTRY
08F7 1447      DSBINT   #IPL$ SYNCH
20 A5 FA45 CF 9E 08FD 1448      MOVAB   W^DZ$TIMER,TQESL_FPC(R5) : ADDRESS OF TIMER SERVICE ROUTINE
00000000'GF D0 0903 14 9      MOVL     G^TTYS$GL_DELTA,TQESQ_DELTA(R5)
090B 14 : INTERVAL IS SYSGEN PARAMETER
0B A5 05 90 090B 1451      MOV      #TQESC_SSREPT,TQESB_RQTYPE(R5)
50 00000000'GF 7D 090F 1452      MOVQ     G^EXES$GQ_SYSTIME,R0
50 00000000'GF C0 0916 1453      ADDL     G^TTYS$GL_DELTA,R0
51 00 08 091D 1454      ADWC     #0,R1
000J0000'GF 16 0920 1455      JSB      G^EXES$INSTIMQ      : INSERT INTO TIMER QUEUE

```

DZDRIVER  
V04-000

- Port Driver for DZ-11 support  
INITIALIZE DZ-11 MODEM POLLING

L 14

16-SEP-1984 02:24:50 VAX/VMS Macro V04-00  
5-SEP-1984 04:15:55 [TTDRVR.SRC]DZDRIVER.MAR;1

Page 34  
(1)

05 0926 1456 ENBINT  
0929 1457 RSB  
092A 1458

; RESTORE IPL

DZ  
V04

```
092A 1460
00000000 1461 .PSECT $$$117_DATA,QUAD
0000 1462 :
0000 1463 : DZ-11 TIMER DATA STRUCTURES FOR DETECTION OF DZ-11 MODEM TRANSITIONS
0000 1464 :
0000 1465 :
0000 1466 DZSL_DIALUP:
00000000 0000 1467 .LONG 0 ; LINKED LIST OF DZ-11 CRB'S
0004 1468 ; USING MODEM CONTROL
0004 1469 DZ$TIMQUENT: ; TIMER QUE ENTRY USED TO
0C04 1470 ; SAMPLE DZ-11 MODEM SIGNALS
0004 1471 ; ON PERIODIC BASIS
0004 1472
00000038 0008 1473 .ALIGN QUAD
0038 1474 .BLKB TQESC_LENGTH
0038 1475 STO_TQE TQESW_SIZE,WORD,TQESC_LENGTH,DZ$TIMQUENT
0038 1476 STO_TQE TQESB_TYPE,BYTE,DYN$C_TQE,DZ$TIMQUENT
0038 1477 STO_TQE TQESB_RQTYPE,BYTE,TQESC_SSREPT,DZ$TIMQUENT
0038 1478
0038 1479 DZ$SEND: ; End of driver
0038 1480
0038 1481 .END
```

DZDRIVER  
Symbol table

- Port Driver for DZ-11 support N 14

16-SEP-1984 02:24:50 VAX/VMS Macro V04-00  
5-SEP-1984 04:15:55 [TTDRVR.SRC]DZDRIVER.MAR;1

Page 36  
(1)

DZV  
V04

\$\$\$	= 00000020	R	02	DZ11\$DS_SET	000002B5	R	03
\$\$\$\$\$	= 00000038	R	04	DZ11\$INTINP	000003E9	RG	03
\$\$OP	= 00000002			DZ11\$INTOUT	000006E9	RG	03
ATS_UBA	= 00000001			DZ11\$MAINT	0000028C	R	03
BIT...	= 00000010			DZ11\$RESUME	000005E6	R	03
CLASS_DDT	= 00000010			DZ11\$SET MODEM	000008AE	R	03
CLASS_DS_TRAN	= 0000000C			DZ11\$STARTIO	00000546	RG	03
CLASS_GETNXT	= 00000000			DZ11\$VEC	00000038	R	03
CLASS_POWERFAIL	= 00000020			DZ11\$VECEND	00000070	R	03
CLASS_PUTNXT	= 00000004			DZ11\$XOFF	0000059A	R	03
CLASS_READERROR	= 00000014			DZ11\$XON	0000059A	R	03
CLASS_SETUP_UCB	= 00000008			DZ11_BURST	0000074F	R	03
CRBSB_DZ_CARRIER	= 0000001D			DZ11_CHAR	00000769	R	03
CRBSB_DZ_DTR	= 0000001E			DZ11_OUT_EXIT	000006DC	R	03
CRBSB_DZ_RING	= 0000001C			DZ11_OUT_LOOP	000006E9	R	03
CRBSB_TT_TYPE	= 0000000B			DZ11_PREMPT	00000786	R	03
CRBSL_DZ_MODEM	= 00000018			DZ11_START_BURST	00000748	R	03
CRBSL_INTD	= 00000024			DZ11_STOP	00000779	R	03
CRBSL_INTD2	= 00000048			DZ32\$DS_SET	000002ED	R	03
DCS_TERM	= 00000042			DZ32\$INTINP	00000477	RG	03
DDBSL_DDT	= 0000000C			DZ32\$INTOUT	000007A3	RG	03
DEVSM_AVL	= 00040000			DZ32\$MAINT	0000025C	R	03
DEVSM_CCL	= 00000002			DZ32\$RESUME	00000676	R	03
DEVSM_IDV	= 04000000			DZ32\$STARTIO	0000056C	RG	03
DEVSM_NNM	= 00000200			DZ32\$VEC	00000070	R	03
DEVSM_ODV	= 08000000			DZ32\$VECEND	000000A8	R	03
DEVSM_REC	= 00000001			DZ32\$XOFF	00000645	R	03
DEVSM_TRM	= 00000004			DZ32\$XON	00000645	R	03
DPTSC_LENGTH	= 00000038			DZ32_BURST	00000814	R	03
DPTSC_VERSION	= 00000004			DZ32_CHAR	0000082E	R	03
DPTSINITAB	= 00000038	R	02	DZ32_OUT_EXIT	00000796	R	03
DPTSM_NOUNLOAD	= 00000004			DZ32_OUT_LOOP	000007A3	R	03
DPTSREINITAB	= 000000D3	R	02	DZ32_PREMPT	00000854	R	03
DPTSTAB	= 00000000	R	02	DZ32_START_BURST	0000080D	R	03
DPTSW_VECTOR	= 0000001E			DZ32_STOP	0000083E	R	03
DTS_DZ11	= 00000042			DZCSRSM_CLEAR	= 00000010		
DTS_DZ32	= 00000043			DZCSRSM_DS_CHG	= 00000800		
DYN\$C_CRB	= 00000005			DZCSRSM_DS_ENAB	= 00000002		
DYN\$C_DDB	= 00000006			DZCSRSM_LINE	= 00000700		
DYN\$C_DPT	= 0000001E			DZCSRSM_MAINT	= 00000008		
DYN\$C_ORB	= 00000049			DZCSRSM_MASTENAB	= 00000020		
DYN\$C_TQE	= 0000000F			DZCSRSM_MODE	= 00000001		
DYN\$C_UCB	= 00000010			DZCSRSM_RCVINT	= 00000040		
DZ\$ABORT	= 000005CC	R	03	DZCSRSM_RCVRDY	= 00000080		
DZ\$CTRL_ERROR	= 0000014A	R	03	DZCSRSM_SNDINT	= 00004000		
DZ\$DDT	= 00000000	RG	03	DZCSRSM_SNDRDY	= 00008000		
DZ\$DPT	= 00000000	RG	02	DZCSRSS_CLEAR	= 00000001		
DZ\$END	= 00000038	R	04	DZCSRSS_DS_CHG	= 00000001		
DZ\$INITIAL	= 000000AD	RG	03	DZCSRSS_DS_ENAB	= 00000001		
DZ\$INITLINE	= 0000014B	RG	03	DZCSRSS_LINE	= 00000003		
DZ\$L_DIALUP	= 00000000	R	04	DZCSRSS_MAINT	= 00000001		
DZ\$NOLL	= 000000AC	R	03	DZCSRSS_MASTENAB	= 00000001		
DZ\$SET LINE	= 00000864	R	03	DZCSRSS_MODE	= 00000001		
DZ\$STOP	= 000005C4	R	03	DZCSRSS_RCVINT	= 00000001		
DZ\$TIMER	= 00000346	R	03	DZCSRSS_RCVRDY	= 00000001		
DZ\$TIMQUENT	= 00000004	R	04	DZCSRSS_SNDINT	= 00000001		
DZ\$UNIT_ERROR	= 00000257	R	03	DZCSRSS_SNDRDY	= 00000001		

DZDRIVER  
Symbol table

- Port Driver for DZ-11 support

B 15

16-SEP-1984 02:24:50 VAX/VMS Macro V04-00  
5-SEP-1984 04:15:55 [TTDRVR.SRC]DZDRIVER.MAR;1

Page 37  
(1)

DZV  
V04

DZCSR\$V_CLEAR	= 00000004	EXE\$GL_ABSTIM	*****	X	03
DZCSR\$V_DS_CHG	= 0000000B	EXE\$GL_TENUSEC	*****	X	03
DZCSR\$V_DS_ENAB	= 00000001	EXE\$GL_UBDELAY	*****	X	03
DZCSR\$V_LINE	= 00000008	EXE\$GQ_SYSTIME	*****	X	03
DZCSR\$V_MAINT	= 00000003	EXE\$INSTIMQ	*****	X	03
DZCSR\$V_MASTENAB	= 00000005	FUNCTAB_LEN	= 00000000		
DZCSR\$V_MODE	= 00000000	IDB\$B_TT_ENABLE	= 0000000E		
DZCSR\$V_RCVINT	= 00000006	IDB\$L_UCBLST	= 00000018		
DZCSR\$V_RCVRDY	= 00000007	IOSM_LINE_OFF	= 00000200		
DZCSR\$V_SNDINT	= 0000000E	IOSM_LINE_ON	= 00000800		
DZCSR\$V_SNDRDY	= 0000000F	IOSM_LOOP	= 00000080		
DZLCS1\$M_ACK	= 00008000	IOSM_LOOP_EXT	= 00001000		
DZLCS1\$S_ACK	= 00000001	IOSM_UNLOOP	= 00000100		
DZLCS1\$V_ACK	= 0000000F	IOC\$MNTVER	*****	X	03
DZLPR\$M_CLOCK	= 00001000	IOC\$RETURN	*****	X	03
DZLPR\$M_LINE	= 00000007	IPL\$_QUEUEAST	= 00000006		
DZLPR\$M_ODD	= 00000080	IPL\$_SYNCH	= 00000008		
DZLPR\$M_PARITY	= 00000040	MODEM\$C_DATASET	= 00000003		
DZLPR\$M_SIZE	= 00000018	MODEM\$C_INIT	= 00000000		
DZLPR\$M_SPEED	= 00000F00	ORB\$B_FLAGS	= 0000000B		
DZLPR\$M_SPLIT	= 00002000	ORB\$L_OWNER	= 00000000		
DZLPR\$M_STOP	= 00000020	ORB\$M_PROT_16	= 00000001		
DZLPR\$S_CLOCK	= 00000001	ORB\$W_PROT	= 00000018		
DZLPR\$S_LINE	= 00000003	PORT_ABORT	= 00000020		
DZLPR\$S_ODD	= 00000001	PORT_DS_SET	= 0000000C		
DZLPR\$S_PARITY	= 00000001	PORT_LENGTH	= 00000038		
DZLPR\$S_SIZE	= 00000002	PORT_MAINT	= 00000030		
DZLPR\$S_SPEED	= 00000004	PORT_RESUME	= 00000024		
DZLPR\$S_SPLIT	= 00000001	PORT_SET_LINE	= 00000008		
DZLPR\$S_STOP	= 00000001	PORT_SET_MODEM	= 00000028		
DZLPR\$V_CLOCK	= 0000000C	PORT_STARTIO	= 00000000		
DZLPR\$V_LINE	= 00000000	PORT_STOP	= 00000018		
DZLPR\$V_ODD	= 00000007	PORT_VECTOR	= 00000038	R	03
DZLPR\$V_PARITY	= 00000006	PORT_XOFF	= 00000014		
DZLPR\$V_SIZE	= 00000003	PORT_XON	= 00000010		
DZLPR\$V_SPEED	= 00000008	PR\$_IPL	= 00000012		
DZLPR\$V_SPLIT	= 0000000D	SIZ...	= 00000001		
DZLPR\$V_STOP	= 00000005	SS\$ NORMAL	= 00000001		
DZRCV\$M_BUF	= 000000FF	TQE\$B_RQTYPE	= 0000000B		
DZRCV\$M_FRAMER	= 00002000	TQE\$B_TYPE	= 0000000A		
DZRCV\$M_LINE	= 00000700	TQE\$C_LENGTH	= 00000030		
DZRCV\$M_OVERRUN	= 00004000	TQE\$C_SSREPT	= 00000005		
DZRCV\$M_PARERR	= 00001000	TQE\$L_FPC	= 0000000C		
DZRCV\$M_VALID	= 00008000	TQE\$Q_DELTA	= 00000020		
DZRCV\$S_BUF	= 00000008	TQE\$W_SIZE	= 00000008		
DZRCV\$S_FRAMER	= 00000001	TT\$M_DS_CTS	= 00000010		
DZRCV\$S_LINE	= 00000003	TT\$M_DS_DSR	= 00000080		
DZRCV\$S_OVERRUN	= 00000001	TT\$V_DS_CARRIER	= 00000005		
DZRCV\$S_PARERR	= 00000001	TT\$V_DS_DTR	= 00000001		
DZRCV\$S_VALID	= 00000001	TT\$V_DS_RING	= 00000006		
DZRCV\$V_BUF	= 00000000	TT\$V_MODEM	= 00000015		
DZRCV\$V_FRAMER	= 0000000D	TT\$_ONKNJWN	= 00000000		
DZRCV\$V_LINE	= 00000008	TTY\$GB_DEFSPEED	*****	X	02
DZRCV\$V_OVERRUN	= 0000000E	TTY\$GB_PARITY	*****	X	02
DZRCV\$V_PARERR	= 0000000C	TTY\$GB_RSPEED	*****	X	02
DZRCV\$V_VALID	= 0000000F	TTY\$GL_DEFCHAR	*****	X	02
EXE\$FORK	*****	TTY\$GL_DEFCHAR2	*****	X	02
	X 03				



DZDRIVER  
Symbol table

- Port Driver for DZ-11 support

C 15

16-SEP-1984 02:24:50 VAX/VMS Macro V04-00  
5-SEP-1984 04:15:55 [TTDRVR.SRC]DZDRIVER.MAR;1

Page 38  
(1)

DZV  
V04

TTY\$GL_DELTA	*****	X	03	UCBSW_TT_UNITBIT	= 00000106
TTY\$GL_DPT	*****	X	03	UCBSW_UNIT	= 00000054
TTY\$GL_OWNUIC	*****	X	02	VECSL_IDB	= 00000008
TTY\$GW_DEFBUF	*****	X	02	VECSL_INITIAL	= 0000000C
TTY\$GW_PROT	*****	X	02	VECSL_UNITINIT	= 00000018
TTY\$M_TANK_BURST	= 00000800				
TTY\$M_TANK_HOLD	= 00000400				
TTY\$M_TANK_PREMPT	= 00000100				
TTY\$M_TANK_STOP	= 00000200				
TTY\$V_PC_NOTIME	= 00000000				
TTY\$V_TANK_BURST	= 0000000B				
UCBSB_DEVCLASS	= 00000040				
UCBSB_DEVTTYPE	= 00000041				
UCBSB_DIPL	= 0000005E				
UCBSB_FIPL	= 0000000B				
UCBSB_TT_DEPARI	= 000000EC				
UCBSB_TT_DETYPE	= 000000F0				
UCBSB_TT_DS_RCV	= 00000124				
UCBSB_TT_DS_TX	= 00000125				
UCBSB_TT_MAINT	= 0000012A				
UCBSB_TT_OUTYPE	= 0000010B				
UCBSB_TT_PARITY	= 000000F8				
UCBSB_TT_PREMPT	= 0000010A				
UCBSC_TT_LENGTH	= 00000134				
UCBSL_CRB	= 00000024				
UCBSL_DDB	= 00000028				
UCBSL_DDT	= 00000088				
UCBSL_DEVCHAR	= 00000038				
UCBSL_DEVCHAR2	= 0000003C				
UCBSL_DEVDEPEND	= 00000044				
UCBSL_DEVDEPN2	= 00000048				
UCBSL_DUETIM	= 0000006C				
UCBSL_TT_CLASS	= 00000114				
UCBSL_TT_DECHA1	= 000000C8				
UCBSL_TT_DECHAR	= 000000C4				
UCBSL_TT_GETNXT	= 0000010C				
UCBSL_TT_OUTADR	= 0000011C				
UCBSL_TT_PORT	= 00000118				
UCBSL_TT_PUTNXT	= 00000110				
UCBSL_TT_RTIMOU	= 000000B4				
UCBSL_TT_WBLINK	= 000000D0				
UCBSL_TT_WFLINK	= 000000CC				
UCBSM_INT	= 00000002				
UCBSM_ONLINE	= 00000010				
UCBSM_TIM	= 00000001				
UCBSM_TT_DSBL	= 00000080				
UCBSV_INT	= 00000001				
UCBSV_POWER	= 00000005				
UCBSV_TT_DSBL	= 00000007				
UCBSW_DEVBUFSIZ	= 00000042				
UCBSW_STS	= 00000064				
UCBSW_TT_DESIZE	= 000000F1				
UCBSW_TT_DESPEE	= 000000E8				
UCBSW_TT_HOLD	= 00000108				
UCBSW_TT_OUTLEN	= 00000120				
UCBSW_TT_PRTCTL	= 00000122				
UCBSW_TT_SPEED	= 000000F4				

-----  
! Psect synopsis !  
-----

PSECT name	Allocation	PSECT No.	Attributes
. ABS	00000000 ( 0.)	00 ( 0.)	NOPIC USR CON ABS LCL NOSHR NOEXE NORD NOWRT NOVEC BYTE
\$ABSS	00000000 ( 0.)	01 ( 1.)	NOPIC USR CON ABS LCL NOSHR EXE RD WRT NOVEC BYTE
\$\$\$105_PROLOGUE	000000DE ( 222.)	02 ( 2.)	NOPIC USR CON REL LCL NOSHR EXE RD WRT NOVEC BYTE
\$\$\$115_DRIVER	0000092A ( 2346.)	03 ( 3.)	NOPIC USR CON REL LCL NOSHR EXE RD WRT NOVEC LONG
\$\$\$117_DATA	00000038 ( 56.)	04 ( 4.)	NOPIC USR CON REL LCL NOSHR EXE RD WRT NOVEC QUAD

-----  
! Performance indicators !  
-----

Phase	Page faults	CPU Time	Elapsed Time
Initialization	30	00:00:00.07	00:00:00.37
Command processing	128	00:00:00.36	00:00:01.19
Pass 1	719	00:00:23.05	00:00:48.04
Symbol table sort	0	00:00:03.36	00:00:06.16
Pass 2	253	00:00:04.73	00:00:09.11
Symbol table output	35	00:00:00.20	00:00:00.26
Psect synopsis output	2	00:00:00.02	00:00:00.02
Cross-reference output	0	00:00:00.00	00:00:00.00
Assembler run totals	1169	00:00:31.80	00:01:05.15

The working set limit was 2250 pages.  
187090 bytes (366 pages) of virtual memory were used to buffer the intermediate code.  
There were 170 pages of symbol table space allocated to hold 3041 non-local and 103 local symbols.  
1481 source lines were read in Pass 1, producing 25 object records in Pass 2.  
72 pages of virtual memory were used to define 67 macros.

-----  
! Macro library statistics !  
-----

Macro library name	Macros defined
_\$255\$DUA28:[SYS.OBJ]LIB.MLB;1	33
-\$255\$DUA28:[SYSLIB]STARLET.MLB;2	12
TOTALS (all libraries)	45

3540 GETS were required to define 45 macros.

There were no errors, warnings or information messages.

MACRO/LIS=LIS\$:DZDRIVER/OBJ=OBJ\$:DZDRIVER MSRC\$:DZDRIVER/UPDATE=(ENH\$:DZDRIVER)+EXECMLS/LIB

