



```

UU      UU  TTTTTTTTTT  LL      DDDDDDDD  EEEEEEEEEEE  FFFFFFFFFF  MM      MM
UU      UU  TTTTTTTTTT  LL      DDDDDDDD  EEEEEEEEEEE  FFFFFFFFFF  MM      MM
UU      UU      TT      LL      DD      DD  EE      FF      MMMM  MMMM
UU      UU      TT      LL      DD      DD  EE      FF      MMMM  MMMM
UU      UU      TT      LL      DD      DD  EE      FF      MM  MM  MM
UU      UU      TT      LL      DD      DD  EE      FF      MM  MM  MM
UU      UU      TT      LL      DD      DD  EE      FF      MM  MM  MM
UU      UU      TT      LL      DD      DD  EE      FF      MM  MM  MM
UU      UU      TT      LL      DD      DD  EE      FF      MM  MM  MM
UU      UU      TT      LL      DD      DD  EE      FF      MM  MM  MM
UU      UU      TT      LL      DD      DD  EE      FF      MM  MM  MM
UUUUUUUUUU  TT      LLLLLLLLLL  DDDDDDDD  EEEEEEEEEEE  FFFFFFFFFF  MM  MM  MM
UUUUUUUUUU  TT      LLLLLLLLLL  DDDDDDDD  EEEEEEEEEEE  FFFFFFFFFF  MM  MM  MM

```

```

MM      MM  AAAAAA  RRRRRRRR
MM      MM  AAAAAA  RRRRRRRR
MMMM  MMMM  AA      AA  RR      RR
MMMM  MMMM  AA      AA  RR      RR
MM  MM  MM  AA      AA  RR      RR
MM  MM  MM  AA      AA  RR      RR
MM      MM  AA      AA  RRRRRRRR
MM      MM  AA      AA  RRRRRRRR
MM      MM  AAAAAAAAAA  RR  RR
MM      MM  AAAAAAAAAA  RR  RR
MM      MM  AA      AA  RR      RR
MM      MM  AA      AA  RR      RR
MM      MM  AA      AA  RR      RR
MM      MM  AA      AA  RR      RR

```

.NLIST

Version: 'V04-000'

```

*****
*
* COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
* DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
* ALL RIGHTS RESERVED.
*
* THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
* ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
* INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
* COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
* OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
* TRANSFERRED.
*
* THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
* AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
* CORPORATION.
*
* DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
* SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.
*
*****

```

Modified by:

```

V03-002 LJK0174 Lawrence J. Kenah 2-Jul-1982
Add .ENABLE SUPPRESSION to $DEFINI and .DISABLE SUPPRESSION
to $DEFEND when the GLOBAL parameter is not supplied.

V03-001 LJK0171 Lawrence J. Kenah 18-Jun-1982
Add .NOCROSS to $DEFINI and .CROSS to $DEFEND

V02-003 BLS0130 Benn Schreiber 4-Jan-1982
Add $SHR_MSGDEF macro

V02.02 HJ0002 Herb Jacobs 14-Aug-1980
New versions of $DEF, $EQU, $EQUYST, $VIELD for improved
performance at assembly time.

V01.01 RN0001 R. Newland 9-Jul-1979
Save local symbol block when saving psect information
in $DEFINI and $OFFSET. SPR #11-24166

```

```

+
$DEF - DEFINE A SYMBOL
SYM = SYMBOL NAME TO BE DEFINED
ALLOC = ASSEMBLER ALLOCATION DIRECTIVE, .BLKL, .BLKB, ETC
SIZ = AMOUNT OF STORAGE TO ALLOCATE IN UNITS SPECIFIED BY ALLOC
-

```

```

+
$EQU - EQUATE A SYMBOL
SYM = SYMBOL NAME TO DEFINE

```

:  
:-

VAL = VALUE TO ASSOCIATE WITH THE SYMBOL

```

: *
: $GBLINI - INITIALIZE THE GLOBAL/LOCAL DEFINITION SWITCH
: GBL = "GLOBAL", "LOCAL", OR NULL.
: IF THIS PARAMETER IS "GLOBAL"
: GLOBAL DEFINITIONS ARE GENERATED. OTHERWISE
: LOCAL DEFINITIONS ARE GENERATED.
:
: .MACRO $GBLINI GBL=LOCAL
: .IF IDN <GBL> <GLOBAL>
: .MACRO $DEF SYM,ALLOC,SIZ
: .IIF NB,SYM,SYM:
: .IIF NB,ALLOC, ALLOC SIZ
: .ENDM $DEF
: .MACRO $EQU SYM,VAL
SYM=VAL
: .ENDM $EQU
: .MACRO $VIELD1 MOD,SEP,SYM,SIZ,MSK
SIZ...=1
: .IIF NB,SIZ, SIZ...=SIZ
: .IF NB,SYM
MOD'SEP'V 'SYM=BIT...
: .IIF NB,SIZ, MOD'SEP'S 'SYM=SIZ
: .IIF NB,MSK, MOD'SEP'M_'SYM=<<<1@SIZ...>-1>@BIT...>
: .ENDC
BIT...=BIT...+SIZ...
: .ENDM $VIELD1
: .IFF
: .IIF DIF <GBL> <LOCAL>,.ERROR ;ARG MUST BE "GLOBAL","LOCAL",OR NULL;
: .MACRO $DEF SYM,ALLOC,SIZ
: .IIF NB,SYM,SYM:
: .IIF NB,ALLOC, ALLOC SIZ
: .ENDM $DEF
: .MACRO $EQU SYM,VAL
SYM=VAL
: .ENDM $EQU
: .MACRO $VIELD1 MOD,SEP,SYM,SIZ,MSK
SIZ...=1
: .IIF NB,SIZ, SIZ...=SIZ
: .IF NB,SYM
MOD'SEP'V 'SYM=BIT...
: .IIF NB,SIZ, MOD'SEP'S 'SYM=SIZ
: .IIF NB,MSK, MOD'SEP'M_'SYM=<<<1@SIZ...>-1>@BIT...>
: .ENDC
BIT...=BIT...+SIZ...
: .ENDM $VIELD1
: .ENDC
: .ENDM $GBLINI
:
: *
: $DEFINI - INITIALIZE FOR A STRUCTURE DEFINITION
: STRUC = STRUCTURE BEING DEFINED
: GBL = GLOBAL/LOCAL INDICATOR
: DOT = INITIAL ABSOLUTE LOCATION, DEFAULT = 0
:
: .MACRO $DEFINI STRUC,GBL,DOT=0
: .SAVE LOCAL_BLOCK
: .NOCROSS

```

```
.IIF DIF <GBL> <GLOBAL>,.ENABLE SUPPRESSION
.PSECT $ABS$,ABS
$GBLINI GBL
.=DOT
.ENDM $DEFINI
```

```
:-+
$DEFEND - END OF A STRUCTURE DEFINITION
STRUC = STRUCTURE NAME BEING DEFINED
GBL = GLOBAL/LOCAL INDICATOR
SUF = STRUCTURE NAME SUFFIX
:-
```

```
.MACRO $DEFEND STRUC,GBL,SUF=DEF
.MACRO $'STRUC'SUF A
.ENDM $'STRUC'SUF
.IIF DIF <GBL> <GLOBAL>,.DISABLE SUPPRESSION
.CROSS
.RESTORE
.ENDM $DEFEND
```

```

+
$VIELD1 - MACRO USED INTERNALLY BY $VIELD AND _VIELD
MOD = MODULE NAME
SEP = SEPARATOR CHARACTER BETWEEN MODULE NAME AND SYMBOL TYPE
SYM = SYMBOL NAME
SIZ = SIZE OF VIELD IN BITS
MSK = "MASK" IF MOD$M_SYM IS DESIRED
-
+
$VIELD - DEFINE A LIST OF VIELDS - GLOBAL FORMAT
MOD = MODULE NAME
INIBIT = INITIAL BIT NUMBER FOR THE VIELDS
LIST = < <SYM1,SIZ1>,<SYM2,SIZ2>, ... <SYMN,SIZN> >
      WHERE A DEGENERATE SYM,SIZ PAIR IS JUST "SYM"
-
.MACRO $VIELD MOD,INIBIT,LIST
.IIF NB,INIBIT, BIT...=INIBIT
.IRP L,<LIST>
$VIELD1 MOD,$,L
.ENDR
.ENDM $VIELD
```

```
:+
_VIELD - DEFINE A LIST OF VIELDS - LOCAL FORMAT
MOD = MODULE NAME
INIBIT = INITIAL BIT NUMBER FOR THE VIELDS
LIST = < <SYM1,SIZ1>,<SYM2,SIZ2>,...<SYMN,SIZN> >
      WHERE A DEGENERATE SYM,SIZ PAIR IS JUST "SYM"
:-

.MACRO VIELD MOD,INIBIT,LIST
.IIF NB,INIBIT, BIT...=INIBIT
.IRP L,<LIST>
$VIELD1 MOD,_,L
.ENDR
.ENDM _VIELD
```

+  
-  
+  
\$EQU1 - USED INTERNALLY BY \$EQU1

\$EQU1 - EQUATE A LIST OF SYMBOLS

PREFIX = PREFIX TO BE ATTACHED TO NAMES IN THE LIST  
 GBL = GLOBAL/LOCAL INDICATOR  
 INIT = INITIAL VALUE TO BE ASSIGNED TO 1ST SYMBOL  
 INCR = INCREMENT TO BE ADDED TO VALUE ASSIGNED TO SYMBOLS  
 LIST = LIST OF SYMBOLS TO BE ASSIGNED VALUES  
 ENTRIES ARE OF THE FORM  
 SYMBOL

OR

<SYMBOL,VALUE>

IF A SIMPLE LIST OF SYMBOLS IS SPECIFIED, THEY ARE ASSIGNED  
 VALUES STARTING WITH THE INIT VALUE, INCREMENTED BY THE  
 SPECIFIED INCR VALUE (DEFAULT = 1).

IF A LIST IS SPECIFIED WITH SYMBOL, VALUE PAIRS, THE  
 SPECIFIED SYMBOL IS EQUATED TO THE VALUE AND THE  
 INIT AND INCR PARAMETERS DO NOT APPLY.

```
.MACRO $EQU1 PREFIX,GBL,INIT,INCR=1,LIST
$GBLINI GBL
.MACRO $EQU1 SYM,VAL=BIT...
$EQU PREFIX''SYM,<VAL>
.IIF IDN <VAL> <BIT...> BIT...=BIT...+INCR
.ENDM $EQU1
.IIF NB,INIT, BIT...=INIT
.IRP L,<LIST>
$EQU1 L
.ENDR
.ENDM $EQU1
```

.....  
: ASSUME - ASSEMBLY TIME CONSISTENCY CHECK

ASSUME EXP1 RELATION EXP2

FORCES ASSEMBLY ERROR IF EXP1 DOES NOT HAVE THE SPECIFIED  
: NUMERICAL RELATION TO EXP2.  
.....

```
.MACRO ASSUME EXP1,RELATION,EXP2  
.IF    RELATION <<EXP1>-<EXP2>>  
.IFF  
.ERROR ; ***** EXP1 MUST BE RELATION EXP2 ;  
.ENDC  
.ENDM ASSUME
```

++  
 MACRO TO GENERATE A OFFSET LIST FOR A DATA STRUCTURE

IT IS USEFUL FOR INPUT ARGUMENT LISTS POSITIVELY INDEXED FROM AP, AND  
 WORK AREAS ALLOCATED IN CALL STACK AND NEGATIVELY INDEXED FROM FP.

CALL: \$OFFSET INITIAL,DIRECTION,<<LAB1,[SIZE]>>,...,<LABN,[SIZE]>>

WHERE: INITIAL IS A REQUIRED VALUE FOR THE INTIAL INDEX WHEN  
 ORIGINATING A DATA STRUCTURE DEFINITION. IT IS NORMALLY  
 (+) 4 FOR ARGUMENT LISTS AND 0 FOR WORK AREAS.

DIRECTION IS A KEYWORD THAT MUST BE:  
 POSITIVE - FOR STRUCTURES GROWING UP IN MEMORY  
 NEGATIVE - FOR STRUCTURES GROWING DOWN IN MEMORY  
 OR BLANK, IN WHICH CASE "POSITIVE" IS ASSUMED.

THE LABEL, SIZE LIST IS THE SYMBOLIC NAME FOR THE LOCATION  
 AND THE OPTIONAL SIZE OF THE ELEMENT. IF BLANK, SIZE IS  
 ASSUMED TO BE 4 ( ONE LONGWORD ).

TO PERMIT THE DEFINITION OF AN INDEFINITLY LARGE NUMBER OF LABELS,  
 THE MACRO MAY BE CONTINUED. IN THIS CASE THE "INITIAL" AND  
 "DIRECTION" ARGUMENTS MUST BE BLANK.

```

--
.MACRO $OFFSET INITVALUE,DIRECTION,SYMLST
.SAVE LOCAL BLOCK
.PSECT $ABSS ABS
.IF B,INITVALUE
.=SAVABS...
.IF NB,DIRECTION
.ERROR ; DIRECTION MUST BE BLANK WHEN CONTINUING;
.MEXIT
.ENDC
.IFF
DIR...=1
.=INITVALUE
.IF NB,DIRECTION
.IF IDN <DIRECTION>,<POSITIVE>
.IFF
.IF IDN <DIRECTION>,<NEGATIVE>
DIR...=-1
.IFF
.ERROR ; "DIRECTION" MUST BE "POSITIVE","NEGATIVE", OR BLANK;
.ENDC
.ENDC
.ENDC
.ENDC
.IRP SYM,<SYMLST>
$OFFST1 SYM
.ENDR
SAVABS...=.
.RESTORE
.ENDM $OFFSET

.MACRO $OFFST1 SYM,SIZ=4

```

```

      .IF      LT,SIZ
      .ERROR
      .ENDC
      .IF      LT,DIR...
      .BLKB   -SIZ
      .ENDC
      .IF NB,SYM
      .LIST   MEB
SYM:
      .NLIST  MEB
      .ENDC
      .IF      GT,DIR...
      .BLKB   SIZ
      .ENDC
      .ENDM  $OFFST1

```

: The \$SHR\_MSGDEF macro defines facility-specific message codes which are based on the system-wide shared message codes.

```
$SHR_MSGDEF name, code, scope, <<msg,severity>>, ... >
```

where:

```

name   is the name of the facility (e.g., COPY)
code   is the corresponding facility code (e.g., 103)
scope  is GLOBAL to define globally, else defined locally
msg    is the name of the shared message (e.g., COPIEDB)
severity is the desired message severity (e.g., 1, 0, 2, 4)

```

Symbols of the form 'name'\$\_'msg' (e.g. COPY\$\_COPIEDB) are defined

```

.MACRO $SHR_MSGDEF NAME, CODE, SCOPE, MSGCODES
  .IF      NDF, SHR$_SHRDEF          ; issue $SHRDEF if not done yet
  SHR$_SHRDEF = 1                   ; define symbol to indic $SHRDEF done
  $SHRDEF                                     ; define shared message codes
  .ENDC
  $$GBL = 0
  .IIF    IDN, SCOPE, GLOBAL, $$GBL = 1
  .IRP   MSGPAIR, <'MSGCODES'>
  $SHR_MSGCOD 'NAME', 'CODE', MSGPAIR
  .ENDR
  .ENDM
.MACRO $SHR_MSGCOD NAME, CODE, MSG, SEVERITY
  .IF      IDN, SEVERITY, WARNING    ; if WARNING, set 0 sev
  .IF EQ $$GBL
  'NAME'$_'MSG' = 0                  ; set 0 sev (WARNING)
  .IFF
  'NAME'$_'MSG' == 0                 ; set 0 sev (WARNING)
  .ENDC
  .IFF
  .IF      IDN, SEVERITY, SUCCESS    ; if SUCCESS, set 1 sev
  .IF EQ $$GBL
  'NAME'$_'MSG' = 1                  ; set 1 sev (SUCCESS)
  .IFF
  'NAME'$_'MSG' == 1                 ; set 1 sev (SUCCESS)

```

```
.ENDC
.iff
  .IF IDN,SEVERITY,ERROR          ; if ERROR, set 2 sev
  .IF EQ $$GBL                    ; set 2 sev (ERROR)
  'NAME'$_'MSG' = 2
  .iff                             ; set 2 sev (ERROR)
  'NAME'$_'MSG' == 2
  .ENDC
  .iff
  .IF IDN,SEVERITY,INFO          ; if INFO, set 3 sev
  .IF EQ $$GBL                    ; set 3 sev (INFO)
  'NAME'$_'MSG' = 3
  .iff                             ; set 3 sev (INFO)
  'NAME'$_'MSG' == 3
  .ENDC
  .iff
  .IF IDN,SEVERITY,SEVERE        ; if SEVERE, set 4 sev
  .IF EQ $$GBL                    ; set 4 sev (SEVERE)
  'NAME'$_'MSG' = 4
  .iff                             ; set 4 sev (SEVERE)
  'NAME'$_'MSG' == 4
  .ENDC
  .iff
  .IF EQ $$GBL                    ; set specified sev
  'NAME'$_'MSG' = 'SEVERITY
  .iff                             ; set specified sev
  'NAME'$_'MSG' == 'SEVERITY
  .ENDC
  .ENDC
  .ENDC
  .ENDC
  .ENDC
  .IF EQ $$GBL
  'NAME'$_'MSG' = 'NAME'$_'MSG'+SHR$_'MSG'+<'CODE'@16>
  .iff
  'NAME'$_'MSG' == 'NAME'$_'MSG'+SHR$_'MSG'+<'CODE'@16>
  .ENDC
.ENDM
```

UTLDEFM.MAR;1

16-SEP-1984 17:07:59.56 <sup>K 15</sup> Page 12

.LIST

UT  
VC

.....

.

