VAX/VMS Show Cluster Utility Reference Manual

Order Number: AA-Z430B-TE

April 1986

This reference manual describes how to use the Show Cluster Utility to monitor and display VAXcluster activity and performance.

Revision/Update Information: Software Version: This is a revised manual. VAX/VMS Version 4.4

digital equipment corporation maynard, massachusetts

April 1986

The information in this document is subject to change without notice and should not be construed as a commitment by Digital Equipment Corporation. Digital Equipment Corporation assumes no responsibility for any errors that may appear in this document.

The software described in this document is furnished under a license and may be used or copied only in accordance with the terms of such license.

No responsibility is assumed for the use or reliability of software on equipment that is not supplied by Digital Equipment Corporation or its affiliated companies.

Copyright ©1986 by Digital Equipment Corporation

All Rights Reserved. Printed in U.S.A.

The postpaid READER'S COMMENTS form on the last page of this document requests the user's critical evaluation to assist in preparing future documentation.

The following are trademarks of Digital Equipment Corporation:

DEC DIBOL DEC/CMS EduSystem DEC/MMS IAS DECnet MASSBUS PDP DECsystem-10 DECSYSTEM-20 PDT DECUS RSTS **DECwriter** RSX

UNIBUS VAX VAXcluster VMS VT

digital

ZK-3031

HOW TO ORDER ADDITIONAL DOCUMENTATION DIRECT MAIL ORDERS

USA & PUERTO RICO*

CANADA

Digital Equipment Corporation P.O. Box CS2008 Nashua, New Hampshire 03061 Digital Equipment of Canada Ltd. 100 Herzberg Road Kanata, Ontario K2K 2A6 Attn: Direct Order Desk

INTERNATIONAL

Digital Equipment Corporation PSG Business Manager c/o Digital's local subsidiary or approved distributor

In Continental USA and Puerto Rico call 800-258-1710.

In New Hampshire, Alaska, and Hawaii call 603-884-6660.

In Canada call 800-267-6215.

^{*}Any prepaid order from Puerto Rico must be placed with the local Digital subsidiary (809-754-7575). Internal orders should be placed through the Software Distribution Center (SDC), Digital Equipment Corporation, Westminster, Massachusetts 01473.

This document was prepared using an in-house documentation production system. All page composition and make-up was performed by TEX, the typesetting system developed by Donald E. Knuth at Stanford University. TEX is a registered trademark of the American Mathematical Society.

SHOW CLUSTER Contents

PREFACE	vii
NEW AND CHANGED FEATURES	ix
FORMAT	SHCL-1
COMMAND SUMMARY	SHCL-2
DESCRIPTION	SHCL-3
INVOKING AND TERMINATING SHOW CLUSTER	SHCL-3
SHOW CLUSTER REPORT	SHCL-3
CONTROLLING THE DISPLAY	SHCL-5
Entering Commands	SHCL-6
Keypad	SHCL-6
Changing the Updating Interval	SHCL-7
Adding Information	SHCL-8
Formatting the Display	SHCL-9
3.5.1 Removing Data	SHCL-9
3.5.2 Modifying Field and Screen Size	SHCL-9
3.5.3 Moving a Window	SHCL-10
3.5.4 Scrolling a Window	SHCL-10
3.5.5 Panning the Display	SHCL-11
Refreshing the Screen	SHCL-11
Receiving Broadcast and Error Messages	SHCL-12
CREATING A STARTUP INITIALIZATION FILE	SHCL-12
Using Command Procedures	SHCL-13

SHOW CLUSTER Contents

COMMAND QUALIFIERS	SHCL-15
/BEGINNING=TIME	SHCL-16
/CONTINUOUS	SHCL-17
/ENDING=TIME	SHCL-18
/INTERVAL=SECONDS	SHCL-19
/OUTPUT=FILE-SPEC	SHCL-20
COMMANDS	SHCL-21
@ (EXECUTE PROCEDURE)	SHCL-22
ADD CIRCUITS	SHCL-23
ADD CLUSTER	SHCL-25
ADD CONNECTIONS	SHCL-26
ADD COUNTERS	SHCL-28
ADD CREDITS	SHCL-29
ADD ERRORS	SHCL-30
ADD (FIELD)	SHCL-31
ADD LOCAL_PORTS	SHCL-41
ADD MEMBERS	SHCL-42
ADD SYSTEMS	SHCL-43
DEFINE/KEY	SHCL-45
DESELECT	SHCL-48
EXIT	SHCL-49
HELP	SHCL-50
INITIALIZE	SHCL-51
MOVE	SHCL-52
PAN	SHCL-54
REFRESH	SHCL-55
REMOVE CIRCUITS	SHCL-56
REMOVE CLUSTER	SHCL-57
REMOVE CONNECTIONS	SHCL-58
REMOVE COUNTERS	SHCL-59

SHOW CLUSTER Contents

REMOVE CREDITS	SHCL-60
REMOVE ERRORS	SHCL-61
REMOVE (FIELD)	SHCL-62
REMOVE LOCAL_PORTS	SHCL-63
REMOVE MEMBERS	SHCL-64
REMOVE SYSTEMS	SHCL-65
SAVE	SHCL-67
SCROLL	SHCL-69
SELECT	SHCL-70
SET AUTO_POSITIONING	SHCL-71
SET (FIELD)	SHCL-72
SET FUNCTION	SHCL-73
SET INTERVAL	SHCL-74
SET SCREEN	SHCL-75
WRITE	SHCL-76

INDEX

-.

Preface

Intended Audience

This manual is intended for VAXcluster users, system managers, and others who routinely monitor cluster activity and performance.

Structure of This Document

This document is composed of four major sections.

The Format Section is an overview of the Show Cluster Utility and is intended as a quick reference guide. The format summary contains the DCL command that invokes the Show Cluster Utility, listing all command qualifiers and parameters. The usage summary describes how to invoke and exit from the Show Cluster Utility, how to direct output, and any restrictions that apply to the use of this utility. The command summary lists all commands and qualifiers that can be used within the Show Cluster environment.

The Description Section explains how to use the Show Cluster Utility.

The Qualifier Section describes each DCL command qualifier. Qualifiers appear in alphabetical order.

The Command Section describes each Show Cluster Utility command, qualifiers and parameters. This section also gives examples for command use. Commands appear in alphabetical order.

Associated Documents

For related information about this utility, see the Guide to VAX clusters.

r

Convention	Meaning		
RET	A symbol with a one- to three-character abbreviation indicates that you press a key on the terminal, for example, RET.		
CTRL/x	The phrase CTRL/x indicates that you must press the key labeled CTRL while you simultaneously press another key, for example, CTRL/C, CTRL/Y, CTRL/O. In examples, this control key sequence is shown as ^x, for example, ^C, ^Y, ^O, because that is how the system echoes control key sequences.		
\$ SHOW TIME 05-JUN-1982 11:55:22	Command examples show all output lines or prompting characters that the system prints or displays in the black letters. All user-entered commands are show in red letters.		
\$ TYPE MYFILE.DAT	Vertical series of periods, or ellipsis, mean either that not all the data that the system would display in response to the particular command is shown or that not all the data a user would enter is shown.		
file-spec,	Horizontal ellipsis indicates that additional parameters, values, or information can be entered.		
[logical-name]	Square brackets indicate that the enclosed item is optional. (Square brackets are not, however, optional in the syntax of a directory name in a file specification or in the syntax of a substring specification in an assignment statement.)		
quotation marks apostrophes	The term quotation marks is used to refer to double quotation marks ("). The term apostrophe (') is used to refer to a single quotation mark.		

Conventions Used in This Document

viii

New and Changed Features

The Show Cluster Utility for Version 4.4 contains the following new features:

New commands:

```
DEFINE/KEY
DESELECT
MOVE
PAN
REFRESH
SAVE
SCROLL
SELECT
SET FUNCTION
SET AUTO_POSITIONING
WRITE
```

- One display report instead of two. (Consequently, the SHOW command is now obsolete.)
- Definable keys and a default keypad.
- Three display windows, each containing related classes. Each window can be manipulated independently.
- Command procedures can be nested up to 16 levels deep.

The VAX/VMS Show Cluster Utility (SHOW CLUSTER) monitors nodes in a VAXcluster and displays information about cluster activity and performance. SHOW CLUSTER information covers approximately 100 fields of data, which appear in three windows. You can customize the appearance of the display and output, or use default displays for access to often-needed data. You can use SHOW CLUSTER interactively or with command procedures and user-defined default settings.

FORMAT

SHOW CLUSTER

Command Qualifiers

/BEGINNING=time /CONTINUOUS /ENDING=time /INTERVAL=seconds /OUTPUT=file-spec Defaults None. None. /INTERVAL=15 /OUTPUT=SYS\$OUTPUT

Command Parameters

None.

usage summary

Invoking To invoke the Show Cluster Utility, specify the following command:

\$ SHOW CLUSTER

If you specify the command without any qualifiers, SHOW CLUSTER displays a single cluster report and then returns control to the DCL level. To invoke a continuous SHOW CLUSTER display, specify the following command:

\$ SHOW CLUSTER/CONTINUOUS

If you request a continuous display, you can then control report output with SHOW CLUSTER commands.

Exiting

By default, SHOW CLUSTER displays a single cluster report and then returns control to the DCL level. If you specify the /CONTINUOUS qualifier, cluster reports are displayed continuously. To exit from a continuous display and return to the DCL level, either specify the EXIT command or press CTRL/Z or CTRL/C.

Directing Output

You can direct SHOW CLUSTER output to a file or device other than to SYS\$OUTPUT by specifying the /OUTPUT qualifier with the SHOW CLUSTER command. For more information, see the description of the /OUTPUT qualifier.

Privileges/Restrictions None.

commands

Svntax command [/qualifier[, . . .]] [parameter] [/qualifier[, . . .]]

SHOW CLUSTER Commands

@ (Execute Procedure) ADD CIRCUITS /ALL /TYPE=ALL TYPE=[NO]OPEN ADD CLUSTER /ALL ADD CONNECTIONS /ALL /TYPE=ALL /TYPE=[NO]OPEN ADD COUNTERS /ALL ADD CREDITS /ALL ADD ERRORS /ALL ADD (Field) ADD LOCAL_PORTS /ALL ADD MEMBERS /ALL ADD SYSTEMS /ALL /ID=system-id /NODE=node-name /TYPE=hardware-type DEFINE/KEY /[NO]ECHO /INO ERASE /INOIF_STATE /INOILOCK_STATE /[NO]LOG /[NO]SET_STATE /[NO]TERMINATE DESELECT EXIT HELP INITIALIZE **MOVE direction value PAN** direction value REFRESH **REMOVE CIRCUITS** /TYPE=ALL /TYPE=[NO]OPEN **REMOVE CLUSTER REMOVE CONNECTIONS** /TYPE=ALL /TYPE=[NO]OPEN **REMOVE COUNTERS REMOVE CREDITS REMOVE ERRORS REMOVE (Field)**

Description

REMOVE LOCAL_PORTS REMOVE MEMBERS REMOVE SYSTEMS /ID=system-id /NODE=node-name /TYPE=hardware-type SAVE [file-spec] SCROLL direction value SELECT [window-name] SET AUTO_POSITIONING (ON, OFF) SET (Field) /WIDTH=field-name-width /FORMAT=radix SET FUNCTION function-name SET INTERVAL SET SCREEN WRITE [file-spec] /ALL

DESCRIPTION The Show Cluster Utility allows you to monitor the activity and performance of a VAXcluster. SHOW CLUSTER collects information from the systems communications services (SCS) database, the connection management database, and the CI (computer interconnect) port database, and outputs it to your terminal or to a specified device or file.

Invoking and Terminating SHOW CLUSTER

You invoke the Show Cluster Utility at the DCL command level by specifying the DCL command SHOW CLUSTER. By default, SHOW CLUSTER displays a single report on your terminal and returns control to the DCL command level.

If you specify the /CONTINUOUS qualifier, SHOW CLUSTER displays data continuously, and updates the display at specific intervals. If you initiate a continuous display you can then control report output with Show Cluster Utility commands.

To terminate a continuous display and return to the DCL command level, specify the SHOW CLUSTER command EXIT. You can also terminate a display session at any time by pressing CTRL/Z or CTRL/C. To interrupt SHOW CLUSTER, press CTRL/Y.

2 SHOW CLUSTER Report

1

The SHOW CLUSTER report provides over 100 fields of data. However, because data alone does not necessarily communicate meaningful information, the Show Cluster Utility provides a framework in which to manipulate the data so that it becomes useful information. This framework consists of fields, classes, and windows.

You can reference each of the fields of data by a unique name. For example, the field containing the number of datagrams received by a local system is named DGS__RCVD. Using the field name, you can selectively remove or add a field from the SHOW CLUSTER report.

Description

Since many of the fields contain related information, SHOW CLUSTER groups related fields into classes. For example, SHOW CLUSTER groups the number of datagrams sent (DGS_SENT field), the number of datagrams received (DGS_RCVD field), the number of messages sent (MSGS_SENT field), and the number of messages received (MSG_RCVD field) into the COUNTERS class. Using the class name, you can selectively add or remove an entire class from the SHOW CLUSTER report.

The third type of informational grouping that SHOW CLUSTER provides is the window. SHOW CLUSTER gathers data from

- SCS database
- Connection management database
- CI port database

Because the data gathered from each source is related, SHOW CLUSTER uses that organization to group data. The SHOW CLUSTER report consists of three windows: SCS, CLUSTER and LOCAL_PORTS. The SCS window primarily contains data collected from the SCS database with the exception of the MEMBERS class data, which is collected from the connection management database. The CLUSTER window contains data collected from the connection management database, and the LOCAL_PORTS window contains data collected from the CI port database. For example, the COUNTERS class is one class of information gathered from the SCS database that SHOW CLUSTER displays in the SCS window.

Each window is a separate entity, and you can manipulate it independently of the other two. In practical terms, this means that you can add, remove, move, or scroll the window.

The following diagram shows the relationship among fields, classes, and windows in the SHOW CLUSTER report.

	00
NODE SOFTWARE STATUS	D
DARBY VMS V4.4 MEMBER DAT DOOLEY HSC V110 ALICAT VMS V4.4 MEMBER MISHA VMS V4.4 MEMBER	ТА И

ZK-4998-86

The following tables show which classes are contained in each of the three windows.

Description

SCS Window Classes		
MEMBERS	Contains information about the systems actively participating in the cluster.	
SYSTEMS	Contains information about systems in the cluster.	
CIRCUITS	Contains information about the virtual circuits on systems in the cluster.	
CONNECTIONS	Contains information about the connections established over a virtual circuit in the cluster.	
COUNTERS	Contains counts of the total accumulated traffic over a connection for the life of the connection.	
CREDITS	Contains information about the send and receive credit counts for connections in the cluster.	
Connection Management		
Window Class		
	Contains general information about the cluster.	
CI Port Window Classes		
ERRORS	Contains information about errors on the local system's Cl interface to the cluster.	
LOCAL_PORTS	Contains information about the local system's CI interface to the cluster.	

For a description of the fields in each class, see the description of the ADD (Field) command.

3 Controlling the Display

In addition to providing you with data about a cluster, SHOW CLUSTER also provides you with mechanisms to control the display of data. The mechanisms include:

- SHOW CLUSTER commands
- Default keypad which can also be redefined
- Initialization file to format display
- Command procedures to control display

Some of the operations that you can perform include:

- Changing the interval at which the display is updated
- Adding information to the display
- Changing the format of the display

Description

- Moving a window
- Scrolling a window
- Panning the display

The following sections describe how to perform these operations.

3.1 Entering Commands

The Show Cluster Utility allows you to customize the display of data within fields, classes, and windows by issuing various commands during a continuous session. The Command Section describes the available SHOW CLUSTER commands in detail.

When you first enter the continuous SHOW CLUSTER environment, no command prompt is visible on the display screen. As soon as you enter a command from the terminal keyboard, the two bottom lines of the display are erased and the following SHOW CLUSTER prompt appears:

COMMAND>

SHOW CLUSTER uses the two bottom lines for displaying commands, error messages, and broadcast messages.

Updating of the continuous display stops as soon as you enter input from the terminal keyboard. When you press the RETURN key after entering a command, updating resumes until another command is entered. By default, updating takes place at 15-second intervals. If no new command is entered within 15 seconds, the information in the two bottom lines is restored with two more lines of data from the original display.

By default, SHOW CLUSTER is set to EDIT function. This means that you can perform DCL line-mode editing at the command prompt (for example, using the LEFT arrow key to move the cursor to the left, or the UP arrow key to recall the previous command). See the VAX/VMS DCL Concepts Manual for information on DCL line-mode editing.

Note: Once you set the function to PAN, SCROLL, or MOVE, the arrow keys are redefined, and DCL line-mode editing is disabled. PAN, SCROLL, and MOVE are described in Section 3.5 and in the Command Section.

To enable editing again once it has been disabled, issue the command SET FUNCTION EDIT.

3.2 Keypad

SHOW CLUSTER provides a predefined keypad that you can use to enter selected commands. By default, the numeric keypad is defined as follows: (Shading over a keypad command indicates that you must press the GOLD key and then the keypad key.)

Description

PF1	PF2	PF3	PF4
GOLD	HELP	REFRESH	INIT
20	10	11	17
7 SET FUNCTION PAN	8 SET FUNCTION SCROLL	9 Set function Move	 SET FUNCTION EDIT
7	8	9	18
4 ADD	5 REMOVE	6 SET AUTO_POS OFF	,
4	5	SET AUTO_POS ON 6	19
1 Set	2 SAVE	3 WRITE	
1	2	3	
0		• SELECT	
	0	DESELECT	21
<u> </u>	0		216 4007.8

If you press a SET FUNCTION key, the arrow keys are redefined to perform the specified function. For example, if you press the SET FUNCTION SCROLL key, the \uparrow , \downarrow , \rightarrow , and \leftarrow arrow keys are redefined as SCROLL UP 1, SCROLL DOWN 1, SCROLL RIGHT 1, and SCROLL LEFT 1, respectively. (See the Command Section for information on specific commands.)

Note: If you set the function to PAN, SCROLL, or MOVE, the arrow keys are no longer defined to perform DCL line-mode editing. Only one function can be enabled at a time. To restore line-mode editing, once it has been changed to another function, issue the command SET FUNCTION EDIT.

You can also use the DEFINE/KEY command to change the definition of a key. See DEFINE/KEY command in the Command Section for more information.

3.3 Changing the Updating Interval

You can change the interval at which SHOW CLUSTER updates the data in the display. By default, the display is updated every 15 seconds, with the changed data displayed in reverse video. To change the rate at which data is updated, you use the SET INTERVAL command. See SET INTERVAL in the Command Section for more information.

You can also change the updating interval by issuing the following command at the DCL level:

SHOW CLUSTER/INTERVAL=seconds

Description

3.4 Adding Information

When you invoke SHOW CLUSTER, the resulting display contains a subset of the total information available. By default, the SHOW CLUSTER display consists of the SCS window, containing the following information:

VIEW OF CLUSTER FROM SYSTEM ID 1209 NODE DARBY 15-APR-1986 15:11:	'R-1986 15:11:34
-------------------------------------------------------------------	------------------

SYS ⁻	TEMS	MEMBERS	
NODE	SOFTWARE	STATUS	- SCS WINDOW
DARBY	VMS V4.4	MEMBER	
DOOLEY	HSC V110		
ALICAT	VMS V4.4	MEMBER	
MISHA	VMS V4.4	MEMBER	
WAYNE	VMS V4.4	MEMBER	
PHENIX	HSC V110		
UPARK	HSC XSJS		
TOONA	VMS V4.4	MEMBER	

ZK-4999-86

You add additional fields and/or classes with the ADD command. To specify a particular field, use the appropriate field name as specified in the description of the ADD (Field) command in the Command Section. To specify a particular class, use the appropriate ADD command as specified in the Command Section.

If you add a field or class that is not in the SCS window, SHOW CLUSTER displays the new window containing the specified class. The following diagrams display the default classes and fields of the LOCAL_PORTS and CLUSTER windows:

		LOCAL PORTS WINDOW					
NAME	LPPORT	PORT	DGS	MSGS	OPEN_C	FORM_C	
ΡΑΑΟ	ONLINE	2	> 2	> 2	4	0	

ZK-5000-86

	_CLUSTER WINDOW					
CL_Q	CL_V	QD_NAME	QF_V	FORMED	LAST_TRANSITION	
2	3		NO	15-APR-86 09:38	30-MAR-86 14:39	

ZK-5001-86

Description

Note: The AUTO_POSITIONING function may place one window below another in such a way that it does not appear within the limits of your current display. See the next section for information on viewing data that extends beyond the limits of the display.

3.5 Formatting the Display

Because the Show Cluster Utility allows you to include additional fields and classes, you may produce displays that overflow the physical limits of the terminal screen. However, you can manipulate the fields, classes, and windows to customize a display to meet your needs. This can be achieved by any of the following methods:

- Removing data by class, field, or type
- Modifying field widths and formats
- Modifying the screen size
- Moving a window
- Scrolling a window
- Panning the display

3.5.1 Removing Data

You may want to remove certain fields or classes to reduce the width of the display to fit the limits of your screen. Also, certain fields or classes may not be important for your particular needs. You can also remove data of a particular type, to reduce the length of the display.

You use the REMOVE command to remove fields, classes, or certain types of data. To remove a particular field, use the appropriate field name in the command, REMOVE field-name. See the ADD (Field) command description for a list of valid field names. To remove a particular class, use the appropriate class name in the command, REMOVE class-name. To remove certain types of data, use the appropriate /TYPE=keyword qualifier with the REMOVE CIRCUITS, REMOVE CONNECTIONS, or REMOVE SYSTEMS command. See the REMOVE commands in the Command Section for appropriate class names and keywords.

3.5.2 Modifying Field and Screen Size

Another way you make the display fit the physical limits of the screen is to change the width of certain fields in the display. For example, if SHOW CLUSTER provides a field width that can contain any possible value and the values your cluster generates do not require that much area, you can adjust the field width with the SET (Field) command. See the SET (Field) command in the Command Section for a description of how to adjust field widths.

SHOW CLUSTER also allows you to adjust the size of the terminal screen. If the terminal is DIGITAL compatible, you can set the screen to a width of up to 512 columns by specifying an appropriate value to the SET SCREEN command. See the SET SCREEN command in the Command Section for more details.

Description

3.5.3 Moving a Window

By default, SHOW CLUSTER operates with AUTO_POSITIONING ON. This means that it automatically arranges the windows to take best advantage of the available display space. However, you may want to position windows manually by overriding the default. Setting AUTO_POSITIONING to OFF allows windows to be repositioned manually.

To reposition a window, you must first select the window to be repositioned. You use the command SELECT *window-name* to specify the window name: SCS, CLUSTER, or LOCAL_PORTS. As an alternative, you can repeatedly press the SELECT key on the keypad to cycle from one window to the next. The selected window appears highlighted.

To move a selected window, you either enter MOVE commands at the command prompt, or use the arrow keys defined as MOVE commands. Issuing the command SET FUNCTION MOVE redefines the \uparrow , \downarrow , \rightarrow , and \leftarrow arrow keys as MOVE UP 1, MOVE DOWN 1, MOVE RIGHT 1, MOVE LEFT 1, respectively.

Note: The SET FUNCTION MOVE command implicitly sets AUTO_ POSITIONING to OFF.

When you issue a MOVE command, the window changes position by column (horizontally), or by line (vertically). For example, entering the command MOVE LEFT 5 moves the window 5 columns to the left. An empty frame appears around the new window position. When you are satisfied with the position of the window, you issue the DESELECT command, which moves the window to the new position. Entering another SELECT command before the previous MOVE operation has been deselected also moves the window to its new position.

In summary, you follow these steps to move a window:

- 1 Set AUTO_POSITIONING to OFF.
- **2** Select a window using the SELECT command.
- **3** Position the window frame by using MOVE commands.
- **4** Terminate the MOVE operation by entering the DESELECT command or another SELECT command.

Note: If you attempt to issue MOVE commands with AUTO_POSITIONING ON, the window will revert to its original position when you issue the DESELECT command.

For more information, see the SELECT, SET FUNCTION, and DESELECT commands in the Command Section.

3.5.4 Scrolling a Window

The SCROLL command provides a means of quickly scanning through a window without changing the selection of information displayed in the window. Scrolling scans a window by field (horizontally) and by line (vertically). The window headings remain stationary when you scroll vertically.

To scroll the view of a window, you must first select a window by issuing the SELECT command. The selected window is highlighted. You scroll a selected window either by entering SCROLL commands at the command prompt, or by using the arrow keys defined as SCROLL commands. Issuing the command SET FUNCTION SCROLL redefines the \uparrow , \downarrow , \rightarrow , and \leftarrow

SHOW CLUSTER Description

arrow keys as SCROLL UP 1, SCROLL DOWN 1, SCROLL RIGHT 1, and SCROLL LEFT 1, respectively.

To issue the SCROLL command at the command prompt, use the format:

SCROLL direction value

See the SET FUNCTION and SCROLL commands in the Command Section for more information.

3.5.5 Panning the Display

The PAN command allows you to view the entire display from a perspective similar to that of a video camera. Panning changes your view of the display by column (horizontally) or by line (vertically). Window headings also move out of view as the windows contained within the display are panned beyond the limits of the screen.

Similar to the effect of panning a video camera, the display seems to move in the opposite direction to which you are panning. For example, the command PAN UP 5 moves the display five lines down; the command PAN RIGHT 5 moves the display five columns to the left.

To pan the display, either enter PAN commands at the command prompt, or use the arrow keys defined as PAN commands. Issuing the command SET FUNCTION PAN redefines the \uparrow , \downarrow , \rightarrow , and \leftarrow arrow keys as PAN UP 1, PAN DOWN 1, PAN RIGHT 1, and PAN LEFT 1, respectively.

Note: Only one function can be enabled at a time. To restore line-mode editing once the function has been changed to PAN, SCROLL, or MOVE, issue the command SET FUNCTION EDIT.

To issue the PAN command at the command prompt, use the format:

PAN direction value

See the SET FUNCTION and PAN commands in the Command Section for more information.

3.6 Refreshing the Screen

Normally a continuous display is updated or *refreshed* according to the specified interval time. The Show Cluster Utility scans the software databases, extracts and stores data for each field, displays any new or changed data, and updates the time. On DIGITAL compatible terminals, reverse video highlights any changed data.

You can refresh the screen at any time by one of the following methods:

- Modifying the format of the display with the ADD, REMOVE, INITIALIZE, or SET command
- Using the REFRESH command
- Pressing CTRL/W

Description

3.7 Receiving Broadcast and Error Messages

When you receive a broadcast message during a continuous SHOW CLUSTER session, the message appears at the bottom of the display screen. A multiline message fills as many lines of the display as it needs.

The last broadcast message remains on the screen until you acknowledge its receipt by entering input from the terminal in one of the following ways:

- Pressing the RETURN key
- Refreshing the screen by pressing CTRL/W
- Issuing a command

If you receive more than one broadcast message, SHOW CLUSTER waits until the next update interval to display the next message.

4 Creating a Startup Initialization File

To override report defaults before the display begins, you can create a startup initialization file, which the utility executes when it is invoked. In order for a startup file to execute before the display begins, you must assign the logical name SHOW_CLUSTER\$INIT to the file name of the procedure. When invoked, SHOW CLUSTER searches for the file defined by SHOW_CLUSTER\$INIT and, if it is found, executes the procedure before beginning the display. If SHOW_CLUSTER\$INIT is not defined or does not include a directory specification, SHOW CLUSTER searches the current default directory. The following example shows how to assign SHOW_CLUSTER\$INIT to a startup initialization procedure file:

DEFINE SHOW_CLUSTER\$INIT DEVA: [JONES] SHCINI

In this example, SHOW CLUSTER looks for DEVA:[JONES]SHCINI.INI when it starts up.

The easiest way to create an initialization file is to follow these steps:

- 1 Define SHOW_CLUSTER\$INIT as device:[directory]SHCINI
- **2** Customize the display using SHOW CLUSTER commands during a continuous SHOW CLUSTER session
- **3** Enter the command

COMMAND> SAVE SHOW_CLUSTER\$INIT: .INI

You must specify SHOW_CLUSTER\$INIT:.INI, because the SAVE command creates a file with a file type of .COM by default. SHOW CLUSTER looks for an .INI file when it searches for a startup initialization file.

You can edit the file that the SAVE command creates to include comments or to improve its efficiency. For more information, see the SAVE command in the Command Section.

Description

The following startup procedure causes SHOW CLUSTER to delete the default MEMBERS class information and add three fields from the CIRCUITS class:

Startup Initialization File I INITIALIZE REMOVE MEMBERS ADD CIR_STATE, REM_STATE, CABLE_STATUS SET SCREEN=132

You can also create an initialization file in the same manner as a command procedure. Section 4.1 describes the rules for creating a command procedure.

If you use an initialization file in noncontinuous mode and the initialization file contains a SET SCREEN command that changes the screen size, SHOW CLUSTER sets the screen to the specified size for one update interval and then resets the screen to the original size.

4.1 Using Command Procedures

You can also create command procedures that contain SHOW CLUSTER commands. Such files let you modify display characteristics without having to enter commands interactively. Command procedures can be used during a continuous SHOW CLUSTER display session to perform a series of commands, for example, customizing the output of the display. Any valid SHOW CLUSTER commands can be used. Command procedures can be nested 16 levels deep. Note that command procedures cannot be run from a batch job.

Each line in a command procedure is interpreted as a command unless the line begins with an exclamation point (!), in which case the line is treated as a comment. Comments are also valid at the ends of lines containing commands; everything to the right of an exclamation point is considered a comment.

Include the SHOW CLUSTER command INITIALIZE as the first command in the file. The INITIALIZE command ensures that the report is in a known state before any commands are executed to modify it.

Note: Do not include an EXIT command at the end of the command procedure. The EXIT command terminates SHOW CLUSTER and erases the SHOW CLUSTER display before you can see it.

The following command procedure customizes a report display:

```
!
!
Include only node field from the default display; show votes
! and quorum for each node and for cluster as a whole.
!
INITIALIZE
REMOVE SOFTWARE,STATUS
ADD VOTES,QUORUM,CL_VOTES,CL_QUORUM
```

This command procedure removes the SOFTWARE and STATUS fields from the report display and adds fields that provide information about cluster quorum and votes.

Description

To execute a command procedure during a continuous SHOW CLUSTER session specify the execute procedure (@) command along with the file name of the command procedure. The default file type for command procedure files is COM. The following command executes the command procedure saved in the default directory under the file name SYSMOD.COM:

COMMAND> CSYSMOD

In this example, since the file type is omitted, the default file type COM is assumed.

Command Qualifiers

COMMAND QUALIFIERS

This section describes the qualifiers that can be used with the DCL command SHOW CLUSTER to invoke the Show Cluster Utility:

- /BEGINNING=time
- /CONTINUOUS
- /ENDING=time
- /INTERVAL=seconds
- /OUTPUT=file-spec

/BEGINNING = time

/BEGINNING = time

Specifies the time that the SHOW CLUSTER session is to begin. You can specify an absolute time, a delta time, or a combination of the two. Observe the syntax rules for time values described in the VAX/VMS DCL Concepts Manual.

If you specify a future time, your process is placed in a state of hibernation until the specified time. You should use this qualifier with the /OUTPUT and /ENDING qualifiers to run SHOW CLUSTER without direct user intervention.

FORMAT /BEGINNING=time

time

You can specify time as an absolute time expressed as [dd-mmm-yyyy[:]] [hh:mm:ss.cc], or a delta time expressed as [dddd-][hh:mm:ss.cc], or a combination of the two. Observe the syntax rules for time values described in the VAX/VMS DCL Concepts Manual.

EXAMPLES

\$ SHOW CLUSTER/BEGINNING=04-JUL-1986:20:30

In this example, specifying an absolute time, the Show Cluster Utility produces a single display at 8:30 P.M. on July 4, 1986.

SHOW CLUSTER/CONTINUOUS/BEGINNING=04-JUL-1986:21:30

In this example, specifying an absolute time, the Show Cluster Utility begins a continuous display at 9:30 P.M. on July 4, 1986.

SHOW CLUSTER/BEGINNING=7-:30

In this example, specifying a delta time, the Show Cluster Utility produces a single display seven days and 30 minutes from now.

SHOW CLUSTER /CONTINUOUS

/CONTINUOUS

Controls whether SHOW CLUSTER runs as a continuously updating display. If you omit the qualifier, SHOW CLUSTER produces a single display and returns control to the DCL command level.

Running SHOW CLUSTER in the continuous mode allows you to use SHOW CLUSTER commands to control the display.

FORMAT /CONTINUOUS

EXAMPLE

\$ SHOW CLUSTER/CONTINUOUS

In this example the Show Cluster Utility begins to display a continuous report that is updated every 15 seconds.

/ENDING = time

/ENDING = time

Specifies the time that the SHOW CLUSTER session is to end. You can specify an absolute time, a delta time, or a combination of the two. Observe the syntax rules for time values described in the *VAX/VMS DCL Concepts Manual*.

You should use this qualifier with the /BEGINNING and /OUTPUT qualifiers to run SHOW CLUSTER without direct user intervention.

FORMAT /ENDING=time

time

You can specify time as an absolute time expressed as [dd-mmmyyyy[:]][hh:mm:ss.cc], or a delta time expressed as [dddd-][hh:mm:ss.cc], or a combination of the two. Observe the syntax rules for time values described in the VAX/VMS DCL Concepts Manual.

EXAMPLE

\$ SHOW CLUSTER/CONTINUOUS/ENDING=04-JUL-1986:15:30

In this example, the Show Cluster Utility begins a continuous display now and ends the display at 3:30 P.M. on July 4, 1986.

SHOW CLUSTER /INTERVAL = seconds

/INTERVAL = seconds

Specifies the number of seconds that display information remains on the screen before it is updated. By default, the interval time is 15 seconds.

If you use an initialization file in noncontinuous mode and the initialization file contains a SET SCREEN command that changes the screen size, SHOW CLUSTER sets the screen to the specified size for one update interval and then sets the screen to the original size.

FORMAT

/INTERVAL=seconds seconds

The number of seconds between display updates.

EXAMPLE

\$ SHOW CLUSTER/INTERVAL=5

In this example the Show Cluster Utility displays a continuous report that is updated every five seconds.

/OUTPUT = file-spec

/OUTPUT = file-spec

Directs the output from SHOW CLUSTER to the specified file instead of the current SYS\$OUTPUT device. You can also direct output to a particular device if the device name specified is valid; if it is not, SHOW CLUSTER assumes it is a file name.

When you use the /OUTPUT qualifier, SHOW CLUSTER output is always in printable file format, regardless of the device type specified. The output can be up to 132 columns wide and can be directed to any file, terminal, or print device.

You can also direct output a file with the WRITE command. See the Command Section for more detail.

FORMAT /OUTPUT=file-spec

file-spec

The name of the file to which SHOW CLUSTER output is directed. The default file name is SHOW_CLUSTER.LIS.

EXAMPLES

\$ SHOW CLUSTER/OUTPUT=[OMALLEY]CLUSTER

In this example the Show Cluster Utility produces one report and directs it to the file CLUSTER.LIS;1 in the directory OMALLEY.

SHOW CLUSTER/OUTPUT=[WARREN]CLUSTER.RPT;1

In this example the Show Cluster Utility produces one report and directs it to the file CLUSTER.RPT;1 in the directory WARREN.

Commands

COMMANDS Once you initiate a continuous SHOW CLUSTER display session, you can use SHOW CLUSTER commands to control the session. This section describes each of the SHOW CLUSTER commands.

@ (Execute Procedure)

@ (Execute Procedure) Executes a command procedure file that contains SHOW CLUSTER commands. FORMAT file-spec **@** command file-spec Specifies the name of the file that contains the commands to be executed. parameters If you omit the file type, the default file type COM is used. No wildcard characters are allowed in the file specification. None. command qualifiers DESCRIPTION The execute procedure (@) command allows you to execute a set of SHOW CLUSTER commands that is contained in a file. For example, a file might contain a set of commands to customize a SHOW CLUSTER display. You can use any valid SHOW CLUSTER commands in the command procedure. You can nest command procedures up to 16 levels deep. SHOW CLUSTER looks for the command procedure in the directory specified by the logical name SHOW_CLUSTER\$INIT. If SHOW_CLUSTER\$INIT is not defined or does not include a directory specification, the utility looks for the command procedure in the current default directory.

EXAMPLE

COMMAND> OMYFILE

The command in this example executes the command procedure MYFILE.COM. Because no file type is specified, the file type defaults to COM.

SHOW CLUSTER ADD CIRCUITS

ADD CIRCUITS

Adds all currently enabled CIRCUITS class fields to the SHOW CLUSTER display. The CIRCUITS class contains information about the virtual circuits on systems in the cluster.

FORMAT ADD CIRCUITS [/qualifier[, . . .]]

command

parameters

command qualifiers None.

/ALL

Specifies that all fields in this class be added to the display.

/TYPE=ALL

Specifies that all types of circuits be included in the display, including formative, open, and closing circuits. By default, the ADD CIRCUITS command without any qualifiers displays all types of circuits.

/TYPE=OPEN

/TYPE=NOOPEN

Controls whether either open circuits or nonopen circuits are added to the display.

DESCRIPTION The ADD CIRCUITS command adds CIRCUITS class information to the SHOW CLUSTER display. This information includes data for all currently enabled fields in the CIRCUITS class. By default, the RPORT_NUM (remote port number), RP_TYPE (remote port type), and CIR_STATE (circuit state) fields are enabled. For a list of valid CIRCUITS class fields, see the ADD (Field) command.

You use the ADD CIRCUITS command together with the REMOVE CIRCUITS command to turn the display of CIRCUITS class information on and off. If you remove the CIRCUITS class from the display and add it again without changing any fields, all of the original fields are once again displayed. If, however, you remove the CIRCUITS class and add new CIRCUITS class fields, all previously enabled fields are disabled, and only the newly added fields are displayed.

EXAMPLES

COMMAND> ADD CIRCUITS

This command adds CIRCUITS class information to the display. This information includes all types of circuits for all enabled CIRCUITS class fields.

SHOW CLUSTER ADD CIRCUITS

COMMAND> ADD CIRCUITS/TYPE=OPEN

This command adds all open circuits to the SHOW CLUSTER display.

COMMAND> REMOVE CIRCUITS COMMAND> ADD RP_OWNER COMMAND> REMOVE CIRCUITS

COMMAND> ADD CIRCUITS

•

The ADD CIRCUITS command adds CIRCUITS class information to the SHOW CLUSTER display. The REMOVE CIRCUITS command removes the CIRCUITS class from the display. The ADD RP_OWNER command adds the CIRCUITS class field RP_OWNER to the display. As a result, all other CIRCUITS class fields are disabled. When the CIRCUITS class is removed and added again, only the RP_OWNER field is displayed.

SHOW CLUSTER ADD CLUSTER

ADD CLUSTER

Adds all currently enabled CLUSTER class fields to the SHOW CLUSTER display.

FORMAT ADD CLUSTER command None. command /ALL

DESCRIPTION The ADD CLUSTER command adds CLUSTER class information to the SHOW CLUSTER display. This information includes data for all currently enabled fields in the CLUSTER class. By default, the CLUSTER class includes CL_QUORUM (cluster quorum), CL_VOTES (cluster votes), QD_NAME (quorum disk name), QF_VOTE (quorum disk contributes a vote), FORMED (when quorum was formed), LAST_TRANSITION (last change in cluster membership). For a list of valid CLUSTER class fields, see the ADD (Field) command.

Specifies that all fields in this class be added to the display.

You use the ADD CLUSTER command together with the REMOVE CLUSTER command to turn the display of CLUSTER class information on and off. If you remove the CLUSTER class from the display and add it again without changing any fields, all of the original fields are once again displayed. If, however, you remove the CLUSTER class and add new CLUSTER class fields, all previously enabled fields are disabled, and only the newly added fields are displayed.

EXAMPLES

qualifier

COMMAND> ADD CLUSTER

This command adds CLUSTER class information to the display. This information includes all enabled CLUSTER class fields.

COMMAND> REMOVE CLUSTER COMMAND> ADD CL_QUORUM COMMAND> REMOVE CLUSTER

COMMAND> ADD CLUSTER

The ADD CLUSTER command in this example adds CLUSTER class information to the SHOW CLUSTER display. The first command removes the CLUSTER class from the display. The second command, ADD CL_QUORUM, adds the CLUSTER class field CL_QUORUM to the display. As a result, all other CLUSTER class fields are disabled. When the CLUSTER class is removed and added again, only the CL_QUORUM field is displayed.

ADD CONNECTIONS

ADD CONNECTIONS

Adds all currently enabled CONNECTIONS class fields to the SHOW CLUSTER display.

ADD CONNECTIONS [/qualifier[, . . .]] FORMAT None command parameters /ALL command qualifiers Specifies that all fields in this class be added to the display. /TYPE=ALL Specifies that all types of connections on each circuit are displayed. By default the ADD CONNECTIONS command without any qualifiers, displays all types of connections. /TYPE=OPEN /TYPE=NOOPEN Controls whether either open connections or nonopen connections are added to the SHOW CLUSTER display. DESCRIPTION The ADD CONNECTIONS command adds CONNECTIONS class information to the SHOW CLUSTER display. This information includes data for all currently enabled fields in the CONNECTIONS class. By default, the LOC_PROC_NAME (local process name) and CON_STATE (connection state) fields are enabled. For a list of valid CONNECTIONS class fields, see the ADD (Field) command. You use the ADD CONNECTIONS command together with the REMOVE CONNECTIONS command to turn the display of CONNECTIONS class information on and off. If you remove the CONNECTIONS class from the display and add it again without changing any fields, all of the original fields are once again displayed. If, however, you remove the CONNECTIONS class and add new CONNECTIONS class fields, all previously enabled fields are disabled, and only the newly added fields are displayed.

EXAMPLES

COMMAND> ADD CONNECTIONS

This command adds CONNECTIONS class information to the display. This information includes all enabled CONNECTIONS class fields.

COMMAND> ADD CONNECTIONS/TYPE=OPEN

This command adds all Open connections to the SHOW CLUSTER display.
SHOW CLUSTER ADD CONNECTIONS

COMMAND> REMOVE CONNECTIONS COMMAND> ADD SCS_STATE COMMAND> REMOVE CONNECTIONS

.

COMMAND> ADD CONNECTIONS

The ADD CONNECTIONS command adds CONNECTIONS class information to the SHOW CLUSTER display. The first command removes the CONNECTIONS class from the display. The second command, ADD SCS_______ STATE, adds the CONNECTIONS class field SCS__STATE to the display. As a result, all other CONNECTIONS class fields are disabled. When the CONNECTIONS class is removed and added again, only the SCS__STATE field is displayed.

ADD	COL	JNT	ERS
-----	-----	-----	-----

ADD COUNTERS

Adds all currently enabled COUNTERS class fields to the SHOW CLUSTER display.

FORMAT ADD COUNTERS command parameters None. command qualifier /ALL Specifies that all fields in this class be added to the display.

DESCRIPTION The ADD COUNTERS command adds COUNTERS class information to the SHOW CLUSTER display. This information includes data for all currently enabled fields in the COUNTERS class. By default, the DGS______SENT (datagrams sent), DGS__RCVD (datagrams received), MSGS_SENT (messages_sent), and MSGS_RCVD (messages received) fields are enabled. For a list of valid COUNTERS class fields, see the ADD (Field) command.

You use the ADD COUNTERS command together with the REMOVE COUNTERS command to turn the display of COUNTERS class information on and off. If you remove the COUNTERS class from the display and add it again without changing any fields, all of the original fields are once again displayed. If, however, you remove the COUNTERS class and add new COUNTERS class fields, all previously enabled fields are disabled, and only the newly added fields are displayed.

EXAMPLES

COMMAND> ADD COUNTERS

This command adds COUNTERS class information to the display. This information includes all enabled COUNTERS class fields.

2 COMMAND> REMOVE COUNTERS COMMAND> ADD MSGS_SENT COMMAND> REMOVE COUNTERS

COMMAND> ADD COUNTERS

The ADD COUNTERS command in this example adds COUNTERS class information to the SHOW CLUSTER display. The first command removes the COUNTERS class from the display. The second command, ADD MSGS_______ SENT, adds the COUNTERS class field MSGS__SENT to the display. As a result, all other COUNTERS class fields are disabled. When the COUNTERS class is removed and added again, only the MSGS__SENT field is displayed.

SHOW CLUSTER ADD CREDITS

ADD CREDITS

Adds all currently enabled CREDITS class fields to the SHOW CLUSTER display.

FORMAT ADD CREDITS

command parameters

None.

command qualifier

/ALL

Specifies that all fields in this class be added to the display. By default, the ADD CREDITS command, used without any qualifiers, displays all the CREDITS class fields.

DESCRIPTION The ADD CREDITS command adds CREDITS class information to the SHOW CLUSTER display. This information includes data for all currently enabled fields in the CREDITS class. By default, all CREDITS class fields are enabled. For a list of valid CREDITS class fields, see the ADD (Field) command.

You use the ADD CREDITS command together with the REMOVE CREDITS command to turn the display of CREDITS class information on and off. If you remove the CREDITS class from the display and then add it again without changing any fields, all of the original fields are once again displayed. If, however, you remove the CREDITS class and add new CREDITS class fields, all previously enabled fields are disabled, and only the newly added fields are displayed.

EXAMPLES

COMMAND> ADD CREDITS

This command adds CREDITS class information to the display. This information includes all enabled CREDITS class fields.

COMMAND> REMOVE CREDITS COMMAND> ADD MIN_REC COMMAND> REMOVE CREDITS

COMMAND> ADD CREDITS

The ADD CREDITS command in this example adds CREDITS class information to the SHOW CLUSTER display. The first command removes the CREDITS class from the display. The second command, ADD MIN_REC, adds the CREDITS class field MIN_REC to the display. As a result, all other CREDITS class fields are disabled. When the CREDITS class is removed and added again, only the MIN_REC field is displayed.

ADD	ER	RO	RS
-----	----	----	----

ADD ERRORS

Adds all currently enabled ERRORS class fields to the SHOW CLUSTER display.

FORMAT	ADD ERRORS
command parameters	None.
command qualifier	/ALL Specifies that all fields in this class be added to the display. By default, ADD ERRORS, used without any qualifiers, displays all the fields in the errors class.
DESCRIPTION	The ADD ERRORS command adds ERRORS class information to the SHOW CLUSTER display. This information includes data for all currently enabled fields in the ERRORS class. By default, all ERRORS class fields are enabled. For a list of valid ERRORS class fields, see the ADD (Field) command. You use the ADD ERRORS command together with the REMOVE ERRORS command to turn the display of ERRORS class information on and off. If you remove the ERRORS class from the display and add it again without changing any fields, all of the original fields are once again displayed. If, however, you remove the ERRORS class and add new ERRORS class fields, all previously enabled fields are disabled, and only the newly added fields are displayed.

EXAMPLES

COMMAND> ADD ERRORS

This command adds ERRORS class information to the display. This information includes all enabled ERRORS class fields.

COMMAND> REMOVE ERRORS COMMAND> ADD ERT_MAX COMMAND> REMOVE ERRORS

COMMAND> ADD ERRORS

The ADD ERRORS command in this example adds ERRORS class information to the SHOW CLUSTER display. The first command removes the ERRORS class from the display. The second command, ADD ERT_MAX, adds the ERRORS class field ERT_MAX to the display. As a result, all other ERRORS class fields are disabled. When the ERRORS class is removed and added again, only the ERT_MAX field is displayed.

SHOW CLUSTER ADD (Field)

ADD (Field)

Enables the display of specific fields of SHOW CLUSTER information.

FORMAT ADD *field-name[, . . .]*

command

parameters

field-name

Specifies one or more of the following fields of information to be added to the display of a particular class.

CIRCUITS Class

Field Name	Description	
CABLE_STATUS	Status of the circuit paths A and B. Crossed cables are also noted. Possible displays:	
	-	Paths A and B are bad.
	A-	Path A is good.
	-В	Path B is good.
	A-B	Paths A and B are good.
	CROSSED	The cables are crossed.
CIR_STATE	The state of	the virtual circuit. Possible displays:
	CLOSED	The circuit is closed.
	OPEN	The circuit is opened.
	ST_REC	The circuit has a start received.
	ST_SENT	The circuit has a start sent.
	VC_FAIL	A virtual circuit failure is in progress.
LPORT_NAME	The VAX/VI associated w	MS device name of the local port vith the circuit (PAA0, PAB0).
NUM_CONNECTIONS	The number of connections on the circuit between the local and remote system.	
REM_STATE	State of the	remote port. Possible displays:
	DISAB	The remote port is disabled.
	ENAB	The remote port is enabled.
	M_DISAB	The remote port is in maintenance mode and is disabled.
	M_ENAB	The remote port is in maintenance mode and is enabled.
	M_UNINIT	The remote port is in maintenance mode and has not been initialized.
	UNINIT	The remote port has not been initialized.

ADD (Field)

Field Name	Description	Description	
RP_FUNCTIONS	Function mask of the remote port.		
RPORTNUM	The port number of the remote port associated with the circuit.		
RP_OWNER	Port numbe	Port number of the remote port owner.	
RP_REVISION	Hardware a remote port	Hardware and/or microcode revision number of the remote port.	
RP_TYPE	The type of circuit. Pos	the remote port associated with the sible displays:	
	CI780	The remote port is a CI780.	
	CI750	The remote port is a CI750.	
	HSC50	The remote port is an HSC50.	
	CINT	The remote port is a CI node tester.	
	PASSTH	The remote port is in passthrough mode.	
SCS_WAITERS	The number control mes	The number of connections waiting to send SCS control messages on the virtual circuit.	

CLUSTER Class

Field Name	Description		
CL_QDVOTES	The number of quorum votes contributed by the quorum disk.		
CL_QUORUM	The maximum quorum of all current members plus any previous CL_QUORUM value.		
CL_VOTES	The total number of votes held by all cluster members.		
FORMED	The time at which the cluster was formed, expressed as dd-mmm-yy hh:mm.		
LAST_TRANSITION	The last time at which a system left or joined the cluster, expressed as dd-mmm-yy hh:mm.		
MEMSEQ	The membership state sequence number.		
QD_NAME	The full device name of the quorum disk.		
QF_VOTE	Indicates whether or not the quorum disk is contributing any votes towards the cluster quorum.		

SHOW CLUSTER ADD (Field)

CONNECTIONS Class

Field Name	Description	
CON_STATE	The state of the connection. Possible displays:	
	ACCP_SENT	An accept request has been sent
	CLOSED	The connection is closed.
	CON_ACK	A connect request has been sent and acknowledged.
	CON_REC	A connect request has been received.
	CON_SENT	A connect request has been sent
	DISC_ACK	A disconnect request is acknowledged.
	DISCMTCH	A disconnect request is matched.
	DISC_REC	A disconnect request has been received.
	DISC_SENT	A disconnect request has been sent.
	LISTEN	The connection is in the listen state.
	OPEN	The connection is open.
	REJ_SENT	A reject has been sent.
	VCFAIL	A virtual circuit has failed.
LOC_CONID	Identification connection.	number of the local side of the
LOC_PROC_NAME	The name of the local process associated with th connection.	
REM_CONID	Identification number of the remote side of the connection. This information does not apply for connections in the listen state.	
REM_PROC_NAME	The name of the remote process associated with the connection. This information does not apply for connections in the listen state.	
SCS_STATE	SCS send blo waiting to ser the SCS send message it is ACCP_PEND	cked state. If the connection is ad an SCS control block message, blocked state indicates what kind waiting to send. Possible displays: Waiting to send an accept reques
	CLEAR	Not blocked.
	CON_PEND	Waiting to send a connection request.
	CR_PEND	Waiting to send credit.
	DCR_PEND	Waiting to send credit in preparation for a disconnect.
	DISC_PEND	Waiting to send a disconnect request.
	REJ_PEND	Waiting to send a reject request.

ADD (Field)

COUNTERS Class

Field Name	Description
BDT_WAITS	The number of times this connection had to wait for a buffer descriptor.
BLKS_REQ	The number of block-request data commands initiated to block transfer data from the remote system to the local system.
BLKS_SENT	The number of block-send data commands. initiated to block-transfer data from the local system to the remote system .
CR_WAITS	The number of times this connection had to wait for send credit.
DGS_DSCRD	The number of application datagrams discarded by PADRIVER.
DGS_RCVD	The number of application datagrams received by the local system over the connection from the remote system and given to SYSAP.
DGS_SENT	The number of application datagrams sent over the connection.
KB_MAPPED	The number of kilobytes of data mapped for block transfer.
KB_RCVD	The number of kilobytes of data received by the local system from the remote system through request-data commands.
KB_SENT	The number of kilobytes of data sent from the local system to the remote system through send-data commands.
MSGS_RCVD	The number of application datagram messages received over the connection.
MSGS_SENT	The number of application datagram messages sent over the connection.

CREDITS Class

Field Name	Description
INIT_REC	The initial receive credit extended to the remote system when the connection was made.
MIN_REC	The minimum receive credit (minimum send credit required by the remote system).
MIN_SEND	The minimum send credit.
PEND_REC	The receive credit not yet extended to the remote system.
RECEIVE	The receive credit (send credit held by the remote system).
SEND	The current send credit.

SHOW CLUSTER ADD (Field)

ERRORS Class

Field Name	Description
ERT_COUNT	The number of port reinitialization attempts remaining.
ERT_MAX	The total number of times a recovery from fatal port errors can be attempted by shutting down all virtual circuits and connections and reinitializing the port.
NUM_ERRORS	The number of errors that have been logged on the port since the system was booted. This number includes errors encountered in reinitialization attempts as well as recoverable errors, such as virtual circuit failure. This is the same error count as that displayed by the DCL command SHOW DEVICE.

LOCAL_PORTS class

Field Name	Descripti	Description	
BUFF_DESCR	The numb	The number of buffer descriptors in use.	
CMDS_QUEUED	The total port com priorities l	The total number of messages, datagrams, and port commands queued for transmission at all priorities by the port.	
COUNTER_OWNER	The name traffic cou	The name of the process currently using the port traffic counters.	
DGI_MAP	A 16-bit digits. Ea cluster fro disabled.	A 16-bit bit map displayed as four hexadecimal digits. Each bit in the map represents a port in the cluster from which datagram reception has been disabled.	
DG_OVRHD_SIZE	The numb and DECn	The number of bytes of port header, SCS header, and DECnet header in a datagram.	
DGS_FREE	The numb queued fo	The number of free datagram buffers currently queued for receive commands.	
FORM_CIRCS	The numb process o	The number of formative circuits (circuits in the process of opening) from the port.	
FREEBUFF	The numb	The number of CI buffer descriptors free for use.	
LB_STATUS	The loopt the star c	back status of each cable from the port to oupler. Possible displays:	
	A-B	Loopback tests pass on paths A and B.	
	A-	Loopback tests pass on path A.	
	-В	Loopback tests pass on path B.	
	-	Loopback tests failed on paths A and B.	
	N/A	Loopback tests are not being done.	

ADD (Field)

Field Name	Description	
LOG_MAP	A 16-bit bit map displayed as four hexadecimal digits. Each bit in the map represents a port in the cluster for which an error was logged. Errors are logged when data provided by the configuration database on the local system conflicts with data provided by the remote system. When a conflict is discovered and an error is logged, virtual circuits to the remote system can no longer be established.	
LP_STATUS	The status of the local port. Possible displays: OFFLINE The port is off line.	
	ONLINE The port is on line.	
LPTYPE	The device type of the port (CI780, CI750, HSC).	
MAX_PORT	The largest port number to which a virtual circuit open is attempted.	
MSGS_FREE	The number of free message buffers currently queued for receives commands.	
MSG_HDR_SIZE	The number of bytes of port header and SCS header in a message.	
NAME	The VAX/VMS device name of the local port.	
OPEN_CIRCS	The number of virtual circuits open from the port.	
POOL_WAITERS	The number of processes waiting for nonpaged pool resources for message buffers.	
PORT_NUM	The port number assigned to the port.	
PRT_MAP	A 16-bit bit map displayed as three hexadecimal digits. Each bit in the map represents a port in the cluster that has been recognized by the host system.	
RSPS_QUEUED	The total number of responses of all kinds received from the port but not yet processed.	

MEMBERS Class

Field Name	Description
ACK_LIM	The maximum number of VAXcluster messages the remote system can receive before sending an acknowledgment reply.
ACKR_SQ	The sequence number of the last acknowledgment received over the VAXcluster connection.

SHOW CLUSTER ADD (Field)

Field Name	Description		
CNX_STATE	The state of the VAXcluster connection. Possible displays:		
	ACCEPT	The initial connection is accepted.	
	CLOSED	The connection is closed.	
	CONNECT	The initial connection is being accepted.	
	DEAD	No connection is possible.	
	DISCONNECT	A disconnection is in progress.	
	NEW	No attempt to make a connection has been made yet.	
	OPEN	The connection is open.	
	REACCEPT	The connection is accepting the reconnect request.	
	RECONNECT	The connection is attempting to reconnect.	
	WAIT	A timeout is in progress.	
CSID	The cluster system identification number. This number is unique over the life of the cluster. Unlike SYS_ID, this identification number may change when the system reboots.		
DIR_WT	The lock manager distributed directory weight.		
PROTOCOL	The protocol version number and ECO level of the connection management software.		
QDVOTES	The number of votes the remote system recommends be contributed by the quorum disk. Normally, the cluster manager sets this number using the SYSGEN parameter QDSKVOTES.		
QF_ACTIVE	Indicates whe is accessible.	Indicates whether the remote system's quorum file is accessible.	
QF_SAME	Indicates whe agree about w	Indicates whether the local and remote systems agree about which disk is the quorum disk.	
QUORUM	The recomme remote syster sets the recor using the SYS	The recommended quorum value set for the remote system. Normally, the cluster manager sets the recommended quorum value for a node using the SYSGEN parameter QUORUM.	
RCVD_SQ	The sequence over the VAX	The sequence number of the last message received over the VAXcluster connection.	
SEND_SQ	The sequence number of the next message to be sent over the VAXcluster connection.		

ADD (Field)

Field Name	Description		
STATUS	The status of the node in the cluster. Possible displays:		
	blank	The system is not being considered as a cluster member.	
	BRK_MEM	The system is a member of the cluster, but the connection manager has lost communication with it.	
	BRK_NEW	The system has just booted, but has not yet joined the cluster and the connection manager has lost communication with it.	
	BRK_NON	The connection manager has lost communication with the system and the system is no longer a member of the cluster.	
	BRK_REM	The connection manager has lost communication with the system, and the system has been removed from the cluster.	
	MEMBER	The system is participating in the cluster. (A default SYSGEN parameter allows a 90-second delay before a failing system is removed from cluster membership status.)	
	NEW	The system has just booted, but has not yet joined the cluster. If this system would normally be a member of the cluster and is displaying NEW in this field, you can expect that the display will eventually change to MEMBER.	
	NON	The system is not a member of the cluster.	
	REMOVED	The system has been removed from the cluster.	
TRANSITION_TIME	The time of membership	The time of the system's last change in membership status (see the STATUS field).	
UNACKED	The number messages re	of unacknowledged VAXcluster ceived by the remote system.	
VOTES	The number toward quoru sets this nun VOTES.	The number of votes the remote node contributes toward quorum. Normally, the cluster manager sets this number with the SYSGEN parameter VOTES.	
WARMCDRPS	The number	of CDRPs on the CDRP free queue.	

SHOW CLUSTER ADD (Field)

SYSTEMS Class (for CLUSTER report)

Field Name	Description	
DG_SIZE	The maximum number of bytes of application data in datagrams sent over the circuit.	
HW_TYPE	The system hardware type (V780, V785, V750, HS50).	
HW_VERS	The revision level of the computer interconnect hardware on the remote system.	
INCARNATION	A unique 16-digit hexadecimal number established when the system is booted.	
INCN_TIME	The incarnation number expressed as a time (dd-mmm-yy hh:mm).	
MSG_SIZE	The maximum number of bytes of application data in messages sent over the circuit.	
NODE	The node name of the remote system. Normally, the cluster manager sets the node name using the SYSGEN parameter SCSNODE. The node name should be the same as the DECnet node name.	
	The number of virtual circuits between the local system and remote systems.	
SOFTWARE	The name and version of the operating system currently running on the remote system.	
SYS_ID	The identification number of the remote system. Normally, the cluster manager sets this number using the SYSGEN parameters SCSSYSTEMID and SCSSYSTEMIDH. This number should be the same as the DECnet node number.	

If you specify more than one field name, insert a comma between each one and the next.

command qualifiers None. DESCRIPTION The ADD (Field) command enables and adds specific fields of information to a SHOW CLUSTER display. When you add a field for a class that is not currently being displayed, the class heading of that field is added to the display.

To remove a field from the SHOW CLUSTER display, use the REMOVE (Field) command.

EXAMPLES

COMMAND> ADD SEND

This command enables the CREDITS class field SEND and adds it to the SHOW CLUSTER display.

ADD (Field)

2 COMMAND> ADD REM_STATE, REM_CONID, LOC_CONID

This command enables the CIRCUITS class field REM_STATE and the CONNECTIONS class fields REM_CONID and LOC_CONID, and adds them to the SHOW CLUSTER display.

ADD LOCAL_PORTS

ADD LOCAL_PORTS

Adds all currently enabled LOCAL_PORTS class fields to the SHOW CLUSTER display.

FORMAT ADD LOCAL_PORTS

command parameters

None.

command

/ALL Specifies that all fields in this class be added to the display.

qualifier S

DESCRIPTION The ADD LOCAL_PORTS command adds LOCAL_PORTS class information to the SHOW CLUSTER display. This information includes data for all currently enabled fields in the LOCAL_PORTS class. By default, the NAME, STATUS, PORT_NUM (port number), DGS_FREE (free datagrams queued), and MSGS_FREE (free messages queued),OPEN_CIRCS (open circuits), FORM_CIRCS (formative circuits) fields are enabled. For a list of valid LOCAL_PORTS class fields, see the ADD (Field) command.

> You use the ADD LOCAL_PORTS command together with the REMOVE LOCAL_PORTS command to turn the display of LOCAL_PORTS class information on and off. If you remove the LOCAL_PORTS class from the display and add it again without changing any fields, all of the original fields are once again displayed. If, however, you remove the LOCAL_PORTS class and add new LOCAL_PORTS class fields, all previously enabled fields are disabled, and only the newly added fields are displayed.

EXAMPLES

COMMAND> ADD LOCAL_PORTS

This command adds LOCAL_PORTS class information to the display. This information includes all enabled LOCAL_PORTS class fields.

COMMAND> REMOVE LOCAL_PORTS COMMAND> ADD LB_STATUS COMMAND> REMOVE LOCAL_PORTS

COMMAND> ADD LOCAL_PORTS

The ADD LOCAL_PORTS command in this example adds LOCAL_PORTS class information to the SHOW CLUSTER display. The first command removes the LOCAL_PORTS class from the display. The second command, ADD LB_STATUS, adds the LOCAL_PORTS class field LB_STATUS to the display. As a result, all other LOCAL_PORTS class fields are disabled. When the LOCAL_PORTS class is removed and added again, only the LB_STATUS field is displayed.

ADD	MEN	IBERS
-----	-----	--------------

ADD MEMBERS

Adds all currently enabled MEMBERS class fields to the SHOW CLUSTER display.

FORMAT	ADD MEMBERS		
command parameters	None. /ALL Specifies that all fields in this class be added to the display.		
command qualifier			
DESCRIPTION	The ADD MEMBERS command adds MEMBERS class information to the SHOW CLUSTER display. This information includes data for all currently enabled fields in the MEMBERS class. By default, the STATUS field is enabled. For a list of valid MEMBERS class fields, see the ADD (Field) command.		
	You use the ADD MEMBERS command together with the REMOVE MEMBERS command to turn the display of MEMBERS class information on and off. If you remove the MEMBERS class from the display and add it again without changing any fields, all of the original fields are once again displayed. If, however, you remove the MEMBERS class and add new MEMBERS class fields, all previously enabled fields are disabled, and only the newly added fields are displayed.		
EXAMPLES			
COMMAND> ADD MEMBERS			
	The command in this example adds MEMBERS class information to the display. This information includes all enabled MEMBERS class fields.		
COMMAND> REMOVE MEMB COMMAND> ADD VOTES	ERS		

COMMAND> ADD MEMBERS

•

COMMAND> REMOVE MEMBERS

The ADD MEMBERS command in this example adds MEMBERS class information to the SHOW CLUSTER display. The first command removes the MEMBERS class from the display. The second command, ADD VOTES, adds the MEMBERS class field VOTES to the display. As a result, all other MEMBERS class fields are disabled. When the MEMBERS class is removed and added again, only the VOTES field is displayed.

ADD SYSTEMS

Adds all currently enabled SYSTEMS class fields to the SHOW CLUSTER display.

FORMAT ADD SYSTEMS [/qualifier[, . . .]]

command

parameters command

qualifier

None.

/ALL

Specifies that all fields in the SYSTEMS class are added to the display.

/ID = system-id

Specifies, by system identification number, systems to be added to the SHOW CLUSTER display. The system-id number can be any system-id as displayed in the SYSID field of the SYSTEMS class.

The /ID qualifier affects all information displayed about the specified system, not just information in the SYSTEMS class display.

/NODE=node-name

Specifies, by node name, systems to be added to the SHOW CLUSTER display. The /NODE qualifier affects all information displayed about the specified node, not just information in the SYSTEMS class display.

/TYPE=hardware-type

Specifies, by hardware type, systems to be added to the SHOW CLUSTER display. You can specify any of the following hardware types:

- V750 for VAX–11/750 systems
- V780 for VAX-11/780 systems
- V785 for VAX-11/785 systems
- HS50 for HSC50 systems
- 8200 for VAX 8200 systems
- 8600 for VAX 8600 systems

The /TYPE qualifier affects all information displayed about the specified hardware type, not just information in the SYSTEMS class display.

DESCRIPTION The ADD SYSTEMS command adds SYSTEMS class information to the SHOW CLUSTER display. This information includes data for all currently enabled fields in the SYSTEMS class. By default, the NODE and SOFTWARE fields are enabled. For a list of valid SYSTEMS class fields, see the ADD (Field) command.

ADD SYSTEMS

You use the ADD SYSTEMS command together with the REMOVE SYSTEMS command to turn the display of SYSTEMS class information on and off. If you remove the SYSTEMS class from the display and add it again without changing any fields, all of the original fields are once again displayed. If, however, you remove the SYSTEMS class and add new SYSTEMS class fields, all previously enabled fields are disabled, and only the newly added fields are displayed.

EXAMPLES

COMMAND> ADD SYSTEMS

This command adds SYSTEMS class information to the display. This information includes all enabled SYSTEMS class fields.

COMMAND> ADD SYSTEMS/NODE=MISHA

This command adds the node MISHA to the SHOW CLUSTER display reporting all currently enabled information about the node.

COMMAND> REMOVE SYSTEMS COMMAND> ADD SYS_ID COMMAND> REMOVE SYSTEMS

COMMAND> ADD SYSTEMS

The ADD SYSTEMS command in this example adds SYSTEMS class information to the SHOW CLUSTER display. The first command removes the SYSTEMS class from the display. The second command, ADD SYS_ID, adds the SYSTEMS class field SYS_ID to the display. As a result, all other SYSTEMS class fields are disabled. When the SYSTEMS class is removed and added again, only the SYS_ID field is displayed.

DEFINE/KEY

Associates an equivalence string and set of attributes with a key on the terminal keyboard. The /KEY qualifier is required.

FORMAT DEFINE/KEY key-name equivalence-string

command

parameter

key-name

Specifies the name of the key that you are defining. Use the following key names when defining keys:

Key Name	LK201	VT100-Type	VT52
PF1	PF1	PF1	[blue]
PF2	PF2	PF2	[red]
PF3	PF3	PF3	[gray]
PF4	PF4	PF4	
KPO, KP1 through KP9	0, 1 through 9	0, 1 through 9	0, 1 through 9
PERIOD			
COMMA	,	,	n/a
MINUS	-	-	n/a
ENTER	Enter	ENTER	ENTER
Find (E1)	Find		
Insert Here (E2)	Insert Here		
Remove (E3)	Remove		
Select (E4)	Select		
Prev Screen (E5)	Prev Screen		
Next Screen (E6)	Next Screen		
HELP	Help		
DO	Do		
F17 through F20	F17 through F20		

You cannot redefine the arrow keys or the function keys 1 through 14.

equivalence-string

Specifies the string which is to be processed when you press the key. The string can be a SHOW CLUSTER command. If the string contains any spaces, enclose the equivalence string in quotation marks.

DEFINE/KEY

command qualifiers

/ECHO (default) /NOECHO

Determines whether the equivalence string is displayed on your screen after the key has been pressed. You cannot use /NOECHO with the /NOTERMINATE qualifier.

/ERASE /NOERASE (default)

Determines whether the current line is erased before the key translation is inserted.

/IF_STATE=(state-name, . . .) /NOIF_STATE

Specifies a list of one or more states, one of which must take effect for the key definition to be in effect. If you omit the /IF_STATE qualifier or use /NOIF_STATE, the current state is used.

/LOCK_STATE /NOLOCK_STATE (default)

Specifies that the state set by the /SET_STATE qualifier remain in effect until explicitly changed. If you use the /NOLOCK_STATE qualifier, the state set by /SET_STATE is in effect only for the next definable key that you press or for the next read-terminating character that you type.

The /LOCK_STATE qualifier can only be specified with the /SET_STATE qualifier.

/LOG (default) /NOLOG

Controls whether the system displays a message indicating that the key definition has been successfully created.

/SET_STATE=state-name /NOSET_STATE (default)

Causes the specified state-name to be set when the key is pressed. The state name can be any alphanumeric string.

If you omit the SET_STATE qualifier or use /NOSET_STATE, the current state that was locked remains in effect. If you have not included this qualifier with a key definition, you can use the SET KEY command to change the current state.

/TERMINATE /NOTERMINATE (default)

Specifies whether the current equivalence string is to be terminated (that is, processed) when the key is pressed. Pressing RETURN has the same effect as using /TERMINATE.

The /NOTERMINATE qualifier allows you to create key definitions that insert text into command lines, after prompts, or into other text that you are typing.

SHOW CLUSTER DEFINE/KEY

DESCRIPTION The DEFINE/KEY command enables you to assign definitions to the keys on certain terminals. The terminals include VT52s, the VT100 series, and terminals with LK201 keyboards.

The equivalence string definition can contain different types of information. Definitions can consist of SHOW CLUSTER commands. When you define a key to insert a text string, use the /NOTERMINATE qualifier so that you can continue typing more data after the string has been inserted.

In most instances you will want to take advantage of the echo feature. The default setting is /ECHO. With the /ECHO qualifier set, the key definition is displayed on the screen each time you press the key.

You can use the /STATE qualifier to increase the number of key definitions available on your terminal. The same key can be assigned any number of definitions as long as each definition is associated with a different state. State names can contain any alphanumeric characters, dollar signs, and underscores. Generally, you will want to create a state name that is easy to remember and type and, if possible, one that might remind you of the types of definitions you created for that state.

EXAMPLE

COMMAND> DEFINE/KEY PF3 "LOCAL_PORT"/NOTERMINATE

The DEFINE/KEY command defines the PF3 key on the keypad to output the "LOCAL_PORT" text string. This key could be used with the ADD key to form the ADD LOCAL_PORT command.

DESELECT

Terminates the selection of a previously selected window.

FORMAT	DESELECT	
command parameters	None.	
command qualifiers	None.	
EXAMPLE		
COMMAND> SELECT COMMAND> MOVE RIGHT 10		
COMMAND> DESELECT		

In this example, the SELECT command selects a window and highlights it. A MOVE operation is then performed on the selected window. The DESELECT command terminates the selection and moves the window to its new position. If you enter another SELECT command, it automatically deselects and moves the previously selected window.

EXIT	
	Terminates the SHOW CLUSTER display and returns control to the DCL command level. You can also type CTRL/C or CTRL/Z to exit at any time.
FORMAT	EXIT
command parameters	None.
command qualifiers	None.
EXAMPLE	

COMMAND> EXIT

This command terminates the SHOW CLUSTER display and returns control to the DCL command level.

HELP

HELP

Provides online help information for using the SHOW CLUSTER commands, parameters, and qualifiers.

FORMAT	HELP [keyword]	
command parameter	keyword Specifies the command, parameter, or qualifier for which help information is to be displayed. If you omit the keyword, HELP displays a list of available help topics, and prompts you for a particular keyword.	
command qualifiers	None.	
EXAMPLES		
COMMAND> HELP IN	ITIALIZE	

The command in this example displays help information about the SHOW CLUSTER command, INITIALIZE.

2 COMMAND> HELP Fields

The command in this example displays help information about the valid field names that can be specified with the ADD, REMOVE, and SET commands.

SHOW CLUSTER INITIALIZE

INITIALIZE

Resets the display using the default values for field names, class names, and field widths. It also restores any systems that were removed from the display by the REMOVE SYSTEMS command.

FORMAT INITIALIZE

EXAMPLE

COMMAND> INITIALIZE

This command resets the current display to the default display and restores any systems that were removed from the display.

MOVE

MOVE	
	Moves a selected window to a specified position.
FORMAT	MOVE direction value
command parameter	direction Direction in which the window is to be moved. If you do not enter a direction for this parameter, SHOW CLUSTER prompts you for one. You must specify one of the following keywords:
	DOWN RIGHT LEFT
	value Number of columns or lines the window is to be moved. You must specify a numeric value from 1 to 512. If you do not enter a number for this parameter, SHOW CLUSTER prompts you for one.
command qualifiers	None.
DESCRIPTION	The MOVE command allows you to manually reposition a window on the display screen. You must first issue the command SET AUTO POSITIONING OFF, which disables the default automatic positioning of windows. Then select a window to be moved by using the SELECT command.
	To move a selected window, you either enter MOVE commands at the command prompt, or use the arrow keys defined as MOVE commands. Issuing the command SET FUNCTION MOVE redefines the \uparrow , \downarrow , \rightarrow , and \leftarrow arrow keys as MOVE UP 1, MOVE DOWN 1, MOVE RIGHT 1, and MOVE LEFT 1, respectively.
Note:	The SET FUNCTION MOVE command implicitly sets AUTO_ POSITIONING to OFF.
	When you issue a MOVE command, the window changes position by column (horizontally), or by line (vertically). An empty frame appears around the new window position. When you are satisfied with the position of the window, issue the DESELECT command, which moves the window to the new position. Entering another SELECT command before the previous window has been deselected also moves the window to its new position.

SHOW CLUSTER MOVE

EXAMPLE

COMMAND> SET AUTO_POSITIONING OFF COMMAND> SELECT CLUSTER COMMAND> MOVE RIGHT 10 COMMAND> DESELECT

This command sequence moves the CLUSTER window ten columns to the right.

PAN

PAN Pans the display screen. **PAN** direction value FORMAT direction command Direction in which the display is to be panned. If you do not enter a direction parameter for this parameter, SHOW CLUSTER prompts you for one. You must specify one of the following keywords: UP DOWN RIGHT LEFT value Number of columns or lines the display is to be panned. You must specify a numeric value from 1 to 512. If you do not enter a number for this parameter, SHOW CLUSTER prompts you for one. None. command qualifiers DESCRIPTION PAN commands pan the entire display by column (horizontally) and by line (vertically). The PAN command functions in a way similar to the panning of a video camera. By issuing PAN commands, a portion of the display that extends beyond the limits of the screen can be brought into view. The display moves in the opposite direction from that specified by the PAN command. In other words, a PAN LEFT 10 command moves the display 10 columns to the right, similar to the effect of panning a camera over a landscape. To pan the display, either enter PAN commands at the command prompt, or use the arrow keys defined as PAN commands. Issuing the command SET FUNCTION PAN redefines the \uparrow , \downarrow , \rightarrow , and \leftarrow arrow keys as PAN UP 1, PAN DOWN 1, PAN RIGHT 1, and PAN LEFT 1, respectively. Note: If you set the function to PAN, the arrow keys are no longer defined to perform DCL line-mode editing. Only one function can be enabled at a time.

EXAMPLE

COMMAND> PAN DOWN 10

This command sequence pans the display ten lines.

SHOW CLUSTER REFRESH

REFRESH

Clears the screen, removes extraneous characters, and updates all fields. Entering CTRL/W has the same effect as typing REFRESH.

FORMAT	REFRESH
command parameters	None.
command qualifiers	None.

EXAMPLE

COMMAND> REFRESH

This command clears the screen, removes extraneous characters, and updates all fields.

REMOVE CIRCUITS

REMOVE CIRCUITS

Removes CIRCUITS class information from the SHOW CLUSTER display.

FORMAT REMOVE CIRCUITS [/qualifier[, . . .]]

command

parameters command

qualifiers

/TYPE=ALL

None.

Specifies that all types of circuits on each system be removed from the display, including formative, open, and closing circuits. If you specify the REMOVE CIRCUITS command without any qualifiers, all types of circuits are removed from the display by default.

/TYPE=OPEN /TYPE=NOOPEN

Controls whether either open circuits or nonopen circuits are removed from the display.

DESCRIPTION The REMOVE CIRCUITS command removes CIRCUITS class information from the SHOW CLUSTER display. CIRCUITS class information includes data for all currently enabled fields in the CIRCUITS class. For a list of valid CIRCUITS class fields, see the ADD (Field) command.

EXAMPLES

COMMAND> REMOVE CIRCUITS

This command removes all currently enabled CIRCUITS class fields from the display.

COMMAND> REMOVE CIRCUITS/TYPE=OPEN

This command removes all open circuits from the display.

SHOW CLUSTER REMOVE CLUSTER

REMOVE CLUSTER

Removes CLUSTER class information from the SHOW CLUSTER display.

DESCRIPTION The REMOVE CLUSTER command removes CLUSTER class information from the SHOW CLUSTER display. CLUSTER class information includes data for all currently enabled fields in the CLUSTER class. For a list of valid CLUSTER class fields, see the ADD (Field) command.

EXAMPLE

COMMAND> REMOVE CLUSTER

This command removes all currently enabled CLUSTER class fields from the SHOW CLUSTER display.

REMOVE CONNECTIONS

REMOVE CONNECTIONS

None.

Removes CONNECTIONS class information from the SHOW CLUSTER display.

FORMAT REMOVE CONNECTIONS [/qualifier[, . . .]]

command

parameters command qualifiers

/TYPE=ALL

Specifies that all types of connections on each circuit be removed from the SHOW CLUSTER display. If you specify the ADD CONNECTIONS command without any qualifiers, all connections are removed from the display by default.

/TYPE=OPEN /TYPE=NOOPEN

Controls whether either open connections or nonopen connections are removed from the SHOW CLUSTER display.

DESCRIPTION

N The REMOVE CONNECTIONS command removes CONNECTIONS class information from the SHOW CLUSTER display. CONNECTIONS class information includes data for all currently enabled fields in the CONNECTIONS class. For a list of valid CONNECTIONS class fields, see the ADD (Field) command.

EXAMPLES

1 COMMAND> REMOVE CONNECTIONS

The command in this example removes all currently enabled CONNECTIONS class fields from the SHOW CLUSTER display.

COMMAND> REMOVE CONNECTIONS/TYPE=OPEN

The command in this example removes all OPEN connections from the SHOW CLUSTER display.

SHOW CLUSTER REMOVE COUNTERS

REMOVE COUNTERS

Removes COUNTERS class information from the SHOW CLUSTER display.

FORMAT REMOVE COUNTERS

command

_

None.

None.

command qualifiers

parameters

DESCRIPTION The REMOVE COUNTERS command removes COUNTERS class information from the SHOW CLUSTER display. COUNTERS class information includes data for all currently enabled fields in the COUNTERS class. For a list of valid COUNTERS class fields, see the ADD (Field) command.

EXAMPLE

COMMAND> REMOVE COUNTERS

This command removes all currently enabled COUNTERS class fields from the SHOW CLUSTER display.

R	EN	ЛC	VE	CR	ED	ITS
---	----	----	----	----	----	-----

REMOVE CREDITS

Removes CREDITS class information from the SHOW CLUSTER display.

FORMAT	REMOVE CREDITS			
command parameters	None. None.			
command qualifiers				
DESCRIPTION	The REMOVE CREDITS command removes CREDITS class information from the SHOW CLUSTER display. CREDITS class information includes data for all currently enabled fields in the CREDITS class. For a list of valid CREDITS class fields, see the ADD (Field) command.			

EXAMPLE

COMMAND> REMOVE CREDITS

This command removes all currently enabled CREDITS class fields from the SHOW CLUSTER display.

SHOW CLUSTER REMOVE ERRORS

REMOVE ERRORS

Removes ERRORS class information from the SHOW CLUSTER display.

FORMAT REMOVE ERRORS

DESCRIPTION The REMOVE ERRORS command removes ERRORS class information from the SHOW CLUSTER display. ERRORS class information includes data for all currently enabled fields in the ERRORS class. For a list of valid ERRORS class fields, see the ADD (Field) command.

EXAMPLE

COMMAND> REMOVE ERRORS

This command removes all currently enabled ERRORS class fields.

REMOVE (Field)

REMOVE (Field)

Disables the display of specific fields of SHOW CLUSTER information.

FORMAT	REMOVE field-name[,]			
command parameter	field-name Specifies one or more fields of information to be removed from the display of a particular class. If you specify more than one field name, insert a comma between each one and the next. For a list of valid field names, see the ADD (Field) command description.			
command qualifiers	None.			

EXAMPLES

1 COMMAND> REMOVE SOFTWARE

This command removes the SYSTEMS class field SOFTWARE from the display.

2 COMMAND> REMOVE SOFTWARE, RP_TYPE, CON_STATE

The command in this example removes the SOFTWARE, RP_TYPE, and CON_STATE fields from the SHOW CLUSTER display.
SHOW CLUSTER REMOVE LOCAL_PORTS

REMOVE LOCAL_PORTS

Removes LOCAL_PORTS class information from the SHOW CLUSTER display.

FORMAT REMOVE LOCAL_PORTS command parameters None. command qualifiers None. DECODUDTION The REMOVE LOCAL_PORTS command removes LOCAL_PORTS class

DESCRIPTION The REMOVE LOCAL_PORTS command removes LOCAL_PORTS class information. For a list of valid LOCAL_PORTS class fields, see the ADD (Field) command.

EXAMPLE

COMMAND> REMOVE LOCAL_PORTS

This command removes all currently enabled LOCAL_PORTS class fields from the LOCAL_PORTS display.

REMOVE MEMBERS

REMOVE MEMBERS

Removes MEMBERS class information from the SHOW CLUSTER display.

FORMAT	REMOVE MEMBERS	
command parameters	None.	
command qualifiers	None.	
DESCRIPTION	The REMOVE MEMBERS command removes MEMBERS class information from the SHOW CLUSTER display. MEMBERS class information includes data for all actively participating members of the cluster. For a list of valid MEMBERS class fields, see the ADD (Field) command.	

EXAMPLE

COMMAND> REMOVE MEMBERS

This command removes all currently enabled MEMBERS class fields from the SHOW CLUSTER display.

REMOVE SYSTEMS

REMOVE SYSTEMS

Removes SYSTEMS class information from the SHOW CLUSTER display.

FORMAT REMOVE SYSTEMS [/qualifier[, . . .]]

command

parameters command

qualifiers

/ID = system-id

None.

Specifies, by system identification number, systems to be removed from the SHOW CLUSTER display. The system identification number can be any system identification as displayed in the SYSID field of the SYSTEMS class of the CLUSTER report.

The /ID qualifier affects all information displayed about the specified system, not just information in the SYSTEMS class display.

/NODE=node-name

Specifies, by node name, systems to be removed from the SHOW CLUSTER display. The /NODE qualifier affects all information displayed about the specified node, not just information in the SYSTEMS class display.

/TYPE=hardware-type

Specifies, by hardware type, systems to be removed from the SHOW CLUSTER display. You can specify any of the following hardware types:

- V750 for VAX-11/750 systems
- V780 for VAX-11/780 systems
- V785 for VAX-11/785 systems
- HS50 for HSC50 systems
- 8200 for VAX 8200 systems
- 8600 for VAX 8600 systems

The /TYPE qualifier affects all information displayed about the specified hardware type, not just information in the SYSTEMS class display.

DESCRIPTION The REMOVE SYSTEMS command removes SYSTEMS class information from the SHOW CLUSTER display. SYSTEMS class information includes data for all currently enabled fields in the SYSTEMS class. For a list of valid SYSTEMS class fields, see the ADD (Field) command.

REMOVE SYSTEMS

EXAMPLES

COMMAND> REMOVE SYSTEMS

This command removes all currently enabled SYSTEMS class fields from the SHOW CLUSTER display.

COMMAND> REMOVE SYSTEMS/TYPE=V780

This command removes all VAX-11/780 systems from the SHOW CLUSTER display.

SHOW CLUSTER SAVE

Allows you to build a command procedure based on the currend display. You can then use the command procedure to format subsequent displays.	nt		
FORMAT SAVE [file-spec]	SAVE [file-spec]		
command parameterfile-specFile specification of the command file. The file name defaults to SHOW CLUSTER.COM. Since the file is an ASCII file, you can edit it.	file-spec File specification of the command file. The file name defaults to SHOW_ CLUSTER.COM. Since the file is an ASCII file, you can edit it.		
command None. qualifiers			
DESCRIPTION The SAVE command allows you to build a command procedure that you use in subsequent SHOW CLUSTER sessions. To use the SAVE comma	u can nd:		
 Customize the display to meet your needs by using SHOW CLUST commands. 	ER		
2 Enter the SAVE command. By default, the command procedure created named SHOW_CLUSTER.COM. If you want a name that is different the default, specify the alternate name on the SAVE command line.	ted is t from		
The file that results from the SAVE command is an ASCII file. You can edit the file to add comments or to improve its efficiency. In some case particular command procedure may not be as efficient as possible becau commands that the SAVE command builds are restricted to one record. example, the SAVE command processes "ADD class", "ADD class /ALL "ADD (Field)" commands separately. It does not combine an "ADD class an "ADD (Field)" command to produce the command "ADD class,field".	n s, a se the For ", and s" and		
Additionally, the SAVE command does not use the "REMOVE (Field)" command. For example, the following command sequence adds all fiel in the circuits class and then removes one field in the circuit class:	ds		
ADD CIRCUITS/ALL REMOVE RP_TYPE			
Subsequently using the SAVE command produces a file with commands add every field in the circuits class except RP_TYPE:	that		
ADD LPORT_NAME, RPORT_NUM, RP_OWNER, NUM_CONNECTIONS, CIR_STATE ADD REM_STATE, CABLE_STATUS, RP_REVISION, RP_FUNCTIONS, SCS_WAITERS			

SAVE

EXAMPLE

COMMAND> ADD CLUSTER COMMAND> REMOVE SOFTWARE COMMAND> SAVE

The first two commands customize the SHOW CLUSTER display. The third command, SAVE, creates a command file, SHOW_CLUSTER.COM, which contains the following commands:

INITIALIZE ADD CLUSTER REMOVE SYSTEMS ADD NODE

SCROLL

Scrolls a selected window.

FORMAT SCROLL direction value

command parameter

direction

Direction in which a window is to be scrolled. If you do not enter a direction for this parameter, SHOW CLUSTER prompts you for one. You must specify one of the following keywords:

UP DOWN RIGHT LEFT

value

None.

Number of fields or lines a window is to be scrolled. You must specify a numeric value from 1 to 512. If you do not enter a number for this parameter, SHOW CLUSTER prompts you for one.

command qualifiers

DESCRIPTION The SCROLL command provides a means of quickly scanning through a window by field (horizontally) and by line (vertically). You can scroll windows independently. Note, however, that if AUTO_POSITIONING is set to ON, other windows in the display may change position as you scroll the selected window.

To scroll a window, you must first select a window by issuing the SELECT command. The selected window is highlighted. You issue SCROLL commands either by entering them at the command line or by pressing the arrow keys. Issuing the command SET FUNCTION SCROLL redefines the \uparrow , \downarrow , \rightarrow , and \leftarrow arrow keys as SCROLL UP 1, SCROLL DOWN 1, SCROLL RIGHT 1, and SCROLL LEFT 1, respectively.

Use the vertical and horizontal lines of the window fields as indicators of the current position of the display. Note that the window headings remain stationary as lines of data are scrolled vertically.

EXAMPLE

COMMAND> SELECT SCS COMMAND> SCROLL UP 10 COMMAND> DESELECT

This command sequence scrolls the SCS window up ten lines.

SELECT

Selects a window to be scrolled or moved.			
SELECT [window-name]			
window-name The name of the selected window. You can specify one of the following window names: SCS, LOCAL_PORTS, or CLUSTER.			
None.			
You select a window either by issuing a SELECT command at the command line prompt, or by pressing the SELECT key on the default keypad.			
If you press the SELECT key on the keypad or issue the SELECT command without specifying the window name, SHOW CLUSTER selects a window for you. Pressing the SELECT key repeatedly cycles through the windows in the order in which they were initially added to the screen. Each subsequent SELECT command terminates the previous one. The currently selected window is highlighted. When the last window in the cycle has been selected, pressing the SELECT key another time begins the cycle again. You use the SELECT command to identify a window to be moved or scrolled. By default, no window is selected and the function is set to EDIT. For more information, see the SET FUNCTION, SCROLL, and MOVE commands.			

EXAMPLE

COMMAND> SELECT LOCAL_PORTS

This command sequence selects the LOCAL_PORTS window. You can then perform a MOVE or SCROLL operation on the selected window.

SHOW CLUSTER SET AUTO_POSITIONING

SET AUTO_POSITIONING

Enables or disables the automatic positioning of windows within a display.

FORMAT SET AUTO_POSITIONING keyword

command keyword Specifies whether or not windows are automatically positioned within a parameter display. By default, SHOW CLUSTER operates with AUTO_POSITIONING enabled. Valid keywords are: ON OFF None. command qualifiers By default, SHOW CLUSTER automatically positions windows based on their DESCRIPTION size and the order in which they were originally added to the display. With AUTO_POSITIONING set to ON, windows do not overlap, but they may extend partially or fully beyond the physical limits of the terminal screen. Setting AUTO_POSITIONING to OFF allows you to control the position of a window within the display. When you use MOVE commands to position a selected window manually, the windows are allowed to overlap. For additional information on moving windows, see the MOVE and SET FUNCTION commands and Section 3.5.3. Note: Setting the function to MOVE implicitly disables AUTO_POSITIONING.

EXAMPLE

COMMAND> SET AUTO_POSITIONING OFF COMMAND> SELECT CLUSTER COMMAND> MOVE RIGHT 5 COMMAND> MOVE DOWN 10 COMMAND> DESELECT

This command sequence disables AUTO_POSITIONING, selects the CLUSTER window, and moves it to a new position in the display.

SET (Field)

Modifies the characteristics of particular fields within the display. SET field-name /qualifier[,] field-name Specifies the name of the field to be modified in the display. For a list of field names, see the ADD (Field) command. //WIDTH = field-width Specifies the number of columns used to display the specified field. This qualifier lets you shrink the display to allow room for more fields or expand it to make it easier to read. Minimum, maximum, and default values for field widths are set up internally. If you specify a field width of 0, the field is set to its minimum width. If you specify a field width that is larger than the internal maximum width, the field
SET field-name /qualifier[,] field-name Specifies the name of the field to be modified in the display. For a list of field names, see the ADD (Field) command. /WIDTH = field-width Specifies the number of columns used to display the specified field. This qualifier lets you shrink the display to allow room for more fields or expand it to make it easier to read. Minimum, maximum, and default values for field widths are set up internally. If you specify a field width of 0, the field is set to its minimum width. If you specify a field width that is larger than the internal maximum width, the field
field-name Specifies the name of the field to be modified in the display. For a list of field names, see the ADD (Field) command. /WIDTH = field-width Specifies the number of columns used to display the specified field. This qualifier lets you shrink the display to allow room for more fields or expand it to make it easier to read. Minimum, maximum, and default values for field widths are set up internally. If you specify a field width of 0, the field is set to its minimum width. If you specify a field width that is larger than the internal maximum width, the field
/WIDTH = field-width Specifies the number of columns used to display the specified field. This qualifier lets you shrink the display to allow room for more fields or expand it to make it easier to read. Minimum, maximum, and default values for field widths are set up internally. If you specify a field width of 0, the field is set to its minimum width. If you specify a field width that is larger than the internal maximum width, the field
Minimum, maximum, and default values for field widths are set up internally. If you specify a field width of 0, the field is set to its minimum width. If you specify a field width that is larger than the internal maximum width, the field
is set to its maximum width.
If the field width is too narrow to display a particular numeric field, asterisks are displayed in place of the data; if the width is too narrow to display a character string field, the character string is truncated on the right.
/FORMAT = radix Specifies the display format used to display the specified field. You can specify either of the following radix values:
DECIMAL for decimal format
HEXADECIMAL for hexadecimal format
A hexadecimal display for a field uses fewer columns than a decimal display. Changing the field format, however, does not change the field width until you specify the next SET (Field) command.
The hardware version field (HW_VERSION) is always displayed in 24 hexadecimal digits.

COMMAND> SET SYSID/FORMAT=HEXADECIMAL

This command sets the format of the SYSID field to a hexadecimal display.

SHOW CLUSTER SET FUNCTION

SET FUNCTION

Enables one of the following SHOW CLUSTER functions: EDIT, MOVE, PAN, or SCROLL.

FORMAT SET FUNCTION function-name

command function-name

parameter Specifies the SHOW CLUSTER function to be enabled. By default, the EDIT function is enabled. Functions include:

EDIT MOVE PAN SCROLL

None.

command qualifiers

DESCRIPTION The SET FUNCTION command redefines the arrow keys to perform the specified function. By default, the function is set to EDIT, which allows you to use the arrow keys to recall a previously issued command or perform DCL line-mode editing at the command prompt. (See the VAX/VMS DCL Concepts Manual for more information on DCL line-mode editing.)

To enable one of the SHOW CLUSTER functions, you either issue the specific SET FUNCTION command at the command prompt, or press the appropriate SET FUNCTION key on the keypad. Only one function can be enabled at a time.

Note: Setting the function to MOVE implicitly disables AUTO_POSITIONING.

EXAMPLE

COMMAND> SET FUNCTION MOVE COMMAND> SELECT SCS COMMAND> MOVE RIGHT 10 COMMAND> DESELECT COMMAND> SET FUNCTION SCROLL

This command sequence sets the function to MOVE and moves the SCS window 10 columns to the right. The window is then deselected, and the function is set to SCROLL. The arrow keys are now redefined to function as SCROLL commands.

SET	INT	ER\	VAL
-----	-----	-----	------------

SET INTERVAL

Changes the interval time between display updates. The interval time is the amount of time that display information remains on the screen before it is updated. By default, the display updates every 15 seconds, unless you use the /INTERVAL qualifier on the SHOW CLUSTER command. If you use the /INTERVAL qualifier on the SHOW CLUSTER command, the time specified becomes the default.

FORMAT	SET INTERVAL=seconds	
command parameter	seconds The number of seconds between display updates.	
command qualifiers	None.	

EXAMPLE

COMMAND> SET INTERVAL=5

This command changes the display interval time to five seconds.

SHOW CLUSTER SET SCREEN

SET SCREEN

Sets the terminal to a display of up to 512 columns. This command can be used only on a DIGITAL-compatible terminal.

FORMAT SET SCREEN=screen-width

commandscreen-widthparameterSpecifies the width o

None.

Specifies the width of the screen display. You can specify a value up to 512.

command qualifiers

EXAMPLE

COMMAND> SET SCREEN=132

This command sets the screen width to 132 columns.

WRITE	
	Outputs the current display to a file which can be printed on a hardcopy device.
FORMAT	WRITE [file-spec]
command parameter	<i>file-spec</i> File specification of the printable output file. By default, the output filename is SHOW_CLUSTER.LIS.
command qualifiers	/ALL Indicates that the output file should contain a display consisting of all classes and all fields. Because SHOW CLUSTER may not currently have the information necessary to display all the possible fields when you specify /ALL qualifier, a display update occurs prior to the output of the file. As a result, the output file may differ from the display currently on the terminal screen.
	You should use the /ALL qualifier to produce an output file or hardcopy file when reporting a cluster-related problem to DIGITAL.
EXAMPLE	

COMMAND> WRITE/ALL

This command creates a file, SHOW_CLUSTER.LIS, which contains all possible SHOW CLUSTER fields. SHOW_CLUSTER.LIS can be printed on a hardcopy device.

Index

A

ADD (Field) command • SHCL-31 to SHCL-40 CIRCUITS class • SHCL-31 to SHCL-32 CLUSTER class • SHCL-32 CONNECTIONS class • SHCL-33 COUNTERS class • SHCL-34 **CREDITS class • SHCL-34** description • SHCL-39 ERRORS class • SHCL-35 examples • SHCL-39 LOCAL_PORTS class • SHCL-35 to SHCL-36 MEMBERS class • SHCL-36 to SHCL-38 SYSTEMS class • SHCL-39 ADD CIRCUITS command • SHCL-23 ADD CLUSTER command

SHCL-25 ADD CONNECTIONS command • SHCL-26 ADD COUNTERS command • SHCL-28 ADD CREDITS command • SHCL-29 ADD ERRORS command • SHCL-30 ADD LOCAL _PORTS command • SHCL-41 ADD MEMBERS command • SHCL-42 ADD SYSTEMS command • SHCL-43 AUTO_POSITIONING command • SHCL-10

B

/BEGINNING qualifier • SHCL-16 Broadcast message • SHCL-12

С

CIRCUITS class • SHCL-31 to SHCL-32 Class of data description • SHCL-4 CLUSTER class • SHCL-32 Command procedure default file type • SHCL-14 description • SHCL-13 to SHCL-14 example • SHCL-13 nesting • SHCL-13 SHOW_CLUSTER\$INIT • SHCL-13 CONNECTIONS class • SHCL-33 /CONTINUOUS qualifier • SHCL-17 COUNTERS class • SHCL-34 CREDITS class • SHCL-34 CTRL/C command • SHCL-3 CTRL/Y command • SHCL-3 CTRL/Z command • SHCL-3

D

Data field • SHCL-4 DEFINE/KEY command • SHCL-45 DESELECT command • SHCL-48 Display controlling • SHCL-5 to SHCL-14 formatting considerations • SHCL-9 to SHCL-11 refreshing the screen • SHCL-11

E

/ENDING qualifier • SHCL-18 ERRORS class • SHCL-35 Execute Procedure (@) command • SHCL-22 usage summary • SHCL-14 EXIT command • SHCL-49

H

HELP command • SHCL-50

Initialization file creating • SHCL-12 to SHCL-13 default file type • SHCL-12 SHOW_CLUSTER\$INIT • SHCL-12 to SHCL-13 INITIALIZE command • SHCL-51 /INTERVAL qualifier • SHCL-19

L

LOCAL_PORTS class • SHCL-35 to SHCL-36

M

MEMBERS class • SHCL-36 to SHCL-38 MOVE command • SHCL-52

0

/OUTPUT qualifier • SHCL-20

Ρ

PAN command • SHCL-11, SHCL-54

Q

SHOW CLUSTER command • SHCL-14 to SHCL-20

R

REFRESH command • SHCL-55 REMOVE (Field) command • SHCL-62 REMOVE CIRCUITS command • SHCL-56 REMOVE CLUSTER command • SHCL-57 REMOVE CONNECTIONS command • SHCL-58 REMOVE COUNTERS command • SHCL-59 REMOVE CREDITS command • SHCL-60 REMOVE ERRORS command • SHCL-61 REMOVE LOCAL __PORTS command • SHCL-63 REMOVE MEMBERS command • SHCL-64 REMOVE SYSTEMS command • SHCL-65

S

SCROLL command • SHCL-10, SHCL-69 SELECT command • SHCL-70 SET (Field) command • SHCL-72 SET AUTO_POSITIONING command • SHCL-71 SET FUNCTION command • SHCL-73 SET INTERVAL command • SHCL-74 SET SCREEN command • SHCL-75 SHOW_CLUSTER\$INIT See Initialization file SHOW CLUSTER command

SHCL-1 controlling the display • SHCL-5 to SHCL-14 creating a command procedure • SHCL-13 to SHCL-14 creating an initialization file • SHCL-12 to SHCL-13 directing output • SHCL-1 entering commands • SHCL-6 exiting • SHCL-1 format • SHCL-1 formatting the display • SHCL-11 invoking • SHCL-1, SHCL-3 modifying display size • SHCL-9 moving a window • SHCL-10 privileges • SHCL-1 prompt • SHCL-6 receiving broadcast messages • SHCL-12 report • SHCL-3 to SHCL-5 restrictions • SHCL-1 terminating • SHCL-3 viewing the display • SHCL-11 SHOW CLUSTER command • SHCL-20 to SHCL-76 /BEGINNING qualifier • SHCL-16 /CONTINUOUS qualifier • SHCL-17 /ENDING qualifier • SHCL-18 /INTERVAL qualifier • SHCL-19 /OUTPUT qualifier • SHCL-20 Startup initialization file • SHCL-12 to SHCL-13 creating • SHCL-12 to SHCL-13 default file type • SHCL-12 example • SHCL-13 SYSTEMS class • SHCL-39

W

WRITE command • SHCL-76

SAVE command • SHCL-67

VAX/VMS Show Cluster Utility Reference Manual AA-Z430B-TE

READER'S COMMENTS

Note: This form is for document comments only. DIGITAL will use comments submitted on this form at the company's discretion. If you require a written reply and are eligible to receive one under Software Performance Report (SPR) service, submit your comments on an SPR form.

Did you find this manual understandable, usable, and well organized? Please make suggestions for improvement.

Did you find errors in this manual? If so, specify the error and the page number.

Please indicate the type of user/reader that you most nearly represent:

 Assembly language programmer Higher-level language programmer Occasional programmer (experienced) User with little programming experience Student programmer Other (please specify) 		
Name	Date	
Organization		
Street	· · · · · · · · · · · · · · · · · · ·	
City	State	Zip Code or Country

— Do Not Tear - Fold Here and Tape —



BUSINESS REPLY MAIL

No Postage

Necessary if Mailed in the United States

Cut Along Dotted Line

FIRST CLASS PERMIT NO.33 MAYNARD MASS.

POSTAGE WILL BE PAID BY ADDRESSEE

SSG PUBLICATIONS ZK1-3/J35 DIGITAL EQUIPMENT CORPORATION 110 SPIT BROOK ROAD NASHUA, NEW HAMPSHIRE 03062-2698

- -- Do Not Tear - Fold Here

VAX/VMS Show Cluster Utility Reference Manual AA-Z430B-TE

READER'S COMMENTS

Note: This form is for document comments only. DIGITAL will use comments submitted on this form at the company's discretion. If you require a written reply and are eligible to receive one under Software Performance Report (SPR) service, submit your comments on an SPR form.

Did you find this manual understandable, usable, and well organized? Please make suggestions for improvement.

Did you find errors in this manual? If so, specify the error and the page number.

Please indicate the type of user/reader that you most nearly represent:

- □ Assembly language programmer
- □ Higher-level language programmer
- □ Occasional programmer (experienced)
- User with little programming experience
- □ Student programmer
- □ Other (please specify) ____

Name	Date	
Organization		
Street		
City	State	Zip Code
		or Country

— Do Not Tear - Fold Here and Tape —





No Postage

Necessary if Mailed in the

United States

1

Cut Along Dotted Line

POSTAGE WILL BE PAID BY ADDRESSEE

SSG PUBLICATIONS ZK1-3/J35 DIGITAL EQUIPMENT CORPORATION 110 SPIT BROOK ROAD NASHUA, NEW HAMPSHIRE 03062-2698

Hhmultilluuthuulillilulilulululututill

- — Do Not Tear - Fold Here