

### **FACT SHEET**

Number 13A, January 1963

## **PHILCO 4000 SERIES PRINTER**

300 Lines Per Minute

The 300 line per minute Printer is used to produce high-quality printed output from the Philco 4000. Sixty-three Philco characters plus a blank column may be printed on continuous forms up to 20 inches in width. The Printer can be connected to any channel of the Philco 4000.

#### **SPEED**

- Prints at the rate of 300 lines per minute.
- Skips at the rate of 6,000 lines per minute.

#### PRINTING

- Produces up to 6 clearly printed single or multiple forms.
- Prints up to 120 characters per line.
- Prints 10 characters per horizontal inch, 6 or 8 lines per vertical inch.
- Prints 63 different characters plus a blank column.

#### PAPER SIZES

• Accepts paper up to 20 inches wide with no limit on form length.

#### TYPE STYLES

• Type faces are interchangeable.

# PROGRAMMING FEATURES

Accepts instructions from the Philco 4000 as follows:

- Connect Electronically connects the Philco 4000 Central Processor to the Printer. This reserves the Printer for use with the Central Processor.
- Print Causes a line of up to 120 characters to be printed.
- Page Advances the paper to the first line of the next form.
- Space Advances the paper the number of lines specified.
- Line Advances the paper to the line specified.
- Disconnect Disconnects the Central Processor from the Printer. This permits the Printer to accept another Connect instruction.

