
THE SYSGEN XL.

An expandable 20 Mbyte hard disk and 60 Mbyte tape back-up system.



Description:

The Sysgen $^{\text{TM}}$ XL $^{\text{TM}}$ provides 20 Mbytes of hard disk storage with 60 Mbytes of streaming tape back-up for the IBM $^{\text{B}}$ PC, XT, and AT $^{\text{TM}}$. It operates under PC DOS $^{\text{B}}$ versions 2.0, 2.1, and 3.0.


The XL may act as either a primary disk storage system or a complement to the XT's and AT's internal hard disks. The tape safeguards data stored on the XL, XT, or AT disks as well as an optional third disk.

The XL streaming tape system provides disk-to-tape and tape-to-disk transfers at 5 Mbytes per minute. Data can be transferred file-by-file or as a single disk or tape unit.

The Sysgen XL allows storage and back-up of active files and creation of an archival data library.

Features:

- 20 Mbytes of disk storage with the capacity to add an additional hard disk drive.
 - The PC can be booted directly from the XL's hard disk.
 - 60 Mbytes of streaming tape backup.
 - Back-up/restore operations handled as a function of selected files or completed disk image for the XL's hard disk.
 - Read-while-write tape feature allows monitoring and confirmation of tape data integrity.
 - Uses ANSI standard certified 1/4" cartridge tape DC600A.





Specifications:

Hard Disk Drive

Capacity

UNFORMATTED CAPACITY

PER DRIVE 25.5 Mbytes PER TRACK 10416 bytes

FORMATTED CAPACITY

PER DRIVE 20.1 Mbytes
PER TRACK 8192 bytes
PER SECTOR 256 bytes
SECTORS PER TRACK 32

Functional

ROTATIONAL SPEED 3600 RPM CYLINDERS 612
READ/WRITE HEADS 4
AVERAGE ACCESS TIME 85 msec.
TRACK-TO-TRACK 15 msec.
AVERAGE LATENCY 8.33 msec.

MTBF 10000 hours
MTTR 30 minutes
SOFT READ ERROR 1 per 10F-10 h

SOFT READ ERROR
HARD READ ERROR
SEEK ERROR

1 per 10E-10 bits read
1 per 10E-12 bits read
1 per 10E-6 seeks

Tape Back-Up Drive

CAPACITY 60 Mbytes per DC600A cartridge

NUMBER OF RECORDING 9 tracks serpentine
TRACKS
RECORDING FORMAT
RECORDING DENSITY
GCR coding
10000 flux FTPI or

8000 BPI

SPEED 90 IPS

START TIME 300 msec.

STOP TIME 300 msec.

Additional Specifications:

EXTERNAL DIMENSIONS 11 ½" x 17" x 5 ½". **POWER REQUIREMENTS** 1.0 amp at 120 VAC.

Trademarks: Sysgen, XL—Sysgen, Inc.; AT—International Business Machines Corporation. Registered trademarks: IBM, PC DOS—International Business Machine Corporation.

